

TEST REPORT

Verified Code: 047125

Report No.:	E202109018709-2	Application No.:	E202109018709
Client:	TowerIQ, Inc.		
Address:	13723 Riverport Drive C/O Potter Electric Signal Company Saint Louis, Missouri 63043		
FCC ID:	2AXVJPSBG-2AUL		
Sample Description:	In-building 2-Way Emergency Radio Communication Enhancement booster		
Model:	TQ-GuardianA2A		
Test Specification:	FCC PART 90 §90.223-RF exposure		
Receipt Date:	2021-09-03		
Test Date:	2021-09-04 to 2021-09-11		
Issue Date:	2021-09-27		
Test Result:	Pass		
Prepared By: Test Engineer <i>Yu shanshan.</i>	Reviewed By: Technical Manager <i>Wu Haoting</i>	Approved By: Manager <i>Johnson</i>	
Other Aspects:			
Note: Note			
Abbreviations: ok / P = passed; fail / F = failed; n.a. / N = not applicable;			
The test result in this test report refers exclusively to the presented test sample. This report shall not be reproduced except in full, without the written approval of GRGT.			



DIRECTIONS OF TEST

- 1. This station carries out test task according to the national regulation of verifications which can be traced to National Primary Standards and BIPM.**
- 2. The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.**
- 3. If there is any objection concerning the test, the client should inform the laboratory within 15 days from the date of receiving the test report.**

TABLE OF CONTENTS

1	Applicant information	3
1.1	Client information	3
1.2	Manufacturer and Factory	3
2	General description of EUT	3
2.1	Basic description of EUT	3
3	Assessment result summary	4
4	Radio frequency radiation exposure	5
4.1	Applicable Standard	5
4.2	Limits for Maximum Permissible Exposure (MPE).....	5
4.3	Test results.....	5
4.3.1	700MHz Band:.....	5
4.3.2	800MHz Band:.....	6
4.4	Test Results	7
APPENDIX A. PHOTOGRAPHS OF EUT.....		8
A.1	External photos.....	8
A.2	Internal photos.....	11
A.2.1	DIF Board	12
A.2.2	RF Board.....	14
A.2.3	Sentry Board	16
A.2.4	Multiband combiner.....	17
A.2.5	Power supply module.....	20

1 Applicant information

1.1 Client information


Name: TowerIQ, Inc.
Address: 13723 Riverport Drive C/O Potter Electric Signal Company Saint Louis, Missouri 63043

1.2 Manufacturer and Factory

Manufacture Name: Potter Elmdene SZ Branch
Address: Room 1483A, Hangdu Plaza, No. 1006 Huafu road, Huahang Community, Huaqiang North Street, Futian District, Shenzhen Bank Name: China Merchants Bank, Head Office, Shenzhen, P.R. China
Factory: Potter Elmdene SZ Branch
Address: Room 1483A, Hangdu Plaza, No. 1006 Huafu road, Huahang Community, Huaqiang North Street, Futian District, Shenzhen Bank Name: China Merchants Bank, Head Office, Shenzhen, P.R. China

2 General description of EUT

2.1 Basic description of EUT

Product Name: In-building 2-Way Emergency Radio Communication Enhancement booster
Product Model: TQ-GuardianA2A
Adding Model: /
Trade Name: 
Power Supply: AC 100~240V, 50/60Hz
Typical working voltage: AC 110V, 50/60Hz
Power cord: AC power cord
Frequency Band^①: 700MHz Band:
Downlink: 769MHz ~ 775MHz, Uplink: 799MHz ~ 805MHz
800MHz Band:
Downlink: 851MHz ~ 861MHz, Uplink: 806MHz ~ 816MHz
Nominal Output Power:
Downlink: 33dBm
Uplink: 27dBm
Nominal System Gain:
Downlink: 90dB
Uplink: 90dB
EUT Operating Temperature: -20 °C to +50 °C
Operating Humidity: 5% to 95%
Antenna Type: N/A^②

NOTE 1: This EUT is a narrowband device, which belongs to Class A signal booster.

NOTE 2: ^① It's an indoor device, The EUT does not provide antenna by Manufacturer's statement, but it is required that the Antenna gain shall not exceed 2 dBi for Downlink and 9 dBi for Uplink when the project is used by Manufacturer's statement.

NOTE 3: According to the manufacturer's statement, the minimum carrier spacing is 2 carrier bandwidths.

3 Assessment result summary

Item	Assessment Requirement	Assessment Method
RF exposure	FCC PART 90 §90.223	FCC PART 1.1307(b) FCC PART 2.1091 FCC PART 2.1093

4 Radio frequency radiation exposure

4.1 Applicable Standard

According to the requirements of FCC PART 90 § 90.223, the test method of RF exposure is based on FCC PART 1.1307(b), FCC PART 2.1091 and FCC PART 2.1093, so RF exposure is calculated.

4.2 Limits for Maximum Permissible Exposure (MPE)

The limits are shown in Table 4-1.

Table 4-1 Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ₂)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

Note: f=frequency in MHz; *=Plane-wave equivalent power density

Prediction of MPE limit at given distance, equations from OET Bulletin 65, Edition 97 - 01:

$$S = (P * G) / (4 * \pi * R^2) \text{ (where } PG = \text{EIRP) Where:}$$

S = power density

P= power input to antenna

G= numeric gain of the antenna

R= distance to the center of radiation of the antenna

4.3 Test results

Devices that operate under CFR47 Part 90 are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if they operate at frequencies of 1.5 GHz or below and limit for power density for general population/uncontrolled exposure is f/1500 W/m². The output power range by Manufacturer statement is 33±2dBm for Downlink and 27±1dBm for Uplink, The sum of antenna gain and cable loss is 2dBi for Downlink and 9dBi for uplink, Therefore, in this report, MPE adopts the maximum output power evaluation, that is, the maximum output power of downlink is 35dBm, and the maximum output power of uplink is 28dBm.so it has the following assessment:

4.3.1 700MHz Band:

4.3.1.1 Frequency range: 769MHz~775MHz/799MHz ~805MHz

4.3.1.1.1 Downlink (769MHz~775MHz)

Prediction frequency (MHz):	769
Maximum peak output power at antenna input terminal (dBm):	35.0
Maximum peak output power at antenna input terminal (W):	3.162
Maximum antenna gain (dBi):	2.0

Maximum RF output power (W): 5.0
 MPE limit for uncontrolled exposure at predication frequency (W/ m²): 0.512
 $S = f/1500 = 769/1500$

$$R1 = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{5}{0.512 * 4 * 3.14}} \approx 0.882m$$

Conversely, when $R > 0.882m$, and $S < \frac{PG}{4\pi R^2} = \frac{5}{4 * 3.14 * 0.882^2} \approx 0.512(W/m^2)$

4.3.1.1.2 Uplink (799MHz ~805MHz)

Prediction frequency (MHz): 799
 Maximum peak output power at antenna input terminal (dBm): 28
 Maximum peak output power at antenna input terminal (W): 0.63
 Maximum antenna gain (dBi): 9.0
 Maximum RF output power (W): 5.0
 MPE limit for uncontrolled exposure at predication frequency (W/ m²): 0.533
 $S = f/1500 = 799/1500$

$$R1 = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{5}{0.533 * 4 * 3.14}} \approx 0.864m$$

Conversely, when $R > 0.864m$, and $S < \frac{PG}{4\pi R^2} = \frac{5}{4 * 3.14 * 0.864^2} \approx 0.533(W/m^2)$

4.3.2 800MHz Band:

4.3.2.1.1 Downlink (851MHz~861MHz)

Prediction frequency (MHz): 851
 Maximum peak output power at antenna input terminal (dBm): 35.0
 Maximum peak output power at antenna input terminal (W): 3.162
 Maximum antenna gain (dBi): 2.0
 Maximum RF output power (W): 5.0
 MPE limit for uncontrolled exposure at predication frequency (W/ m²): 0.567
 $S = f/1500 = 851/1500$

$$R1 = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{5}{0.567 * 4 * 3.14}} \approx 0.838m$$

Conversely, when $R > 0.838m$, and $S < \frac{PG}{4\pi R^2} = \frac{5}{4 * 3.14 * 0.838^2} \approx 0.567(W/m^2)$

4.3.2.1.2 Uplink (806MHz~816MHz)

Prediction frequency (MHz): 806

Maximum peak output power at antenna input terminal (dBm):	28
Maximum peak output power at antenna input terminal (W):	0.63
Maximum antenna gain (dBi):	9.0
Maximum RF output power (W):	5.0
MPE limit for uncontrolled exposure at predication frequency (W/ m ²):	0.537
$S = f/1500 = 806/1500$	

$$R1 = \sqrt{\frac{PG}{4\pi S}} = \sqrt{\frac{5}{0.537 * 4 * 3.14}} \approx 0.861m$$


$$\text{Conversely, when } R > 0.861m, \text{ and } S < \frac{PG}{4\pi R^2} = \frac{5}{4 * 3.14 * 0.861^2} \approx 0.537(W/m^2)$$

4.4 Test Results

The above all ,when the sum of antenna gain and cable loss is 2dBi for downlink and the shortest distance from the human specific is 0.882m, the device is compliant with the requirement MPE limit for uncontrolled exposure.

APPENDIX A. PHOTOGRAPHS OF EUT

A.1 External photos



Top surface



Front surface



Side surface-1



Side surface-2




Behind surface



Bottom surface


A.2 Internal photos




A.2.1 DIF Board



DIF A and DIF B




DIF Board-A



DIF Board-A




DIF Board-B





DIF Board-B

A.2.2 RF Board





A.2.3 Sentry Board







A.2.4 Multiband combiner







A.2.5 Power supply module







-----This is the last page of the report. -----