

M910 Frequency range: 902.1 MHz-927.9 MHz

Equipment System: Analog signal

M910 operating instructions:



- 1、 on / off: long press ON / OFF to turn it on and shut it off
- 2、 Volume plus: Short press can increase the volume of the microphone
- 3、 Volume reduction: Short press to reduce the volume
- 4、 set up: Short press the SET key can switch the frequency point in the frequency table, switch the blue light flashing, the blue light flashing stop, the frequency point switching successfully;
- 5、 locking key: After pressing lock, the default current microphone frequency priority, lock state is green
- 6、 Charging input: the red indicator light is on when charging, and the red indicator light is off when fully charged

FCC Warning

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- ▶ -Reorient or relocate the receiving antenna.
- ▶ -Increase the separation between the equipment and receiver.
- ▶ -Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- ▶ -Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.