

CUSTOMER

KFT-107

ROHS

## SPECIFICATION FOR APPROVAL

MODEL NO. : RC 25X2.5-12mm-8.1uH-01

KEFEITE NO. : 107-RC25X2.5-0.08X24PX14TS-10mm-8.1uH-01

CUSTOMER P/N: M5

DATE : 2022/09/30

REV : A1

※产品符合: RoHS PAHS 6P REACH

PLEASE RETURN TO US COPY OF "SPECIFICATION FOR APPROVAL" WITH YOUR APPROVED SIGNATURES.

	"√"	CUSTOMER'S SIGNATURE	NOTE
FULL APPROVED			
CONDITIONAL APPROVED			
REJECTED			

## SHENZHEN KEFEITE ELELECTRONICS CO., LTD

FactoryAddress:2/F, Guantiancommunity, Shenzhen. New era industrial area  
C Building

TEL:86-755-27352660

FAX:86-755-27352742

HTTP:WWW.Kefeite.net







# SHENZHEN KEFEITE ELECTRONICS CO., LTD

CUSTOMER:	KFT-107	VERSION:	A1
CUSTOMER NO:	M5	PAGE:	3/5
KFT P/N:	107-RC25X2.5-0.08X240X14TS-10mm-8.1uH-01	Date:	2022/09/30

## 1. CONFIGURATION&DIMENSIONS:



A	14.1±0.2mm
B	20±0.2mm
C	25.0mm MAX
D	10±1.5mm
E	2~4mm
F	2.8mm MAX

1. Outgoin line:cross outgoing line, pasted reversely on the magnetic sheet
2. Magnet is installed in the center hole with the "s" Pole facing upwards(7.8x2.5mm≥3200GS)
3. Double sided adhesive tape on the back of the product
4. F Size thickness does not include release paper

## 2. ELEETRICAL CHARACTER:


PROJECT	SPECFICTIONS	TEST CONDITIONS	TEST INSTRUMENT
(Ls) Coil	4.8±10%uH	100KHZ/1.0V	CH1062
(Ls)Coil+Core	8.1±10%uH	100KHZ/1.0V	CH1062
(RDC)	≤280mΩ	At:25℃	HG2512

## 3. SCHEMATIC



## 4. PART NUMBERING:PRODUCT IDENTIFICATION

107 RC25X2.5 0.08X24PX14TS 10mm 8.1uH 01



DRAWN BY:	CHECKED BY:	Q. C DEPT:	APPROVED BY:
FI GO	QIONJINFU		W. J. J



# SHENZHEN KEFEITE ELECTRONICS CO., LTD

CUSTOMER:	KFT-107	VERSION:	A1
CUSTOMER NO:	M5	PAGE:	4/5
KFT P/N:	107-RC25X2.5-0.08X240X14TS-10mm-8.1uH-01	Date:	2022/09/30

## 5. MATERIAL LIST:

NO	ITEM	DESCRIPTION	RATING	SUPPLIERS	UL NO.	REMARK
1	WIRE	Acetone line	155°C	SHANTOU SHENGANG ELECTRICAL INDUSTRIAL CO.,LTD	E239508	
2	SOLDER	99.3/0.7		SHENZHEN Hong Xing Wei solder Limited		
3	CORE	25/7.7/2.5		Changxing BO Cheng Electronics CO.,LTD		
4	EPOXY	1603HFR-HS		DONGBU FINE CHEMICAL CO LTD		
5	Strong Magnet	7.8X2.5>3000GS		DONGBU FINE CHEMICAL CO LTD		

## 6. GENERAL SPECIFICATION:

- 1 Tested at 1.0KHZ/0.25Vrms, 0 Adc.  
Average current for 40°C temperature rise from 25°C.
- 2 Saturation current (Isat):  
Inductance drop: 10% typ at Isat.
- 3 Heat rating current (Irms):  
 $L @ Irms = \Delta T \leq 40^\circ C$ .
- 4 Electrical specifications at 25°C
- 5 Storage Temp: -40°C....+85°C
- 6 Operating Temp: -40°C....+85°C

DRAWN BY:	CHECKED BY:	Q. C DEPT:	APPROVED BY:
FI GO	QIONJINFU		W. J. J