

ATC

TEST REPORT

Applicant Name : ORAIMO TECHNOLOGY LIMITED
Address : FLAT N 16/F BLOCK B UNIVERSAL INDUSTRIAL CENTRE 19-25
SHAN MEI STREET FOTAN NT Hong Kong
Report Number : RA230109-01561E-RF-00D
FCC ID: 2AXYP-OEB-E104DC-R

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: True Wireless Earbuds
Model No.: OEB-E104DC
Multiple Model(s) No.: N/A
Trade Mark: oraimo
Date Received: 2023/01/09
Report Date: 2023/01/31

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Handwritten signature of Andy Yu.

Andy Yu
EMC Engineer

Approved By:

Handwritten signature of Candy Li.

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “*”.

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “*”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY4
GENERAL INFORMATION.....	.5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)5
OBJECTIVE5
TEST METHODOLOGY5
MEASUREMENT UNCERTAINTY.....	.6
SYSTEM TEST CONFIGURATION.....	.7
DESCRIPTION OF TEST CONFIGURATION7
EQUIPMENT MODIFICATIONS7
EUT EXERCISE SOFTWARE8
DUTY CYCLE8
SUPPORT EQUIPMENT LIST AND DETAILS8
EXTERNAL I/O CABLE.....	.8
BLOCK DIAGRAM OF TEST SETUP8
SUMMARY OF TEST RESULTS9
TEST EQUIPMENT LIST10
FCC§15.247 (I), §1.1307 (B) (3) &§2.1093 – RF EXPOSURE11
APPLICABLE STANDARD11
FCC §15.203 - ANTENNA REQUIREMENT.....	.12
APPLICABLE STANDARD12
ANTENNA CONNECTOR CONSTRUCTION12
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....	.13
APPLICABLE STANDARD13
EUT SETUP13
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP14
TEST PROCEDURE14
FACTOR & MARGIN CALCULATION14
TEST DATA14
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH21
APPLICABLE STANDARD21
TEST PROCEDURE21
TEST DATA21
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER22
APPLICABLE STANDARD22
TEST PROCEDURE22
TEST DATA22
FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE23
APPLICABLE STANDARD23
TEST PROCEDURE23
TEST DATA23
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	.24
APPLICABLE STANDARD24
TEST PROCEDURE24
TEST DATA24

APPENDIX	25
APPENDIX A: DTS BANDWIDTH	25
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	28
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	31
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	34
APPENDIX E: BAND EDGE MEASUREMENTS.....	37
APPENDIX F: DUTY CYCLE	39

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230109-01561E-RF-00D	Original Report	2023-01-31

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE: 2402-2480MHz
Maximum Conducted Peak Output Power	BLE: -2.56dBm
Modulation Technique	BLE: GFSK
Antenna Specification*	2.5dBi (provided by the applicant)
Voltage Range	DC3.7V from battery
Sample serial number	1Y4F-6 for Radiated Emissions Test 1Y4N-4 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter	Uncertainty
Occupied Channel Bandwidth	5%
RF Frequency	0.082×10^{-7}
RF output power, conducted	0.73dB
Unwanted Emission, conducted	1.6dB
AC Power Lines Conducted Emissions	2.72dB
Emissions, Radiated	
9kHz - 30MHz	2.66dB
30MHz - 1GHz	4.28dB
1GHz - 18GHz	4.98dB
18GHz - 26.5GHz	5.06dB
26.5GHz - 40GHz	4.72dB
Temperature	1°C
Humidity	6%
Supply voltages	0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“FCC_assist_1.0.2.2.exe” software was used to test, the software and power level was provided by manufacturer and power level as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
BLE	1Mbps/2Mbps	Default	Default	Default

Duty cycle

Test Result: Compliant. Please refer to the Appendix

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

For Radiated Emissions:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (3) & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

Not Applicable: the Bluetooth function cannot be used when in charging.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emissions Test					
Rohde&Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2022/11/30	2025/11/29
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24
RF conducted test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/11/25	2023/11/24
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
WEINSCHEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.31	RF-01	Each time	Each time

*** Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) (3) &§2.1093 – RF EXPOSURE**Applicable Standard**

According to FCC §2.1093 and §1.1307(b) (3), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D04 Interim General RF Exposure Guidance

1-mW Test Exemption:

Per § 1.1307(b)(3)(i)(A), a single RF source is exempt RF device (from the requirement to show data demonstrating compliance to RF exposure limits, as previously mentioned) if the available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption applies to all operating configurations and exposure conditions, for the frequency range 100 kHz to 100 GHz, regardless of fixed, mobile, or portable device exposure conditions. This is a standalone exemption, and it cannot be applied in conjunction with any other test exemption.

For worst case:

Frequency (MHz)	Maximum Tune-up Conducted Power (dBm)	Antenna Gain		Maximum Tune-up ERP		Exemption Limit (mW)	Test Exemption
		(dBi)	(dBd)	(dBm)	(mW)		
2402-2480	-2.0	2.5	0.35	-1.65	0.68	1	Yes

Note: 0dBd=2.15dBi

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.



Antenna Connector Construction

The EUT has one integral antenna which was permanently attached, and the maximum antenna gain is 2.5dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	>1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “Over Limit/Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions


Temperature:	24~25.5°C
Relative Humidity:	52~58%
ATM Pressure:	101.0 kPa

The testing was performed by Jimi Zheng on 2023-01-16 for below 1GHz and above 1GHz

EUT operation mode: Transmitting(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axes of orientation was recorded)

30MHz-1GHz: (Worst case is low channel)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.

Horizontal:


Site : chamber

Condition: 3m HORIZONTAL

Job No. : RA230109-01561E-RF

Test Mode: BLE Transmitting

	Freq	Factor	Read Level	Limit Level	Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	47.243	-10.00	28.98	18.98	40.00	-21.02	Peak
2	100.890	-11.70	27.66	15.96	43.50	-27.54	Peak
3	192.925	-11.28	28.32	17.04	43.50	-26.46	Peak
4	406.979	-6.57	29.35	22.78	46.00	-23.22	Peak
5	595.394	-2.66	29.71	27.05	46.00	-18.95	Peak
6	843.238	0.36	29.03	29.39	46.00	-16.61	Peak

Vertical

Site : chamber
Condition: 3m VERTICAL
Job No. : RA230109-01561E-RF
Test Mode: BLE Transmitting

Freq	Factor	Read		Limit		Over	Remark
		MHz	dB/m	dBuV	dBuV/m	Line	Limit
1	50.741	-9.94	29.68	19.74	40.00	-20.26	Peak
2	102.449	-11.60	28.51	16.91	43.50	-26.59	Peak
3	157.421	-14.61	30.35	15.74	43.50	-27.76	Peak
4	190.906	-11.43	28.97	17.54	43.50	-25.96	Peak
5	284.478	-9.45	28.54	19.09	46.00	-26.91	Peak
6	688.960	-1.52	30.28	28.76	46.00	-17.24	Peak

1-25 GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/Ave		Height (m)	Polar (H/V)									
BLE 1M														
Low Channel 2402MHz														
2310	61.32	PK	193	2.3	H	-7.24	54.08	74	-19.92					
2310	49.36	AV	193	2.3	H	-7.24	42.12	54	-11.88					
2310	61.06	PK	282	1.6	V	-7.24	53.82	74	-20.18					
2310	48.96	AV	282	1.6	V	-7.24	41.72	54	-12.28					
2390	63.79	PK	117	2.2	H	-7.22	56.57	74	-17.43					
2390	51.24	AV	117	2.2	H	-7.22	44.02	54	-9.98					
2390	63.89	PK	159	1.2	V	-7.22	56.67	74	-17.33					
2390	50.79	AV	159	1.2	V	-7.22	43.57	54	-10.43					
4804	60.89	PK	11	1.5	H	-3.51	57.38	74	-16.62					
4804	55.73	AV	11	1.5	H	-3.51	52.22	54	-1.78					
4804	61.29	PK	148	1.6	V	-3.51	57.78	74	-16.22					
4804	55.56	AV	148	1.6	V	-3.51	52.05	54	-1.95					
Middle Channel 2440MHz														
4880	61.39	PK	291	2	H	-3.38	58.01	74	-15.99					
4880	54.96	AV	291	2	H	-3.38	51.58	54	-2.42					
4880	60.83	PK	319	1.6	V	-3.38	57.45	74	-16.55					
4880	54.98	AV	319	1.6	V	-3.38	51.6	54	-2.40					
High Channel 2480MHz														
2483.5	63.64	PK	352	1.6	H	-7.20	56.44	74	-17.56					
2483.5	50.76	AV	352	1.6	H	-7.20	43.56	54	-10.44					
2483.5	63.62	PK	220	2	V	-7.20	56.42	74	-17.58					
2483.5	51.45	AV	220	2	V	-7.20	44.25	54	-9.75					
2500	63.09	PK	345	1.2	H	-7.18	55.91	74	-18.09					
2500	50.51	AV	345	1.2	H	-7.18	43.33	54	-10.67					
2500	62.57	PK	227	1	V	-7.18	55.39	74	-18.61					
2500	50.32	AV	227	1	V	-7.18	43.14	54	-10.86					
4960	61.21	PK	110	1.5	H	-3.01	58.20	74	-15.80					
4960	55.67	AV	110	1.5	H	-3.01	52.66	54	-1.34					
4960	61.14	PK	144	1.5	V	-3.01	58.13	74	-15.87					
4960	55.19	AV	144	1.5	V	-3.01	52.18	54	-1.82					

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)					
	Reading (dB μ V)	PK/Ave		Height (m)	Polar (H/V)									
BLE 2M														
Low Channel 2402MHz														
2310	61.05	PK	329	1	H	-7.24	53.81	74	-20.19					
2310	49.45	AV	329	1	H	-7.24	42.21	54	-11.79					
2310	61.30	PK	178	2.4	V	-7.24	54.06	74	-19.94					
2310	49.12	AV	178	2.4	V	-7.24	41.88	54	-12.12					
2390	63.58	PK	287	1.7	H	-7.22	56.36	74	-17.64					
2390	50.72	AV	287	1.7	H	-7.22	43.50	54	-10.50					
2390	63.55	PK	38	1.1	V	-7.22	56.33	74	-17.67					
2390	50.63	AV	38	1.1	V	-7.22	43.41	54	-10.59					
4804	62.59	PK	230	1.7	H	-3.51	59.08	74	-14.92					
4804	52.80	AV	230	1.7	H	-3.51	49.29	54	-4.71					
4804	63.10	PK	236	1.8	V	-3.51	59.59	74	-14.41					
4804	52.92	AV	236	1.8	V	-3.51	49.41	54	-4.59					
Middle Channel 2440MHz														
4880	63.17	PK	206	2.4	H	-3.38	59.79	74	-14.21					
4880	53.16	AV	206	2.4	H	-3.38	49.78	54	-4.22					
4880	62.61	PK	358	1.1	V	-3.38	59.23	74	-14.77					
4880	53.10	AV	358	1.1	V	-3.38	49.72	54	-4.28					
High Channel 2480MHz														
2483.5	64.74	PK	113	2.2	H	-7.20	57.54	74	-16.46					
2483.5	51.34	AV	113	2.2	H	-7.20	44.14	54	-9.86					
2483.5	64.95	PK	298	1.9	V	-7.20	57.75	74	-16.25					
2483.5	50.67	AV	298	1.9	V	-7.20	43.47	54	-10.53					
2500	62.72	PK	47	2.2	H	-7.18	55.54	74	-18.46					
2500	50.15	AV	47	2.2	H	-7.18	42.97	54	-11.03					
2500	62.91	PK	284	1.2	V	-7.18	55.73	74	-18.27					
2500	50.13	AV	284	1.2	V	-7.18	42.95	54	-11.05					
4960	63.12	PK	56	2.5	H	-3.01	60.11	74	-13.89					
4960	53.16	AV	56	2.5	H	-3.01	50.15	54	-3.85					
4960	62.40	PK	281	1.5	V	-3.01	59.39	74	-14.61					
4960	53.09	AV	281	1.5	V	-3.01	50.08	54	-3.92					



Note:



Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading

Margin = Corrected Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.

1-18 GHz:**Pre-scan for BLE 1M, High Channel****Horizontal****Vertical**

18 -25GHz:**Pre-scan for BLE 1M, High Channel****Horizontal****Vertical**

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	45 %
ATM Pressure:	101.0 kPa

The testing was performed by Andy Yu on 2023-01-16.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.

Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.9.1.1

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	45 %
ATM Pressure:	101.0 kPa

The testing was performed by Andy Yu on 2023-01-16.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE


Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	45 %
ATM Pressure:	101.0 kPa

The testing was performed by Andy Yu on 2023-01-16.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(e) - POWER SPECTRAL DENSITY


Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25°C
Relative Humidity:	45 %
ATM Pressure:	101.0 kPa

The testing was performed by Andy Yu on 2023-01-16.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


APPENDIX

Appendix A: DTS Bandwidth Test Result

Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.52	0.5	PASS
		2440	0.52	0.5	PASS
		2480	0.50	0.5	PASS
BLE_2M	Ant1	2402	0.85	0.5	PASS
		2440	0.85	0.5	PASS
		2480	0.85	0.5	PASS

Test Graphs







**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Frequency[MHz]	OCB [MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	1.039	---	---
		2440	1.059	---	---
		2480	1.027	---	---
BLE_2M	Ant1	2402	2.042	---	---
		2440	2.05	---	---
		2480	2.046	---	---

Test Graphs







**Appendix C: Maximum conducted output power
Test Result**

Test Mode	Antenna	Frequency[MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Verdict
BLE_1M	Ant1	2402	-2.71	≤30	PASS
		2440	-2.64	≤30	PASS
		2480	-2.89	≤30	PASS
BLE_2M	Ant1	2402	-2.66	≤30	PASS
		2440	-2.56	≤30	PASS
		2480	-2.80	≤30	PASS

Test Graphs







**Appendix D: Maximum power spectral density
Test Result**

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-23.20	≤8.00	PASS
		2440	-22.88	≤8.00	PASS
		2480	-22.53	≤8.00	PASS
BLE_2M	Ant1	2402	-24.47	≤8.00	PASS
		2440	-24.63	≤8.00	PASS
		2480	-24.85	≤8.00	PASS

Test Graphs






Appendix E: Band edge measurements

Test Graphs






Appendix F: Duty Cycle Test Result

Test Mode	Antenna	Frequency[MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]
BLE_1M	Ant1	2440	1.63	1.88	86.70
BLE_2M	Ant1	2440	0.40	0.63	63.49

Test Graphs



***** END OF REPORT *****