

TEST REPORT

Product Name : Flashback Wireless Kit
Model Number : AI7015, AI9004, AI7015-X, AI7015-XX,
AI9004-X, AI9004-XX,
AI9004-XXX(X denotes different color.)
FCC ID : 2AY38-AI7015

Prepared for : DONGGUAN YEST SCIENCE&TECHNOLOGY CO.,LTD
Address : Room301. NO. 33 Hehe Road. Xiangxi Village. Liaobu
Town. Dongguan City. Guangdong Province, China

Prepared by : EMTEK (DONGGUAN) CO., LTD.
Address : -1&2/F.,Building 2, Zone A, Zhongda Marine Biotechnology
Research and Development Base, No.9, Xincheng Avenue,
Songshanhu High-technology Industrial Development Zone,
Dongguan, Guangdong, China

TEL: +86-0769-22807078
FAX: +86-0769-22807079

Report Number : EDG2404250042E00402R
Date(s) of Tests : Apr 25, 2024 to May 16, 2024
Date of issue : May 17, 2024

Table of Contents

1. TEST RESULT CERTIFICATION	3
2. EUT SPECIFICATION	5
3. TEST REQUIREMENT	6
4. MEASUREMENT RESULT	6



1. TEST RESULT CERTIFICATION

Applicant : DONGGUAN YEST SCIENCE&TECHNOLOGY CO.,LTD
 Address : Room301. NO. 33 Hehe Road. Xiangxi Village. Liaobu Town. Dongguan City. Guangdong Province, China
 Manufacturer : DONGGUAN YEST SCIENCE&TECHNOLOGY CO.,LTD
 Address : Room301. NO. 33 Hehe Road. Xiangxi Village. Liaobu Town. Dongguan City. Guangdong Province, China
 Factory : DONGGUAN YEST SCIENCE&TECHNOLOGY CO.,LTD
 Address : Room301. NO. 33 Hehe Road. Xiangxi Village. Liaobu Town. Dongguan City. Guangdong Province, China
 EUT : Flashback Wireless Kit
 Model Name : AI7015, AI9004, AI7015-X, AI7015-XX, AI7015-XXX, AI9004-X, AI9004-XX, AI9004-XXX(X denotes different color.)
 Trademark : AIWA

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report


Date of Test : Apr 25, 2024 to May 16, 2024

Prepared by : Warren Deng

Prepared by : Warren Deng /Editor

Reviewer : Tim Dong

Reviewer : Tim Dong /Supervisor

Approve & Authorized Signer : 

Approve & Authorized Signer : Sam Lv / Manager



Modified History

Version	Report No.	Revision Date	Summary
	EDG2404250042E00402R	/	Original Report



2. EUT Specification

Characteristics	Description
Product:	Flashback Wireless Kit
Model Number:	AI7015, AI9004, AI7015-X, AI7015-XX, AI7015-XXX, AI9004-X, AI9004-XX, AI9004-XXX(X denotes different color.) All products are identical except the model number and color. Here we selected AI7015 for all the test.
Sample:	1#
Data Rate:	1Mbps for GFSK modulation 2Mbps for $\pi/4$ -DQPSK modulation 3Mbps for 8DPSK modulation
Modulation:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Operating Frequency Range(s) :	2402-2480MHz
Number of Channels:	79 channels
Transmit Power Max:	-3.37 dBm(0.000460 W)
Antenna Gain:	-0.68 dBi
Power supply:	DC 5V from USB DC 3.7V from battery
Evaluation applied:	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

3. Test Requirement

SAR Evaluation

According to 447498 D01 V06, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$

$[\sqrt{f_{(\text{GHz})}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

4. Measurement Result

Antenna gain: -0.68 dBi

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power (dBm)	Calculation Result	1-g SAR
2402	GFSK	-4.29	-4±1	-3	0.1554	3
2441	GFSK	-4.56	-4±1	-3	0.1566	3
2480	GFSK	-4.80	-5±1	-4	0.1254	3
2402	Π/4-DQPSK	-3.71	-3±1	-2	0.1956	3
2441	Π/4-DQPSK	-4.07	-4±1	-3	0.1566	3
2480	Π/4-DQPSK	-4.25	-4±1	-3	0.1579	3
2402	8DPSK	-3.37	-3±1	-2	0.1956	3
2441	8DPSK	-3.80	-4±1	-3	0.1566	3
2480	8DPSK	-3.94	-4±1	-3	0.1579	3

According to KDB 447498 D01 V06, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

*** End of Report ***