

FCC - TEST REPORT

Report Number : **68.950.23.0210.01** Date of Issue: **2023-03-15**

Model : **DP19/6x24WRG**

Product Type : Dual Monocular

Applicant : InfiRay Technologies Co., Ltd.

Address : Building C3, A1, Innovation Industrial Park, 230088 Hefei
PEOPLE'S REPUBLIC OF CHINA

Manufacturer : InfiRay Technologies Co., Ltd.

Address : Building C3, A1, Innovation Industrial Park, 230088 Hefei
PEOPLE'S REPUBLIC OF CHINA

Test Result : **Positive** **Negative**

Total pages including Appendices : **61**

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation, chapter A-3.4.



1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks	7
7	Test Setups	8
8	Systems test configuration	9
9	Technical Requirement	10
9.1	Conducted Emission	10
9.2	Conducted peak output power	13
9.3	6dB bandwidth and 99% Occupied Bandwidth	15
9.4	Power spectral density	24
9.5	Spurious RF conducted emissions	28
9.6	Band edge testing	39
9.7	Spurious radiated emissions for transmitter	43
10	Test Equipment List.....	59
11	System Measurement Uncertainty	61

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12 & 13, Zhiheng Wisdomland Business Park, Nantou Checkpoint
Road 2, Nanshan District
Shenzhen 518052
P.R. China

Telephone: 86 755 8828 6998

Fax: 86 755 8828 5299

FCC Registration No.: 514049

FCC Designation Number: CN5009

3 Description of the Equipment Under Test

Product:	Dual Monocular
Model no.:	DP19/6x24WRG
FCC ID:	2AY3N-DUAL19
Rating:	Charged by 5.0VDC, 3.0A adapter Or 3.85VDC by Rechargeable Lithium-ion battery
Options and accessories:	Adapter and USB Cable
Rechargeable Li-ion Battery	Model: 36AQS17-11 Specification:3.85V/3600mAh(13.09Wh) Model: 603063 Specification: 3.85V/3600mAh
Adapter:	Model: LX18AA-050300-ZE Input:100-240V~ 50/60Hz 0.7A; Output:5VDC 3.0A
RF Transmission Frequency:	2412MHz-2462MHz
No. of Operated Channel:	11
Modulation:	DSSS, OFDM
Antenna Type:	Integrated antenna
Antenna Gain:	2.0dbi
Description of the EUT:	The Equipment Under Test (EUT) is a Dual Monocular which support Wi-Fi. The TX and RX range is 2412MHz – 2462MHz for 2.4GHz Wi-Fi

4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2020 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to
KDB 558074 D01 15.247 Meas Guidance v05r02,
ANSI C63.10 (2013).

5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	10	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247 (b) (1)	Conducted peak output power	13	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1)	20dB bandwidth	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)	Carrier frequency separation	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii)	Dwell Time	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(2)	6dB bandwidth and 99% Occupied Bandwidth	15	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(e)	Power spectral density	24	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Spurious RF conducted emissions	28	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Band edge	39	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Spurious radiated emissions for transmitter	43	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.203	Antenna requirement	See note 2		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Note 1: N/A=Not Applicable.

Note 2: The EUT uses an internal antenna, which gain is 2.0 dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AY3N-DUAL19, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

- Performed

- **Not** Performed

The Equipment Under Test

- **Fulfills** the general approval requirements.

- **Does not** fulfill the general approval requirements.


Sample Received Date: 2023-02-10

Testing Start Date: 2023-02-10

Testing End Date: 2023-03-10

TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch

Reviewed by:




John Zhi
Project Manager

Prepared by:



Warlen Song
Project Engineer


Tested by:



Carry Cai
Test Engineer


7 Test Setups

7.1 AC Power Line Conducted Emission test setups




7.2 Radiated test setups


Below 1GHz



Above 1GHz



7.3 Conducted RF test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
PC	Lenovo	X240	---
Adapter	IRay Technology Co., Ltd.	LX18AA-050300-ZE	

The system was configured to non-hopping mode.

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

9 Technical Requirement

9.1 Conducted Emission

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


Limit

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

Conducted Emission

Product Type : Dual Monocular
 M/N : DP19/6x24WRG
 Operating Condition : Charging + Transmit
 Test Specification : Power Line, Live
 Comment : AC 120V/60Hz



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.185500	59.95	---	64.04	4.09	L1	9.59
0.206500	58.23	---	63.53	5.30	L1	9.60
0.257500	55.52	---	61.50	5.98	L1	9.60
3.430000	40.40	---	56.00	15.60	L1	9.71
5.418000	38.33	---	60.00	21.67	L1	9.79
23.362000	41.07	---	60.00	18.93	L1	10.09

Final Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.185500	---	21.20	54.24	33.03	L1	9.59
0.185500	32.17	---	64.24	32.06	L1	9.59
0.206500	---	23.03	53.35	30.31	L1	9.60
0.206500	33.32	---	63.35	30.02	L1	9.60
0.257500	---	23.01	51.51	28.51	L1	9.60
0.257500	32.02	---	61.51	29.49	L1	9.60

Remark :


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

Conducted Emission

Product Type : Dual Monocular
 M/N : DP19/6x24WRG
 Operating Condition : Charging + Transmit
 Test Specification : Power Line, Neutral
 Comment : AC 120V/60Hz (External adapter)



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
0.170000	36.00	---	64.96	28.96	N	9.58
0.534000	36.70	---	56.00	19.30	N	9.63
1.350000	34.83	---	56.00	21.17	N	9.65
2.298000	35.53	---	56.00	20.47	N	9.67
3.998000	34.54	---	56.00	21.46	N	9.73
22.198000	38.10	---	60.00	21.90	N	10.11

Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---		---

Remark :

Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

9.2 Conducted peak output power

Test Method

1. The EUT was placed on 0.8m height table, the RF output of EUT was connected to the power meter by RF cable. The path loss was compensated to the results for each measurement.
2. Setting the highest output power level of the EUT
3. Record the power value.

Limits

According to §15.247 (b) (3), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Test result as below table

802.11b_ modulation Test Result

Frequency (MHz)	Conducted Peak Output Power (dBm)	Result
	Ant 0	
Low channel 2412MHz	16.7	Pass
Middle channel 2437MHz	17.1	Pass
High channel 2462MHz	17.1	Pass

802.11g_ modulation Test Result

Frequency (MHz)	Conducted Peak Output Power (dBm)	Result
	Ant 0	
Low channel 2412MHz	16.8	Pass
Middle channel 2437MHz	17.7	Pass
High channel 2462MHz	17.6	Pass

802.11n20_modulation Test Result

Frequency (MHz)	Conducted Peak Output Power (dBm)	Result
	Ant0	
Low channel 2412MHz	16.7	Pass
Middle channel 2437MHz	17.3	Pass
High channel 2462MHz	17.3	Pass

9.3 6dB bandwidth and 99% Occupied Bandwidth

Test Method for 6 dB Bandwidth

1. Use the following spectrum analyzer settings:
RBW=100K, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be \geq 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Test Method for 99 % Bandwidth

1. Use the following spectrum analyzer settings:
RBW=1% to 5% of the actual occupied, VBW \geq 3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be \geq 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

Limit


Limit [kHz]

\geq 500

6dB Bandwidth


TestMode	Antenna	Channel [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
11B	Ant0	2412	8.320	2408.080	2416.400	0.5	PASS
	Ant0	2437	7.280	2433.360	2440.640	0.5	PASS
	Ant0	2462	9.120	2457.400	2466.520	0.5	PASS
11G	Ant0	2412	16.440	2403.800	2420.240	0.5	PASS
	Ant0	2437	16.440	2428.760	2445.200	0.5	PASS
	Ant0	2462	16.440	2453.760	2470.200	0.5	PASS
11N20	Ant0	2412	15.200	2404.400	2419.600	0.5	PASS
	Ant0	2437	16.400	2428.200	2444.600	0.5	PASS
	Ant0	2462	15.520	2454.400	2469.920	0.5	PASS

11B_Ant1_2412




Date: 16 FEB 2023 14:33:39

11B_Ant1_2437




Date: 16 FEB 2023 14:38:06

11B_Ant1_2462



Date: 16 FEB 2023 14:41:29

11G_Ant1_2412




Date: 16 FEB 2023 14:45:13

11G_Ant1_2437




Date: 16 FEB 2023 14:48:36


11G_Ant1_2462




11N20SISO_Ant1_2412



11N20SISO_Ant1_2437





11N20SISO_Ant1_2462




99% Bandwidth

TestMode	Antenna	Channel [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant0	2412	13.866	2405.087	2418.953	---	PASS
		2437	13.906	2430.047	2443.953	---	PASS
		2462	13.906	2455.047	2468.953	---	PASS
11G	Ant0	2412	17.662	2403.249	2420.911	---	PASS
		2437	17.702	2428.209	2445.911	---	PASS
		2462	17.662	2453.209	2470.871	---	PASS
11N20SISO	Ant0	2412	19.301	2402.569	2421.870	---	PASS
		2437	19.341	2427.490	2446.830	---	PASS
		2462	19.540	2452.490	2472.030	---	PASS




11B_Ant1_2462




Date: 16 FEB 2023 14:41:40

11G_Ant1_2412




Date: 16 FEB 2023 14:45:24

11G_Ant1_2437




Date: 16 FEB 2023 14:48:47

11G_Ant1_2462




Date: 16 FEB 2023 14:51:46

11N20SISO_Ant1_2412




Date: 16 FEB 2023 14:54:45

11N20SISO_Ant1_2437



Date: 16 FEB 2023 14:58:25

11N20SISO_Ant1_2462



9.4 Power spectral density

Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. The RF output of EUT was connected to the test receiver by RF cable. The path loss was compensated to the results for each measurement.
2. Set analyzer center frequency to DTS channel center frequency. RBW=3kHz, VBW≥3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
3. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
4. Repeat above procedures until other frequencies measured were completed.

Limit

Limit [dBm/3KHz

≤8

802.11b modulation Test Result

Frequency (MHz)	Power spectral density (dBm/3KHz)	Limit (dBm)	Result
	Ant 0		
Low channel 2412MHz	-6.42	8	Pass
Middle channel 2437MHz	-6.98	8	Pass
High channel 2462MHz	-5.49	8	Pass


802.11g modulation Test Result

Frequency (MHz)	Power spectral density (dBm/3KHz)	Limit (dBm)	Result
	Ant 0		
Low channel 2412MHz	-9.86	8	Pass
Middle channel 2437MHz	-8.47	8	Pass
High channel 2462MHz	-8.08	8	Pass

802.11n_HT20 modulation Test Result


Frequency (MHz)	Power spectral density (dBm/3KHz)	Limit (dBm)	Result
	Ant 0		
Low channel 2412MHz	-8.86	8	Pass
Middle channel 2437MHz	-8.68	8	Pass
High channel 2462MHz	-8.35	8	Pass

11B_Ant1_2412




Date: 16 FEB 2023 14:34:01

11B_Ant1_2437




Date: 16 FEB 2023 14:38:29

11B_Ant1_2462




Date: 16 FEB 2023 14:41:52

11G_Ant1_2412




Date: 16 FEB 2023 14:45:36

11G_Ant1_2437




Date: 16 FEB 2023 14:48:58

11G_Ant1_2462




Date: 16 FEB 2023 14:51:58


11N20SISO_Ant1_2412



11N20SISO_Ant1_2437



11N20SISO_Ant1_2462



9.5 Spurious RF conducted emissions

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize. Set the marker on the peak of any spurious emission recorded.
4. The level displayed must comply with the limit specified in this Section. Submit these plots.
5. Repeat above procedures until all frequencies measured were complete.


Limit

Frequency Range MHz	Limit (dBm)
30-25000	-20

Spurious RF conducted emissions


TestMode	Antenna	Channel(dBm)	FreqRange(MHz)	Result(dBm)	Limit(dBm)	Verdict
11B	Ant0	2412	Reference	6.79	---	PASS
			30~1000	-68.66	<=-13.21	PASS
			1000~26500	-39.72	<=-13.21	PASS
	Ant0	2437	Reference	7.19	---	PASS
			30~1000	-67.75	<=-12.81	PASS
			1000~26500	-51.76	<=-12.81	PASS
	Ant0	2462	Reference	7.10	---	PASS
			30~1000	-68.11	<=-12.9	PASS
			1000~26500	-52.14	<=-12.9	PASS
11G	Ant0	2412	Reference	5.41	---	PASS
			30~1000	-68.56	<=-14.59	PASS
			1000~26500	-26.54	<=-14.59	PASS
	Ant0	2437	Reference	6.37	---	PASS
			30~1000	-67.62	<=-13.63	PASS
			1000~26500	-43.99	<=-13.63	PASS
	Ant0	2462	Reference	6.40	---	PASS
			30~1000	-68.47	<=-13.6	PASS
			1000~26500	-38.78	<=-13.6	PASS
11N20SISO	Ant0	2412	Reference	5.69	---	PASS
			30~1000	-67.7	<=-14.31	PASS
			1000~26500	-24.94	<=-14.31	PASS
	Ant0	2437	Reference	5.53	---	PASS
			30~1000	-67.45	<=-14.47	PASS
			1000~26500	-50.7	<=-14.47	PASS
	Ant0	2462	Reference	6.37	---	PASS
			30~1000	-67.6	<=-13.63	PASS
			1000~26500	-30.63	<=-13.63	PASS

11B_Ant1_2412_0~Reference




Date: 16 FEB 2023 14:34:16

11B_Ant1_2412_30~1000




Date: 16 FEB 2023 14:34:22

11B_Ant1_2412_1000~26500




Date: 16 FEB 2023 14:34:30


11B_Ant1_2437_0~Reference




11B_Ant1_2437_30~1000




11B_Ant1_2437_1000~26500




11B_Ant1_2462_0~Reference




11B_Ant1_2462_30~1000




11B_Ant1_2462_1000~26500




11G_Ant1_2412_0~Reference




11G_Ant1_2412_30~1000




11G_Ant1_2412_1000~26500




11G_Ant1_2437_0~Reference




11G_Ant1_2437_30~1000



11G_Ant1_2437_1000~26500




11G_Ant1_2462_0~Reference




Date: 16 FEB 2023 14:52:13

11G_Ant1_2462_30~1000




Date: 16 FEB 2023 14:52:19

11G_Ant1_2462_1000~26500




Date: 16 FEB 2023 14:52:27

11N20SISO_Ant1_2412_0~Reference




Date: 16 FEB 2023 14:55:11

11N20SISO_Ant1_2412_30~1000




Date: 16 FEB 2023 14:55:17

11N20SISO_Ant1_2412_1000~26500




Date: 16 FEB 2023 14:55:25


11N20SISO_Ant1_2437_0~Reference




11N20SISO_Ant1_2437_30~1000



11N20SISO_Ant1_2437_1000~26500




11N20SISO_Ant1_2462_0~Reference




Date: 16 FEB 2023 15:02:17

11N20SISO_Ant1_2462_30~1000



Date: 16 FEB 2023 15:02:23

11N20SISO_Ant1_2462_1000~26500



Date: 16 FEB 2023 15:02:31

9.6 Band edge testing

Test Method

1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 kHz, VBW \geq RBW, Sweep = auto, Detector function = peak, Trace = max hold
3. Allow the trace to stabilize, use the peak and delta measurement to record the result.
4. The level displayed must comply with the limit specified in this Section.
5. Repeat the test at the hopping off and hopping on mode, submit all the plots.

Limit:


According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Frequency Range MHz	Limit (dBc)
30-25000	-20

Band edge testing


TestMode	Antenna	ChName	Channel (MHz)	RefLevel (dBm)	Result (dBm)	Limit (dBm)	Verdict
11B	Ant0	Low	2412	6.09	-37.45	<=-13.91	PASS
	Ant0	High	2462	7.01	-51.35	<=-12.99	PASS
11G	Ant0	Low	2412	4.79	-27.59	<=-15.21	PASS
	Ant0	High	2462	6.11	-30.31	<=-13.89	PASS
11N20	Ant0	Low	2412	4.53	-21.99	<=-15.47	PASS
	Ant0	Low	2462	6.60	-26.57	<=-13.4	PASS

11B_Ant1_Low_2412



Date: 16 FEB 2023 14:34:10

11B_Ant1_High_2462



Date: 16 FEB 2023 14:42:01


11G_Ant1_Low_2412




11G_Ant1_High_2462



11N20SISO_Ant1_Low_2412



11N20SISO_Ant1_High_2462



9.7 Spurious radiated emissions for transmitter

Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meters chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
4. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
6. Use the following spectrum analyzer settings According to C63.10:
For Below 1GHz
Use the following spectrum analyzer settings:
Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 100 KHz to 120KHz, VBW \geq RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious
RBW = 1MHz, VBW \geq RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) VBW \ [3 \times RBW].
- c) Detector = RMS (power averaging), if [span / (# of points in sweep)] \ RBW / 2.
Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Limit

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205, must comply with the radiated emission limits specified in section 15.209.


Frequency MHz	Field Strength μ V/m	Field Strength dB μ V/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

Spurious radiated emissions for transmitter


According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Transmitting spurious emission test result as below:

30MHz to 1000MHz:



Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
53.280000	21.53	40.00	18.47	200.0	H	0.0	20.92
102.689375	17.91	43.50	25.59	200.0	H	218.0	19.40
199.689375	19.16	43.50	24.34	200.0	H	291.0	19.40
305.298125	21.40	46.00	24.60	200.0	H	61.0	21.75
521.729375	28.03	46.00	17.97	200.0	H	117.0	26.48
939.375000	33.71	46.00	12.29	200.0	H	107.0	32.69




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
33.273750	22.92	40.00	17.08	100.0	V	355.0	17.15
52.188750	19.66	40.00	20.34	100.0	V	292.0	20.91
100.810000	17.61	43.50	25.89	100.0	V	346.0	19.19
197.082500	18.02	43.50	25.48	100.0	V	0.0	19.45
349.857500	22.91	46.00	23.09	100.0	V	160.0	23.49
904.394375	33.87	46.00	12.13	100.0	V	87.0	32.45

1GHz -18GHz:


11B-Ant0_2412MHz

Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5467.500000	48.86	79.50	30.64	150.0	H	103.0	5.63
12679.500000	50.02	79.50	29.48	150.0	H	103.0	18.21
16475.000000	51.97	79.50	27.53	150.0	H	356.0	22.16

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5218.500000	48.42	79.50	31.08	150.0	V	160.0	5.47
12338.500000	48.62	79.50	30.88	150.0	V	356.0	17.25
16813.500000	51.54	79.50	27.96	150.0	V	108.0	23.84

11B-Ant0_2437MHz
Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2967.500000	44.48	79.50	35.02	150.0	H	177.0	-0.99
5096.500000	48.68	79.50	30.82	150.0	H	239.0	4.81
17146.000000	52.47	79.50	27.03	150.0	H	333.0	24.19

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5452.000000	49.24	79.50	30.26	150.0	V	84.0	5.56
13219.500000	49.99	79.50	29.51	150.0	V	4.0	17.29
16787.500000	51.35	79.50	28.15	150.0	V	252.0	23.76

11B-Ant0_2462MHz
Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4524.500000	47.38	79.50	32.12	150.0	H	87.0	3.07
11885.500000	49.46	79.50	30.04	150.0	H	282.0	16.84
17061.500000	51.46	79.50	28.04	150.0	H	91.0	24.15

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3178.500000	45.40	79.50	34.10	150.0	V	0.0	-0.64
12541.500000	49.36	79.50	30.14	150.0	V	175.0	17.60
16769.000000	51.72	79.50	27.78	150.0	V	63.0	23.68

11G-Ant0_2412MHz
Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2386.000000	43.91	79.50	35.59	150.0	H	352.0	-2.98
5220.000000	49.52	79.50	29.98	150.0	H	219.0	5.47
16817.000000	51.64	79.50	27.86	150.0	H	300.0	23.85

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3814.500000	45.71	79.50	33.79	150.0	V	308.0	0.77
12669.000000	48.86	79.50	30.64	150.0	V	80.0	18.36
16820.000000	51.80	79.50	27.70	150.0	V	133.0	23.85

11G-Ant0_2437MHz
Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2976.500000	43.21	79.50	36.29	150.0	H	358.0	-0.95
9425.000000	46.23	79.50	33.27	150.0	H	134.0	13.65
17076.500000	51.52	79.50	27.98	150.0	H	300.0	24.14

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4010.500000	45.69	79.50	33.81	150.0	V	112.0	1.42
12685.500000	49.33	79.50	30.17	150.0	V	131.0	18.13
16964.000000	52.09	79.50	27.41	150.0	V	6.0	24.17

11G-Ant0_2462MHz
Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
3251.000000	44.50	79.50	35.00	150.0	H	355.0	-0.58
11073.500000	47.82	79.50	31.68	150.0	H	6.0	15.34
17811.500000	52.13	79.50	27.37	150.0	H	300.0	23.79

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
4185.000000	46.07	79.50	33.43	150.0	V	258.0	2.03
11149.000000	48.20	79.50	31.30	150.0	V	161.0	15.56
17139.500000	52.83	79.50	26.67	150.0	V	77.0	24.18

11N-HT20-Ant 0_2412MHz
Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5302.000000	49.06	79.50	30.44	150.0	H	0.0	5.26
15026.000000	51.86	79.50	27.64	150.0	H	131.0	18.84
17163.000000	52.06	79.50	27.44	150.0	H	185.0	24.21

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5134.500000	48.67	79.50	30.83	150.0	V	249.0	5.14
11032.000000	47.55	79.50	31.95	150.0	V	5.0	15.04
16737.000000	50.67	79.50	28.83	150.0	V	330.0	23.55

11N-HT20-Ant 0_2437MHz
Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5140.500000	48.84	79.50	30.66	150.0	H	94.0	5.18
13008.000000	49.48	79.50	30.02	150.0	H	215.0	17.81
17113.500000	51.58	79.50	27.92	150.0	H	6.0	24.15

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5225.000000	48.22	79.50	31.28	150.0	V	50.0	5.45
12663.000000	49.42	79.50	30.08	150.0	V	77.0	18.44
16834.000000	51.26	79.50	28.24	150.0	V	157.0	23.88

11N-HT20-Ant 0_2462MHz
Horizontal:



Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5459.000000	48.91	79.50	30.59	150.0	H	328.0	5.59
11953.500000	49.07	79.50	30.43	150.0	H	199.0	17.08
16826.500000	51.03	79.50	28.47	150.0	H	30.0	23.87

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
5699.500000	49.63	79.50	29.87	150.0	V	301.0	5.71
7565.000000	43.01	79.50	36.49	150.0	V	170.0	10.33
11097.500000	48.76	79.50	30.74	150.0	V	4.0	15.51

Above 18GHz:


11B_2412MHz

Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
23262.125000	42.65	74.00	31.35	150.0	H	0.0	0.12
24976.062500	42.52	74.00	31.48	150.0	H	4.0	1.21
29192.500000	43.25	74.00	30.75	150.0	H	177.0	1.24
32443.687500	44.72	74.00	29.28	150.0	H	207.0	1.95

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
22480.437500	42.42	74.00	31.58	150.0	V	31.0	0.43
25134.875000	42.76	74.00	31.24	150.0	V	312.0	1.25
28466.500000	42.50	74.00	31.50	150.0	V	0.0	0.96
33080.312500	45.50	74.00	28.50	150.0	V	126.0	2.41

11B_2437MHz
Horizontal:




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
23050.375000	41.43	74.00	32.57	150.0	H	0.0	0.52
24399.937500	42.82	74.00	31.18	150.0	H	264.0	0.59
27979.750000	42.74	74.00	31.26	150.0	H	66.0	1.24
38211.125000	49.39	74.00	24.61	150.0	H	188.0	6.03

Vertical




Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
20142.937500	41.63	74.00	32.37	150.0	V	265.0	-2.28
23820.375000	42.05	74.00	31.95	150.0	V	4.0	0.60
28023.750000	42.58	74.00	31.42	150.0	V	0.0	1.23
30400.437500	45.34	74.00	28.66	150.0	V	295.0	2.06
33817.312500	46.63	74.00	27.37	150.0	V	326.0	3.10

11B_2462MHz
Horizontal:



Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
21223.687500	41.72	74.00	32.28	150.0	H	0.0	-0.55
24784.250000	42.03	74.00	31.97	150.0	H	111.0	0.75
30492.562500	44.79	74.00	29.21	150.0	H	233.0	2.00
34262.812500	45.93	74.00	28.07	150.0	H	80.0	3.56

Vertical



Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
21040.812500	42.31	74.00	31.69	150.0	V	0.0	-0.62
26336.625000	43.20	74.00	30.80	150.0	V	199.0	1.46
31364.312500	44.42	74.00	29.58	150.0	V	153.0	1.72
38398.812500	49.19	74.00	24.81	150.0	V	16.0	6.57

10 Test Equipment List

Radiated Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2023-5-27
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9162	68-4-80-19-003	284	1	2023-7-12
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	1	2023-6-19
Pre-amplifier	Rohde & Schwarz	SCU 08F2	68-4-29-19-004	08400018	1	2023-8-17
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	1	2023-5-28
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	1	2023-5-27
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	2	2023-5-28
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.02	N/A	N/A

Radiated Emission 2# Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2023-5-28
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9162	68-4-80-19-003	284	1	2023-1-17
Wave Guide Antenna	ETS	3117	68-4-80-19-001	00218954	1	2023-5-9
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-001	100745	1	2023-5-28
Pre-amplifier	Rohde & Schwarz	SCU 18F	68-4-29-19-002	100746	1	2023-5-28
Sideband Horn Antenna	Q-PAR	QWH-SL-18-40-K-SG	68-4-80-14-008	12827	1	2023-7-12
Pre-amplifier	Rohde & Schwarz	SCU 40A	68-4-29-14-002	100432	1	2023-7-27
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-002	15542	1	2023-5-27
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	2	2023-5-28
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.02	N/A	N/A

Conducted Emission Test

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	68-4-74-19-002	102590	1	2023-5-27
LISN	Rohde & Schwarz	ENV216	68-4-87-19-001	102472	1	2023-5-27
Attenuator	Shanghai Huaxiang	TS2-26-3	68-4-81-16-003	080928189	1	2023-5-27
Test software	Rohde & Schwarz	EMC32	68-4-90-19-005-A01	Version10.35.02	N/A	N/A
Shielding Room	TDK	CSR #2	68-4-90-19-005	----	3	2025-10-15

Conducted RF Test System

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	1	2023-5-27
RF Switch Module	Rohde & Schwarz	OSP120/OS P-B157	68-4-93-14-003	101226/100851	1	2023-5-27
Power Splitter	Weinschel	1580	68-4-85-14-001	SC319	1	2023-5-28
10dB Attenuator	Weinschel	4M-10	68-4-81-14-003	43152	1	2023-5-27
10dB Attenuator	R&S	DNF	68-4-81-14-004	DNF-001	1	2023-5-27
10dB Attenuator	R&S	DNF	68-4-81-14-005	DNF-002	1	2023-5-27
10dB Attenuator	R&S	DNF	68-4-81-14-006	DNF-003	1	2023-5-27
10dB Attenuator	R&S	DNF	68-4-81-14-007	DNF-004	1	2023-5-27
Test software	Tonscend	System for BT/WIFI	68-4-74-14-006-A13	Version 2.6.77.0518	N/A	N/A
Shielding Room	TDK	TS8997	68-4-90-19-003	----	3	2025-10-15

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Conducted Emission 150kHz-30MHz (for test using AMN ENV432 or ENV4200)	3.33dB
Uncertainty for Radiated Spurious Emission 30MHz-1000MHz	Horizontal: 4.59dB; Vertical: 4.75dB;
Uncertainty for Radiated Spurious Emission 1000MHz-18000MHz	Horizontal: 5.08dB; Vertical: 5.09dB;
Uncertainty for Radiated Spurious Emission 18000MHz-40000MHz	Horizontal: 3.14dB; Vertical: 3.12dB;
Uncertainty for Conducted RF test with TS 8997	RF Power Conducted: 1.31dB Frequency test involved: 0.6×10 ⁻⁸ or 1%
Uncertainty Evaluation for Humidity	0.936%
Uncertainty Evaluation for Temperature	0.195 °C