

FCC Test Report

Report No.: AGC07307230302FE10

FCC ID	:	2AY9HVRR030012
PRODUCT DESIGNATION	:	remote control
BRAND NAME	:	N/A
MODEL NAME	:	100130570 Remote
APPLICANT	:	Artsun Enterprise Company Limited
DATE OF ISSUE	:	Mar. 10, 2023
STANDARD(S)	:	FCC Part 15 Subpart C §15.231
REPORT VERSION	:	V 1.0
<u>Attestation of</u>	<u><i>G</i>lo</u>	pal compliance (Shenzhen) Co., Ltd





Page 2 of 29

REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Mar. 10, 2023	Valid	Initial Release



Page 3 of 29

TABLE OF CONTENTS

1. GENERAL INFORMATION	5
2. PRODUCT INFORMATION	6
2.1 PRODUCT TECHNICAL DESCRIPTION	6
2.2 TEST FREQUENCY LIST	6
2.3 RELATED SUBMITTAL(S) / GRANT (S)	7
2.4 TEST METHODOLOGY	7
2.5 SPECIAL ACCESSORIES	7
2.6 EQUIPMENT MODIFICATIONS	7
2.7 ANTENNA REQUIREMENT	7
3. TEST ENVIRONMENT	8
3.1 ADDRESS OF THE TEST LABORATORY	8
3.2 TEST FACILITY	8
3.3 ENVIRONMENTAL CONDITIONS	9
3.4 MEASUREMENT UNCERTAINTY	9
3.5 LIST OF EQUIPMENTS USED	10
4.SYSTEM TEST CONFIGURATION	11
4.1 EUT CONFIGURATION	11
4.2 EUT EXERCISE	11
4.3 CONFIGURATION OF TESTED SYSTEM	11
4.4 EQUIPMENT USED IN TESTED SYSTEM	11
4.5 SUMMARY OF TEST RESULTS	12
5. DESCRIPTION OF TEST MODES	13
6. PROVISION FOR MOMENTARY OPERATION	14
6.1 PROVISIONS APPLICABLE	14
6.2 MEASUREMENT PROCEDURE	14
6.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	14
6.4 MEASUREMENT RESULTS	15
7. DUTY CYCLE CORRECTION FACTOR	16
7.1 PROVISIONS APPLICABLE	16
7.2 MEASUREMENT PROCEDURE	16
7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	16
7.4 MEASUREMENT RESULTS	16
8. 20 DB BANDWIDTH	19
8.1 PROVISIONS APPLICABLE	19



Page	4	of	29
i ugo	•	0.	20

8.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	
8.4 MEASUREMENT RESULTS	
9. RADIATED EMISSION	
9.1 LIMITS OF RADIATED EMISSION TEST	21
9.2 MEASUREMENT PROCEDURE	
9.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)	24
9.4 MEASUREMENT RESULT	
APPENDIX I: PHOTOGRAPHS OF TEST SETUP	
APPENDIX II: PHOTOGRAPHS OF TEST EUT	



Page 5 of 29

1. GENERAL INFORMATION

Applicant	Artsun Enterprise Company Limited	
Address	19H Maxgrandplaza, No.3 Tai Yau Street, San Po Kong, Kowloon, HongKong	
Manufacturer	Artsun Enterprise Company Limited	
Address	19H Maxgrandplaza, No.3 Tai Yau Street, San Po Kong, Kowloon, HongKong	
Factory	TELSTAR VIETNAM COMPANY LIMITED	
Address	CN-07-01 factory, lot CN-07, Van Trung Industrial Park, Van Trung Ward, Viet Yen District, Bac Giang Province, Viet Nam	
Product Designation	remote control	
Brand Name	N/A	
Test Model	100130570 Remote	
Deviation from Standard	No any deviation from the test method	
Date of receipt of test item	Mar. 07, 2023	
Date of Test	Mar. 07, 2023 to Mar. 10, 2023	
Test Result	Pass	
Test Report Form No	AGCTR-ER-FCC-SRDV1.0	

Thea Huang Prepared By Thea Huang Mar. 10, 2023 (Project Engineer) **Reviewed By** Calvin Liu Mar. 10, 2023 (Reviewer) x Ira Approved By Max Zhang

Max Zhang (Authorized Officer)

Mar. 10, 2023



2. PRODUCT INFORMATION

2.1 PRODUCT TECHNICAL DESCRIPTION

Hardware Version	RVE:02
Software Version	V1.0
Operation Frequency	433.92MHz
Modulation Type	ООК
Number of channels	1
Field Strength of Fundamental	78.28dBuV/m(PK)@3m 69.35dBuV/m(AV)@3m
Antenna Designation	PCB Antenna
Dimension	12mm*9mm
Antenna Gain	10dBi
Power Supply	DC 3V by battery

2.2 TEST FREQUENCY LIST

Frequency Band	Channel Number	Frequency
	01	433.92MHz

Note: According to manufacturer's requirements, periodic operation in the band 40.66-40.70 MHz and above 70MHz.



2.3 RELATED SUBMITTAL(S) / GRANT (S)

This submittal(s) (test report) is intended for **FCC ID: 2AY9HVRR030012** filing to comply with Part 2, Part 15 of the Federal Communication Commission rules.

2.4 TEST METHODOLOGY

The tests were performed according to following standards:

No.	Identity	Document Title		
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations		
2	FCC 47 CFR Part 15	Radio Frequency Devices		
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices		

2.5 SPECIAL ACCESSORIES

Not available for this EUT intended for grant.

2.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7 ANTENNA REQUIREMENT

Standard Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antennathat uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a brokenantenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The non-detachable antenna inside the device cannot be replaced by the user at will. The gain of the antenna is 2 dBi.



3. TEST ENVIRONMENT

3.1 ADDRESS OF THE TEST LABORATORY

Laboratory: Attestation of Global Compliance (Shenzhen) Co., Ltd.

Address: 1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China

3.2 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5488

Attestation of Global Compliance (Shenzhen) Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 5054.02

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

FCC-Registration No.: 975832

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files with Registration 975832.

IC-Registration No.: 24842 (CAB identifier: CN0063)

Attestation of Global Compliance (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the Certification and Engineering Bureau of Industry Canada. The acceptance letter from the IC is maintained in our files with Registration 24842.



3.3 ENVIRONMENTAL CONDITIONS

	NORMAL CONDITIONS	EXTREME CONDITIONS	
Temperature range (°C)	15 - 35	-20 - 50	
Relative humidty range	20 % - 75 %	20 % - 75 %	
Pressure range (kPa)	86 - 106	86 - 106	
Power supply			
Note: The Extreme Temperature and Extreme Voltages declared by the manufacturer.			

3.4 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y \pm U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty	
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$	
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$	
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$	
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$	
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$	
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$	
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$	



Report No.: AGC07307230302FE10 Page 10 of 29

3.5 LIST OF EQUIPMENTS USED

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023
LISN	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023
Test software	R&S	ES-K1	Ver.V1.71	N/A	N/A
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Aug. 04, 2022	Aug. 03, 2023
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	Mar. 22, 2022	Mar. 21, 2024
Attenuator	ZHINAN	E-002	N/A	Aug. 04, 2022	Aug. 03, 2024
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 21, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Aug. 03, 2022	Aug. 02, 2024
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 05, 2023	Jan. 04, 2025
Test software	Tonscend	JS32-RE	Ver.2.5	N/A	N/A



4.SYSTEM TEST CONFIGURATION

4.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commission's requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

4.2 EUT EXERCISE

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

4.3 CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:



4.4 EQUIPMENT USED IN TESTED SYSTEM

The Following Peripheral Devices And Interface Cables Were Connected During The Measurement: Test Accessories Come From The Laboratory

Test Accessories Come From The Manufacturer

Item	Equipment	Model No.	Identifier	Note
1	remote control	100130570 Remote	FCC ID: 2AY9HVRR030012	EUT



4.5 SUMMARY OF TEST RESULTS

ltem	FCC Rules	Description Of Test	Result
1	§15.203	Antenna Equipment P	
2	§15.231(a)	Transmission Time (Activated automatically)	Pass
3	§15.231	Field Strength of Fundamental	Pass
4	§15.209	Radiated Emission	Pass
5	§15.205(a)	Restricted Bands of Operation	Pass
6	§15.231(c)	20dB Bandwidth	Pass
7	§15.207	AC Power Line Conducted Emission N/A	

Note: 1.N/A means not applicable

Note: 2. The device under test is battery-powered and does not require evaluation of AC Power Line Conducted Emission.



5. DESCRIPTION OF TEST MODES

Summary table of Test Cases				
	Data Rate / Modulation			
Test Item	Short-range equipment / OOK			
Radiated&Conducted Test Cases	Mode 1: TX _433.92 MHz			
AC Conducted Emission				
Note: 1. Only the result of the worst case was recorded in the report, if no other cases.				

Unly the result of the worst case was recorded in the report, if no other cases.

1. 2. 3. The battery is full-charged during the test.

For Radiated Emission, 3axis were chosen for testing for each applicable mode.

For Conducted Test method, a temporary antenna connector is provided by the manufacture.



6. PROVISION FOR MOMENTARY OPERATION


6.1 PROVISIONS APPLICABLE

- (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- (2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- (3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.
- (4) Intentional radiators which are employed for radio control purposes during emergencies involving fire, security, and safety of life, when activated to signal an alarm, may operate during the pendency of the alarm condition.
- (5) Transmission of set-up information for security systems may exceed the transmission duration limits in (1) and (2) above, provided such transmission are under the control of a professional installer and do not exceed ten seconds after a manually operated switch is released or a transmitter is activated automatically. Such set-up information may include data.

6.2 MEASUREMENT PROCEDURE

- 1. Set the parameters of SPA as below:
- 2. Centre frequency = Operation Frequency
- 3. RBW=100KHz, VBW=300KHz Span: 0Hz Sweep time: 20S
- 4. Set the EUT to transmit by manually operated. Use the "View" function of SPA to find the transmission time of being released.
- 5. Record the data and Reported.

6.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)





6.4 MEASUREMENT RESULTS

Test Mode	Test Channel (MHz)	The time of stopping transmission after automatically activation by alarm sensor (s)	Limits	Pass or Fail
OOK	433.92	0.26	5s	Pass

🎉 Keysight Spe	ectrum Analyzer - Swept SA							
Center F	RF 50 Ω AC req 433.920000	MHz	SENSE:I		ALIGN AUTO Type: Log-Pwr	10:38:40 PM Mar 09 TRACE 12	3456	Frequency
Gentern	100 4 00.020000 1	PNO: Wide ++	Trig: Free Ru Atten: 10 dB			TYPE WWA	N N N N	
		IFGain:Low	Atten: To ub			Mkr1 260.0	me	Auto Tune
10 dB/div Log	Ref 0.00 dBm					-0.28	dB	
-10.0								Center Freq
-20.0	102							433.920000 MHz
-30.0	X <u>}</u>							
-40.0								Start Freq
-50.0								433.920000 MHz
-60.0								
-70.0								Stop Freq
-80.0 <mark></mark>								433.920000 MHz
-90.0								
Center 43 Res BW 1	3.920000 MHz 100 kHz	#VBW	/ 300 kHz		Sweep	Span 20.00 s (1001	0 Hz pts)	CF Step 100.000 kHz
			Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALU	JE 🔺	<u>Auto</u> Man
2 F 1		260.0 ms (Δ) 3.100 s	-0.28 dB -29.95 dBm					Freq Offset
3 4								0 Hz
5							=	
7								
9								
11							-	
MSG			III		STATU	3	+	
MSG					STATU	6		

Test Graphs Of Launch Operation Time



7. DUTY CYCLE CORRECTION FACTOR

7.1 PROVISIONS APPLICABLE

According to FCC Part 15.231 (b)(2) and 15.35 (c), For pulse operation transmitter, the averaging pulsed emissions are calculated by peak value of measured emission plus duty cycle factor.

7.2 MEASUREMENT PROCEDURE

After the antenna of the EUT is connected, the output signal of the EUT is received by the connected test antenna

To the spectrum analyzer. Set the center frequency to the actual working frequency of the EUT, and then set the spectrum analyzer to Zero Span for

Release time reading. During the test, the switch is released and the EUT is automatically closed

1. Set the parameters of SPA as below:

Centre frequency = Operation Frequency RBW=100KHz, VBW=300KHz Span: 0Hz

Sweep time: more than two pulse trains or more than each type of pulse occupancy time

- 2. Set the EUT to transmit by manually operated. Use the "Delta mark" function of SPA to find the period time between two pulse trains and each type of pulse occupancy time.
- 3. Record the plots and Reported.

7.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)



Spectrum Analyzer

7.4 MEASUREMENT RESULTS

Type of Pules	Width of Pules (ms)	Quantity of Pules (pcs)	Transmission Time (ms)	Total Time (Ton) (ms)
Pules 1	0.610	11	6.710	0.590
Pules 2	0.205	14	2.870	9.580

Test Period (Tp)	Total Time (Ton)	Duty Cycle	Duty Cycle Correction Factor
(ms)	(ms)	(%)	(dB)
26.80	9.580	35.75	-8.93


NOTE 1: Duty Cycle Factor=20 log (Duty Cycle) =-8.93 NOTE 2: The maximum reference value of the test cycle is 100ms.

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



Page 17 of 29




Test Graphs of Test Period





Page 18 of 29



Test Graphs of Pules 1



8. 20 dB BANDWIDTH

8.1 PROVISIONS APPLICABLE

According to FCC Part 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. Bandwidth is determined at the points 20 dB down from the modulated carrier

8.2 MEASUREMENT PROCEDURE

1. Set the parameters of SPA as below: Centre frequency = Operation Frequency RBW=1KHz VBW=3KHz Span: 100KHz Sweep time: Auto

- 2. Set the EUT to continue transmitting mode. Allow the trace to stabilize. Use the "N dB down" function of SPA to define the bandwidth.
- 3. Record the plots and Reported.

8.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)



Spectrum Analyzer



8.4 MEASUREMENT RESULTS

	Test Dat	ta of Occupied	d Bandwidth	and -20dB Bai	ndwidt	h	
Test Mode	Test Channel (MHz)	В	-20dB Bandwidth (Mł	Hz)		Limits (kHz)	Pass or Fail
OOK	433.92		0.01424			1084.8	Pass
		Test Grap	hs of -20dB	Bandwidth			
	Keysight Spectrum Analyzer - Occupied I L RF 50 Ω AC X DB -20.000 dB AC	Cente	SENSE:INT er Freq: 433.920000 MHz Free Run Avg Ho n: 10 dB	ALIGN AUTO 111:59:08 PM Radio Std: N Nd:>10/10 Radio Devic	lone	Save State	
	15 dB/div Ref -10.00 dB 25 0	3m		Span	<u>لی مراجع</u>	Register 1 Last: 5/25/2020 10:56:41 PM Register 2 (empty)	
	#Res BW 1 kHz	#	¢VBW/3kHz	Sweep 1		Register 3 (empty)	
	Occupied Bandwid Transmit Freq Error x dB Bandwidth	lth 28.998 kHz -21.509 kHz 14.24 kHz	Total Power OBW Power x dB	-33.3 dBm 99.00 % -20.00 dB		Register 4 (empty) More 1 of 3	
	MSG			STATUS			



9. RADIATED EMISSION

9.1 LIMITS OF RADIATED EMISSION TEST

15.209 Limit in the below table has to be followed:

Frequency	Distance	Field Streng	gths Limit		
(MHz)	Meters	բ V/m	dB(µV)/m		
0.009 ~ 0.490	300	2400/F(kHz)			
0.490 ~ 1.705	30	24000/F(kHz)			
1.705 ~ 30	30	30			
30 ~ 88	3	100	40.0		
88 ~ 216	3	150	43.5		
216 ~ 960	3	200	46.0		
960 ~ 1000	3	500	54.0		
Alt aug 4000		74.0 dB(μV)	/m (Peak)		
Above 1000	3	54.0 dB(µV)/r	n (Average)		
Remark: (1) Emission level dB μ V = 20 log Emission level μ V/m					
(2) The smal	(2) The smaller limit shall apply at the cross point between two frequency bands.				
(3) Distance	(3) Distance is the distance in meters between the measuring instrument, antenna and the				
closest p	pint of any part of the device	or system.			

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

15.231(b) Limit in the below table has to be followed:

Fundamental Frequency	Field Strength of Fundamental (microvolts/meter)	Field Strength of Harmonics (microvolts/meter)
40.66-40.70MHz	2250	225
70-130MHz	1250	125
130-174MHz	1250 to 3750	125 to 375
174-260MHz	3750	375
260-470MHz	3750 to 12500	375 to 1250
Above 470MHz	12500	1250



Fundamental Frequency	Field Strength of Fundamental (microvolts/meter)	Field Strength of Harmonics (microvolts/meter)
40.66-40.70MHz	1000	225
70-130MHz	1250	125
130-174MHz	1250 to 3750	125 to 375
174-260MHz	3750	375
260-470MHz	3750 to 12500	375 to 1250
Above 470MHz	12500	1250

15.231(e) Limit in the below table has to be followed:

9.2 MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not



have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.

- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.

Spectrum Parameter	Setting	
Start ~Stop Frequency 9KHz~150KHz/RB 200Hz for QP		
Start ~Stop Frequency 150KHz~30MHz/RB 9KHz for QP		
Start ~Stop Frequency 30MHz~1000MHz/RB 120KHz for QP		
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/3MHz for Peak, 1MHz/3MHz for Average	

The following table is the setting of spectrum analyzer and receiver.


Receiver Parameter	Setting			
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP			
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP			
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP			




Page 24 of 29

9.3 MEASUREMENT SETUP (BLOCK DIAGRAM OF CONFIGURATION)


RADIATED EMISSION TEST SETUP 9KHz-30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com



9.4 MEASUREMENT RESULT

RADIATED EMISSION BELOW 30MHz


The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.

RADIATED EMISSION FROM 30MHz ~1000MHz

			RADIATED	EMISSION F	ROM 30MHz	~1000MHz			
EUT	JT remote control			Model	Model Name		100130570 Remote		
Temp	Temperature 22° C				Relativ	Relative Humidity		54%	
Pressure 960hPa				Test V	oltage	Normal	Normal Voltage		
Test Mode Mod			Node 1		Anten	Antenna		Horizontal	
	92.0 dB	uV/m							
							Limit: — Margin: —	-	
						3 X			
	52							f	
							6 X	-1	
								J	
							4 5 X X	4/M	
				2		provider the man	wa www.		
			1	Juliant many	when and all a strate when and	A Share and the			
	12.0 minut	hunneredupendage	all and the sterring of all the	Marine	Programmer and the second of the				
	30.000	40 50	60 70 80	(MHz) 3	00 400 500	600 700 10	00.000	
Susp	ected Data	List_ Peak	Detection	ſ					
NO.	Freq.	Level	Factor	Limit	Margin	Height	Angle	Polarity	
NO.	[MHz]	[dBµV/m]		[dBµV/m]	[dB]	[cm]	[°]	-	
1	60.0690	19.03	13.20	40.00	20.97	150	357	Horizontal	
2	140.3420	23.18	17.17	43.50	20.32	150	35	Horizontal	
3	433.9200 612.0642	78.28	24.31	100.82	22.54	150	46	Horizontal	
4		32.48	26.37	46.00	13.52	150	41	Horizontal	
5	716.6820	32.83	26.35	46.00	13.17	150	49	Horizontal	
6 Final	869.1302	46.85	29.65	80.82	33.97	150	112	Horizontal	
rinal	data result_				AV Level				
NO.	Freq. [MHz]	PK Level [dBµV/m]		Duty cycle factor(dB)		Limit [dBµV/m]	Margin [dB]	Polarity	
1	433.9200	78.28	-8.	-8.93		80.82	11.47	Horizontal	
2	869.1302	46.85	-8.	-8.93		60.82	22.90	Horizontal	
DECI	JLT: PASS		•			•			



Page 26 of 29




RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Limit- Level.



Page 27 of 29






RESULT: PASS



RADIATED EMISSION FROM ABOVE 1GHZ



RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Margin=Limit-Level.

The "Factor" value can be calculated automatically by software of measurement system.



Page 29 of 29

APPENDIX I: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC07307230302AP01

APPENDIX II: PHOTOGRAPHS OF TEST EUT

Refer to the Report No.: AGC07307230302AP02

-----END OF REPORT-----



Conditions of Issuance of Test Reports

1. All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.