

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

FCC ID	2AY9HVRR030012				
Product Description	remote control				
Model Name	100130570 Remote				
	WLAN: 2.412GHz ~ 2.462GHz				
	WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz				
Frequency Band (Operating)	WLAN: 5.745GHz ~ 5825GHz				
	Bluetooth: 2.402GHz ~ 2.480GHz				
	⊠Others (433.92MHz)				
Device Category	Portable (<20cm separation)				
	Mobile (>20cm separation)				
	Others:				
	Single antenna				
	Multiple antennas				
Antenna Diversity	Tx diversity				
	Rx diversity				
	Tx/Rx diversity				
	78.28dBuV/m(PK)@3m				
Field Strength of Fundamental	69.35dBuV/m(AV)@3m				
Antenna Gain	10dBi				
Minimum Assessment Distance	5mm				
Evaluation Applied	MPE Evaluation				
	SAR Evaluation				
Evaluation Result	Pass				



2. PORTABLE DEVICE EVALUATION METHOD AND LIMIT

Following FCC KDB 447498 D01 "General SAR test exclusion guidance" The corresponding SAR Exclusion Threshold condition, listed below:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] [if(GHz)] s 3.0 for 1-g SAR and ñ 7.5 for 10-g extremity SAR, where

- > f(GHz) is the RF channel transmit frequency in GHz.
- > Power and distance are rounded to the nearest mW and mm before calculation.
- ➤ The result is rounded to one decimal place for comparison The test exclusions are applicable only when the minimum test separation distance is ≤50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.</p>
- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
 - a) [Threshold at 50 mm in step 1) + (test separation distance 50mm) (f(MHz)/150)] mW, at 100MHz to 1500 MHz;
 - b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)-10] mW at > 1500 MHz and ≤ 6 GHz;
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
 - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by [1 + log(100/f(MHz))] for test separation distances > 50 mm and < 200 mm.
 - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by 1/2 for test separation distances ñ 50 mm.
 - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.



3. MOBILE DEVICE EVALUATION METHOD AND LIMIT

Human exposure to RF emissions from mobile devices (47 CFR §2.1091) may be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and/or power density, as appropriate, since exposures are assumed to occur at distances of 20 cm or more from persons.

LIMITS FOR GENERAL FOFULATION / UNCONTROLLED EXPOSURE								
Frequency	E-field Strength (E)	Magnetic Field	Power Density	Averaging Time				
Range	• • • •	Strength (H)	(S)	E ² , H ² or S				
(MHz)	(V/m)	(A/m)	(mW/cm ²)	(Minutes)				
0.3 1.34	614	1.63	(100)*	30				
1.34 30	824/f	2.19/f	(180/f ²)*	30				
30 300	27.5	0.073	0.2	30				
300 1500			f/1500	30				
1500 100,000			1.0	30				

LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE

*Note:

1. f= Frequency in MHz * Plane-wave Equivalent Power Density

2. The averaging time for General Population/Uncontrolled exposure to fixed transmitters is not applicable for mobile and portable transmitters. See 47 CFR §§2.1091 and 2.1093 on source-based time-averaging requirement for mobile and portable transmitters.

S=PG/4πR²

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna



4. MEASUREMENT RESULT

Test Mode	Channel Frequency (MHz)	Field Strength (dBµV/m)	Max Output power (mW)	Calculati on Value (Note 1)	Threshold Value			
OOK								
SRD_PK	433.92	78.28	0.020	0.003	3.0			
SRD_AV	433.92	69.35	0.003	0.0004	3.0			

Note 1:Calculation Value =[(max. power of channel, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}]$.

SRD_PK: Fox example: 0.020/5*√0.43392=0.003≤ 3.0

SRD_AV: Fox example: 0.003/5*√0.43392=0.0004≤ 3.0

Note 2:Max Power (dBm) = Field Strength of Fundamental (dBuV/m@3m)-95.23

Note 3:Max Power (mW) = 10^{(Max power (dBm)/10)

According to KDB447498 D01 V06, threshold at which no SAR required is ≤3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required. 5. CONCLUSION

Since Source-base time average power is below SAR test exclusion power thresholds, the SAR evaluation is not required.