



# FCC TEST REPORT

For

Shenzhen Sdion Electronics & Technology Co., Ltd

Car Phone Holder Mount/WIRELESS CHARGING AUTO-CLAMPING CAR MOUNT/Electric wireless car charging mount

Test Model: HC-WC01

Additional Model No.: SDA068

Prepared for : Shenzhen Sdion Electronics & Technology Co., Ltd  
Address : 2nd Floor, A Building Bao San He, Guanlan Kukeng 1 Road, Longhua District, ShenZhen, China

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : November 24, 2023  
Number of tested samples : 2  
Serial number : A231122012-1(Engineer sample), A231122012-2(Normal sample)  
Date of Test : November 24, 2023 ~ December 04, 2023  
Date of Report : December 06, 2023





FCC TEST REPORT
FCC CFR 47 PART 15C

Report Reference No. : LCSA11233015EA

Date Of Issue : December 06, 2023

Testing Laboratory Name : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street, Baoan District, Shenzhen, China

Testing Location/ Procedure : Full application of Harmonised standards [checked]
Partial application of Harmonised standards [unchecked]
Other standard testing method [unchecked]

Applicant's Name : Shenzhen Sdion Electronics & Technology Co., Ltd

Address : 2nd Floor, A Building Bao San He, Guanlan Kukeng 1 Road, Longhua District, ShenZhen, China

Test Specification

Standard : FCC CFR 47 PART 15C

Test Report Form No. : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test Item Description : Car Phone Holder Mount/WIRELESS CHARGING
AUTO-CLAMPING CAR MOUNT/Electric wireless car charging mount

Trade Mark : N/A

Test Model : HC-WC01

Power Supply : Input: DC 5V/2A, DC 9V/2A
Wireless Charging Output: 15W(Max)
DC 3.7V by Rechargeable Li-ion Battery, 150mAh

Result : Positive

Compiled by:

Martin Lee (signature)

Martin Lee/ Administrator

Supervised by:

Cary Luo (signature)

Cary Luo/ Technique principal

Approved by:

Gavin Liang (signature)

Gavin Liang/ Manager



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add:101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



### FCC TEST REPORT

<b>Test Report No. :</b> LCSA11233015EA	<u>December 06, 2023</u> Date of issue
---	---

<b>Test Model</b> .....	: HC-WC01
<b>EUT</b> .....	: Car Phone Holder Mount/WIRELESS CHARGING AUTO-CLAMPING CAR MOUNT/Electric wireless car charging mount
<b>Applicant</b> .....	: <b>Shenzhen Sdion Electronics &amp; Technology Co., Ltd</b>
<b>Address</b> .....	: 2nd Floor, A Building Bao San He, Guanlan Kukeng 1 Road, Longhua District, ShenZhen, China
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /
<b>Manufacturer</b> .....	: <b>Shenzhen Sdion Electronics &amp; Technology Co., Ltd</b>
<b>Address</b> .....	: 2nd Floor, A Building Bao San He, Guanlan Kukeng 1 Road, Longhua District, ShenZhen, China
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /
<b>Factory</b> .....	: /
<b>Address</b> .....	: /
<b>Telephone</b> .....	: /
<b>Fax</b> .....	: /

<b>Test Result</b>	<b>Positive</b>
--------------------	-----------------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





### Revision History

Report Version	Issue Date	Revision Content	Revised By
000	December 06, 2023	Initial Issue	--





# TABLE OF CONTENTS

- 1. GENERAL INFORMATION ..... 6**
  - 1.1 Description of Device (EUT) ..... 6
  - 1.2 Support equipment List ..... 6
  - 1.3 External I/O Cable ..... 6
  - 1.4 Description of Test Facility ..... 6
  - 1.5 Statement of the Measurement Uncertainty ..... 6
  - 1.6 Measurement Uncertainty ..... 7
  - 1.7 Description of Test Modes ..... 7
- 2. TEST METHODOLOGY ..... 8**
  - 2.1 EUT Configuration ..... 8
  - 2.2 EUT Exercise ..... 8
  - 2.3 General Test Procedures ..... 8
    - 2.3.1 Conducted Emissions ..... 8
    - 2.3.2 Radiated Emissions ..... 8
  - 2.4. Test Sample ..... 8
- 3. SYSTEM TEST CONFIGURATION ..... 9**
  - 3.1 Justification ..... 9
  - 3.2 EUT Exercise Software ..... 9
  - 3.3 Special Accessories ..... 9
  - 3.4 Block Diagram/Schematics ..... 9
  - 3.5 Equipment Modifications ..... 9
  - 3.6 Test Setup ..... 9
- 4. SUMMARY OF TEST EQUIPMENT ..... 10**
- 5. SUMMARY OF TEST RESULT ..... 11**
- 6. RADIATED EMISSION MEASUREMENT ..... 12**
  - 6.1. Block Diagram of Test Setup ..... 12
  - 6.2. Radiated Emission Limit ..... 13
  - 6.3. EUT Configuration on Measurement ..... 13
  - 6.4. Operating Condition of EUT ..... 13
  - 6.5. Measuring Setting ..... 14
  - 6.6. Test Procedure ..... 14
  - 6.7. Test Results ..... 15
- 7. 20 DB BANDWIDTH MEASUREMENT ..... 19**
  - 7.1. Block Diagram of Test Setup ..... 19
  - 7.2. Test Procedure ..... 19
  - 7.3. Test Results ..... 20
- 8. PHOTOGRAPHS OF TEST SETUP ..... 21**
- 9. EXTERNAL PHOTOGRAPHS OF THE EUT ..... 21**
- 10. INTERNAL PHOTOGRAPHS OF THE EUT ..... 21**





# 1. GENERAL INFORMATION

## 1.1 Description of Device (EUT)

- EUT : Car Phone Holder Mount/WIRELESS CHARGING AUTO-CLAMPING CAR MOUNT/Electric wireless car charging mount
- Test Model : HC-WC01
- Additional Model No. : SDA068
- Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested
- Power Supply : Input: DC 5V/2A, DC 9V/2A  
Wireless Charging Output: 15W(Max)  
DC 3.7V by Rechargeable Li-ion Battery, 150mAh
- Hardware Version : /
- Software Version : /
- Wireless Charging :
  - Operating Frequency : 110.0~205.0KHz
  - Modulation Type : Continuous Wave
  - Antenna Type : Coil Antenna

## 1.2 Support equipment List

Manufacturer	Description	Model	Serial Number	Certificate
Honor	Phone	V30pro	---	FCC
SHENZHEN TIANYIN ELECTRONICS CO., LTD	Power Adapter	TPA-46050200UU	---	FCC

Note: Auxiliary equipment is provided by the laboratory.

## 1.3 External I/O Cable

I/O Port Description	Quantity	Cable
Type-C USB Port	1	USB Cable: 1.0m, unshielded

## 1.4 Description of Test Facility

NVLAP Accreditation Code is 600167-0.

FCC Designation Number is CN5024

CAB identifier is CN0071.

CNAS Registration Number is L4595.

Test Firm Registration Number: 254912.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

## 1.5 Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add:101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

### 1.6 Measurement Uncertainty

Test Item	Frequency Range	Uncertainty	Note
Radiation Uncertainty	9KHz~30MHz	3.10dB	(1)
	30MHz~200MHz	2.96dB	(1)
	200MHz~1000MHz	3.10dB	(1)
	1GHz~26.5GHz	3.80dB	(1)
	26.5GHz~40GHz	3.90dB	(1)
Conduction Uncertainty	150kHz~30MHz	1.63dB	(1)
Power disturbance	30MHz~300MHz	1.60dB	(1)

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 1.7 Description of Test Modes

Equipment under test was operated during the measurement under the following conditions:

Charging and communication mode

Modulation Type: CW (Continuous Wave)

Test Modes		
Mode 1	Battery+Car charger(9V/2A)+EUT+mobile phone (Battery Status: <1%)	Record
Mode 2	Battery+Car charger(9V/2A)+EUT+mobile phone (Battery Status: <50%)	Pre-tested
Mode 3	Battery+Car charger(9V/2A)+EUT+mobile phone (Battery Status: 100%)	Pre-tested

Note: All test modes were pre-tested, but we only recorded the worst case in this report.





## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10-2013, FCC CFR PART 15C 15.207.

### 2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2 EUT Exercise

The EUT was operated in the normal operating mode and a continuous transmits mode for other tests. According to its specifications, the EUT must comply with the requirements of the Section 15.207 under the FCC Rules Part 15 Subpart C.

### 2.3 General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz and 1.5 m above ground plane above 1GHz. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

### 2.4. Test Sample

The application provides 2 samples to meet requirement;

Sample Number	Description
Sample 1(A231122012-1)	Engineer sample – continuous transmit
Sample 2(A231122012-2)	Normal sample – Intermittent transmit







### 3. SYSTEM TEST CONFIGURATION

#### 3.1 Justification

The system was configured for testing in a normal condition.

#### 3.2 EUT Exercise Software

N/A.

#### 3.3 Special Accessories

No.	Equipment	Manufacturer	Model No.	Serial No.	Length	shielded/ unshielded	Notes
/	/	/	/	/	/	/	/

#### 3.4 Block Diagram/Schematics

Please refer to the related document.

#### 3.5 Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### 3.6 Test Setup

Please refer to the test setup photo.





#### 4. SUMMARY OF TEST EQUIPMENT

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	MXA Signal Analyzer	Agilent	N9020A	MY49100040	2023-06-09	2024-06-08
2	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2023-07-17	2024-07-16
3	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2023-06-09	2024-06-08
4	Positioning Controller	Max-Full	MF7802BS	MF780208586	N/A	N/A
5	EMI Test Software	AUDIX	E3	/	N/A	N/A
6	EMI Test Receiver	R&S	ESR 7	101181	2023-08-15	2024-08-14
7	Active Loop Antenna	SCHWARZBECK	FMZB 1519B	00005	2021-08-29	2024-08-28
8	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
9	EMI Test Receiver	R&S	ESPI	101940	2023-08-15	2024-08-14
10	Artificial Mains	R&S	ENV216	101288	2023-06-09	2024-06-08
11	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2023-06-09	2024-06-08
12	EMI Test Software	Farad	EZ	/	N/A	N/A



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add:101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



### 5. SUMMARY OF TEST RESULT

FCC Rules	Description of Test	Test Sample	Result
§15.207(a)	AC Conducted Emissions	Sample 1	N/A
§15.209	Radiated Spurious Emissions	Sample 1	Compliant
§15.215	20 dB Bandwidth	Sample 1	Compliant

Remark: The measurement uncertainty is not included in the test result.


N/A – Not Applicable!!!






## 6. RADIATED EMISSION MEASUREMENT

### 6.1. Block Diagram of Test Setup



Below 30MHz



Below 1GHz





### 6.2. Radiated Emission Limit

15.205 (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
\1\ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(\2\)
13.36-13.41			

\1\ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

\2\ Above 38.6

According to §15.247 (d): 20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

### 6.3. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 6.4. Operating Condition of EUT

(1) Setup the EUT as shown in Section 6.1.





## 6.5. Measuring Setting

The following table is the setting of spectrum analyzer and receiver.

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP/Average
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP/Average
Start ~ Stop Frequency	30MHz~1000MHz / RB 100kHz for QP

## 6.6. Test Procedure

### 1) Sequence of testing 9 kHz to 30 MHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.0 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

#### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add:101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: webmaster@lcs-cert.com | Web: www.lcs-cert.com

Scan code to check authenticity



## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

## 6.7. Test Results

PASS.

*Only report the worst test data (Mode 1) in test report;*


*The test data please refer to following page:*

Temperature	23.8°C	Humidity	52.1%
Test Engineer	Taylor Hu	Configurations	Transmit





0.009 MHz – 30 MHz  
0 degree



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	0.1121	80.86	-9.71	71.15	106.54	-35.39	QP
2	0.3353	58.56	-9.73	48.83	97.08	-48.25	QP
3	0.9318	54.67	-9.32	45.35	68.22	-22.87	QP
4	4.8358	46.92	-9.40	37.52	69.54	-32.02	QP
5	6.4235	44.01	-9.40	34.61	69.54	-34.93	QP
6	13.6584	37.00	-10.02	26.98	69.54	-42.56	QP

Remark: 1). Measured at antenna position 0 degree and 90 degree, recorded worst case at 0 degree.

2). Margin=Reading level + Factor- Limit








Temperature	23.8°C	Humidity	52.1%
Test Engineer	Taylor Hu	Configurations	Transmit

Below 1GHz

Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	35.2511	40.82	-17.79	23.03	40.00	-16.97	QP
2	66.4989	42.05	-19.25	22.80	40.00	-17.20	QP
3	93.4402	42.25	-18.64	23.61	43.50	-19.89	QP
4	181.2834	55.28	-18.51	36.77	43.50	-6.73	QP
5	273.2340	47.88	-15.38	32.50	46.00	-13.50	QP
6	726.8052	43.08	-10.50	32.58	46.00	-13.42	QP





Vertical



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	35.2512	44.27	-17.79	26.48	40.00	-13.52	QP
2	67.4382	42.15	-19.32	22.83	40.00	-17.17	QP
3	93.4402	43.64	-18.64	25.00	43.50	-18.50	QP
4	180.0165	57.36	-18.68	38.68	43.50	-4.82	QP
5	266.6089	49.36	-15.45	33.91	46.00	-12.09	QP
6	729.3583	33.28	-10.46	22.82	46.00	-23.18	QP


- 1). Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 2). Margin=Reading level + Factor- Limit.





## 7. 20 DB BANDWIDTH MEASUREMENT

### 7.1. Block Diagram of Test Setup



### 7.2. Test Procedure

Use the following spectrum analyzer settings:

Span = 1kHz

RBW = 100Hz

VBW = 300Hz

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).



Shenzhen LCS Compliance Testing Laboratory Ltd.

Add: 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Yabianxueziwei, Shajing Street, Baoan District, Shenzhen, 518000, China

Tel: +(86) 0755-82591330 | E-mail: [webmaster@lcs-cert.com](mailto:webmaster@lcs-cert.com) | Web: [www.lcs-cert.com](http://www.lcs-cert.com)

Scan code to check authenticity




### 7.3. Test Results

Test Result Of 20dB Bandwidth Measurement			
Test Mode	Test Frequency (MHz)	20dB Bandwidth (kHz)	Limit (kHz)
TM1	0.1383	0.261	Non-Specified

Result: Pass

Please refer to the following page for test plot.





## 8. PHOTOGRAPHS OF TEST SETUP

Please refer to separated files for Test Setup Photos of the EUT.

## 9. EXTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

## 10. INTERNAL PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----

