

FCC TEST REPORT

FCC ID:2AY9T-45092VSB02

Report Number..... : ZKT-211213L6860-03

Date of Test..... Dec. 02, 2021 – Dec. 23, 2021

Date of issue : Dec. 23, 2021

Total number of pages 86

Test Result : PASS

Testing Laboratory..... : **Shenzhen ZKT Technology Co., Ltd.**

Address : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

Applicant's name : Shenzhen Ranboda Technology Co., Ltd

Address : Building A20, Fengminggu Intelligent Industrial Park, 4048 Songbai Road, Fenghuang Street, Guangming New District, Shenzhen, China

Manufacturer's name : Shenzhen Ranboda Technology Co., Ltd

Address : Building A20, Fengminggu Intelligent Industrial Park, 4048 Songbai Road, Fenghuang Street, Guangming New District, Shenzhen, China

Test specification:

Standard : FCC CFR Title 47 Part 15 Subpart C Section 15.247
ANSI C63.10:2013
KDB558074 D0115.247 Meas Guidance v 05r02

Test procedure..... : /

Non-standard test method : N/A

Test Report Form No. : TRF-EL-110_V0

Test Report Form(s) Originator : ZKT Testing

Master TRF : Dated: 2020-01-06

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name : 4K Signage Box 2

Trademark : N/A

Model/Type reference : 45092VSB02

Ratings..... : AC 120V 60Hz

Testing procedure and testing location:

Testing Laboratory..... : **Shenzhen ZKT Technology Co., Ltd.**

Address..... : 1/F, No. 101, Building B, No. 6, Tangwei Community
Industrial Avenue, Fuhai Street, Bao'an District,
Shenzhen, China

Tested by (name + signature)

Am. He

Reviewer (name + signature).....

Joe. Liu

Approved (name + signature)


Labe. Xie

Table of Contents

	Page
1. VERSION	5
2. SUMMARY OF TEST RESULTS	6
2.1 TEST FACILITY	7
2.2 MEASUREMENT UNCERTAINTY	7
3. GENERAL INFORMATION	7
3.1 GENERAL DESCRIPTION OF EUT	7
3.2 DESCRIPTION OF TEST MODES	8
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	9
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
3.5EQUIPMENTS LIST FOR ALL TEST ITEMS	10
4. EMC EMISSION TEST	11
4.1 CONDUCTED EMISSION MEASUREMENT	11
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
4.1.2 TEST PROCEDURE	11
4.1.3 DEVIATION FROM TEST STANDARD	11
4.1.4 TEST SETUP	12
4.1.5 EUT OPERATING CONDITIONS	12
4.1.6 TEST RESULT	13
4.2 RADIATED EMISSION MEASUREMENT	15
4.2.1 RADIATED EMISSION LIMITS	15
4.2.2 TEST PROCEDURE	15
4.2.3 DEVIATION FROM TEST STANDARD	16
4.2.4 TEST SETUP	16
4.2.5 EUT OPERATING CONDITIONS	17
4.2.6 TEST RESULTS	18
5.RADIATED BAND EMISSIONMEASUREMENT	31
5.1 TEST REQUIREMENT:	31
5.2 TEST PROCEDURE	31
5.3 DEVIATION FROM TEST STANDARD	31
5.4 TEST SETUP	32
5.5 EUT OPERATING CONDITIONS	32
5.6 TEST RESULT	33
6.POWER SPECTRAL DENSITY TEST	38
6.1 APPLIED PROCEDURES / LIMIT	38
6.2 TEST PROCEDURE	38
6.3 DEVIATION FROM STANDARD	38
6.4 TEST SETUP	38
6.5 EUT OPERATION CONDITIONS	38

6.6 TEST RESULT	39
7. CHANNEL BANDWIDTH	44
7.1 APPLIED PROCEDURES / LIMIT	44
7.2 TEST PROCEDURE	44
7.3 DEVIATION FROM STANDARD	44
7.4 TEST SETUP	44
7.5 EUT OPERATION CONDITIONS	44
7.6 TEST RESULT	45
8.OUTPUT POWER TEST	50
8.1 APPLIED PROCEDURES/LIMIT	50
8.2 TEST PROCEDURE	50
8.3 DEVIATION FROM STANDARD	50
8.4 TEST SETUP	50
8.5 EUT OPERATION CONDITIONS	50
8.6 TEST RESULT	51
9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION	52
9.1 APPLICABLE STANDARD	52
9.2 TEST PROCEDURE	52
9.3 DEVIATION FROM STANDARD	52
9.4 TEST SETUP	52
9.5 EUT OPERATION CONDITIONS	52
9.6 TEST RESULTS	52
10. ANTENNA REQUIREMENT	85
11. TEST SETUP PHOTO	86
12. EUT CONSTRUCTIONAL DETAILS	86

1. VERSION

ReportNo.	Version	Description	Approved
ZKT-211213L6860-03	Rev.01	Initial issue of report	Dec. 23, 2021

2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Result	Remark
FCC part 15.203/15.247 (c)	Antenna requirement	PASS	
FCC part 15.207	AC Power Line Conducted Emission	PASS	
FCC part 15.247 (b)(3)	Conducted Peak Output Power	PASS	
FCC part 15.247 (a)(2)	Channel Bandwidth& 99% OCB	PASS	
FCC part 15.247 (e)	Power Spectral Density	PASS	
FCC part 15.247(d)	Band Edge	PASS	
FCC part 15.205/15.209	Spurious Emission	PASS	

NOTE:

(1) " N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.

Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225

Designation Number: CN1299

IC Registered No.: 27033


2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$ · where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$ · providing a level of confidence of approximately 95 % .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF powerconducted	$\pm 0.16\text{dB}$
3	Spurious emissionsconducted	$\pm 0.21\text{dB}$
4	All emissionsradiated(<1G)	$\pm 4.68\text{dB}$
5	All emissionsradiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^{\circ}\text{C}$
7	Humidity	$\pm 2\%$

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	4K Signage Box 2	
Model No.:	45092VSB02	
Sample(s) Status:	Engineer sample	
Channel numbers:	802.11b/802.11g /802.11n(HT20):11 802.11n(HT40):7	
Channel separation:	5MHz	
Modulation technology:	802.11b: Direct Sequence Spread Spectrum(DSSS) 802.11g/802.11n(H20)/802.11 n(HT40): Orthogonal Frequency Division Multiplexing(OFDM)	
Antenna Type:	FPC antenna	
Antenna gain:	WIFI ANT1: 3dBi; WIFI ANT2: 3dBi ;	MIMO: 6.01dBi
Power supply:	AC 120V 60Hz	
POWER ADAPTER:	INPUT:AC100-240V~ 50/60Hz OUTPUT:12V  1A	

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	X	

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency (MHz)
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

Test channel	Frequency (MHz)
	802.11n(HT40)
Lowest channel	2422MHz
Middle channel	2437MHz
Highest channel	2452MHz

WorstCase Configuration

Description	MIMO (802.11N-HT20 low channel)
Antenna	MIMO
Channel	1
Operating Frequency (MHz)	2412
Data Rate (Mbps)	6.5Mbps

3.2 DESCRIPTION OF TEST MODES

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the duty cycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:


Pre-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)	802.11n(HT40)
Data rate	1Mbps	6Mbps	6.5Mbps	MCS0

Test Software	Test Tool
Powerlevelsetup	<20dBm

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission



Radiated Emission




Conducted Spurious



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Tablet PC	N/A	M10	N/A	EUT
2	adapter	/	INPUT:AC100-240V~ 50/60Hz OUTPUT:12V  1A	N/A	Provide by client

Item	Shielded Type	Ferrite Core	Length	Note

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

3.5EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Sep. 21, 2021	Sep. 22, 2022
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Sep. 21, 2021	Sep. 22, 2022
3	Test Receiver (9kHz-7GHz)	R&S	ESC17	101169	Sep. 21, 2021	Sep. 22, 2022
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Sep. 21, 2021	Sep. 22, 2022
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Sep. 21, 2021	Sep. 22, 2022
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Sep. 21, 2021	Sep. 22, 2022
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Sep. 21, 2021	Sep. 22, 2022
8	Amplifier (1GHz-40GHz)	QUANJUDA	DLE-161	097	Sep. 21, 2021	Sep. 22, 2022
9	Loop Antenna (9kHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Sep. 21, 2021	Sep. 22, 2022
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Sep. 21, 2021	Sep. 22, 2022
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Sep. 21, 2021	Sep. 22, 2022
13	CMW500 Test	R&S	CMW500	106504	Sep. 21, 2021	Sep. 22, 2022
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Sep. 21, 2021	Sep. 22, 2022
15	Signal Generator	Agilent	N5182A	MY47420215	Sep. 21, 2021	Sep. 22, 2022
16	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
17	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Sep. 21, 2021	Sep. 22, 2022
2	LISN	CYBERTEK	EM5040A	E185040014 9	Sep. 21, 2021	Sep. 22, 2022
3	Test Cable	N/A	C01	N/A	Sep. 21, 2021	Sep. 22, 2022
4	Test Cable	N/A	C02	N/A	Sep. 21, 2021	Sep. 22, 2022
5	EMI Test Receiver	R&S	ESRP3	101946	Sep. 21, 2021	Sep. 22, 2022
6	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 21, 2021	Sep. 22, 2022

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION LIMITS

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.


4.1.2 TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.e.
8. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP




4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULT

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase	L
Test Voltage :	AC 120V/60Hz		




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1532	43.48	9.75	53.23	65.82	-12.59	QP	
2	0.1582	26.50	9.75	36.25	55.55	-19.30	AVG	
3	0.5380	19.69	9.85	29.54	46.00	-16.46	AVG	
4	0.5620	36.35	9.84	46.19	56.00	-9.81	QP	
5 *	1.1697	36.68	9.73	46.41	56.00	-9.59	QP	
6	1.1857	20.18	9.73	29.91	46.00	-16.09	AVG	
7	2.3420	19.79	9.63	29.42	46.00	-16.58	AVG	
8	2.3660	36.46	9.63	46.09	56.00	-9.91	QP	
9	5.3018	20.16	9.65	29.81	50.00	-20.19	AVG	
10	5.9419	38.21	9.64	47.85	60.00	-12.15	QP	
11	11.2139	39.90	9.77	49.67	60.00	-10.33	QP	
12	12.9618	23.05	9.75	32.80	50.00	-17.20	AVG	

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor

Temperature :	26°C	Relative Humidity:	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz		



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1516	24.81	9.75	34.56	55.91	-21.35	AVG	
2	0.1565	44.61	9.75	54.36	65.64	-11.28	QP	
3	0.5701	34.14	9.84	43.98	56.00	-12.02	QP	
4	0.5978	15.10	9.84	24.94	46.00	-21.06	AVG	
5 *	1.1818	37.80	9.73	47.53	56.00	-8.47	QP	
6	1.1938	11.49	9.73	21.22	46.00	-24.78	AVG	
7	1.8898	11.61	9.66	21.27	46.00	-24.73	AVG	
8	2.4060	36.40	9.65	46.05	56.00	-9.95	QP	
9	6.5057	37.81	9.63	47.44	60.00	-12.56	QP	
10	7.3738	14.64	9.61	24.25	50.00	-25.75	AVG	
11	12.3857	37.06	9.75	46.81	60.00	-13.19	QP	
12	13.9177	18.10	9.71	27.81	50.00	-22.19	AVG	

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Measurement Level = Reading level + Correct Factor

4.2 RADIATED EMISSION MEASUREMENT

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	

4.2.1 RADIATED EMISSION LIMITS

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoiccamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

- g. Different from above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change from table 0.8 metre to 1.5 metre (Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD


No deviation

4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.


Between 30MHz – 1GHz

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	AC 120V/60Hz		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		43.5057	33.62	-11.41	22.21	40.00	-17.79	QP	300	180	
2		81.7833	38.75	-13.78	24.97	40.00	-15.03	QP	100	360	
3	*	139.3613	46.09	-5.74	40.35	43.50	-3.15	QP	300	360	
4		326.7395	32.73	-3.23	29.50	46.00	-16.50	QP	100	180	
5		501.1790	28.13	-0.15	27.98	46.00	-18.02	QP	300	360	
6		912.8620	26.04	7.30	33.34	46.00	-12.66	QP	100	180	

Temperature:	26°C	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	AC 120V/60Hz		



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	cm	degree	Comment
1	!	30.5306	34.57	0.66	35.23	40.00	-4.77	QP	100	180
2	!	41.5670	44.51	-10.12	34.39	40.00	-5.61	QP	100	360
3	*	78.4133	50.04	-13.56	36.48	40.00	-3.52	QP	100	360
4	!	126.7723	45.04	-5.28	39.76	43.50	-3.74	QP	100	180
5		236.6447	34.91	-6.14	28.77	46.00	-17.23	QP	100	180
6		900.1474	28.10	7.17	35.27	46.00	-10.73	QP	100	360

- Remarks:
- 1.Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
 - 2.The emission levels of other frequencies are very lower than the limit and not show in test report.
 - 3.The test data shows only the worst case-MIMO -802.11N-HT20 highest channel

1GHz~25GHz

802.11b-ANT1

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	58.31	30.55	5.77	24.66	58.19	74.00	-15.81	PK
V	4824	45.25	30.55	5.77	24.66	45.13	54.00	-8.87	AV
V	7236	56.27	30.33	6.32	24.55	56.81	74.00	-17.19	PK
V	7236	44.87	30.33	6.32	24.55	45.41	54.00	-8.59	AV
V	9648	44.30	30.85	7.45	24.69	45.59	74.00	-28.41	PK
V	9648	44.13	30.85	7.45	24.69	45.42	54.00	-8.58	AV
H	4824	43.69	31.02	8.99	25.57	47.23	74.00	-26.77	PK
H	4824	45.01	31.02	8.99	25.57	48.55	54.00	-5.45	AV
H	7236	44.48	30.55	5.77	24.66	44.36	74.00	-29.64	PK
H	7236	46.60	30.55	5.77	24.66	46.48	54.00	-7.52	AV
H	9648	44.28	30.33	6.32	24.55	44.82	74.00	-29.18	PK
H	9648	43.63	30.33	6.32	24.55	44.17	54.00	-9.83	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	52.02	30.55	5.77	24.66	51.90	74.00	-22.10	PK
V	4874	43.59	30.55	5.77	24.66	43.47	54.00	-10.53	AV
V	7311	56.02	30.33	6.32	24.55	56.56	74.00	-17.44	PK
V	7311	45.44	30.33	6.32	24.55	45.98	54.00	-8.02	AV
V	9748	45.62	30.85	7.45	24.69	46.91	74.00	-27.09	PK
V	9748	46.07	30.85	7.45	24.69	47.36	54.00	-6.64	AV
H	4874	44.49	31.02	8.99	25.57	48.03	74.00	-25.97	PK
H	4874	44.99	31.02	8.99	25.57	48.53	54.00	-5.47	AV
H	7311	46.11	30.55	5.77	24.66	45.99	74.00	-28.01	PK
H	7311	45.00	30.55	5.77	24.66	44.88	54.00	-9.12	AV
H	9748	44.44	30.33	6.32	24.55	44.98	74.00	-29.02	PK
H	9748	43.90	30.33	6.32	24.55	44.44	54.00	-9.56	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampli fier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	52.05	30.55	5.77	24.66	51.93	74.00	-22.07	PK
V	4924	43.21	30.55	5.77	24.66	43.09	54.00	-10.91	AV
V	7386	56.71	30.33	6.32	24.55	57.25	74.00	-16.75	PK
V	7386	46.14	30.33	6.32	24.55	46.68	54.00	-7.32	AV
V	9848	45.09	30.85	7.45	24.69	46.38	74.00	-27.62	PK
V	9848	44.49	30.85	7.45	24.69	45.78	54.00	-8.22	AV
H	4924	44.50	31.02	8.99	25.57	48.04	74.00	-25.96	PK
H	4924	43.79	31.02	8.99	25.57	47.33	54.00	-6.67	AV
H	7386	46.37	30.55	5.77	24.66	46.25	74.00	-27.75	PK
H	7386	45.98	30.55	5.77	24.66	45.86	54.00	-8.14	AV
H	9848	45.74	30.33	6.32	24.55	46.28	74.00	-27.72	PK
H	9848	43.68	30.33	6.32	24.55	44.22	54.00	-9.78	AV

802.11g-ANT1

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Low Channel:2412MHz									
V	4824	58.27	30.55	5.77	24.66	58.15	74.00	-15.85	PK
V	4824	45.33	30.55	5.77	24.66	45.21	54.00	-8.79	AV
V	7236	57.06	30.33	6.32	24.55	57.60	74.00	-16.40	PK
V	7236	46.36	30.33	6.32	24.55	46.90	54.00	-7.10	AV
V	9648	44.31	30.85	7.45	24.69	45.60	74.00	-28.40	PK
V	9648	44.11	30.85	7.45	24.69	45.40	54.00	-8.60	AV
H	4824	44.69	31.02	8.99	25.57	48.23	74.00	-25.77	PK
H	4824	44.79	31.02	8.99	25.57	48.33	54.00	-5.67	AV
H	7236	46.02	30.55	5.77	24.66	45.90	74.00	-28.10	PK
H	7236	45.73	30.55	5.77	24.66	45.61	54.00	-8.39	AV
H	9648	45.69	30.33	6.32	24.55	46.23	74.00	-27.77	PK
H	9648	45.85	30.33	6.32	24.55	46.39	54.00	-7.61	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
Middle Channel:2437MHz									
V	4874	52.05	30.55	5.77	24.66	51.93	74.00	-22.07	PK
V	4874	44.74	30.55	5.77	24.66	44.62	54.00	-9.38	AV
V	7311	55.53	30.33	6.32	24.55	56.07	74.00	-17.93	PK
V	7311	46.10	30.33	6.32	24.55	46.64	54.00	-7.36	AV
V	9748	46.26	30.85	7.45	24.69	47.55	74.00	-26.45	PK
V	9748	44.98	30.85	7.45	24.69	46.27	54.00	-7.73	AV
H	4874	45.24	31.02	8.99	25.57	48.78	74.00	-25.22	PK
H	4874	46.22	31.02	8.99	25.57	49.76	54.00	-4.24	AV
H	7311	44.55	30.55	5.77	24.66	44.43	74.00	-29.57	PK
H	7311	44.47	30.55	5.77	24.66	44.35	54.00	-9.65	AV
H	9748	43.72	30.33	6.32	24.55	44.26	74.00	-29.74	PK
H	9748	45.01	30.33	6.32	24.55	45.55	54.00	-8.45	AV

Polar (H/V)	Frequency	Meter Reading	Pre-amplifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	
High Channel:2462MHz									
V	4924	53.23	30.55	5.77	24.66	53.11	74.00	-20.89	PK
V	4924	44.13	30.55	5.77	24.66	44.01	54.00	-9.99	AV
V	7386	57.34	30.33	6.32	24.55	57.88	74.00	-16.12	PK
V	7386	44.82	30.33	6.32	24.55	45.36	54.00	-8.64	AV
V	9848	45.25	30.85	7.45	24.69	46.54	74.00	-27.46	PK
V	9848	44.91	30.85	7.45	24.69	46.20	54.00	-7.80	AV
H	4924	43.72	31.02	8.99	25.57	47.26	74.00	-26.74	PK
H	4924	46.19	31.02	8.99	25.57	49.73	54.00	-4.27	AV
H	7386	45.44	30.55	5.77	24.66	45.32	74.00	-28.68	PK
H	7386	46.54	30.55	5.77	24.66	46.42	54.00	-7.58	AV
H	9848	45.73	30.33	6.32	24.55	46.27	74.00	-27.73	PK
H	9848	44.14	30.33	6.32	24.55	44.68	54.00	-9.32	AV

802.11n20-ANT1

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	56.60	30.55	5.77	24.66	56.48	74.00	-17.52	PK
V	4824	42.67	30.55	5.77	24.66	42.55	54.00	-11.45	AV
V	7236	56.23	30.33	6.32	24.55	56.77	74.00	-17.23	PK
V	7236	45.34	30.33	6.32	24.55	45.88	54.00	-8.12	AV
V	9648	44.14	30.85	7.45	24.69	45.43	74.00	-28.57	PK
V	9648	44.17	30.85	7.45	24.69	45.46	54.00	-8.54	AV
H	4824	45.43	31.02	8.99	25.57	48.97	74.00	-25.03	PK
H	4824	44.83	31.02	8.99	25.57	48.37	54.00	-5.63	AV
H	7236	46.60	30.55	5.77	24.66	46.48	74.00	-27.52	PK
H	7236	46.29	30.55	5.77	24.66	46.17	54.00	-7.83	AV
H	9648	45.32	30.33	6.32	24.55	45.86	74.00	-28.14	PK
H	9648	46.54	30.33	6.32	24.55	47.08	54.00	-6.92	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	56.29	30.55	5.77	24.66	56.17	74.00	-17.83	PK
V	4874	43.48	30.55	5.77	24.66	43.36	54.00	-10.64	AV
V	7311	55.83	30.33	6.32	24.55	56.37	74.00	-17.63	PK
V	7311	47.12	30.33	6.32	24.55	47.66	54.00	-6.34	AV
V	9748	44.15	30.85	7.45	24.69	45.44	74.00	-28.56	PK
V	9748	46.36	30.85	7.45	24.69	47.65	54.00	-6.35	AV
H	4874	44.87	31.02	8.99	25.57	48.41	74.00	-25.59	PK
H	4874	45.54	31.02	8.99	25.57	49.08	54.00	-4.92	AV
H	7311	45.91	30.55	5.77	24.66	45.79	74.00	-28.21	PK
H	7311	45.25	30.55	5.77	24.66	45.13	54.00	-8.87	AV
H	9748	45.55	30.33	6.32	24.55	46.09	74.00	-27.91	PK
H	9748	45.44	30.33	6.32	24.55	45.98	54.00	-8.02	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	51.63	30.55	5.77	24.66	51.51	74.00	-22.49	PK
V	4924	43.14	30.55	5.77	24.66	43.02	54.00	-10.98	AV
V	7386	54.83	30.33	6.32	24.55	55.37	74.00	-18.63	PK
V	7386	47.55	30.33	6.32	24.55	48.09	54.00	-5.91	AV
V	9848	44.10	30.85	7.45	24.69	45.39	74.00	-28.61	PK
V	9848	46.32	30.85	7.45	24.69	47.61	54.00	-6.39	AV
H	4924	46.56	31.02	8.99	25.57	50.10	74.00	-23.90	PK
H	4924	45.74	31.02	8.99	25.57	49.28	54.00	-4.72	AV
H	7386	43.85	30.55	5.77	24.66	43.73	74.00	-30.27	PK
H	7386	46.05	30.55	5.77	24.66	45.93	54.00	-8.07	AV
H	9848	45.19	30.33	6.32	24.55	45.73	74.00	-28.27	PK
H	9848	45.63	30.33	6.32	24.55	46.17	54.00	-7.83	AV

802.11n40-ANT1

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2422MHz									
V	4844	54.60	30.55	5.77	24.66	54.48	74.00	-19.52	PK
V	4844	44.57	30.55	5.77	24.66	44.45	54.00	-9.55	AV
V	7266	54.61	30.33	6.32	24.55	55.15	74.00	-18.85	PK
V	7266	44.68	30.33	6.32	24.55	45.22	54.00	-8.78	AV
V	9688	44.65	30.85	7.45	24.69	45.94	74.00	-28.06	PK
V	9688	45.04	30.85	7.45	24.69	46.33	54.00	-7.67	AV
H	4844	45.37	31.02	8.99	25.57	48.91	74.00	-25.09	PK
H	4844	46.28	31.02	8.99	25.57	49.82	54.00	-4.18	AV
H	7266	45.72	30.55	5.77	24.66	45.60	74.00	-28.40	PK
H	7266	45.67	30.55	5.77	24.66	45.55	54.00	-8.45	AV
H	9688	43.91	30.33	6.32	24.55	44.45	74.00	-29.55	PK
H	9688	43.68	30.33	6.32	24.55	44.22	54.00	-9.78	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	54.71	30.55	5.77	24.66	54.59	74.00	-19.41	PK
V	4874	42.62	30.55	5.77	24.66	42.50	54.00	-11.50	AV
V	7311	55.82	30.33	6.32	24.55	56.36	74.00	-17.64	PK
V	7311	45.46	30.33	6.32	24.55	46.00	54.00	-8.00	AV
V	9748	45.22	30.85	7.45	24.69	46.51	74.00	-27.49	PK
V	9748	44.44	30.85	7.45	24.69	45.73	54.00	-8.27	AV
H	4874	45.08	31.02	8.99	25.57	48.62	74.00	-25.38	PK
H	4874	44.75	31.02	8.99	25.57	48.29	54.00	-5.71	AV
H	7311	44.79	30.55	5.77	24.66	44.67	74.00	-29.33	PK
H	7311	44.21	30.55	5.77	24.66	44.09	54.00	-9.91	AV
H	9748	45.84	30.33	6.32	24.55	46.38	74.00	-27.62	PK
H	9748	45.65	30.33	6.32	24.55	46.19	54.00	-7.81	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904	55.49	30.55	5.77	24.66	55.37	74.00	-18.63	PK
V	4904	44.06	30.55	5.77	24.66	43.94	54.00	-10.06	AV
V	7356	54.91	30.33	6.32	24.55	55.45	74.00	-18.55	PK
V	7356	45.49	30.33	6.32	24.55	46.03	54.00	-7.97	AV
V	9808	45.05	30.85	7.45	24.69	46.34	74.00	-27.66	PK
V	9808	46.56	30.85	7.45	24.69	47.85	54.00	-6.15	AV
H	4904	44.76	31.02	8.99	25.57	48.30	74.00	-25.70	PK
H	4904	43.93	31.02	8.99	25.57	47.47	54.00	-6.53	AV
H	7356	44.60	30.55	5.77	24.66	44.48	74.00	-29.52	PK
H	7356	46.53	30.55	5.77	24.66	46.41	54.00	-7.59	AV
H	9808	46.50	30.33	6.32	24.55	47.04	74.00	-26.96	PK
H	9808	43.87	30.33	6.32	24.55	44.41	54.00	-9.59	AV

802.11b-ANT2

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	56.04	30.55	5.77	24.66	55.92	74.00	-18.08	PK
V	4824	45.49	30.55	5.77	24.66	45.37	54.00	-8.63	AV
V	7236	55.37	30.33	6.32	24.55	55.91	74.00	-18.09	PK
V	7236	46.78	30.33	6.32	24.55	47.32	54.00	-6.68	AV
V	9648	45.49	30.85	7.45	24.69	46.78	74.00	-27.22	PK
V	9648	44.34	30.85	7.45	24.69	45.63	54.00	-8.37	AV
H	4824	46.10	31.02	8.99	25.57	49.64	74.00	-24.36	PK
H	4824	46.26	31.02	8.99	25.57	49.80	54.00	-4.20	AV
H	7236	45.80	30.55	5.77	24.66	45.68	74.00	-28.32	PK
H	7236	44.49	30.55	5.77	24.66	44.37	54.00	-9.63	AV
H	9648	45.34	30.33	6.32	24.55	45.88	74.00	-28.12	PK
H	9648	44.35	30.33	6.32	24.55	44.89	54.00	-9.11	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	58.59	30.55	5.77	24.66	58.47	74.00	-15.53	PK
V	4874	45.17	30.55	5.77	24.66	45.05	54.00	-8.95	AV
V	7311	57.59	30.33	6.32	24.55	58.13	74.00	-15.87	PK
V	7311	45.86	30.33	6.32	24.55	46.40	54.00	-7.60	AV
V	9748	46.43	30.85	7.45	24.69	47.72	74.00	-26.28	PK
V	9748	44.74	30.85	7.45	24.69	46.03	54.00	-7.97	AV
H	4874	45.68	31.02	8.99	25.57	49.22	74.00	-24.78	PK
H	4874	46.36	31.02	8.99	25.57	49.90	54.00	-4.10	AV
H	7311	45.34	30.55	5.77	24.66	45.22	74.00	-28.78	PK
H	7311	45.40	30.55	5.77	24.66	45.28	54.00	-8.72	AV
H	9748	46.41	30.33	6.32	24.55	46.95	74.00	-27.05	PK
H	9748	45.57	30.33	6.32	24.55	46.11	54.00	-7.89	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	53.53	30.55	5.77	24.66	53.41	74.00	-20.59	PK
V	4924	43.12	30.55	5.77	24.66	43.00	54.00	-11.00	AV
V	7386	55.82	30.33	6.32	24.55	56.36	74.00	-17.64	PK
V	7386	46.91	30.33	6.32	24.55	47.45	54.00	-6.55	AV
V	9848	45.34	30.85	7.45	24.69	46.63	74.00	-27.37	PK
V	9848	44.23	30.85	7.45	24.69	45.52	54.00	-8.48	AV
H	4924	45.20	31.02	8.99	25.57	48.74	74.00	-25.26	PK
H	4924	46.54	31.02	8.99	25.57	50.08	54.00	-3.92	AV
H	7386	43.88	30.55	5.77	24.66	43.76	74.00	-30.24	PK
H	7386	43.90	30.55	5.77	24.66	43.78	54.00	-10.22	AV
H	9848	46.19	30.33	6.32	24.55	46.73	74.00	-27.27	PK
H	9848	45.48	30.33	6.32	24.55	46.02	54.00	-7.98	AV

802.11g-ANT2

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	52.32	30.55	5.77	24.66	52.20	74.00	-21.80	PK
V	4824	45.30	30.55	5.77	24.66	45.18	54.00	-8.82	AV
V	7236	56.18	30.33	6.32	24.55	56.72	74.00	-17.28	PK
V	7236	45.15	30.33	6.32	24.55	45.69	54.00	-8.31	AV
V	9648	46.38	30.85	7.45	24.69	47.67	74.00	-26.33	PK
V	9648	44.42	30.85	7.45	24.69	45.71	54.00	-8.29	AV
H	4824	45.22	31.02	8.99	25.57	48.76	74.00	-25.24	PK
H	4824	44.84	31.02	8.99	25.57	48.38	54.00	-5.62	AV
H	7236	46.50	30.55	5.77	24.66	46.38	74.00	-27.62	PK
H	7236	45.58	30.55	5.77	24.66	45.46	54.00	-8.54	AV
H	9648	46.35	30.33	6.32	24.55	46.89	74.00	-27.11	PK
H	9648	45.68	30.33	6.32	24.55	46.22	54.00	-7.78	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	51.91	30.55	5.77	24.66	51.79	74.00	-22.21	PK
V	4874	45.22	30.55	5.77	24.66	45.10	54.00	-8.90	AV
V	7311	57.41	30.33	6.32	24.55	57.95	74.00	-16.05	PK
V	7311	44.78	30.33	6.32	24.55	45.32	54.00	-8.68	AV
V	9748	44.65	30.85	7.45	24.69	45.94	74.00	-28.06	PK
V	9748	45.76	30.85	7.45	24.69	47.05	54.00	-6.95	AV
H	4874	44.17	31.02	8.99	25.57	47.71	74.00	-26.29	PK
H	4874	44.64	31.02	8.99	25.57	48.18	54.00	-5.82	AV
H	7311	45.62	30.55	5.77	24.66	45.50	74.00	-28.50	PK
H	7311	45.89	30.55	5.77	24.66	45.77	54.00	-8.23	AV
H	9748	45.90	30.33	6.32	24.55	46.44	74.00	-27.56	PK
H	9748	46.35	30.33	6.32	24.55	46.89	54.00	-7.11	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	57.91	30.55	5.77	24.66	57.79	74.00	-16.21	PK
V	4924	44.75	30.55	5.77	24.66	44.63	54.00	-9.37	AV
V	7386	56.10	30.33	6.32	24.55	56.64	74.00	-17.36	PK
V	7386	47.06	30.33	6.32	24.55	47.60	54.00	-6.40	AV
V	9848	44.74	30.85	7.45	24.69	46.03	74.00	-27.97	PK
V	9848	44.35	30.85	7.45	24.69	45.64	54.00	-8.36	AV
H	4924	45.24	31.02	8.99	25.57	48.78	74.00	-25.22	PK
H	4924	46.41	31.02	8.99	25.57	49.95	54.00	-4.05	AV
H	7386	45.63	30.55	5.77	24.66	45.51	74.00	-28.49	PK
H	7386	43.61	30.55	5.77	24.66	43.49	54.00	-10.51	AV
H	9848	44.02	30.33	6.32	24.55	44.56	74.00	-29.44	PK
H	9848	43.82	30.33	6.32	24.55	44.36	54.00	-9.64	AV

802.11n-ANT2

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	56.39	30.55	5.77	24.66	56.27	74.00	-17.73	PK
V	4824	44.10	30.55	5.77	24.66	43.98	54.00	-10.02	AV
V	7236	55.20	30.33	6.32	24.55	55.74	74.00	-18.26	PK
V	7236	45.91	30.33	6.32	24.55	46.45	54.00	-7.55	AV
V	9648	45.12	30.85	7.45	24.69	46.41	74.00	-27.59	PK
V	9648	44.56	30.85	7.45	24.69	45.85	54.00	-8.15	AV
H	4824	44.84	31.02	8.99	25.57	48.38	74.00	-25.62	PK
H	4824	46.04	31.02	8.99	25.57	49.58	54.00	-4.42	AV
H	7236	44.26	30.55	5.77	24.66	44.14	74.00	-29.86	PK
H	7236	43.67	30.55	5.77	24.66	43.55	54.00	-10.45	AV
H	9648	44.73	30.33	6.32	24.55	45.27	74.00	-28.73	PK
H	9648	46.58	30.33	6.32	24.55	47.12	54.00	-6.88	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	53.73	30.55	5.77	24.66	53.61	74.00	-20.39	PK
V	4874	45.60	30.55	5.77	24.66	45.48	54.00	-8.52	AV
V	7311	56.93	30.33	6.32	24.55	57.47	74.00	-16.53	PK
V	7311	47.45	30.33	6.32	24.55	47.99	54.00	-6.01	AV
V	9748	45.95	30.85	7.45	24.69	47.24	74.00	-26.76	PK
V	9748	43.90	30.85	7.45	24.69	45.19	54.00	-8.81	AV
H	4874	44.85	31.02	8.99	25.57	48.39	74.00	-25.61	PK
H	4874	45.61	31.02	8.99	25.57	49.15	54.00	-4.85	AV
H	7311	45.76	30.55	5.77	24.66	45.64	74.00	-28.36	PK
H	7311	43.75	30.55	5.77	24.66	43.63	54.00	-10.37	AV
H	9748	45.96	30.33	6.32	24.55	46.50	74.00	-27.50	PK
H	9748	46.09	30.33	6.32	24.55	46.63	54.00	-7.37	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	52.40	30.55	5.77	24.66	52.28	74.00	-21.72	PK
V	4924	43.75	30.55	5.77	24.66	43.63	54.00	-10.37	AV
V	7386	56.36	30.33	6.32	24.55	56.90	74.00	-17.10	PK
V	7386	45.66	30.33	6.32	24.55	46.20	54.00	-7.80	AV
V	9848	45.99	30.85	7.45	24.69	47.28	74.00	-26.72	PK
V	9848	45.90	30.85	7.45	24.69	47.19	54.00	-6.81	AV
H	4924	44.39	31.02	8.99	25.57	47.93	74.00	-26.07	PK
H	4924	45.60	31.02	8.99	25.57	49.14	54.00	-4.86	AV
H	7386	45.07	30.55	5.77	24.66	44.95	74.00	-29.05	PK
H	7386	45.75	30.55	5.77	24.66	45.63	54.00	-8.37	AV
H	9848	45.28	30.33	6.32	24.55	45.82	74.00	-28.18	PK
H	9848	43.73	30.33	6.32	24.55	44.27	54.00	-9.73	AV

802.11n40-ANT2

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2422MHz									
V	4844	52.20	30.55	5.77	24.66	52.08	74.00	-21.92	PK
V	4844	44.91	30.55	5.77	24.66	44.79	54.00	-9.21	AV
V	7266	54.85	30.33	6.32	24.55	55.39	74.00	-18.61	PK
V	7266	45.52	30.33	6.32	24.55	46.06	54.00	-7.94	AV
V	9688	45.08	30.85	7.45	24.69	46.37	74.00	-27.63	PK
V	9688	46.50	30.85	7.45	24.69	47.79	54.00	-6.21	AV
H	4844	46.02	31.02	8.99	25.57	49.56	74.00	-24.44	PK
H	4844	46.54	31.02	8.99	25.57	50.08	54.00	-3.92	AV
H	7266	46.20	30.55	5.77	24.66	46.08	74.00	-27.92	PK
H	7266	45.31	30.55	5.77	24.66	45.19	54.00	-8.81	AV
H	9688	45.31	30.33	6.32	24.55	45.85	74.00	-28.15	PK
H	9688	44.53	30.33	6.32	24.55	45.07	54.00	-8.93	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	56.56	30.55	5.77	24.66	56.44	74.00	-17.56	PK
V	4874	45.51	30.55	5.77	24.66	45.39	54.00	-8.61	AV
V	7311	56.27	30.33	6.32	24.55	56.81	74.00	-17.19	PK
V	7311	46.11	30.33	6.32	24.55	46.65	54.00	-7.35	AV
V	9748	45.91	30.85	7.45	24.69	47.20	74.00	-26.80	PK
V	9748	45.09	30.85	7.45	24.69	46.38	54.00	-7.62	AV
H	4874	44.52	31.02	8.99	25.57	48.06	74.00	-25.94	PK
H	4874	44.92	31.02	8.99	25.57	48.46	54.00	-5.54	AV
H	7311	44.47	30.55	5.77	24.66	44.35	74.00	-29.65	PK
H	7311	45.70	30.55	5.77	24.66	45.58	54.00	-8.42	AV
H	9748	46.34	30.33	6.32	24.55	46.88	74.00	-27.12	PK
H	9748	44.26	30.33	6.32	24.55	44.80	54.00	-9.20	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904	55.11	30.55	5.77	24.66	54.99	74.00	-19.01	PK
V	4904	42.83	30.55	5.77	24.66	42.71	54.00	-11.29	AV
V	7356	57.50	30.33	6.32	24.55	58.04	74.00	-15.96	PK
V	7356	44.63	30.33	6.32	24.55	45.17	54.00	-8.83	AV
V	9808	43.72	30.85	7.45	24.69	45.01	74.00	-28.99	PK
V	9808	46.02	30.85	7.45	24.69	47.31	54.00	-6.69	AV
H	4904	44.43	31.02	8.99	25.57	47.97	74.00	-26.03	PK
H	4904	44.68	31.02	8.99	25.57	48.22	54.00	-5.78	AV
H	7356	46.56	30.55	5.77	24.66	46.44	74.00	-27.56	PK
H	7356	44.87	30.55	5.77	24.66	44.75	54.00	-9.25	AV
H	9808	45.65	30.33	6.32	24.55	46.19	74.00	-27.81	PK
H	9808	45.59	30.33	6.32	24.55	46.13	54.00	-7.87	AV

MIMO-802.11n

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2412MHz									
V	4824	56.08	30.55	5.77	24.66	55.96	74.00	-18.04	PK
V	4824	43.23	30.55	5.77	24.66	43.11	54.00	-10.89	AV
V	7236	56.96	30.33	6.32	24.55	57.50	74.00	-16.50	PK
V	7236	47.12	30.33	6.32	24.55	47.66	54.00	-6.34	AV
V	9648	45.39	30.85	7.45	24.69	46.68	74.00	-27.32	PK
V	9648	46.21	30.85	7.45	24.69	47.50	54.00	-6.50	AV
H	4824	46.26	31.02	8.99	25.57	49.80	74.00	-24.20	PK
H	4824	44.18	31.02	8.99	25.57	47.72	54.00	-6.28	AV
H	7236	44.59	30.55	5.77	24.66	44.47	74.00	-29.53	PK
H	7236	45.09	30.55	5.77	24.66	44.97	54.00	-9.03	AV
H	9648	44.07	30.33	6.32	24.55	44.61	74.00	-29.39	PK
H	9648	45.80	30.33	6.32	24.55	46.34	54.00	-7.66	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	56.32	30.55	5.77	24.66	56.20	74.00	-17.80	PK
V	4874	44.07	30.55	5.77	24.66	43.95	54.00	-10.05	AV
V	7311	56.94	30.33	6.32	24.55	57.48	74.00	-16.52	PK
V	7311	46.49	30.33	6.32	24.55	47.03	54.00	-6.97	AV
V	9748	44.99	30.85	7.45	24.69	46.28	74.00	-27.72	PK
V	9748	44.30	30.85	7.45	24.69	45.59	54.00	-8.41	AV
H	4874	44.65	31.02	8.99	25.57	48.19	74.00	-25.81	PK
H	4874	45.92	31.02	8.99	25.57	49.46	54.00	-4.54	AV
H	7311	46.34	30.55	5.77	24.66	46.22	74.00	-27.78	PK
H	7311	44.07	30.55	5.77	24.66	43.95	54.00	-10.05	AV
H	9748	46.38	30.33	6.32	24.55	46.92	74.00	-27.08	PK
H	9748	46.49	30.33	6.32	24.55	47.03	54.00	-6.97	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2462MHz									
V	4924	54.78	30.55	5.77	24.66	54.66	74.00	-19.34	PK
V	4924	43.30	30.55	5.77	24.66	43.18	54.00	-10.82	AV
V	7386	56.32	30.33	6.32	24.55	56.86	74.00	-17.14	PK
V	7386	46.19	30.33	6.32	24.55	46.73	54.00	-7.27	AV
V	9848	44.84	30.85	7.45	24.69	46.13	74.00	-27.87	PK
V	9848	45.21	30.85	7.45	24.69	46.50	54.00	-7.50	AV
H	4924	44.79	31.02	8.99	25.57	48.33	74.00	-25.67	PK
H	4924	44.93	31.02	8.99	25.57	48.47	54.00	-5.53	AV
H	7386	45.08	30.55	5.77	24.66	44.96	74.00	-29.04	PK
H	7386	45.91	30.55	5.77	24.66	45.79	54.00	-8.21	AV
H	9848	45.21	30.33	6.32	24.55	45.75	74.00	-28.25	PK
H	9848	44.21	30.33	6.32	24.55	44.75	54.00	-9.25	AV

MIMO-802.11n40

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low Channel:2422MHz									
V	4844	52.00	30.55	5.77	24.66	51.88	74.00	-22.12	PK
V	4844	44.00	30.55	5.77	24.66	43.88	54.00	-10.12	AV
V	7266	56.90	30.33	6.32	24.55	57.44	74.00	-16.56	PK
V	7266	45.85	30.33	6.32	24.55	46.39	54.00	-7.61	AV
V	9688	44.35	30.85	7.45	24.69	45.64	74.00	-28.36	PK
V	9688	44.02	30.85	7.45	24.69	45.31	54.00	-8.69	AV
H	4844	45.50	31.02	8.99	25.57	49.04	74.00	-24.96	PK
H	4844	45.46	31.02	8.99	25.57	49.00	54.00	-5.00	AV
H	7266	45.55	30.55	5.77	24.66	45.43	74.00	-28.57	PK
H	7266	43.79	30.55	5.77	24.66	43.67	54.00	-10.33	AV
H	9688	45.43	30.33	6.32	24.55	45.97	74.00	-28.03	PK
H	9688	46.07	30.33	6.32	24.55	46.61	54.00	-7.39	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Middle Channel:2437MHz									
V	4874	54.51	30.55	5.77	24.66	54.39	74.00	-19.61	PK
V	4874	43.33	30.55	5.77	24.66	43.21	54.00	-10.79	AV
V	7311	55.32	30.33	6.32	24.55	55.86	74.00	-18.14	PK
V	7311	47.13	30.33	6.32	24.55	47.67	54.00	-6.33	AV
V	9748	45.65	30.85	7.45	24.69	46.94	74.00	-27.06	PK
V	9748	43.94	30.85	7.45	24.69	45.23	54.00	-8.77	AV
H	4874	46.15	31.02	8.99	25.57	49.69	74.00	-24.31	PK
H	4874	46.58	31.02	8.99	25.57	50.12	54.00	-3.88	AV
H	7311	44.95	30.55	5.77	24.66	44.83	74.00	-29.17	PK
H	7311	45.51	30.55	5.77	24.66	45.39	54.00	-8.61	AV
H	9748	45.51	30.33	6.32	24.55	46.05	74.00	-27.95	PK
H	9748	44.32	30.33	6.32	24.55	44.86	54.00	-9.14	AV

Polar (H/V)	Frequency	Meter Reading	Pre-ampl ifier	Cable Loss	Antenna Factor	Emission Level	Limits	Margin	Detect or Type
	(MHz)	(dBuV)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
High Channel:2452MHz									
V	4904	56.04	30.55	5.77	24.66	55.92	74.00	-18.08	PK
V	4904	44.18	30.55	5.77	24.66	44.06	54.00	-9.94	AV
V	7356	55.84	30.33	6.32	24.55	56.38	74.00	-17.62	PK
V	7356	47.22	30.33	6.32	24.55	47.76	54.00	-6.24	AV
V	9808	44.27	30.85	7.45	24.69	45.56	74.00	-28.44	PK
V	9808	44.30	30.85	7.45	24.69	45.59	54.00	-8.41	AV
H	4904	45.35	31.02	8.99	25.57	48.89	74.00	-25.11	PK
H	4904	45.11	31.02	8.99	25.57	48.65	54.00	-5.35	AV
H	7356	45.11	30.55	5.77	24.66	44.99	74.00	-29.01	PK
H	7356	43.84	30.55	5.77	24.66	43.72	54.00	-10.28	AV
H	9808	43.85	30.33	6.32	24.55	44.39	74.00	-29.61	PK
H	9808	44.69	30.33	6.32	24.55	45.23	54.00	-8.77	AV

5.RADIATED BAND EMISSIONMEASUREMENT

5.1 TEST REQUIREMENT:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013				
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could bestopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dBmargin would be re-tested one by one using peak, quasi-peak or average method as specified and then reportedin a data sheet.
- g. Test the EUT in the lowest channel,the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

ANT1

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11b	LowChannel 2412MHz									
	H	2390.00	56.18	30.22	4.85	23.98	54.79	74.00	PK	PASS
	H	2390.00	43.02	30.22	4.85	23.98	41.63	54.00	AV	PASS
	H	2400.00	54.72	30.22	4.85	23.98	53.33	74.00	PK	PASS
	H	2400.00	46.65	30.22	4.85	23.98	45.26	54.00	AV	PASS
	V	2390.00	52.38	30.22	4.85	23.98	50.99	74.00	PK	PASS
	V	2390.00	43.05	30.22	4.85	23.98	41.66	54.00	AV	PASS
	V	2400.00	55.62	30.22	4.85	23.98	54.23	74.00	PK	PASS
	V	2400.00	45.83	30.22	4.85	23.98	44.44	54.00	AV	PASS
	HighChannel 2462MHz									
	H	2483.50	54.58	30.22	4.85	23.98	53.19	74.00	PK	PASS
	H	2485.50	43.16	30.22	4.85	23.98	41.77	54.00	AV	PASS
	H	2483.50	54.89	30.22	4.85	23.98	53.50	74.00	PK	PASS
	H	2485.50	46.63	30.22	4.85	23.98	45.24	54.00	AV	PASS
	V	2483.50	58.08	30.22	4.85	23.98	56.69	74.00	PK	PASS
	V	2485.50	42.96	30.22	4.85	23.98	41.57	54.00	AV	PASS
V	2483.50	54.92	30.22	4.85	23.98	53.53	74.00	PK	PASS	
V	2485.50	45.52	30.22	4.85	23.98	44.13	54.00	AV	PASS	

802.11g	LowChannel 2412MHz									
	H	2390.00	55.05	30.22	4.85	23.98	53.66	74.00	PK	PASS
	H	2390.00	42.96	30.22	4.85	23.98	41.57	54.00	AV	PASS
	H	2400.00	55.44	30.22	4.85	23.98	54.05	74.00	PK	PASS
	H	2400.00	46.51	30.22	4.85	23.98	45.12	54.00	AV	PASS
	V	2390.00	52.35	30.22	4.85	23.98	50.96	74.00	PK	PASS
	V	2390.00	43.55	30.22	4.85	23.98	42.16	54.00	AV	PASS
	V	2400.00	56.50	30.22	4.85	23.98	55.11	74.00	PK	PASS
	V	2400.00	47.19	30.22	4.85	23.98	45.80	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	53.41	30.22	4.85	23.98	52.02	74.00	PK	PASS
	H	2485.50	44.25	30.22	4.85	23.98	42.86	54.00	AV	PASS
	H	2483.50	57.51	30.22	4.85	23.98	56.12	74.00	PK	PASS
	H	2485.50	44.98	30.22	4.85	23.98	43.59	54.00	AV	PASS
	V	2483.50	56.02	30.22	4.85	23.98	54.63	74.00	PK	PASS
	V	2485.50	43.00	30.22	4.85	23.98	41.61	54.00	AV	PASS
V	2483.50	56.35	30.22	4.85	23.98	54.96	74.00	PK	PASS	
V	2485.50	46.97	30.22	4.85	23.98	45.58	54.00	AV	PASS	

		LowChannel 2412MHz										
		H	2390.00	54.40	30.22	4.85	23.98	53.01	74.00	PK	PASS	
802.11n20		H	2390.00	45.51	30.22	4.85	23.98	44.12	54.00	AV	PASS	
		H	2400.00	56.82	30.22	4.85	23.98	55.43	74.00	PK	PASS	
		H	2400.00	44.82	30.22	4.85	23.98	43.43	54.00	AV	PASS	
		V	2390.00	58.17	30.22	4.85	23.98	56.78	74.00	PK	PASS	
		V	2390.00	44.19	30.22	4.85	23.98	42.80	54.00	AV	PASS	
		V	2400.00	56.96	30.22	4.85	23.98	55.57	74.00	PK	PASS	
		V	2400.00	47.03	30.22	4.85	23.98	45.64	54.00	AV	PASS	
				High Channel 2462MHz								
		H	2483.50	55.58	30.22	4.85	23.98	54.19	74.00	PK	PASS	
		H	2485.50	42.66	30.22	4.85	23.98	41.27	54.00	AV	PASS	
		H	2483.50	57.58	30.22	4.85	23.98	56.19	74.00	PK	PASS	
		H	2485.50	46.16	30.22	4.85	23.98	44.77	54.00	AV	PASS	
		V	2483.50	53.27	30.22	4.85	23.98	51.88	74.00	PK	PASS	
		V	2485.50	43.79	30.22	4.85	23.98	42.40	54.00	AV	PASS	
V	2483.50	55.60	30.22	4.85	23.98	54.21	74.00	PK	PASS			
V	2485.50	44.86	30.22	4.85	23.98	43.47	54.00	AV	PASS			

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

		LowChannel 2422MHz										
		H	2390.00	57.07	30.22	4.85	23.98	55.68	74.00	PK	PASS	
802.11n40		H	2390.00	43.11	30.22	4.85	23.98	41.72	54.00	AV	PASS	
		H	2400.00	57.43	30.22	4.85	23.98	56.04	74.00	PK	PASS	
		H	2400.00	46.37	30.22	4.85	23.98	44.98	54.00	AV	PASS	
		V	2390.00	58.07	30.22	4.85	23.98	56.68	74.00	PK	PASS	
		V	2390.00	44.04	30.22	4.85	23.98	42.65	54.00	AV	PASS	
		V	2400.00	56.34	30.22	4.85	23.98	54.95	74.00	PK	PASS	
		V	2400.00	45.22	30.22	4.85	23.98	43.83	54.00	AV	PASS	
				High Channel 2452MHz								
		H	2483.50	57.52	30.22	4.85	23.98	56.13	74.00	PK	PASS	
		H	2485.50	44.47	30.22	4.85	23.98	43.08	54.00	AV	PASS	
		H	2483.50	56.99	30.22	4.85	23.98	55.60	74.00	PK	PASS	
		H	2485.50	47.16	30.22	4.85	23.98	45.77	54.00	AV	PASS	
		V	2483.50	58.59	30.22	4.85	23.98	57.20	74.00	PK	PASS	
		V	2485.50	42.98	30.22	4.85	23.98	41.59	54.00	AV	PASS	
V	2483.50	56.76	30.22	4.85	23.98	55.37	74.00	PK	PASS			
V	2485.50	44.78	30.22	4.85	23.98	43.39	54.00	AV	PASS			

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

ANT2

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
802.11b	LowChannel 2412MHz									
	H	2390.00	54.41	30.22	4.85	23.98	53.02	74.00	PK	PASS
	H	2390.00	42.74	30.22	4.85	23.98	41.35	54.00	AV	PASS
	H	2400.00	54.97	30.22	4.85	23.98	53.58	74.00	PK	PASS
	H	2400.00	45.86	30.22	4.85	23.98	44.47	54.00	AV	PASS
	V	2390.00	56.40	30.22	4.85	23.98	55.01	74.00	PK	PASS
	V	2390.00	45.54	30.22	4.85	23.98	44.15	54.00	AV	PASS
	V	2400.00	56.23	30.22	4.85	23.98	54.84	74.00	PK	PASS
	V	2400.00	46.90	30.22	4.85	23.98	45.51	54.00	AV	PASS
	HighChannel 2462MHz									
	H	2483.50	52.67	30.22	4.85	23.98	51.28	74.00	PK	PASS
	H	2485.50	45.03	30.22	4.85	23.98	43.64	54.00	AV	PASS
	H	2483.50	57.51	30.22	4.85	23.98	56.12	74.00	PK	PASS
	H	2485.50	44.86	30.22	4.85	23.98	43.47	54.00	AV	PASS
	V	2483.50	52.05	30.22	4.85	23.98	50.66	74.00	PK	PASS
	V	2485.50	44.97	30.22	4.85	23.98	43.58	54.00	AV	PASS
V	2483.50	56.98	30.22	4.85	23.98	55.59	74.00	PK	PASS	
V	2485.50	46.75	30.22	4.85	23.98	45.36	54.00	AV	PASS	

802.11g	LowChannel 2412MHz									
	H	2390.00	51.98	30.22	4.85	23.98	50.59	74.00	PK	PASS
	H	2390.00	44.93	30.22	4.85	23.98	43.54	54.00	AV	PASS
	H	2400.00	56.64	30.22	4.85	23.98	55.25	74.00	PK	PASS
	H	2400.00	45.97	30.22	4.85	23.98	44.58	54.00	AV	PASS
	V	2390.00	58.08	30.22	4.85	23.98	56.69	74.00	PK	PASS
	V	2390.00	43.50	30.22	4.85	23.98	42.11	54.00	AV	PASS
	V	2400.00	54.62	30.22	4.85	23.98	53.23	74.00	PK	PASS
	V	2400.00	45.18	30.22	4.85	23.98	43.79	54.00	AV	PASS
	High Channel 2462MHz									
	H	2483.50	52.44	30.22	4.85	23.98	51.05	74.00	PK	PASS
	H	2485.50	44.12	30.22	4.85	23.98	42.73	54.00	AV	PASS
	H	2483.50	56.27	30.22	4.85	23.98	54.88	74.00	PK	PASS
	H	2485.50	45.47	30.22	4.85	23.98	44.08	54.00	AV	PASS
	V	2483.50	58.31	30.22	4.85	23.98	56.92	74.00	PK	PASS
	V	2485.50	45.28	30.22	4.85	23.98	43.89	54.00	AV	PASS
V	2483.50	54.93	30.22	4.85	23.98	53.54	74.00	PK	PASS	
V	2485.50	45.54	30.22	4.85	23.98	44.15	54.00	AV	PASS	

		LowChannel 2412MHz										
		H	2390.00	57.00	30.22	4.85	23.98	55.61	74.00	PK	PASS	
802.11n20		H	2390.00	44.66	30.22	4.85	23.98	43.27	54.00	AV	PASS	
		H	2400.00	55.13	30.22	4.85	23.98	53.74	74.00	PK	PASS	
		H	2400.00	44.71	30.22	4.85	23.98	43.32	54.00	AV	PASS	
		V	2390.00	57.32	30.22	4.85	23.98	55.93	74.00	PK	PASS	
		V	2390.00	43.26	30.22	4.85	23.98	41.87	54.00	AV	PASS	
		V	2400.00	56.36	30.22	4.85	23.98	54.97	74.00	PK	PASS	
		V	2400.00	47.53	30.22	4.85	23.98	46.14	54.00	AV	PASS	
				High Channel 2462MHz								
		H	2483.50	54.12	30.22	4.85	23.98	52.73	74.00	PK	PASS	
		H	2485.50	42.85	30.22	4.85	23.98	41.46	54.00	AV	PASS	
		H	2483.50	57.55	30.22	4.85	23.98	56.16	74.00	PK	PASS	
		H	2485.50	45.07	30.22	4.85	23.98	43.68	54.00	AV	PASS	
		V	2483.50	54.37	30.22	4.85	23.98	52.98	74.00	PK	PASS	
		V	2485.50	45.26	30.22	4.85	23.98	43.87	54.00	AV	PASS	
V	2483.50	57.49	30.22	4.85	23.98	56.10	74.00	PK	PASS			
V	2485.50	47.27	30.22	4.85	23.98	45.88	54.00	AV	PASS			

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

		LowChannel 2422MHz										
		H	2390.00	57.34	30.22	4.85	23.98	55.95	74.00	PK	PASS	
802.11n40		H	2390.00	43.74	30.22	4.85	23.98	42.35	54.00	AV	PASS	
		H	2400.00	55.86	30.22	4.85	23.98	54.47	74.00	PK	PASS	
		H	2400.00	45.95	30.22	4.85	23.98	44.56	54.00	AV	PASS	
		V	2390.00	54.49	30.22	4.85	23.98	53.10	74.00	PK	PASS	
		V	2390.00	44.59	30.22	4.85	23.98	43.20	54.00	AV	PASS	
		V	2400.00	55.86	30.22	4.85	23.98	54.47	74.00	PK	PASS	
		V	2400.00	46.96	30.22	4.85	23.98	45.57	54.00	AV	PASS	
				High Channel 2452MHz								
		H	2483.50	54.04	30.22	4.85	23.98	52.65	74.00	PK	PASS	
		H	2485.50	44.18	30.22	4.85	23.98	42.79	54.00	AV	PASS	
		H	2483.50	55.67	30.22	4.85	23.98	54.28	74.00	PK	PASS	
		H	2485.50	46.87	30.22	4.85	23.98	45.48	54.00	AV	PASS	
		V	2483.50	58.02	30.22	4.85	23.98	56.63	74.00	PK	PASS	
		V	2485.50	44.49	30.22	4.85	23.98	43.10	54.00	AV	PASS	
V	2483.50	55.74	30.22	4.85	23.98	54.35	74.00	PK	PASS			
V	2485.50	46.70	30.22	4.85	23.98	45.31	54.00	AV	PASS			

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

MIMO

		LowChannel 2412MHz								
		H	2390.00	56.97	30.22	4.85	23.98	55.58	74.00	PK
H	2390.00	44.51	30.22	4.85	23.98	43.12	54.00	AV	PASS	
H	2400.00	56.80	30.22	4.85	23.98	55.41	74.00	PK	PASS	
H	2400.00	46.08	30.22	4.85	23.98	44.69	54.00	AV	PASS	
V	2390.00	53.50	30.22	4.85	23.98	52.11	74.00	PK	PASS	
V	2390.00	44.36	30.22	4.85	23.98	42.97	54.00	AV	PASS	
V	2400.00	57.33	30.22	4.85	23.98	55.94	74.00	PK	PASS	
V	2400.00	45.47	30.22	4.85	23.98	44.08	54.00	AV	PASS	
		High Channel 2462MHz								
		H	2483.50	53.46	30.22	4.85	23.98	52.07	74.00	PK
H	2485.50	44.83	30.22	4.85	23.98	43.44	54.00	AV	PASS	
H	2483.50	55.29	30.22	4.85	23.98	53.90	74.00	PK	PASS	
H	2485.50	46.51	30.22	4.85	23.98	45.12	54.00	AV	PASS	
V	2483.50	56.46	30.22	4.85	23.98	55.07	74.00	PK	PASS	
V	2485.50	44.24	30.22	4.85	23.98	42.85	54.00	AV	PASS	
V	2483.50	54.65	30.22	4.85	23.98	53.26	74.00	PK	PASS	
V	2485.50	44.93	30.22	4.85	23.98	43.54	54.00	AV	PASS	
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

		LowChannel 2422MHz								
		H	2390.00	56.89	30.22	4.85	23.98	55.50	74.00	PK
H	2390.00	44.53	30.22	4.85	23.98	43.14	54.00	AV	PASS	
H	2400.00	54.77	30.22	4.85	23.98	53.38	74.00	PK	PASS	
H	2400.00	44.91	30.22	4.85	23.98	43.52	54.00	AV	PASS	
V	2390.00	58.45	30.22	4.85	23.98	57.06	74.00	PK	PASS	
V	2390.00	43.15	30.22	4.85	23.98	41.76	54.00	AV	PASS	
V	2400.00	56.55	30.22	4.85	23.98	55.16	74.00	PK	PASS	
V	2400.00	46.02	30.22	4.85	23.98	44.63	54.00	AV	PASS	
		High Channel 2452MHz								
		H	2483.50	58.26	30.22	4.85	23.98	56.87	74.00	PK
H	2485.50	45.55	30.22	4.85	23.98	44.16	54.00	AV	PASS	
H	2483.50	56.19	30.22	4.85	23.98	54.80	74.00	PK	PASS	
H	2485.50	46.36	30.22	4.85	23.98	44.97	54.00	AV	PASS	
V	2483.50	51.88	30.22	4.85	23.98	50.49	74.00	PK	PASS	
V	2485.50	44.17	30.22	4.85	23.98	42.78	54.00	AV	PASS	
V	2483.50	54.73	30.22	4.85	23.98	53.34	74.00	PK	PASS	
V	2485.50	47.09	30.22	4.85	23.98	45.70	54.00	AV	PASS	
Remark:										
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit										

6.POWER SPECTRAL DENSITY TEST

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8dBm/3kHz	2400-2483.5	PASS

6.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.


6.6 TEST RESULT


Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V


Test mode	Test channel	Power Spectral Density (dBm/MHz)			Limit:	Result
		ANT1	ANT2	SUM		
802.11b	Lowest	-13.819	-12.977	/	8dBm	PASS
	Middle	-13.904	-13.926	/		
	Highest	-14.256	-14.048	/		
802.11g	Lowest	-19.805	-20.263	/	8dBm	PASS
	Middle	-20.238	-20.347	/		
	Highest	-20.367	-21.315	/		
802.11n(HT20)	Lowest	-19.298	-19.668	-16.47	7.99dBm	PASS
	Middle	-19.753	-20.295	-17.01		
	Highest	-20.911	-20.432	-17.65		
802.11n(HT40)	Lowest	-22.254	-22.740	-19.48	7.99dBm	PASS
	Middle	-23.052	-22.401	-19.70		
	Highest	-23.232	-23.420	-20.31		


Remark:

1. Measured peak power spectrum density at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. Please refer to following plots;
4. The PSD limits of IEEE 802.11n HT20 and IEEE 802.11 n HT40 for MIMO with CDD technology should be reduce $10 \cdot \log(2) = 0.010\text{dBi}$ according to KDB662911D01;
5. For MIMO with CCD technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain;
Array gain = $10 \log(N_{ant})$, where N_{ant} is the number of transmit antennas.









7. CHANNEL BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS


7.2 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


7.6 TEST RESULT







Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120
Test Mode :	TX Mode		


Test mode	Test channel	6dB Emission Bandwidth (MHz)		Limit:	Test Result:
		ANT1	ANT2		
802.11b	Lowest	10.11	10.12	>500kHz	PASS
	Middle	10.10	9.645		
	Highest	9.592	10.08		
802.11g	Lowest	16.36	16.34	>500kHz	PASS
	Middle	16.40	16.40		
	Highest	16.36	16.37		
802.11n(HT20)	Lowest	17.35	17.58	>500kHz	PASS
	Middle	17.54	17.53		
	Highest	17.53	17.58		
802.11n(HT40)	Lowest	35.79	36.00	>500kHz	PASS
	Middle	35.73	35.85		
	Highest	35.79	36.08		

Test plot as follows:





ANT1 802.11n(HT20) Lowest channel	ANT2 802.11n(HT20) Lowest channel
 <p>Center Freq: 2.412000000 GHz</p> <p>Center Freq: 2.412000000 GHz</p> <p>Center: 2.412 GHz</p> <p>Occupied Bandwidth: 17.652 MHz</p> <p>Total Power: 12.2 dBm</p> <p>Transmit Freq Error: -10.568 kHz</p> <p>x dB Bandwidth: 17.35 MHz</p>	 <p>Center Freq: 2.412000000 GHz</p> <p>Center Freq: 2.412000000 GHz</p> <p>Center: 2.412 GHz</p> <p>Occupied Bandwidth: 17.614 MHz</p> <p>Total Power: 11.9 dBm</p> <p>Transmit Freq Error: -6.653 kHz</p> <p>x dB Bandwidth: 17.58 MHz</p>
Middle channel	Middle channel
 <p>Center Freq: 2.437000000 GHz</p> <p>Center Freq: 2.437000000 GHz</p> <p>Center: 2.437 GHz</p> <p>Occupied Bandwidth: 17.635 MHz</p> <p>Total Power: 11.8 dBm</p> <p>Transmit Freq Error: -4.568 kHz</p> <p>x dB Bandwidth: 17.54 MHz</p>	 <p>Center Freq: 2.437000000 GHz</p> <p>Center Freq: 2.437000000 GHz</p> <p>Center: 2.437 GHz</p> <p>Occupied Bandwidth: 17.661 MHz</p> <p>Total Power: 11.4 dBm</p> <p>Transmit Freq Error: -12.675 kHz</p> <p>x dB Bandwidth: 17.53 MHz</p>
Highest channel	Highest channel
 <p>Center Freq: 2.462000000 GHz</p> <p>Center Freq: 2.462000000 GHz</p> <p>Center: 2.462 GHz</p> <p>Occupied Bandwidth: 17.644 MHz</p> <p>Total Power: 11.1 dBm</p> <p>Transmit Freq Error: -6.661 kHz</p> <p>x dB Bandwidth: 17.53 MHz</p>	 <p>Center Freq: 2.462000000 GHz</p> <p>Center Freq: 2.462000000 GHz</p> <p>Center: 2.462 GHz</p> <p>Occupied Bandwidth: 17.623 MHz</p> <p>Total Power: 11.2 dBm</p> <p>Transmit Freq Error: -16.926 kHz</p> <p>x dB Bandwidth: 17.58 MHz</p>



8.OUTPUT POWER TEST

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

8.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

8.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP



8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

8.6 TEST RESULT

Temperature :	26°C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V

Test Channel	Frequency (MHz)	Maximum Peak Conducted Output Power(dBm)			LIMIT dBm
		Antenna 1	Antenna 2	MIMO	
TX 802.11b Mode					
CH01	2412	13.53	12.89	/	30
CH06	2437	13.14	12.61	/	30
CH11	2462	12.89	12.60	/	30
TX 802.11g Mode					
CH01	2412	12.88	12.50	/	30
CH06	2437	12.51	12.32	/	30
CH11	2462	12.39	12.12	/	30
TX 802.11n20 Mode					
CH01	2412	12.80	12.68	15.75	29.99
CH06	2437	12.55	12.34	15.46	29.99
CH11	2462	11.47	12.00	14.75	29.99
TX 802.11n40 Mode					
CH03	2422	12.64	12.64	15.65	29.99
CH06	2437	12.42	12.50	15.47	29.99
CH09	2452	12.21	12.24	15.24	29.99
Note: This product supports antenna 1 and antenna 2 launch, but only support 802.11 n for MIMO mode, not support 802.11 b and 802.11 g for MIMO mode.					

Remark:

1. Measured peak power at difference data rate for each mode and recorded worst case for each mode.
2. Test results including cable loss;
3. For MIMO with OFDM technology device, The Directional Gain= Gain of individual transmit antennas (dBi) + Array gain; Array gain = $10 \log(N_{ant})$, where N_{ant} is the number of transmit antennas.
4. The Power limits of IEEE 802.11n HT20 and IEEE 802.11 n HT40 for MIMO with CDD technology should be reduce $10 * \log(2) = 0.010\text{dBi}$ according to KDB662911D01;so limit= $30 - (6.01 - 6) = 29.99$ dBm

9. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

9.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

9.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- A) Set the RBW = 100KHz.
- B) Set the VBW = 300KHz.
- C) Sweep time = auto couple.
- D) Detector function = peak.
- E) Trace mode = max hold.
- F) Allow trace to fully stabilize.

9.3 DEVIATION FROM STANDARD

No deviation.

9.4 TEST SETUP



9.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

9.6 TEST RESULTS



Test plot as follows:

ANT1



802.11b Modulation

Spurious emission



Low Channel




Middle Channel



High Channel




Lowest Channel



Left Band Edge

Highest Channel






Right Band Edge


802.11g Modulation

Spurious emission



Low Channel




Middle Channel



High Channel




Lowest Channel



Left Band Edge

Highest Channel






Right Band Edge



802.11n20 Modulation

Spurious emission




Low Channel




Middle Channel



High Channel




Lowest Channel



Left Band Edge

Highest Channel






Right Band Edge



802.11n40 Modulation

Spurious emission




Low Channel




Middle Channel



High Channel




Lowest Channel





Left Band Edge

Highest Channel




Right Band Edge


Middle Channel



High Channel




Lowest Channel



Left Band Edge

Highest Channel






Right Band Edge




802.11g Modulation

Spurious emission




Low Channel




Middle Channel



High Channel




Lowest Channel



Left Band Edge

Highest Channel





Right Band Edge


802.11n20 Modulation

Spurious emission


Low Channel




Middle Channel



High Channel




Lowest Channel



Left Band Edge

Highest Channel






Right Band Edge



802.11n40 Modulation

Spurious emission




Low Channel




Middle Channel



High Channel




Lowest Channel




Left Band Edge

Highest Channel



Right Band Edge

10. ANTENNA REQUIREMENT

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
<p>For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247, if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.</p> <p>Refer to statement below for compliance.</p> <p>The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.</p> <p>Antenna Connected Construction</p> <p>The antenna used in this product is FPC antenna, and the best case gain of the antenna is antenna port 1:3dBi and Antenna port 2:3dBi, and MIMO: 6.01dBi</p>	
<p>FPC Antenna: 2.4Gwifi & 5Gwifi ANT</p> 	

11. TEST SETUP PHOTO

Please refer to the report NO.: ZKT-211213L6860-01

12. EUT CONSTRUCTIONAL DETAILS

Reference to the external photos file and internal photos file for details.

******* END OF REPORT *******