

# RADIO TEST REPORT – 436028-5ARFWL

Type of assessment:

**SAR Exemption report**

Applicant:

**Canary Medical USA LLC**

Product:

**Clinical Base Station**

Model:

**CBS**

Model variant(s):

**NA**

FCC ID: 2AYAJ-CBS

Specifications:

- ◆ **FCC 47 CFR Part 2 Subpart J, §2.1093**
- ◆ **FCC KDB 447498 D01 General RF Exposure Guidance v06**

Attestation:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Date of issue: **October 13, 2022**

**Chip Fleury**

Prepared by



Signature



Lab locations

---

Nemko San Diego



## Table of Contents

<b>Table of Contents</b> .....	<b>3</b>
<b>Section 1 Evaluation summary</b> .....	<b>4</b>
1.1 SAR exemption for standalone transmission .....	4
1.2 SAR exemption for simultaneous transmission .....	6

## Section 1 Evaluation summary

### 1.1 SAR exemption for standalone transmission

#### 1.1.1 References, definitions and limits

##### FCC §2.1093

- (2) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

##### FCC KDB 447498 D01

#### 4.3.1 Standalone SAR test exclusion considerations

During normal operation, user extremities can come within 20 cm of the internal antenna and therefore product is considered as “Portable”.

The 1-g head or body and 10-g extremity SAR test exclusion thresholds for 100 MHz to 6 GHz at Test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) \div (\text{min. test separation distance, mm})] \times [V(F_{\text{GHz}})] \leq 3.0 \text{ for 1-g head or body SAR, and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$F_{\text{GHz}}$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm according to section 4.1(f) is applied to determine SAR test exclusion

**Table 1.1-1: SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and  $\leq 50$  mm**

Separation:	5 mm	10 mm	15 mm	20 mm	25 mm	30 mm	35 mm	40 mm	45 mm	50 mm
150 MHz	39	77	116	155	194	232	271	310	349	387
300 MHz	27	55	82	110	137	164	192	219	246	274
450 MHz	22	45	67	89	112	134	157	179	201	224
835 MHz	16	33	49	66	82	98	115	131	148	164
900 MHz	16	32	47	63	79	95	111	126	142	158
1500 MHz	12	24	37	49	61	73	86	98	110	122
1900 MHz	11	22	33	44	54	65	76	87	98	109
2450 MHz	10	19	29	38	48	57	67	77	86	96
3600 MHz	8	16	24	32	40	47	55	63	71	79
5200 MHz	7	13	20	26	33	39	46	53	59	66
5400 MHz	6	13	19	26	32	39	45	52	58	65
5800 MHz	6	12	19	25	31	37	44	50	56	62

Notes: Values in the table are in mW  
 10-g Extremity SAR Test Exclusion Power Thresholds are 2.5 times higher than the 1-g SAR Test Exclusion Thresholds indicated above. These thresholds do not apply, by extrapolation or other means, to occupational exposure limits.

References, definitions and limits, continued

**Table 1.1-2: SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and > 50 mm**

Separation:	50 mm	60 mm	70 mm	80 mm	90 mm	100 mm	110 mm	120 mm	130 mm	140 mm	150 mm	160 mm	170 mm	180 mm	190 mm
100 MHz	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567
150 MHz	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527
300 MHz	274	294	314	334	354	374	394	414	434	454	474	494	514	534	554
450 MHz	224	254	284	314	344	374	404	434	464	494	524	554	584	614	644
835 MHz	164	220	275	331	387	442	498	554	609	665	721	776	832	888	943
900 MHz	158	218	278	338	398	458	518	578	638	698	758	818	878	938	998
1500 MHz	122	222	322	422	522	622	722	822	922	1022	1122	1222	1322	1422	1522
1900 MHz	109	209	309	409	509	609	709	809	909	1009	1109	1209	1309	1409	1509
2450 MHz	96	196	296	396	496	596	696	796	896	996	1096	1196	1296	1396	1496
3600 MHz	79	179	279	379	479	579	679	779	879	979	1079	1179	1279	1379	1479
5200 MHz	66	166	266	366	466	566	666	766	866	966	1066	1166	1266	1366	1466
5400 MHz	65	165	265	365	465	565	665	765	865	965	1065	1165	1265	1365	1465
5800 MHz	62	162	262	362	462	562	662	762	862	962	1062	1162	1262	1362	1462

Notes: Values in the table are in mW

**Table 1.1-3: SAR Test Exclusion Thresholds for <100 MHz and < 50 mm**

Separation:	<50 mm	50 mm	60 mm	70 mm	80 mm	90 mm	100 mm	110 mm	120 mm	130 mm	140 mm	150 mm	160 mm	170 mm	180 mm	190 mm
100 MHz	237	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567
50 MHz	308	617	625	634	643	651	660	669	677	686	695	703	712	721	729	738
10 MHz	474	948	961	975	988	1001	1015	1028	1041	1055	1068	1081	1095	1108	1121	1135
1 MHz	711	1422	1442	1462	1482	1502	1522	1542	1562	1582	1602	1622	1642	1662	1682	1702
0.1 MHz	948	1896	1923	1949	1976	2003	2029	2056	2083	2109	2136	2163	2189	2216	2243	2269
0.05 MHz	1019	2039	2067	2096	2125	2153	2182	2211	2239	2268	2297	2325	2354	2383	2411	2440
0.01 MHz	1185	2370	2403	2437	2470	2503	2537	2570	2603	2637	2670	2703	2737	2770	2803	2837

Notes: Values in the table are in mW

---

## 1.1.2 EUT technical information

---

## 1.2 SAR exemption for simultaneous transmission

---

### 1.2.1 References, definitions, and limits

---

#### FCC §2.1093

- (2) The SAR limits for general population/uncontrolled exposure are 0.08 W/kg, as averaged over the whole body, and a peak spatial-average SAR of 1.6 W/kg, averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube). Exceptions are the parts of the human body treated as extremities, such as hands, wrists, feet, ankles, and pinnae, where the peak spatial-average SAR limit is 4 W/kg, averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube). Exposure may be averaged over a time period not to exceed 30 minutes to determine compliance with general population/uncontrolled SAR limits.

#### FCC KDB 447498 D01

##### 4.3.2 Simultaneous transmission SAR test exclusion considerations

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneously transmitting antenna. When the sum of 1-g or 10-g SAR of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit, SAR test exclusion applies to that simultaneous transmission configuration.

When an antenna qualifies for the standalone SAR test exclusion of 4.3.1 and transmits simultaneously with other antennas, the standalone SAR value must be estimated for each applicable radio transmitter according to the following to determine the simultaneous transmission SAR test exclusion criteria, and the SAR estimations are then individually summed to ensure they meet the SAR limit:

- 1) The 1-g head or body and 10-g extremity **SAR value estimation** at Test separation distances  $\leq 50$  mm are determined by:  
[(max. power of channel, including tune-up tolerance, mW)  $\div$  (min. test separation distance, mm)]  $\times$   
[ $\sqrt{F_{(\text{GHz})}}/X$ ]  
 $F_{(\text{GHz})}$  is the RF channel transmit frequency in GHz  
 $X = 7.5$  for 1-g head or body SAR and  $x = 18.75$  for 10-g extremity SAR  
Power and distance are rounded to the nearest mW and mm before calculation  
The result is rounded to one decimal place for comparison
- 2) The 1-g head or body and 10-g extremity **SAR value estimation** at Test separation distances  $> 50$  mm are equal to 0.4 W/kg for 1-g head or body SAR and 1.0 W/kg for 10-g extremity SAR.

1.2.2 EUT technical information

	Med Radio	FCC 15.249
Operational frequency	402 – 405 MHz	2410 – 2430 MHz
Antenna type	Spring	Embedded
Antenna gain	0.67 dBi	4.94 dB
Number of antennas	1	2 (*)
Maximum transmitter conducted power	-18.34 dBm (0.01466 mW)	-12.97 dBm (0.05048 mW)
Maximum EIRP	-17.60 dBm (0.01738 mW)	-8.03 dBm (0.157442 mW)

1.2.3 Justification for Simultaneous Transmission SAR test exclusion

Estimated SAR value (Transmitter 1) =  $(EIRP_{(mW)} \div \text{min. test separation distance mm}) \times \sqrt{\text{Frequency}_{(GHz)} / x} = \text{result W/kg}$   
 Assuming worst case – 1-g SAR so x = 7.5

Table 1.2-1: SAR exemption verification for simultaneous transmission

Transmitter type	Transmit frequency, GHz	Maximum EIRP, mW	Separation distance, mm	Estimated SAR value (W/kg)	Sum of SAR values (W/kg)	Margin, W/kg
MICS	402.15	0.01738	5	0.002	0.00754	7.49
Wifi	2.42022	0.05048	5	0.00574		

1.2.4 Verdict

The calculated Estimated Simultaneous Transmission SAR level is below the applicable SAR limit, therefore the product exempt from the SAR test requirements.

End of the test report