

FCC §1.1310& §2.1091 - MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/		f/1500	30
1500-100,000	/		1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Maximum Antenna Gain		Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
		(dBi)	(numeric)	(dBm)	(mW)			
802.11b	2412-2462	7.0	5.01	24.50	281.84	20	0.2809	1.0
802.11g		7.0	5.01	22.50	177.83	20	0.1772	1.0
802.11n-HT20		7.0	5.01	22.00	158.49	20	0.1579	1.0
802.11n-HT40	2422-2452	7.0	5.01	21.00	125.89	20	0.1255	1.0
802.11a	5150~5250	9.0	7.94	12.00	15.85	20	0.0250	1.0
	5725~5850	9.0	7.94	15.50	35.48	20	0.0561	1.0
802.11ac20	5150~5250	9.0	7.94	12.00	15.85	20	0.0250	1.0
	5725~5850	9.0	7.94	18.00	63.10	20	0.0997	1.0
802.11n-HT20	5150~5250	9.0	7.94	12.00	15.85	20	0.0250	1.0
	5725~5850	9.0	7.94	18.00	63.10	20	0.0997	1.0
802.11ac40	5150~5250	9.0	7.94	12.00	15.85	20	0.0250	1.0
	5725~5850	9.0	7.94	17.50	56.23	20	0.0889	1.0
802.11n-HT40	5150~5250	9.0	7.94	12.00	15.85	20	0.0250	1.0
	5725~5850	9.0	7.94	17.50	56.23	20	0.0889	1.0
802.11ac80	5210	9.0	7.94	12.00	15.85	20	0.0250	1.0
	5775	9.0	7.94	17.00	50.12	20	0.0792	1.0

Note:

- (1) The tune-up output power was declared by the manufacturer.
(2) 2.4G Wi-Fi and 5G Wi-Fi cannot transmit simultaneously.

Result: The device meets FCC MPE at 20 cm distance.