

TEST REPORT

Reference No...... : WTK21D03016284W002
FCC ID : 2AYBP-F6
Applicant..... : Wingo Times Shenzhen Group Co., Ltd
Address..... : 1101, Building H, ChuangxinYungu Workshop, No.48 Paotai Road,
First Industrial Zone, Lisonglang Community, Gongming Street,
Guangming District, Shenzhen
Manufacturer : Same as above
Address..... : Same as above
Product..... : 3-in-1 Wireless charging Station
Model(s) : F6
Standards..... : FCC CFR47 Part 1.1307
FCC CFR47 Part 1.1310
Date of Receipt sample : 2021-03-10
Date of Test : 2021-03-11 to 2021-03-29
Date of Issue..... : 2021-03-30
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

Approved by:

Estel Qian

Estel Qian / Project Engineer



Daniel Liu

Daniel Liu / Designated Reviewer

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 REVISION HISTORY	3
4 GENERAL INFORMATION	4
4.1 GENERAL DESCRIPTION OF E.U.T.....	4
4.2 DETAILS OF ACCESSORIES	4
4.3 TEST MODE	5
4.4 TEST FACILITY	5
5 TEST SUMMARY	6
6 EQUIPMENT USED DURING TEST	7
6.1 EQUIPMENTS LIST	7
6.2 DESCRIPTION OF AUXILIARY EQUIPMENT	7
6.3 TEST EQUIPMENT CALIBRATION	7
7 RF EXPOSURE	8
7.1 TEST SETUP	8
7.2 EQUIPMENT APPROVAL CONSIDERATIONS (CLAUSE 5 B) OF KDB 680106 D01 V03	8
7.3 FCC RULES.....	9
7.4 EUT OPERATION.....	9
7.5 TEST RESULT	10
8 PHOTOGRAPHS OF TEST SETUP	11

3 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTK21D03016 284W002	2021-03-10	2021-03-11 to 2021-03-29	2021-03-30	original	-	Valid

4 General Information

4.1 General Description of E.U.T

Product:	3-in-1 Wireless charging Station
Model(s):	F6
Model Difference:	N/A
Type of Modulation:	ASK
Frequency Range:	110-205kHz
Antenna installation:	Inductive loop coil Antenna
Hardware Version:	V1.1
Software Version:	V1.1

4.2 Details of accessories

Ratings	:	Input: 9V $\overline{\text{---}}$ 2A or 12V $\overline{\text{---}}$ 2A
		Output: 1 Top: 3W Max
		2 Front: 15W Max
		3 Back: 5W Max

4.3 Test Mode

Test Mode	Descriptions
Standby mode	EUT alone powered by AC/DC adapter
Charging mode	Ant.1 loading of 3W
	Ant.2 loading of 15W
	Ant.3 loading of 15W
	Ant.4 loading of 5W

Note: EUT was investigated with client device under normal charging condition as above then worst value was only report.

4.4 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Services (Shenzhen) Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Services (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Test Summary

Test Items	Test Requirement	Result
Electric Field Strength (E) (V/m)	FCC CFR 47 part1 § 1.1310	PASS
Magnetic Field Strength (H) (A/m)	KDB 680106 D01 v03	PASS

Note: -

6 Equipment Used during Test

6.1 Equipments List

RF EXPOSURE						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Calibration Date	Valid
1	E-Field Probe	NARDA	EP-601	611WX70311	2021-01-13	1Year
2	H-Field Probe	NARDA	ELT-400	M-0155/M-0170	2020-07-24	1Year

6.2 Description of Auxiliary Equipment


Equipment	Manufacturer	Model No.	Series No.
Power Adapter	Flextronics Sales & Marketing (A-P) Ltd	A1882	/
Cellular Phone	HAWEI	MATE 20 PRO	/
Watch	Apple	SE	/
Wireless Charging Case	Apple	A2031	/

6.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R. China.

7 RF Exposure

7.1 Test Setup



The RF exposure test was performed in anechoic chamber.

The probe was placed at test distance (15cm) which is between the edge of the charger and the geometric centre of probe.

The EUT was put in different directions (Left, Right, Front, Rear, Top and Bottom) to obtain the maximum reading.

The EUT was measured according to the dictates of KDB 680106 D01 RF Exposure Wireless Charging App v03.

7.2 Equipment approval considerations (clause 5 b) of KDB 680106 D01 v03

- (1) Power transfer frequency is less than 1 MHz.
- (2) Output power from each primary coil is less than or equal to 15 watts.
- (3) The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils.
- (4) Client device is placed directly in contact with the transmitter.
- (5) Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).
- (6) The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

7.3 FCC Rules

§1.1310: The criteria listed in the following table 1 shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of FCC part 2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

Note:

RF exposure compliance will need to be determined with respect to 1.1307(C) and (d) of the FCC rule s. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150Khz:614V/m, 1.63A/m).

7.4 EUT Operation

Operating Environment:

Temperature: 22.3 °C

Humidity: 50.1 % RH

Atmospheric Pressure: 101.2kPa

EUT Operation: Charging mode: Loading of 15 W

Only the worst-case transmitting mode were record in the report.

7.5 Test Result

Maximum RF exposure reading and percentage

Electric Field Limit			Magnetic Field Limit		
FCC	Maximum RMS (V/m)	Percentage (%)	FCC	Maximum RMS (A/m)	Percentage (%)
614	15.33	2.50	1.623	0.26	15.88

E-Filed Strength (V/m) of charging mode: Ant.1 loading of 3 W

Frequency Range MHz	Test Position					Maximum (V/m)
	A	B	C	D	E	
0.127	15.33	11.00	9.96	10.54	8.01	15.33

H-Filed Strength (A/m) of charging mode: Ant.2 loading of 3 W

Frequency Range MHz	Test Position					Maximum (A/m)
	A	B	C	D	E	
0.127	0.258	0.085	0.099	0.187	0.099	0.258

8 Photographs of test setup

Note: Please refer to appendix: Appendix-F6-Photos.

=====**End of Report**=====