



Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.407

Report Reference No.....: GTS20220803009-1-41

FCC ID.....: 2AYD5-I22D01A

Compiled by

(position+printed name+signature) .: File administrators Peter Xiao

Supervised by

(position+printed name+signature) .: Test Engineer Evan Ouyang

Approved by

(position+printed name+signature) .: Manager Jason Hu



Date of issue: Jul.25, 2023

Representative Laboratory Name.: Shenzhen Global Test Service Co.,Ltd.

Address: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong,China

Applicant's name.....: Imin Technology Pte Ltd

Address: 11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943

Test specification

Standard.....: **FCC Part 15.407: General technical requirements**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF: Dated 2014-12

Shenzhen Global Test Service Co.,Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description POS Device

Trade Mark:

Manufacturer: Imin Technology Pte Ltd

Model/Type reference: I22D01

Listed Models: N/A

Operation Frequency.....: From 5180MHz to 5240MHz/ 5260MHz to 5320MHz/ 5500MHz to 5700MHz/ 5745MHz to 5825MHz

Hardware Version: V1.0

Software Version.....: N/A

Rating: DC 24V/2.5A by adapter or
DC 24V/1.5A by adapter

Result: **PASS**

TEST REPORT

Test Report No. : GTS20220803009-1-41	Jul.25, 2023 Date of issue
--	-------------------------------

Equipment under Test : POS Device

Model /Type : I22D01

Listed model : N/A

Applicant : **Imin Technology Pte Ltd**

Address : 11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943

Manufacturer : **Imin Technology Pte Ltd**

Address : 11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943

Test Result:	PASS
---------------------	-------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

1. TEST STANDARDS	4
2. SUMMARY	5
2.1. General Remarks	5
2.2. Product Description	5
2.3. Equipment Under Test	5
2.4. Short description of the Equipment under Test (EUT)	6
2.5. EUT operation mode	6
2.6. Block Diagram of Test Setup	7
2.7. Related Submittal(s) / Grant (s)	7
2.8. EUT Exercise Software	7
2.9. Special Accessories	8
2.10. External I/O Cable	8
2.11. Modifications	8
3. TEST ENVIRONMENT	9
3.1. Address of the test laboratory	9
3.2. Test Facility	9
3.3. Environmental conditions	9
3.4. Statement of the measurement uncertainty	9
3.5. Test Description	10
3.6. Equipments Used during the Test.....	12
4. TEST CONDITIONS AND RESULTS	13
4.1. AC Power Conducted Emission	13
4.2. Radiated Emission	14
4.3. Duty Cycle	36
4.4. Maximum Average Output Power	37
4.5. Power Spectral Density	38
4.6. 99% and 6dB Bandwidth	39
4.7. 99% and 26dBc Bandwidth	40
4.8. Conducted Spurious Emissions and Band Edge Compliance	41
4.9. Frequency Stability.....	43
4.10. Antenna Requirement	47
5. TEST SETUP PHOTOS OF THE EUT.....	48
6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	48

1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.407](#): General technical requirements.

[ANSI C63.10-2020](#): American National Standard for Testing Unlicensed Wireless Devices


[KDB 789033 D02 General U-NII Test Procedures New Rules v02r01](#): UNII, U-NII, U-NII Test Procedures

2. SUMMARY

2.1. General Remarks

Date of receipt of test sample	:	Jun. 19, 2023
Testing commenced on	:	Jun. 19, 2023
Testing concluded on	:	Jul. 11, 2023

2.2. Product Description

Product Name:	POS Device
Trade Mark:	
Model/Type reference:	I22D01
List Model:	N/A
Model Declaration	N/A
Power supply:	DC 24V/2.5A by adapter or DC 24V/1.5A by adapter
Hardware Version	V1.0
Software Version	N/A
Sample ID	GTS20220803009-1-S0001-5#& GTS20220803009-1-S0001-6#
Bluetooth	
Frequency Range	2402MHz ~ 2480MHz
Channel Number	79 channels for Bluetooth (DSS) 40 channels for Bluetooth (DTS)
Channel Spacing	1MHz for Bluetooth (DSS) 2MHz for Bluetooth (DTS)
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK for Bluetooth (DSS) GFSK for Bluetooth (DTS)
2.4G WLAN	
WLAN Operation frequency	IEEE 802.11b:2412-2462MHz IEEE 802.11g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz
WLAN Modulation Type	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Channel number:	11 Channel for IEEE 802.11b/g/n(HT20)
Channel separation:	5MHz
WIFI(5.2G/5.3G/5.7G Band)	
Frequency Range	5180MHz ~ 5240MHz, 5260MHz ~ 5320MHz, 5500MHz ~ 5700MHz
Channel Number	4 Channels for 20MHz bandwidth(5180-5240MHz) 4 Channels for 20MHz bandwidth(5260-5320MHz) 11 Channels for 20MHz bandwidth(5500-5700MHz) 2 channels for 40MHz bandwidth(5190~5230MHz) 2 channels for 40MHz bandwidth(5270~5310MHz) 5 Channels for 40MHz bandwidth(5510-5670MHz) 1 channels for 80MHz bandwidth(5210MHz) 1 channels for 80MHz bandwidth(5290MHz) 2 Channels for 80MHz bandwidth(5530-5610MHz)
Modulation Type	802.11a/n/ac: OFDM
WIFI (5.8G Band)	
Frequency Range	5745MHz ~ 5825MHz
Channel Number	5 channels for 20MHz bandwidth(5745-5825MHz) 2 channels for 40MHz bandwidth(5755~5795MHz) 1 channels for 80MHz bandwidth(5775MHz)
Modulation Type	802.11a/n/ac: OFDM
Antenna Description	FPC Antenna, 5.12dBi(Max.) for 2.4G Band and 7.16dBi(Max.) for 5G Band

RFID(13.56MHz) (Optional)	
Frequency Range	13.56MHz
Channel Number	1
Modulation Type	ASK
Antenna Description	Internal Antenna, 0dBi (Max.)
GPS(RX)	Support
Remark:The I22D01 model has 2 versions; Version A: One large display and one small display Version B: Only one large display	

2.3. Equipment Under Test

Power supply system utilised

Power supply voltage	:	<input type="radio"/> 230V / 50 Hz	<input type="radio"/> 120V / 60Hz
		<input type="radio"/> 12 V DC	<input checked="" type="radio"/> 24 V DC
		<input type="radio"/> Other (specified in blank below)	

DC 24.0V

2.4. Short description of the Equipment under Test (EUT)

This is a POS Device.

For more details, refer to the user's manual of the EUT.

2.5. EUT operation mode

The application provider specific test software to control sample in continuous TX and RX.

Antenna	Chain0 (ANT0)			Chain1 (ANT1)			Simultaneously
	20MHz	40MHz	80MHz	20MHz	40MHz	80MHz	
IEEE 802.11a	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11n	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
IEEE 802.11ac	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

IEEE 802.11a/ac20/ac40/ac80/n20/n40:

UNII-1		UNII-1		UNII-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

U-NI-2A		U-NI-2A		U-NI-2A	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				


U-NI-2C		U-NI-2C		U-NI-2C	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590		
112	5560	126	5630		
116	5580	134	5670		
120	5600				
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				

U-NI-3		U-NI-3		U-NI-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position. AC main conducted emission pre-test voltage at both AC 120V/60Hz and AC 240V/60Hz, recorded worst case; AC main conducted emission pre-test at charge from PC modes, recorded worst case; Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be IEEE 802.11ac VHT20 mode (HCH).

2.6. Block Diagram of Test Setup



2.7. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2AYD5-I22D01A** filing to comply with Section 15.407 of the FCC Part 15, Subpart E Rules.

2.8. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (adb mode) provided by application.

2.9. Special Accessories

Manufacturer	Description	Model	Serial Number	Certificate
JiangSu Sunward Electronic Technology Co., Ltd	Adapter	AD65CM240150	--	SDOC
Shenzhen SOY Technology Co.,Ltd.	Adapter	SOY-2400250-332-A	--	SDOC
SHENZHEN HONOR ELECTRONIC CO.,LTD.	Adapter	ADS-65HI-19A-1 24036E	--	SDOC
Jiangsu Chenyang Electron Co.,Ltd.	Adapter	CYZS36-240150	--	SDOC
LENOVO	Keyboard	T460S	--	SDOC
LENOVO	Mouse	Howard	--	SDOC
LENOVO	PC	DESKYOP-EUIVCNR	--	SDOC
--	SD Card	--	--	--
aigo	USB flash disk	U330	--	SDOC

Note: The PC, Keyboard, Mouse, SD Card and USB flash disk is only used for auxiliary testing.

2.10. External I/O Cable

I/O Port Description	Quantity	Cable
DC IN Port	1	1.2M, Unscreened Cable
USB	3	N/A
LAN	1	1.2M, Unscreened Cable
HDMI	1	0.4M, Unscreened Cable
RS232	2	N/A

2.11. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Global Test Service Co.,Ltd.

No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong, China.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS (No. CNAS L8169)

Shenzhen Global Test Service Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2019 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA (Certificate No. 4758.01)

Shenzhen Global Test Service Co., Ltd. has been assessed by the American Association for Laboratory Accreditation (A2LA). Certificate No. 4758.01.

Industry Canada Registration Number. is 24189.

FCC Designation Number is CN1234.

FCC Registered Test Site Number is165725.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

3.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10 dB	(1)
Radiated Emission	1~18GHz	4.32 dB	(1)
Radiated Emission	18-40GHz	5.54 dB	(1)
Conducted Disturbance	0.15~30MHz	3.12 dB	(1)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.5. Test Description

Applied Standard: FCC Part 15 Subpart E				
FCC Rules	Description of Test	Test Sample	Result	Remark
/	On Time and Duty Cycle	GTS20220803009-1-S0001-5#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.407(a)	Maximum Conducted Output Power	GTS20220803009-1-S0001-5#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.407(a)	Power Spectral Density	GTS20220803009-1-S0001-5#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.407(a)	26dB&6dB Bandwidth and 99% Bandwidth	GTS20220803009-1-S0001-5#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.209, §15.407(b)	Radiated Emissions	GTS20220803009-1-S0001-5# GTS20220803009-1-S0001-6#	Compliant	Note 1
§15.209, §15.407(b)	Conducted Spurious Emissions and Band Edges Test	GTS20220803009-1-S0001-5#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.209, §15.407(b)	Emissions at Restricted Band	GTS20220803009-1-S0001-5#	Compliant	Appendix D Appendix E Appendix F Appendix G
§15.407(g)	Frequency Stability	GTS20220803009-1-S0001-5#	Compliant	Note 1
§15.207(a)	AC Mians Line Conducted Emissions	GTS20220803009-1-S0001-6#	Compliant	Note 1
§15.203 §15.407(h)	Antenna Requirements	GTS20220803009-1-S0001-5#	Compliant	Note 1
§15.407 §2.1091	RF Exposure	/	Compliant	Note 2

Remark:

1. The measurement uncertainty is not included in the test result.
2. NA = Not Applicable; NP = Not Performed
3. Note 1 – Test results inside test report;
4. Note 2 – Test results in other test report (MPE Report).
5. We tested all test mode and recorded worst case in report

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Peak Conducted Output Power Power Spectral Density 6dB Bandwidth 26dB Bandwidth Radiated Emission30M~1GHz& Radiated Emission 1GHz~10 th Harmonic	802.11a	6 Mbps
	802.11ac20/ac40/ac80 802.11n HT20/40	MCS0
Band Edge	802.11a	6 Mbps
	802.11ac20/ac40/ac80 802.11n HT20/40	MCS0

3.6. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	CYBERTEK	EM5040A	E1850400105	2022/07/13	2023/07/12
LISN	R&S	ESH2-Z5	893606/008	2022/07/13	2023/07/12
EMI Test Receiver	R&S	ESPI3	101841-cd	2022/07/13	2023/07/12
EMI Test Receiver	R&S	ESCI7	101102	2022/09/09	2023/09/08
Spectrum Analyzer	Agilent	N9020A	MY48010425	2022/09/09	2023/09/08
Spectrum Analyzer	R&S	FSV40	100019	2022/07/13	2023/07/12
Vector Signal generator	Agilent	N5181A	MY49060502	2022/07/13	2023/07/12
Signal generator	Agilent	N5182A	3610AO1069	2022/09/09	2023/09/08
Climate Chamber	ESPEC	EL-10KA	A20120523	2022/09/09	2023/09/08
Controller	EM Electronics	Controller EM 1000	N/A	N/A	N/A
Horn Antenna	Schwarzbeck	BBHA 9120D	01622	2022/09/09	2023/09/08
Active Loop Antenna	Beijing Da Ze Technology Co.,Ltd.	ZN30900C	15006	2022/09/09	2023/09/08
Bilog Antenna	Schwarzbeck	VULB9163	000976	2022/07/13	2023/07/12
Broadband Horn Antenna	SCHWARZBECK	BBHA 9170	791	2022/09/09	2023/09/08
Amplifier	Schwarzbeck	BBV 9743	#202	2022/07/13	2023/07/12
Amplifier	Schwarzbeck	BBV9179	9719-025	2022/07/13	2023/07/12
Amplifier	EMCI	EMC051845B	980355	2022/07/13	2023/07/12
Temperature/Humidity Meter	Gangxing	CTH-608	02	2022/07/13	2023/07/12
High-Pass Filter	K&L	9SH10-2700/X12750-O/O	KL142031	2022/07/13	2023/07/12
High-Pass Filter	K&L	41H10-1375/U12750-O/O	KL142032	2022/07/13	2023/07/12
RF Cable(below 1GHz)	HUBER+SUHNER	RG214	RE01	2022/07/13	2023/07/12
RF Cable(above 1GHz)	HUBER+SUHNER	RG214	RE02	2022/07/13	2023/07/12
Data acquisition card	Agilent	U2531A	TW53323507	2022/07/13	2023/07/12
Power Sensor	Agilent	U2021XA	MY5365004	2022/07/13	2023/07/12
Test Control Unit	Tonscend	JS0806-1	178060067	2022/07/13	2023/07/12
Automated filter bank	Tonscend	JS0806-F	19F8060177	2022/07/13	2023/07/12
EMI Test Software	Tonscend	JS1120-1	Ver 2.6.8.0518	/	/
EMI Test Software	Tonscend	JS1120-3	Ver 2.5.77.0418	/	/
EMI Test Software	Tonscend	JS32-CE	Ver 2.5	/	/
EMI Test Software	Tonscend	JS32-RE	Ver 2.5.1.8	/	/

Note: The Cal.Interval was one year.

4. TEST CONDITIONS AND RESULTS

4.1. AC Power Conducted Emission

TEST CONFIGURATION



TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2020.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2020
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2020
- 4 The EUT received DC 24.0V power, the adapter received AC120V/60Hz or AC 240V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.

AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST RESULTS


Remark: We measured Conducted Emission at all mode in AC 120V/60Hz, the worst case was recorded .

Temperature	25°C	Humidity	60%
Test Engineer	Evan Ouyang	Configurations	IEEE 802.11ac20 HCH

Version A:
Adapter: AD65CM240150

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph




Final Data List												
N.O.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1634	34.94	20.41	9.60	44.54	30.01	65.29	55.29	20.75	25.28	L1	PASS
2	0.1809	28.01	16.39	9.59	37.60	25.98	64.44	54.44	26.84	28.46	L1	PASS
3	0.6220	32.90	26.70	9.63	42.53	36.33	56.00	46.00	13.47	9.67	L1	PASS
4	1.4275	18.71	11.92	9.38	28.09	21.30	56.00	46.00	27.91	24.70	L1	PASS
5	20.6002	28.72	21.72	9.23	37.95	30.95	60.00	50.00	22.05	19.05	L1	PASS
6	23.0220	29.02	22.42	9.25	38.27	31.67	60.00	50.00	21.73	18.33	L1	PASS

Note:1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph



Final Data List												
N.O.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1591	35.55	21.97	9.60	45.15	31.57	65.51	55.51	20.36	23.94	N	PASS
2	0.1905	29.53	18.54	9.60	39.13	28.14	64.01	54.01	24.88	25.87	N	PASS
3	0.6179	39.38	33.72	9.40	48.78	43.12	56.00	46.00	7.22	2.88	N	PASS
4	1.7171	25.39	19.10	9.36	34.75	28.46	56.00	46.00	21.25	17.54	N	PASS
5	9.6820	23.71	15.71	9.28	32.99	24.99	60.00	50.00	27.01	25.01	N	PASS
6	23.8841	32.57	25.83	9.25	41.82	35.08	60.00	50.00	18.18	14.92	N	PASS


Note:1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Adapter: SOY-2400250-332-A

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph



Final Data List


N.O.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.1630	35.11	20.47	9.60	44.71	30.07	65.31	55.31	20.60	25.24	L1	PASS
2	0.3180	20.14	12.83	9.42	29.56	22.25	59.76	49.76	30.20	27.51	L1	PASS
3	0.6153	34.39	28.95	9.65	44.04	38.60	56.00	46.00	11.96	7.40	L1	PASS
4	1.7249	20.03	13.87	9.37	29.40	23.24	56.00	46.00	26.60	22.76	L1	PASS
5	8.0017	18.24	11.42	9.25	27.49	20.67	60.00	50.00	32.51	29.33	L1	PASS
6	21.3966	28.72	21.95	9.24	37.96	31.19	60.00	50.00	22.04	18.81	L1	PASS

Note:1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph



Final Data List

N.O.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.1590	35.40	21.89	9.60	45.00	31.49	65.52	55.52	20.52	24.03	N	PASS
2	0.6159	39.53	33.96	9.40	48.93	43.36	56.00	46.00	7.07	2.64	N	PASS
3	1.2845	22.67	16.76	9.37	32.04	26.13	56.00	46.00	23.96	19.87	N	PASS
4	1.7065	25.44	19.44	9.36	34.80	28.80	56.00	46.00	21.20	17.20	N	PASS
5	5.1377	23.42	16.49	9.34	32.76	25.83	60.00	50.00	27.24	24.17	N	PASS
6	23.8698	32.91	25.15	9.25	42.16	34.40	60.00	50.00	17.84	15.60	N	PASS


Note:1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Adapter: ADS-65HI-19A-1 24036E

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph




Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1633	35.01	20.46	9.60	44.61	30.06	65.30	55.30	20.69	25.24	L1	PASS
2	0.1899	30.62	18.11	9.57	40.19	27.68	64.04	54.04	23.85	26.36	L1	PASS
3	0.4075	18.70	13.20	9.44	28.14	22.64	57.70	47.70	29.56	25.06	L1	PASS
4	0.6177	34.31	28.83	9.65	43.96	38.48	56.00	46.00	12.04	7.52	L1	PASS
5	1.7349	20.06	14.03	9.37	29.43	23.40	56.00	46.00	26.57	22.60	L1	PASS
6	22.4462	28.88	22.23	9.24	38.12	31.47	60.00	50.00	21.88	18.53	L1	PASS

Note: 1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph



Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1586	34.67	21.18	9.60	44.27	30.78	65.54	55.54	21.27	24.76	N	PASS
2	0.3856	20.14	14.26	9.48	29.62	23.74	58.16	48.16	28.54	24.42	N	PASS
3	0.6231	37.73	30.79	9.40	47.13	40.19	56.00	46.00	8.87	5.81	N	PASS
4	5.1210	23.39	16.49	9.35	32.74	25.84	60.00	50.00	27.26	24.16	N	PASS
5	9.0454	23.66	16.50	9.30	32.96	25.80	60.00	50.00	27.04	24.20	N	PASS
6	23.4767	32.71	24.61	9.24	41.95	33.85	60.00	50.00	18.05	16.15	N	PASS


Note: 1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Model: CYZS36-240150

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph




Final Data List												
NO.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.1627	35.31	20.63	9.60	44.91	30.23	65.33	55.33	20.42	25.10	L1	PASS
2	0.3651	16.22	9.21	9.43	25.65	18.64	58.61	48.61	32.96	29.97	L1	PASS
3	0.6162	34.27	28.96	9.65	43.92	38.61	56.00	46.00	12.08	7.39	L1	PASS
4	1.5844	15.88	10.63	9.38	25.26	20.01	56.00	46.00	30.74	25.99	L1	PASS
5	11.2241	21.31	13.51	9.17	30.48	22.68	60.00	50.00	29.52	27.32	L1	PASS
6	21.8157	28.80	22.05	9.23	38.03	31.28	60.00	50.00	21.97	18.72	L1	PASS

Note: 1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph



Final Data List												
NO.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.1590	35.47	21.97	9.60	45.07	31.57	65.52	55.52	20.45	23.95	N	PASS
2	0.6156	39.35	33.92	9.40	48.75	43.32	56.00	46.00	7.25	2.68	N	PASS
3	1.7429	25.12	18.57	9.35	34.47	27.92	56.00	46.00	21.53	18.08	N	PASS
4	4.3125	22.77	16.24	9.38	32.15	25.62	56.00	46.00	23.85	20.38	N	PASS
5	9.8099	23.79	16.51	9.28	33.07	25.79	60.00	50.00	26.93	24.21	N	PASS
6	22.6181	32.19	25.20	9.25	41.44	34.45	60.00	50.00	18.56	15.55	N	PASS


Note: 1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Version B:
Adapter: AD65CM240150

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph




Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1629	34.08	19.60	9.60	43.68	29.20	65.32	55.32	21.64	26.12	L1	PASS
2	0.6189	33.25	27.68	9.64	42.89	37.32	56.00	46.00	13.11	8.68	L1	PASS
3	1.7145	19.20	13.33	9.37	28.57	22.70	56.00	46.00	27.43	23.30	L1	PASS
4	5.1547	16.93	10.24	9.36	26.29	19.60	60.00	50.00	33.71	30.40	L1	PASS
5	11.4425	20.74	13.50	9.17	29.91	22.67	60.00	50.00	30.09	27.33	L1	PASS
6	24.4320	28.30	21.47	9.26	37.56	30.73	60.00	50.00	22.44	19.27	L1	PASS

Note:1. Result (dBµV) = Reading (dBµV) + F factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph



Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1632	34.00	20.53	9.60	43.60	30.13	65.30	55.30	21.70	25.17	N	PASS
2	0.4467	27.32	22.75	9.44	36.76	32.19	56.94	46.94	20.18	14.75	N	PASS
3	0.6180	39.32	33.73	9.40	48.72	43.13	56.00	46.00	7.28	2.87	N	PASS
4	1.4486	25.87	18.96	9.36	35.23	28.32	56.00	46.00	20.77	17.68	N	PASS
5	3.2874	24.32	17.37	9.35	33.67	26.72	56.00	46.00	22.33	19.28	N	PASS
6	22.4843	32.04	25.32	9.24	41.28	34.56	60.00	50.00	18.72	15.44	N	PASS


Note:1. Result (dBµV) = Reading (dBµV) + F factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Adapter: SOY-2400250-332-A

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph




Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1589	36.58	22.24	9.60	46.18	31.84	65.52	55.52	19.34	23.68	L1	PASS
2	0.1958	28.81	16.72	9.56	38.37	26.28	63.79	53.79	25.42	27.51	L1	PASS
3	0.6201	32.80	26.48	9.64	42.44	36.12	56.00	46.00	13.56	9.88	L1	PASS
4	1.4411	19.91	13.46	9.38	29.29	22.84	56.00	46.00	26.71	23.16	L1	PASS
5	5.3853	16.95	10.24	9.36	26.31	19.60	60.00	50.00	33.69	30.40	L1	PASS
6	22.4547	28.78	20.91	9.24	38.02	30.15	60.00	50.00	21.98	19.85	L1	PASS

Note:1. Result (dBµV) = Reading (dBµV) + F factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph



Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1633	32.96	19.46	9.60	42.56	29.06	65.30	55.30	22.74	26.24	N	PASS
2	0.1777	27.79	16.93	9.59	37.38	26.52	64.59	54.59	27.21	28.07	N	PASS
3	0.6199	38.68	32.47	9.40	48.08	41.87	56.00	46.00	7.92	4.13	N	PASS
4	1.1835	25.52	18.87	9.38	34.90	28.25	56.00	46.00	21.10	17.75	N	PASS
5	3.8576	22.57	15.34	9.38	31.95	24.72	56.00	46.00	24.05	21.28	N	PASS
6	23.1003	33.00	25.21	9.25	42.25	34.46	60.00	50.00	17.75	15.54	N	PASS


Note:1. Result (dBµV) = Reading (dBµV) + F factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Adapter: ADS-65HI-19A-1 24036E

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph




Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1582	35.52	21.10	9.60	45.12	30.70	65.56	55.56	20.44	24.86	L1	PASS
2	0.1728	29.18	16.58	9.59	38.77	26.17	64.82	54.82	26.05	28.65	L1	PASS
3	0.6209	33.25	26.74	9.64	42.89	36.38	56.00	46.00	13.11	9.62	L1	PASS
4	1.0468	16.53	10.16	9.38	25.91	19.54	56.00	46.00	30.09	26.46	L1	PASS
5	5.2332	16.69	8.77	9.35	26.04	18.12	60.00	50.00	33.96	31.88	L1	PASS
6	23.6785	29.49	21.47	9.26	38.75	30.73	60.00	50.00	21.25	19.27	L1	PASS

Note: 1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph



Final Data List												
NO.	Frequency	QP	AVG.	Factor	QP	AVG.	QP	AVG.	QP	AVG.	Line	Remark
		Reading	Reading		Result	Result	Limit	Limit	Margin	Margin		
1	0.1585	34.75	21.18	9.60	44.35	30.78	65.54	55.54	21.19	24.76	N	PASS
2	0.3400	17.56	9.96	9.47	27.03	19.43	59.20	49.20	32.17	29.77	N	PASS
3	0.6177	38.74	32.73	9.40	48.14	42.13	56.00	46.00	7.86	3.87	N	PASS
4	1.7656	24.16	17.12	9.35	33.51	26.47	56.00	46.00	22.49	19.53	N	PASS
5	4.3814	23.06	15.13	9.38	32.44	24.51	56.00	46.00	23.56	21.49	N	PASS
6	23.7681	32.77	24.83	9.26	42.03	34.09	60.00	50.00	17.97	15.91	N	PASS


Note: 1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Model: CYZS36-240150

Power supply:	AC 120V/60Hz	Polarization	L
---------------	--------------	--------------	---

Test Graph




Final Data List												
N.O.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.1549	35.90	21.46	9.60	45.50	31.06	65.73	55.73	20.23	24.67	L1	PASS
2	0.1821	28.13	16.15	9.59	37.72	25.74	64.39	54.39	26.67	28.65	L1	PASS
3	0.6180	33.68	27.71	9.65	43.33	37.36	56.00	46.00	12.67	8.64	L1	PASS
4	1.4755	19.65	13.18	9.38	29.03	22.56	56.00	46.00	26.97	23.44	L1	PASS
5	5.4634	17.40	10.08	9.36	26.76	19.44	60.00	50.00	33.24	30.56	L1	PASS
6	22.8921	29.42	21.27	9.25	38.67	30.52	60.00	50.00	21.33	19.48	L1	PASS

Note: 1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).

Power supply:	AC 120V/60Hz	Polarization	N
---------------	--------------	--------------	---

Test Graph



Final Data List												
N.O.	Frequency	QP Reading	AVG. Reading	Factor	QP Result	AVG. Result	QP Limit	AVG. Limit	QP Margin	AVG. Margin	Line	Remark
1	0.1543	35.05	21.47	9.61	44.66	31.08	65.76	55.76	21.10	24.68	N	PASS
2	0.6197	38.60	32.29	9.40	48.00	41.69	56.00	46.00	8.00	4.31	N	PASS
3	1.4487	25.63	18.40	9.36	34.99	27.76	56.00	46.00	21.01	18.24	N	PASS
4	2.0120	24.11	16.96	9.34	33.45	26.30	56.00	46.00	22.55	19.70	N	PASS
5	7.0215	22.97	14.96	9.31	32.28	24.27	60.00	50.00	27.72	25.73	N	PASS
6	22.6435	32.39	24.07	9.25	41.64	33.32	60.00	50.00	18.36	16.68	N	PASS


Note: 1. Result (dBµV) = Reading (dBµV) + Factor (dB).

2. Factor (dB) = Cable loss (dB) + LISN Factor (dB).


4.2. Radiated Emission

TEST CONFIGURATION


Frequency range 9 KHz – 30MHz



Frequency range 30MHz – 1000MHz



Frequency range above 1GHz



TEST PROCEDURE

1. The EUT was placed on a turn table which is 0.8m above ground plane when testing frequency range 9 KHz –1GHz;the EUT was placed on a turn table which is 1.5m above ground plane when testing above 1GHz.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.
5. The EUT minimum operation frequency was 24MHz and maximum operation frequency was 5825MHz.so radiated emission test frequency band from 9KHz to 40GHz.
6. The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
9KHz-30MHz	Active Loop Antenna	3
30MHz-1GHz	Ultra-Broadband Antenna	3
1GHz-18GHz	Double Ridged Horn Antenna	3
18GHz-25GHz	Horn Antenna	1

7. Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
9KHz-150KHz	RBW=200Hz/VBW=3KHz, Sweep time=Auto	QP
150KHz-30MHz	RBW=9KHz/VBW=100KHz, Sweep time=Auto	QP
30MHz-1GHz	RBW=120KHz/VBW=1000KHz, Sweep time=Auto	QP
1GHz-40GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Transd=AF +CL-AG

RADIATION LIMIT

According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBµV/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 (beyond 10MHz of the bandedge)	68.2
	-17 (within 10 MHz of band edge)	78.2

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	2400/F(KHz)
0.49-1.705	3	$20\log(24000/F(KHz))+ 40\log(30/3)$	24000/F(KHz)
1.705-30	3	$20\log(30)+ 40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST RESULTS

Remark: We measured Radiated Emission at all mode from 9KHz to 25GHz in AC 120V/60Hz and the worst case was recorded.

Temperature	23.4°C	Humidity	54.5%
Test Engineer	Evan Ouyang	Configurations	IEEE 802.11ac20 HCH

For 9 KHz~30MHz

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Over Limit (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);


Limit line = specific limits (dBuV) + distance extrapolation factor.

For 30MHz-1GHz

Version A:
Adapter: AD65CM240150

Horizontal

Test Graph




Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Lim it [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Rem ark
1	46.005	43.86	-15.60	28.26	40.00	11.74	100	258	PK	Horizontal	PASS
2	101.78	49.79	-17.69	32.10	43.50	11.40	100	285	PK	Horizontal	PASS
3	149.795	56.96	-22.19	34.77	43.50	8.73	100	295	PK	Horizontal	PASS
4	260.86	48.44	-17.41	31.03	46.00	14.97	100	74	PK	Horizontal	PASS
5	545.07	42.95	-12.75	30.20	46.00	15.80	100	0	PK	Horizontal	PASS
6	769.14	45.12	-9.63	35.49	46.00	10.51	100	212	PK	Horizontal	PASS

Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Lim it [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Rem ark
1	35.82	54.38	-18.70	35.68	40.00	4.32	100	94	PK	Vertical	PASS
2	46.49	50.08	-15.40	34.68	40.00	5.32	100	98	PK	Vertical	PASS
3	107.6	51.13	-17.20	33.93	43.50	9.57	100	337	PK	Vertical	PASS
4	159.01	56.72	-20.94	35.78	43.50	7.72	100	307	PK	Vertical	PASS
5	351.555	42.77	-15.34	27.43	46.00	18.57	100	94	PK	Vertical	PASS
6	765.26	44.12	-9.71	34.41	46.00	11.59	100	29	PK	Vertical	PASS


Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Adapter: SOY-2400250-332-A

Horizontal

Test Graph




Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	48.915	44.99	-15.76	29.23	40.00	10.77	100	111	PK	Horizontal	PASS
2	104.69	53.68	-17.33	36.35	43.50	7.15	100	350	PK	Horizontal	PASS
3	159.98	55.26	-20.78	34.48	43.50	9.02	100	62	PK	Horizontal	PASS
4	260.86	48.17	-17.41	30.76	46.00	15.24	100	84	PK	Horizontal	PASS
5	441.28	43.66	-13.95	29.71	46.00	16.29	100	356	PK	Horizontal	PASS
6	907.85	44.68	-7.63	37.05	46.00	8.95	100	2	PK	Horizontal	PASS

Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph





Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	36.305	53.62	-18.56	35.06	40.00	4.94	100	38	PK	Vertical	PASS
2	46.49	49.90	-15.40	34.50	40.00	5.50	100	81	PK	Vertical	PASS
3	106.145	52.14	-17.24	34.90	43.50	8.60	100	146	PK	Vertical	PASS
4	159.98	55.20	-20.78	34.42	43.50	9.08	100	308	PK	Vertical	PASS
5	282.2	44.63	-17.31	27.32	46.00	18.68	100	74	PK	Vertical	PASS
6	641.585	44.63	-11.28	33.35	46.00	12.65	100	91	PK	Vertical	PASS

Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).


Adapter: ADS-65HI-19A-1 24036E



Adapter: CYZS36-240150

Horizontal

Test Graph




Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	46.49	43.61	-15.40	28.21	40.00	11.79	100	82	PK	Horizontal	PASS
2	104.69	51.14	-17.33	33.81	43.50	9.69	100	357	PK	Horizontal	PASS
3	160.466	58.07	-20.94	37.13	43.50	6.37	100	266	PK	Horizontal	PASS
4	260.86	47.22	-17.41	29.81	46.00	16.19	100	29	PK	Horizontal	PASS
5	478.14	43.93	-13.92	30.01	46.00	15.99	100	341	PK	Horizontal	PASS
6	913.67	44.86	-7.50	37.36	46.00	8.64	100	46	PK	Horizontal	PASS

Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	36.305	53.15	-18.56	34.59	40.00	5.41	100	94	PK	Vertical	PASS
2	45.035	50.21	-15.72	34.49	40.00	5.51	100	358	PK	Vertical	PASS
3	107.6	50.62	-17.20	33.42	43.50	10.08	100	226	PK	Vertical	PASS
4	158.525	56.96	-21.12	35.84	43.50	7.66	100	311	PK	Vertical	PASS
5	296.266	44.68	-16.92	27.76	46.00	18.24	100	347	PK	Vertical	PASS
6	624.61	44.71	-11.24	33.47	46.00	12.53	100	272	PK	Vertical	PASS


Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Version B:
 Adapter: AD65CM240150

Horizontal

Test Graph




Suspected List												
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark	
1	46.975	44.34	-15.45	28.89	40.00	11.11	100	94	PK	Horizontal	PASS	
2	103.235	53.54	-17.65	35.89	43.50	7.61	100	298	PK	Horizontal	PASS	
3	153.19	58.37	-21.76	36.61	43.50	6.89	100	259	PK	Horizontal	PASS	
4	260.86	48.47	-17.41	31.06	46.00	14.94	100	68	PK	Horizontal	PASS	
5	496.085	43.07	-13.50	29.57	46.00	16.43	100	104	PK	Horizontal	PASS	
6	785.145	44.89	-9.25	35.64	46.00	10.36	100	45	PK	Horizontal	PASS	

Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List												
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark	
1	42.125	50.08	-16.46	33.62	40.00	6.38	100	42	PK	Vertical	PASS	
2	48.43	50.21	-15.77	34.44	40.00	5.56	100	108	PK	Vertical	PASS	
3	106.145	52.51	-17.24	35.27	43.50	8.23	100	25	PK	Vertical	PASS	
4	159.495	55.53	-20.86	34.67	43.50	8.83	100	294	PK	Vertical	PASS	
5	327.79	43.64	-16.40	27.24	46.00	18.76	100	64	PK	Vertical	PASS	
6	903	44.92	-8.06	36.86	46.00	9.14	100	91	PK	Vertical	PASS	


Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Adapter: SOY-2400250-332-A

Horizontal

Test Graph




Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	44.55	44.37	-15.81	28.56	40.00	11.44	100	217	PK	Horizontal	PASS
2	104.69	53.73	-17.33	36.40	43.50	7.10	100	148	PK	Horizontal	PASS
3	160.465	57.88	-20.94	36.94	43.50	6.56	100	118	PK	Horizontal	PASS
4	242.915	47.31	-17.82	29.49	46.00	16.51	100	184	PK	Horizontal	PASS
5	433.035	43.14	-14.36	28.78	46.00	17.22	100	276	PK	Horizontal	PASS
6	658.075	45.57	-10.82	34.75	46.00	11.25	100	342	PK	Horizontal	PASS

Note.1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph





Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	35.82	52.07	-18.70	33.37	40.00	6.63	100	28	PK	Vertical	PASS
2	46.975	50.00	-15.45	34.55	40.00	5.45	100	97	PK	Vertical	PASS
3	107.6	51.09	-17.20	33.89	43.50	9.61	100	239	PK	Vertical	PASS
4	154.16	56.41	-21.61	34.80	43.50	8.70	100	311	PK	Vertical	PASS
5	290.93	44.28	-16.83	27.45	46.00	18.55	100	94	PK	Vertical	PASS
6	652.74	44.83	-10.97	33.86	46.00	12.14	100	81	PK	Vertical	PASS

Note.1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).


Adapter: ADS-65HI-19A-1 24036E



Adapter: CYZS36-240150

Horizontal

Test Graph




Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	48.915	44.74	-15.76	28.98	40.00	11.02	100	3	PK	Horizontal	PASS
2	103.235	48.72	-17.65	31.07	43.50	12.43	100	16	PK	Horizontal	PASS
3	152.705	57.67	-21.82	35.85	43.50	7.65	100	108	PK	Horizontal	PASS
4	226.425	49.05	-18.76	30.29	46.00	15.71	100	359	PK	Horizontal	PASS
5	437.885	44.38	-14.02	30.36	46.00	15.64	100	200	PK	Horizontal	PASS
6	913.185	44.19	-7.49	36.70	46.00	9.30	100	223	PK	Horizontal	PASS

Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

Vertical

Test Graph



Suspected List											
NO.	Frequency [MHz]	Reading [dBµV/m]	Factor [dB]	Result [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Detector	Polarity	Remark
1	38.73	50.44	-17.30	33.14	40.00	6.86	100	58	PK	Vertical	PASS
2	44.55	49.12	-15.81	33.31	40.00	6.69	100	25	PK	Vertical	PASS
3	107.6	48.81	-17.20	31.61	43.50	11.89	100	193	PK	Vertical	PASS
4	159.98	55.29	-20.78	34.51	43.50	8.99	100	315	PK	Vertical	PASS
5	293.84	44.70	-16.96	27.74	46.00	18.26	100	344	PK	Vertical	PASS
6	705.12	46.04	-10.83	35.21	46.00	10.79	100	117	PK	Vertical	PASS

Note:1. Result (dBµV/m) = Reading(dBµV/m) + Factor (dB) .

2. Factor (dB) = Antenna Factor (dB/m) + Cable loss (dB) - Pre Amplifier gain (dB).

For 1GHz to 40GHz

5150-5250MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 36_ 5180 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10360	39.59	38.55	33.13	11.26	56.27	68.20	-11.93	Peak	Horizontal
1	10360	30.87	38.55	33.13	11.26	47.55	54.00	-6.45	AV	Horizontal
1	10360	40.93	38.55	33.13	11.26	57.61	68.20	-10.59	Peak	Vertical
1	10360	28.56	38.55	33.13	11.26	45.24	54.00	-8.76	AV	Vertical

802.11a Mode_Channel 40_ 5200 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10400	40.40	38.55	33.13	11.26	57.08	68.20	-11.12	Peak	Horizontal
1	10400	31.23	38.55	33.13	11.26	47.91	54.00	-6.09	AV	Horizontal
1	10400	40.50	38.55	33.13	11.26	57.18	68.20	-11.02	Peak	Vertical
1	10400	29.95	38.55	33.13	11.26	46.63	54.00	-7.37	AV	Vertical

802.11a Mode_Channel 48_ 5240 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10480	40.37	38.55	33.13	11.26	57.05	68.20	-11.15	Peak	Horizontal
1	10480	30.74	38.55	33.13	11.26	47.42	54.00	-6.58	AV	Horizontal
1	10480	41.87	38.55	33.13	11.26	58.55	68.20	-9.65	Peak	Vertical
1	10480	29.29	38.55	33.13	11.26	45.97	54.00	-8.03	AV	Vertical

5260-5320MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 52_ 5260 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10520	39.65	38.55	33.13	11.26	56.33	68.20	-11.87	Peak	Horizontal
1	10520	30.74	38.55	33.13	11.26	47.42	54.00	-6.58	AV	Horizontal
1	10520	41.38	38.55	33.13	11.26	58.06	68.20	-10.14	Peak	Vertical
1	10520	29.57	38.55	33.13	11.26	46.25	54.00	-7.75	AV	Vertical

802.11a Mode_Channel 56_ 5280 MHz

Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Margin (dB)	Detector	Polarization
1	10560	39.64	38.55	33.13	11.26	56.32	68.20	-11.88	Peak	Horizontal
1	10560	31.75	38.55	33.13	11.26	48.43	54.00	-5.57	AV	Horizontal
1	10560	40.77	38.55	33.13	11.26	57.45	68.20	-10.75	Peak	Vertical
1	10560	28.04	38.55	33.13	11.26	44.72	54.00	-9.28	AV	Vertical

802.11a Mode_Channel 64_ 5320 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	10640	40.80	38.55	33.13	11.26	57.48	68.20	-10.72	Peak	Horizontal
1	10640	30.02	38.55	33.13	11.26	46.70	54.00	-7.30	AV	Horizontal
1	10640	41.10	38.55	33.13	11.26	57.78	68.20	-10.42	Peak	Vertical
1	10640	40.80	38.55	33.13	11.26	57.48	68.20	-10.72	AV	Vertical

5500-5700MHz:**IEEE 802.11a (Worst Case)****802.11a Mode_Channel 100_ 5500 MHz**

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11000	40.37	38.55	33.13	11.26	57.05	68.20	-11.15	Peak	Horizontal
1	11000	31.51	38.55	33.13	11.26	48.19	54.00	-5.81	AV	Horizontal
1	11000	41.62	38.55	33.13	11.26	58.30	68.20	-9.90	Peak	Vertical
1	11000	29.96	38.55	33.13	11.26	46.64	54.00	-7.36	AV	Vertical

802.11a Mode_Channel 120_ 5600 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11200	39.69	38.55	33.13	11.26	56.37	68.20	-11.83	Peak	Horizontal
1	11200	31.12	38.55	33.13	11.26	47.80	54.00	-6.20	AV	Horizontal
1	11200	40.32	38.55	33.13	11.26	57.00	68.20	-11.20	Peak	Vertical
1	11200	28.66	38.55	33.13	11.26	45.34	54.00	-8.66	AV	Vertical

802.11a Mode_Channel 140_ 5700 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11400	40.95	38.55	33.13	11.26	57.63	68.20	-10.57	Peak	Horizontal
1	11400	31.38	38.55	33.13	11.26	48.06	54.00	-5.94	AV	Horizontal
1	11400	40.44	38.55	33.13	11.26	57.12	68.20	-11.08	Peak	Vertical
1	11400	29.06	38.55	33.13	11.26	45.74	54.00	-8.26	AV	Vertical

5725-5850MHz:

IEEE 802.11a (Worst Case)

802.11a Mode_Channel 149 _ 5745 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11490	40.66	38.55	33.13	11.26	57.34	68.20	-10.86	Peak	Horizontal
1	11490	31.67	38.55	33.13	11.26	48.35	54.00	-5.65	AV	Horizontal
1	11490	40.74	38.55	33.13	11.26	57.42	68.20	-10.78	Peak	Vertical
1	11490	29.89	38.55	33.13	11.26	46.57	54.00	-7.43	AV	Vertical

802.11a Mode_Channel 157 _ 5785 MHz

Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11570	39.14	38.55	33.13	11.26	55.82	68.20	-12.38	Peak	Horizontal
1	11570	31.65	38.55	33.13	11.26	48.33	54.00	-5.67	AV	Horizontal
1	11570	40.64	38.55	33.13	11.26	57.32	68.20	-10.88	Peak	Vertical
1	11570	29.77	38.55	33.13	11.26	46.45	54.00	-7.55	AV	Vertical

802.11a Mode_Channel 165 _ 5825 MHz


Item (Mark)	Freq (MHz)	Read Level (dB μ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss (dB)	Result Level (dB μ V/m)	Limit Line (dB μ V/m)	Margin (dB)	Detector	Polarization
1	11650	40.27	38.55	33.13	11.26	56.95	68.20	-11.25	Peak	Horizontal
1	11650	30.92	38.55	33.13	11.26	47.60	54.00	-6.40	AV	Horizontal
1	11650	41.97	38.55	33.13	11.26	58.65	68.20	-9.55	Peak	Vertical
1	11650	29.11	38.55	33.13	11.26	45.79	54.00	-8.21	AV	Vertical

REMARKS:

1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. Margin = Result Level - Limit
3. The other emission levels were very low against the limit.
4. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak;

4.3. Duty Cycle

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Duty Cycle (x),
Transmission Duration (T):

- a. A diode detector and an oscilloscope that together have sufficiently short response time to permit accurate measurements of the on and off times of the transmitted signal
- b. The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set $RBW \geq EBW$ if possible; otherwise, set RBW to the largest available value. Set $VBW \geq RBW$. Set detector = peak or average. The zerospan measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in section II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST RESULTS

For reporting purpose only.

Please refer to Appendix D.3.


Please refer to Appendix E.3.

Please refer to Appendix F.3.

Please refer to Appendix G.3.

4.4. Maximum Average Output Power

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 Measurement using a Power Meter (PM):

- a. Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the conditions listed below are satisfied
 - 1. The EUT is configured to transmit continuously or to transmit with a constant duty cycle
 - 2. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 - 3. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- b. If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in section II.B
- c. Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:

Frequency Range (MHz)	Limit
5150-5250	Fixed: 1 Watt (30dBm) Mobile and portable: 250mW (24dBm)
5250-5350	250mW (24dBm)
5470-5725	250mW (24dBm)
5725-5850	1 Watt (30dBm)

Note: The maximum e.i.r.p at any elevation angle above 30 degrees as measured from the horizon must not exceed 125mW(21dBm)

TEST RESULTS

For reporting purpose only.

Please refer to Appendix D.4.


Please refer to Appendix E.4.

Please refer to Appendix F.4.

Please refer to Appendix G.4.

4.5. Power Spectral Density

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01: The rules requires “maximum power spectral density” measurements where the intent is to measure the maximum value of the time average of the power spectral density measured during a period of continuous transmission

- a. Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, “Compute power...”. (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
- b. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
- c. Make the following adjustments to the peak value of the spectrum, if applicable:
 1. If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum.
 2.) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
- d. The result is the Maximum PSD over 1 MHz reference bandwidth.
- e. For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:
 1. Set $RBW \geq 1/T$, where T is defined in section II.B.I.a).
 2. Set $VBW \geq 3 RBW$.
 3. If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/RBW)$ to the measured result, whereas RBW (< 500 KHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
 4. If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/RBW)$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
 5. Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 KHz for the sections 5.c) and 5.d) above, since RBW=100 KHz is available on nearly all spectrum analyzers.
- f. Adjust the measurement in dBm by adding $10 \log(1/x)$ where x is the duty cycle (e.g., $10 \log(1/0.25)$ if the duty cycle is 25 percent).

LIMIT

According to §15.407(a): The maximum output power should be not exceed follow:


Frequency Range (MHz)	Limit
5150-5250	Other then Mobile and portable:17dBm/MHz Mobile and portable:11dBm/MHz
5250-5350	11dBm/MHz
5470-5725	11dBm/MHz
5725-5850	30dBm/500kHz

TEST RESULTS

For reporting purpose only.
 Please refer to Appendix D.5.
 Please refer to Appendix E.5.
 Please refer to Appendix F.5.
 Please refer to Appendix G.5.

4.6. 99% and 6dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 for one of the following procedures may be used for section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a. Set RBW = 100 kHz.
- b. Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize
- g. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

LIMIT

For Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz

TEST RESULTS


For reporting purpose only.

Please refer to Appendix G.1.

Please refer to Appendix G.2.

4.7. 99% and 26dBc Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

According to KDB789033 D02 General U-NII Test Procedures New Rules v02r01 for one of the following procedures may be used for Emission Bandwidth (EBW) measurement:

- a. Set RBW = 220 kHz/430 kHz /820 kHz (approximately 1% of the emission bandwidth).
- b. Set the video bandwidth (VBW) = 3* RBW)
- c. Detector = Peak.
- d. Trace mode = max hold.
- e. Sweep = auto couple.
- f. Allow the trace to stabilize
- g. Measure the maximum width of the emission that is 26 dB down from the maximum of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

LIMIT

No Limits for 26dBc Bandwith

TEST RESULTS

For reporting purpose only.

Please refer to Appendix D.1.

Please refer to Appendix D.2.

Please refer to Appendix E.1.


Please refer to Appendix E.2.

Please refer to Appendix F.1.

Please refer to Appendix F.2.

4.8. Conducted Spurious Emissions and Band Edge Compliance

TEST CONFIGURATION



LIMIT

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequency (MHz)	Distance (Meters)	Radiated (dBµV/m)	Radiated (µV/m)
0.009-0.49	3	$20\log(2400/F(KHz))+40\log(300/3)$	$2400/F(KHz)$
0.49-1.705	3	$20\log(24000/F(KHz))+40\log(30/3)$	$24000/F(KHz)$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

According to §15.407 (b): Except as shown in paragraph (b)(7) of this section, the maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits

Frequency (MHz)	EIRP Limit (dBm)	Equivalent Field Strength at 3m (dBµV/m)
5150-5250	-27	68.2
5250-5350	-27	68.2
5470-5725	-27	68.2
5725-5850	-27 (beyond 10MHz of the bandedge)	68.2
	-17 (within 10 MHz of band edge)	78.2

TEST PROCEDURE

- The EUT was placed on a turn table which is 1.5m above 1GHz.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT.
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed..
- The distance between test antenna and EUT as following table states:

Test Frequency range	Test Antenna Type	Test Distance
1GHz-18GHz	Double Ridged Horn Antenna	3

- Setting test receiver/spectrum as following table states:

Test Frequency range	Test Receiver/Spectrum Setting	Detector
1GHz-18GHz	Peak Value: RBW=1MHz/VBW=3MHz, Sweep time=Auto Average Value: RBW=1MHz/VBW=10Hz, Sweep time=Auto	Peak

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

TEST RESULTS

Remark:For radiated bandedge We measured at both mode, recorded worst case in antenna 0's 802.11 ac20 mode;

For Conducted at Restricted Band Measurement

For reporting purpose only.

Please refer to Appendix D.8.

Please refer to Appendix E.8.

Please refer to Appendix F.8.

Please refer to Appendix G.8.

For Conducted Band edge Measurement

For reporting purpose only.

Please refer to Appendix D.6.

Please refer to Appendix E.6.

Please refer to Appendix F.6.

Please refer to Appendix G.6.

For Conducted Spurious Emissions Measurement

For reporting purpose only.

Please refer to Appendix D.7.

Please refer to Appendix E.7.

Please refer to Appendix F.7.

Please refer to Appendix G.7.

4.9. Frequency Stability

Standard Applicable

According to FCC §15.407(g) “Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user manual.”


According to FCC §2.1055(a) “The frequency stability shall be measured with variation of ambient temperature as follows:”

(1) From -30° to + 50° centigrade for all equipment except that specified in paragraphs (a) (2) and (3) of this section.

(2) From -20° to + 50° centigrade for equipment to be licensed for use in the Maritime Services under part 80 of this chapter, except for Class A, B, and S Emergency Position Indicating Radiobeacons (EPIRBS), and equipment to be licensed for use above 952 MHz at operational fixed stations in all services, stations in the Local Television Transmission Service and Point-to-Point Microwave Radio Service under part 21 of this chapter, equipment licensed for use aboard aircraft in the Aviation Services under part 87 of this chapter, and equipment authorized for use in the Family Radio Service under part 95 of this chapter.

(3) From 0° to + 50° centigrade for equipment to be licensed for use in the Radio Broadcast Services under part 73 of this chapter.

Test Configuration



Test Procedure

The equipment under test was connected to an external AC or DC power supply and input rated voltage. RF output was connected to a frequency counter or spectrum analyzer via feed through attenuators. The EUT was placed inside the temperature chamber. Set the spectrum analyzer RBW low enough to obtain the desired frequency resolution and measure EUT 20 degree operating frequency as reference frequency. Turn EUT off and set the chamber temperature to -30 degree. After the temperature stabilized for approximately 30 minutes recorded the frequency. Repeat step measure with 10 degree increased per stage until the highest temperature of +50 degree reached.

Test Results

PASS

Remark:

1. Measured all conditions and recorded worst case.

IEEE 802.11a Mode / 5180 – 5240 MHz / 5180 MHz

Environment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5171.545438	5150 – 5250	PASS
20	DC 21.6V	5171.551328	5150 – 5250	PASS
50	DC 24.0V	5171.564994	5150 – 5250	PASS
40	DC 24.0V	5171.532326	5150 – 5250	PASS
30	DC 24.0V	5171.552198	5150 – 5250	PASS
20	DC 24.0V	5171.587274	5150 – 5250	PASS
10	DC 24.0V	5171.594873	5150 – 5250	PASS
0	DC 24.0V	5171.550825	5150 – 5250	PASS
-10	DC 24.0V	5171.571559	5150 – 5250	PASS
-20	DC 24.0V	5171.623146	5150 – 5250	PASS
-30	DC 24.0V	5171.640101	5150 – 5250	PASS

IEEE 802.11a Mode / 5180 – 5240 MHz / 5240 MHz

Environment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5248.641410	5150 – 5250	PASS
20	DC 21.6V	5248.616404	5150 – 5250	PASS
50	DC 24.0V	5248.542623	5150 – 5250	PASS
40	DC 24.0V	5248.546707	5150 – 5250	PASS
30	DC 24.0V	5248.519942	5150 – 5250	PASS
20	DC 24.0V	5248.617376	5150 – 5250	PASS
10	DC 24.0V	5248.554230	5150 – 5250	PASS
0	DC 24.0V	5248.678879	5150 – 5250	PASS
-10	DC 24.0V	5248.529658	5150 – 5250	PASS
-20	DC 24.0V	5248.636975	5150 – 5250	PASS
-30	DC 24.0V	5248.645160	5150 – 5250	PASS

IEEE 802.11a Mode / 5260 – 5320 MHz / 5260 MHz

Environment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5251.668163	5250 – 5350	PASS
20	DC 21.6V	5251.560153	5250 – 5350	PASS
50	DC 24.0V	5251.643354	5250 – 5350	PASS
40	DC 24.0V	5251.523085	5250 – 5350	PASS
30	DC 24.0V	5251.683017	5250 – 5350	PASS
20	DC 24.0V	5251.591838	5250 – 5350	PASS
10	DC 24.0V	5251.608587	5250 – 5350	PASS
0	DC 24.0V	5251.634157	5250 – 5350	PASS
-10	DC 24.0V	5251.644021	5250 – 5350	PASS
-20	DC 24.0V	5251.625734	5250 – 5350	PASS
-30	DC 24.0V	5251.672819	5250 – 5350	PASS

IEEE 802.11a Mode / 5260 – 5320 MHz / 5320 MHz

Environment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5328.542478	5250 – 5350	PASS
20	DC 21.6V	5328.536823	5250 – 5350	PASS
50	DC 24.0V	5328.568903	5250 – 5350	PASS
40	DC 24.0V	5328.626079	5250 – 5350	PASS
30	DC 24.0V	5328.633483	5250 – 5350	PASS
20	DC 24.0V	5328.667184	5250 – 5350	PASS
10	DC 24.0V	5328.576398	5250 – 5350	PASS
0	DC 24.0V	5328.565727	5250 – 5350	PASS
-10	DC 24.0V	5328.525470	5250 – 5350	PASS
-20	DC 24.0V	5328.572577	5250 – 5350	PASS
-30	DC 24.0V	5328.553851	5250 – 5350	PASS

IEEE 802.11a Mode / 5500 – 5700 MHz / 5500 MHz

Environment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5491.626260	5470 – 5725	PASS
20	DC 21.6V	5491.509032	5470 – 5725	PASS
50	DC 24.0V	5491.602807	5470 – 5725	PASS
40	DC 24.0V	5491.634290	5470 – 5725	PASS
30	DC 24.0V	5491.673980	5470 – 5725	PASS
20	DC 24.0V	5491.553521	5470 – 5725	PASS
10	DC 24.0V	5491.519726	5470 – 5725	PASS
0	DC 24.0V	5491.662025	5470 – 5725	PASS
-10	DC 24.0V	5491.554250	5470 – 5725	PASS
-20	DC 24.0V	5491.639458	5470 – 5725	PASS
-30	DC 24.0V	5491.564823	5470 – 5725	PASS

IEEE 802.11a Mode / 5500 – 5700 MHz / 5700 MHz

Environment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5708.624584	5470 – 5725	PASS
20	DC 21.6V	5708.564143	5470 – 5725	PASS
50	DC 24.0V	5708.695389	5470 – 5725	PASS
40	DC 24.0V	5708.590078	5470 – 5725	PASS
30	DC 24.0V	5708.624372	5470 – 5725	PASS
20	DC 24.0V	5708.602120	5470 – 5725	PASS
10	DC 24.0V	5708.502590	5470 – 5725	PASS
0	DC 24.0V	5708.629010	5470 – 5725	PASS
-10	DC 24.0V	5708.656312	5470 – 5725	PASS
-20	DC 24.0V	5708.553494	5470 – 5725	PASS
-30	DC 24.0V	5708.617399	5470 – 5725	PASS

IEEE 802.11a Mode / 5745 – 5825 MHz / 5745 MHz

Environment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5736.625862	5725 – 5850	PASS
20	DC 21.6V	5736.551634	5725 – 5850	PASS
50	DC 24.0V	5736.699267	5725 – 5850	PASS
40	DC 24.0V	5736.593770	5725 – 5850	PASS
30	DC 24.0V	5736.655669	5725 – 5850	PASS
20	DC 24.0V	5736.625992	5725 – 5850	PASS
10	DC 24.0V	5736.683556	5725 – 5850	PASS
0	DC 24.0V	5736.677915	5725 – 5850	PASS
-10	DC 24.0V	5736.599189	5725 – 5850	PASS
-20	DC 24.0V	5736.621563	5725 – 5850	PASS
-30	DC 24.0V	5736.579722	5725 – 5850	PASS

IEEE 802.11a Mode / 5745 – 5825 MHz / 5825 MHz

Environment Temperature (Degree)	Voltage (V)	Measured Frequency (MHz)	Limit Range (MHz)	Test Results
20	DC 26.4V	5833.560971	5725 – 5850	PASS
20	DC 21.6V	5833.572714	5725 – 5850	PASS
50	DC 24.0V	5833.683278	5725 – 5850	PASS
40	DC 24.0V	5833.647799	5725 – 5850	PASS
30	DC 24.0V	5833.556654	5725 – 5850	PASS
20	DC 24.0V	5833.612005	5725 – 5850	PASS
10	DC 24.0V	5833.662791	5725 – 5850	PASS
0	DC 24.0V	5833.561183	5725 – 5850	PASS
-10	DC 24.0V	5833.600745	5725 – 5850	PASS
-20	DC 24.0V	5833.614993	5725 – 5850	PASS
-30	DC 24.0V	5833.550950	5725 – 5850	PASS

4.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.407 (a), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Antenna Information

The antenna is FPC Aantenna, through the buckle stretched out, The directional gains of antenna used for transmitting is 7.16dBi.

Reference to the Test Report: **GTS20220803009-1-38.**

5. TEST SETUP PHOTOS OF THE EUT

Reference to the test report No. GTS20220803009-1-38.

6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT

Reference to the test report No. GTS20220803009-1-38.

.....**End of Report**.....