



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.org.cn

TEST REPORT

Report No.....: CTC20221207E05
FCC ID.....: 2AYD5-I22T01
Applicant: Imin Technology Pte Ltd
Address.....: 11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943
Manufacturer.....: Imin Technology Pte Ltd
Address.....: 11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943
Product Name: POS Device
Trade Mark: /
Model/Type reference.....: I22T01
Listed Model(s): /
Standard: FCC Part 15, Subpart E 15. 407
Date of receipt of test sample...: Jul. 06, 2022
Date of testing.....: Jul. 07, 2022 ~ Aug. 01, 2022
Date of issue.....: Aug. 02, 2022
Result.....: PASS

Compiled by:
(Printed name+signature) Terry Su 
Supervised by:
(Printed name+signature) Eric Zhang 
Approved by:
(Printed name+signature) Totti Zhao 

Testing Laboratory Name.....: CTC Laboratories, Inc.
Address: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park,
Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.

**Table of Contents**

	Page
1. TEST SUMMARY.....	3
1.1. TEST STANDARDS.....	3
1.2. REPORT VERSION.....	3
1.3. TEST DESCRIPTION.....	4
1.4. TEST FACILITY	5
1.5. MEASUREMENT UNCERTAINTY.....	5
1.6. ENVIRONMENTAL CONDITIONS	6
2. GENERAL INFORMATION.....	7
2.1. CLIENT INFORMATION	7
2.2. GENERAL DESCRIPTION OF EUT.....	8
2.3. ACCESSORY EQUIPMENT INFORMATION	9
2.4. OPERATION STATE.....	10
2.5. MEASUREMENT INSTRUMENTS LIST	12
3. TEST ITEM AND RESULTS.....	13
3.1. CONDUCTED EMISSION.....	13
3.2. RADIATED EMISSION	16
3.3. BAND EDGE EMISSIONS	139
3.4. BANDWIDTH TEST	210
3.5. OUTPUT POWER TEST	212
3.6. POWER SPECTRAL DENSITY TEST	214
3.7. FREQUENCY STABILITY MEASUREMENT	216
3.8. ANTENNA REQUIREMENT.....	217
3.9. DYNAMIC FREQUENCY SELECTION(DFS)	218

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cnFor anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

[FCC Part 15, Subpart E\(15.407\)](#) — for 802.11a/n/ac, the test procedure follows the FCC KDB 789033 D02 General UNII Test Procedures New Rules V02r01.

[RSS-247 Issue 2 February 2017](#) — Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

[RSS-Gen](#) — General Requirements for Compliance of Radio Apparatus

1.2. Report version

Revised No.	Date of issue	Description
01	Aug. 02, 2022	Original



1.3. Test Description

FCC Part 15 Subpart E (15.407) / RSS-247 Issue 2 February 2017				
Test Item	Test require		Result	Test Engineer
	FCC	IC		
Antenna Requirement	15.203	/	Pass	Alicia Liu
Conducted Emission	15.207	RSS-Gen 8.8	Pass	Ice Lu
Band Edge Emissions	15.407(b)	RSS-247 6.2.1.2 RSS-247 6.2.2.2 RSS-247 6.2.4.2	Pass	Alicia Liu
26dB Bandwidth & 99% Bandwidth	15.407(a) (5)	RSS-247 6.2.1.2	Pass	Alicia Liu
6dB Bandwidth (only for UNII-3)	15.407(e)	RSS-247 6.2.4.1	Pass	Alicia Liu
Peak Output Power	15.407(a)	RSS-247 6.2.1.1 RSS-247 6.2.4.1	Pass	Alicia Liu
Power Spectral Density	15.407(a)	RSS-247 6.2	Pass	Alicia Liu
Transmitter Radiated Spurious Emission	15.407(b) &15.209	RSS-Gen 8.9 RSS-247 6.2.1.2 RSS-247 6.2.4.2	Pass	Alicia Liu
Frequency Stability	15.407(g)	/	Pass	Alicia Liu
Dynamic Frequency Selection (DFS)	15.407(h)	RSS-247 6.3	Pass	Alicia Liu

Note: "N/A" is not applicable.

The measurement uncertainty is not included in the test result.



1.4. Test Facility

CTC Laboratories, Inc.

Add: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5365

CTC Laboratories, Inc. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation. Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025:2017 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 2" and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.



Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.42 dB	(1)
Transmitter power Radiated	2.14 dB	(1)
Conducted spurious emissions 9kHz~40GHz	1.60 dB	(1)
Radiated spurious emissions 9kHz~40GHz	2.20 dB	(1)
Conducted Emissions 9kHz~30MHz	3.08 dB	(1)
Radiated Emissions 30~1000MHz	4.51 dB	(1)
Radiated Emissions 1~18GHz	5.84 dB	(1)
Radiated Emissions 18~40GHz	6.12 dB	(1)
Occupied Bandwidth	-----	(1)

Note (1): This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

1.6. Environmental conditions

Normal Condition	Temperature	22 °C ~ 28°C
	Relative humidity	50% ~ 65%
	Voltage	The equipment shall be the nominal voltage for which the equipment was designed.
Extreme Condition	Temperature	Measurements shall be made over the extremes of the operating temperature range as declared by the manufacturer
	Voltage	Measurements shall be made over the extremes of the operating voltage range as declared by the manufacturer

Normal Condition	T_N =Normal Temperature	22 °C ~ 28°C
Extreme Condition	T_L =Lower Temperature	0 °C
	T_H =Higher Temperature	50 °C



2. GENERAL INFORMATION

2.1. Client Information

Applicant:	Imin Technology Pte Ltd
Address:	11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943
Manufacturer:	Imin Technology Pte Ltd
Address:	11 Bishan Street 21, #03-05 Bosch Building, Singapore 573943



2.2. General Description of EUT

Product Name:	POS Device			
Trade Mark:	/			
Model/Type reference:	I22T01			
Listed Model(s):	/			
Power supply:	24Vdc/2.5A from AC/DC Adapter			
Adapter Model:	AD65CM240250A Input: 100-240V~ 50/60Hz 1.5A Max Output: 24Vdc/2.5A			
Hardware version:	/			
Software version:	/			
Antenna type:	FPC Antenna			
Antenna gain:	2.32dBi Max			

Technical index for 5G WIFI

Operation Band:	<input checked="" type="checkbox"/> U-NII-1	<input checked="" type="checkbox"/> U-NII-2A	<input checked="" type="checkbox"/> U-NII-2C	<input checked="" type="checkbox"/> U-NII-3
Operation Frequency Range:	U-NII-1:	5150MHz~5250MHz		
	U-NII-2A:	5250MHz~5350MHz		
	U-NII-2C:	5470MHz~5725MHz		
	U-NII-3:	5725MHz~5850MHz		
Support bandwidth:	802.11a	<input checked="" type="checkbox"/> 20MHz		
	802.11n	<input checked="" type="checkbox"/> 20MHz	<input checked="" type="checkbox"/> 40MHz	
	802.11ac	<input checked="" type="checkbox"/> 20MHz	<input checked="" type="checkbox"/> 40MHz	<input checked="" type="checkbox"/> 80MHz
Modulation:	802.11a:	OFDM (BIT/SK, QPSK, BPSK, 16QAM)		
	802.11n:	OFDM (BIT/SK, QPSK, BPSK, 16QAM, 64QAM)		
	802.11ac:	OFDM (BIT/SK, QPSK, BPSK, 16QAM, 64QAM, 256QAM)		
Bit Rate of Transmitter:	802.11a:	6/9/12/18/24/36/48/54 Mbps		
	802.11n:	up to 300Mbps		
	802.11ac:	at most 866.7 Mbps		

Remark: This device does not transmit any beacons or initiate any transmissions in UNII Band 2A or 2C.



2.3. Accessory Equipment information

Equipment Information			
Name	Model	S/N	Manufacturer
/	/	/	/
/	/	/	/
Cable Information			
Name	Shielded Type	Ferrite Core	Length
/	/	/	/
Test Software Information			
Name	Versions	/	/
Engineering mode	/	/	/

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



2.4. Operation state

Operation Frequency List:

Band (MHz)	20MHz Bandwidth		40MHz Bandwidth		80MHz Bandwidth			
	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)		
U-NII-1	36	5180	38	5190	42	5210		
	40	5200						
	44	5220	46	5230				
	48	5240						
U-NII-2A	52	5260	54	5270	56	5290		
	56	5280						
	60	5300	62	5310				
	64	5320						
U-NII-2C	100	5500	102	5510	106	5530		
	104	5520						
	108	5540	110	5550				
	112	5560						
	116	5580	118	5590	122	5610		
	120	5600						
	124	5620	126	5630				
	128	5640						
	132	5660	134	5670				
	136	5680						
U-NII-3	140	5700	151	5755	155	5775		
	149	5745						
	153	5765	159	5795				
	157	5785						
	161	5805						
	165	5825						



Test channel is below:

Operating Band	Test Channel	20MHz		40MHz		80MHz	
		Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
U-NII-1	CH _L	36	5180	38	5190	/	/
	CH _M	40	5200	/	/	42	5210
	CH _H	48	5240	46	5230	/	/
U-NII-2A	CH _L	52	5260	54	5270	/	/
	CH _M	56	5280	/	/	56	5290
	CH _H	64	5320	62	5310	/	/
U-NII-2C	CH _L	100	5500	102	5510	106	5530
	CH _M	116	5580	110	5550	/	/
	CH _H	140	5700	134	5670	122	5610
U-NII-3	CH _L	149	5745	151	5755	/	/
	CH _M	157	5785	/	/	155	5775
	CH _H	165	5825	159	5795	/	/

Data Rated

Preliminary tests were performed in different data rate, and found which the below bit rate is worst case mode, so only show data which it is a worst case mode.

Mode	Data rate (worst mode)
802.11a	6Mbps
802.11n(HT20)/ 802.11n(HT40)	HT-MCS0
802.11ac(VHT20)/ 802.11ac(VHT40) / 802.11ac(VHT80)	VHT-MCS0

Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.
For DFS test items
The EUT has been tested under test mode condition. The Applicant provides software to control the EUT for staying in DFS mode for testing.



2.5. Measurement Instruments List

Tonscend JS0806-2 Test system					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Rohde & Schwarz	FSU26	100105	Dec. 23, 2022
2	Spectrum Analyzer	Rohde & Schwarz	FUV40-N	101331	Mar. 15, 2023
3	MXG Vector Signal Generator	Agilent	N5182A	MY47420864	Dec. 23, 2022
4	Signal Generator	Agilent	E8257D	MY46521908	Dec. 23, 2022
5	Power Sensor	Agilent	U2021XA	MY5365004	Mar. 15, 2023
6	Power Sensor	Agilent	U2021XA	MY5365006	Mar. 15, 2023
7	High and low temperature box	ESPEC	MT3035	N/A	Mar. 15, 2023
8	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	102414	Dec. 23, 2022
9	300328 v2.2.2 test system	TONSCEND	v2.6	/	/

Radiated emission(3m chamber 2)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-1013	Jan. 12, 2023
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 23, 2022
3	Spectrum Analyzer	R&S	FSU26	100105	Dec. 23, 2022
4	Spectrum Analyzer	R&S	FSV40-N	101331	Mar. 15, 2023
5	Pre-Amplifier	SONOMA	310	186194	Dec. 23, 2022
6	Low Noise Pre-Amplifier	EMCI	EMC051835	980075	Dec. 23, 2022
7	Test Receiver	R&S	ESCI7	100967	Dec. 23, 2022

Radiated emission(3m chamber 3)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated Until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-759	Nov. 09, 2022
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 23, 2022
3	Test Receiver	Keysight	N9038A	MY56400071	Dec. 23, 2022
4	Broadband Premplifier	SCHWARZBECK	BBV9743B	259	Dec. 23, 2022
5	Mirowave Broadband Amplifier	SCHWARZBECK	BBV9718C	111	Dec. 23, 2022

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101112	Dec. 23, 2022
2	LISN	R&S	ENV216	101113	Dec. 23, 2022
3	EMI Test Receiver	R&S	ESCS30	100353	Dec. 23, 2022

Note: 1. The Cal. Interval was one year.

2. The cable loss has calculated in test result which connection between each test instruments.

3. TEST ITEM AND RESULTS

3.1. Conducted Emission


Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.207/ RSS – Gen 8.8:

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration




Test Procedure

1. The EUT was setup according to ANSI C63.10:2013 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
4. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
5. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
6. Conducted Emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
7. During the above scans, the emissions were maximized by cable manipulation.

Test Mode

Please refer to the clause 2.4.


**Test Results****Final Measurement Detector 1**

Frequency (MHz)	QuasiPeak (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.646590	32.2	1000.00	9.000	On	L1	9.7	23.8	56.0	
1.064990	34.9	1000.00	9.000	On	L1	9.7	21.1	56.0	
1.181470	34.8	1000.00	9.000	On	L1	9.7	21.2	56.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
1.148910	24.4	1000.00	9.000	On	L1	9.7	21.6	46.0	
1.181470	24.5	1000.00	9.000	On	L1	9.7	21.5	46.0	
2.282880	21.5	1000.00	9.000	On	L1	9.7	24.5	46.0	

Emission Level= Read Level+ Correct Factor



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.569050	37.6	1000.00	9.000	On	N	10.0	18.4	56.0	
1.205280	35.2	1000.00	9.000	On	N	10.0	20.8	56.0	
2.273790	30.3	1000.00	9.000	On	N	10.0	25.7	56.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dB μ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dB μ V)	Comment
0.575910	31.5	1000.00	9.000	On	N	10.0	14.5	46.0	
0.795760	27.5	1000.00	9.000	On	N	10.0	18.5	46.0	
1.210110	26.0	1000.00	9.000	On	N	10.0	20.0	46.0	

Emission Level= Read Level+ Correct Factor



3.2. Radiated Emission

Limit

FCC CFR Title 47 Part 15 Subpart C Section 15.209/ RSS-Gen 8.9

Frequency	Limit (dBuV/m @3m)	Value
30 MHz ~ 88 MHz	40.00	Quasi-peak
88 MHz ~ 216 MHz	43.50	Quasi-peak
216 MHz ~ 960 MHz	46.00	Quasi-peak
960 MHz ~ 1 GHz	54.00	Quasi-peak
Above 1 GHz	54.00	Average
	74.00	Peak

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)= 20log Emission Level (uV/m).

Limits of unwanted emission out of the restricted bands


FCC CFR Title 47 Part 15 Subpart C Section 15.407(b)/ RSS-247 6.2.1.2 & RSS-247 6.2.4.2

Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.2
5250~5350	-27	68.2
5470~5725	-27	68.2
5725~5825	-27(Note 2)	68.2
	10(Note 2)	105.2
	15.6(Note 2)	110.8
	27(Note 2)	122.2


Note: 1. The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength: $E = \frac{1000000\sqrt{30P}}{3}$ uV/m, where P is the eirp (Watts)

2. According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.


Test Configuration



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China
Tel.: (86)755-27521059

Fax: (86)755-27521011

[Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)
For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
 5. Set to the maximum power setting and enable the EUT transmit continuously.
 6. Use the following spectrum analyzer settings
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - (3) From 1 GHz to 10th harmonic:
RBW=1MHz, VBW=3MHz Peak detector for Peak value.
RBW=1MHz, VBW \geq 1/T Peak detector for Average value.
- Note 1: For the 1/T& Duty Cycle please refer to clause Duty Cycle.

Test Mode

Please refer to the clause 2.4.

Test Result


9 KHz~30 MHz

From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.




30MHz-1GHz





Ant. Pol.:	Vertical
Test Mode:	TX 802.11a Mode 5180MHz (U-NII-1)
Remark:	Only worse case is reported



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	37.1133	52.04	-15.49	36.55	40.00	-3.45	QP
2	571.9067	45.05	-7.39	37.66	46.00	-8.34	QP
3 !	623.9633	46.57	-6.42	40.15	46.00	-5.85	QP
4	676.0200	42.33	-5.81	36.52	46.00	-9.48	QP
5	728.0767	42.56	-5.13	37.43	46.00	-8.57	QP
6	935.9800	36.93	-2.28	34.65	46.00	-11.35	QP

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value




Above 1GHz

Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10360.429</td><td>26.21</td><td>13.59</td><td>39.80</td><td>54.00</td><td>-14.20</td><td>AVG</td></tr><tr><td>2</td><td>10360.750</td><td>39.69</td><td>13.60</td><td>53.29</td><td>74.00</td><td>-20.71</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10360.429	26.21	13.59	39.80	54.00	-14.20	AVG	2	10360.750	39.69	13.60	53.29	74.00	-20.71	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10360.429	26.21	13.59	39.80	54.00	-14.20	AVG																								
2	10360.750	39.69	13.60	53.29	74.00	-20.71	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10360.572</td><td>26.00</td><td>13.59</td><td>39.59</td><td>54.00</td><td>-14.41</td><td>AVG</td></tr><tr><td>2</td><td>10360.783</td><td>40.79</td><td>13.60</td><td>54.39</td><td>74.00</td><td>-19.61</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10360.572	26.00	13.59	39.59	54.00	-14.41	AVG	2	10360.783	40.79	13.60	54.39	74.00	-19.61	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10360.572	26.00	13.59	39.59	54.00	-14.41	AVG																								
2	10360.783	40.79	13.60	54.39	74.00	-19.61	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															





Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5200MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 Detailed description: This is a spectral plot showing RF power levels in dBuV/m on the y-axis against frequency in MHz on the x-axis. The y-axis ranges from -10 to 90.0 dBuV/m with major grid lines every 10 units. The x-axis ranges from 1000.000 to 40000.0 MHz with major grid lines every 4000 units. A red horizontal line is drawn at 74.00 dBuV/m and is labeled 'FCC Part15 C - Above 1G PK'. A green horizontal line is drawn at 53.50 dBuV/m and is labeled 'FCC Part15 C - Above 1G AV'. Two data points are plotted: point 1 is at a frequency of approximately 10399.282 MHz with a reading of 39.83 dBuV, labeled 'X'. Point 2 is at a frequency of approximately 10399.416 MHz with a reading of 26.15 dBuV, also labeled 'X'.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10399.282</td><td>39.83</td><td>13.67</td><td>53.50</td><td>74.00</td><td>-20.50</td><td>peak</td></tr><tr><td>2 *</td><td>10399.416</td><td>26.15</td><td>13.67</td><td>39.82</td><td>54.00</td><td>-14.18</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10399.282	39.83	13.67	53.50	74.00	-20.50	peak	2 *	10399.416	26.15	13.67	39.82	54.00	-14.18	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10399.282	39.83	13.67	53.50	74.00	-20.50	peak																								
2 *	10399.416	26.15	13.67	39.82	54.00	-14.18	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11a Mode 5240MHz (U-NII-1)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10479.424</td><td>40.30</td><td>13.80</td><td>54.10</td><td>74.00</td><td>-19.90</td><td>peak</td></tr><tr><td>2 *</td><td>10480.552</td><td>26.15</td><td>13.80</td><td>39.95</td><td>54.00</td><td>-14.05</td><td>AVG</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10479.424	40.30	13.80	54.10	74.00	-19.90	peak	2 *	10480.552	26.15	13.80	39.95	54.00	-14.05	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1	10479.424	40.30	13.80	54.10	74.00	-19.90	peak																									
2 *	10480.552	26.15	13.80	39.95	54.00	-14.05	AVG																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5240MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10480.000</td><td>40.56</td><td>13.80</td><td>54.36</td><td>74.00</td><td>-19.64</td><td>peak</td></tr><tr><td>2 *</td><td>10480.000</td><td>25.01</td><td>13.80</td><td>38.81</td><td>54.00</td><td>-15.19</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10480.000	40.56	13.80	54.36	74.00	-19.64	peak	2 *	10480.000	25.01	13.80	38.81	54.00	-15.19	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10480.000	40.56	13.80	54.36	74.00	-19.64	peak																								
2 *	10480.000	25.01	13.80	38.81	54.00	-15.19	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level - Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<p>The graph shows the measured RF power levels (dBuV/m) on the Y-axis against frequency (MHz) on the X-axis. The Y-axis ranges from -10 to 90.0 dBuV/m with major grid lines every 10 units. The X-axis ranges from 1000.000 to 40000.0 MHz with major grid lines every 4000 units. A red horizontal line at 74.00 dBuV/m is labeled "FCC Part15 C-Above 1G PK". A green horizontal line at 54.00 dBuV/m is labeled "FCC Part15 C-Above 1G AV". Two data points are plotted: point 1 at approximately 10359.830 MHz with a reading of 40.03 dBuV, and point 2 at approximately 10360.944 MHz with a reading of 25.67 dBuV.</p>																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10359.830</td><td>40.03</td><td>13.60</td><td>53.63</td><td>74.00</td><td>-20.37</td><td>peak</td></tr><tr><td>2 *</td><td>10360.944</td><td>25.67</td><td>13.60</td><td>39.27</td><td>54.00</td><td>-14.73</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10359.830	40.03	13.60	53.63	74.00	-20.37	peak	2 *	10360.944	25.67	13.60	39.27	54.00	-14.73	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10359.830	40.03	13.60	53.63	74.00	-20.37	peak																								
2 *	10360.944	25.67	13.60	39.27	54.00	-14.73	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10360.000</td><td>40.35</td><td>13.60</td><td>53.95</td><td>74.00</td><td>-20.05</td><td>peak</td></tr><tr><td>2 *</td><td>10360.000</td><td>24.63</td><td>13.60</td><td>38.23</td><td>54.00</td><td>-15.77</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10360.000	40.35	13.60	53.95	74.00	-20.05	peak	2 *	10360.000	24.63	13.60	38.23	54.00	-15.77	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10360.000	40.35	13.60	53.95	74.00	-20.05	peak																								
2 *	10360.000	24.63	13.60	38.23	54.00	-15.77	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11n(HT20) Mode 5200MHz (U-NII-1)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10399.004</td><td>26.21</td><td>13.67</td><td>39.88</td><td>54.00</td><td>-14.12</td><td>AVG</td></tr><tr><td>2</td><td>10399.941</td><td>40.53</td><td>13.67</td><td>54.20</td><td>74.00</td><td>-19.80</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10399.004	26.21	13.67	39.88	54.00	-14.12	AVG	2	10399.941	40.53	13.67	54.20	74.00	-19.80	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	10399.004	26.21	13.67	39.88	54.00	-14.12	AVG																									
2	10399.941	40.53	13.67	54.20	74.00	-19.80	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Vertical
Test Mode:	TX 802.11n(HT20) Mode 5200MHz (U-NII-1)
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10400.000	39.91	13.67	53.58	74.00	-20.42	peak
2 *	10400.000	24.96	13.67	38.63	54.00	-15.37	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5240MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10479.717</td><td>26.01</td><td>13.80</td><td>39.81</td><td>54.00</td><td>-14.19</td><td>AVG</td></tr><tr><td>2</td><td>10480.699</td><td>39.88</td><td>13.80</td><td>53.68</td><td>74.00</td><td>-20.32</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10479.717	26.01	13.80	39.81	54.00	-14.19	AVG	2	10480.699	39.88	13.80	53.68	74.00	-20.32	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10479.717	26.01	13.80	39.81	54.00	-14.19	AVG																								
2	10480.699	39.88	13.80	53.68	74.00	-20.32	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															





Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10359.314</td><td>40.38</td><td>13.60</td><td>53.98</td><td>74.00</td><td>-20.02</td><td>peak</td></tr><tr><td>2 *</td><td>10359.578</td><td>25.71</td><td>13.60</td><td>39.31</td><td>54.00</td><td>-14.69</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10359.314	40.38	13.60	53.98	74.00	-20.02	peak	2 *	10359.578	25.71	13.60	39.31	54.00	-14.69	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10359.314	40.38	13.60	53.98	74.00	-20.02	peak																								
2 *	10359.578	25.71	13.60	39.31	54.00	-14.69	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10360.179</td><td>39.32</td><td>13.60</td><td>52.92</td><td>74.00</td><td>-21.08</td><td>peak</td></tr><tr><td>2 *</td><td>10360.330</td><td>25.58</td><td>13.59</td><td>39.17</td><td>54.00</td><td>-14.83</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10360.179	39.32	13.60	52.92	74.00	-21.08	peak	2 *	10360.330	25.58	13.59	39.17	54.00	-14.83	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10360.179	39.32	13.60	52.92	74.00	-21.08	peak																								
2 *	10360.330	25.58	13.59	39.17	54.00	-14.83	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5200MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10400.653</td><td>26.07</td><td>13.67</td><td>39.74</td><td>54.00</td><td>-14.26</td><td>AVG</td></tr><tr><td>2</td><td>10400.710</td><td>39.97</td><td>13.67</td><td>53.64</td><td>74.00</td><td>-20.36</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10400.653	26.07	13.67	39.74	54.00	-14.26	AVG	2	10400.710	39.97	13.67	53.64	74.00	-20.36	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10400.653	26.07	13.67	39.74	54.00	-14.26	AVG																								
2	10400.710	39.97	13.67	53.64	74.00	-20.36	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																															
Test Mode:	TX 802.11ac(VHT20) Mode 5200MHz (U-NII-1)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10399.795</td><td>25.93</td><td>13.67</td><td>39.60</td><td>54.00</td><td>-14.40</td><td>AVG</td></tr><tr><td>2</td><td>10400.949</td><td>40.72</td><td>13.67</td><td>54.39</td><td>74.00</td><td>-19.61</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10399.795	25.93	13.67	39.60	54.00	-14.40	AVG	2	10400.949	40.72	13.67	54.39	74.00	-19.61	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	10399.795	25.93	13.67	39.60	54.00	-14.40	AVG																									
2	10400.949	40.72	13.67	54.39	74.00	-19.61	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5240MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 90.0 dBuV/m 80 70 60 50 40 30 20 10 0 -10 FCC Part15 C - Above 1G PK FCC Part15 C - Above 1G AV 1000.000 4900.00 8800.00 12700.00 16600.00 (MHz) 24400.00 28300.00 32200.00 36100.00 40000.0																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10479.737</td><td>40.31</td><td>13.80</td><td>54.11</td><td>74.00</td><td>-19.89</td><td>peak</td></tr><tr><td>2 *</td><td>10480.348</td><td>25.83</td><td>13.80</td><td>39.63</td><td>54.00</td><td>-14.37</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10479.737	40.31	13.80	54.11	74.00	-19.89	peak	2 *	10480.348	25.83	13.80	39.63	54.00	-14.37	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10479.737	40.31	13.80	54.11	74.00	-19.89	peak																								
2 *	10480.348	25.83	13.80	39.63	54.00	-14.37	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5240MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10480.435</td><td>40.22</td><td>13.80</td><td>54.02</td><td>74.00</td><td>-19.98</td><td>peak</td></tr><tr><td>2 *</td><td>10480.930</td><td>26.08</td><td>13.80</td><td>39.88</td><td>54.00</td><td>-14.12</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10480.435	40.22	13.80	54.02	74.00	-19.98	peak	2 *	10480.930	26.08	13.80	39.88	54.00	-14.12	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10480.435	40.22	13.80	54.02	74.00	-19.98	peak																								
2 *	10480.930	26.08	13.80	39.88	54.00	-14.12	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT40) Mode 5190MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10379.211</td><td>25.72</td><td>13.63</td><td>39.35</td><td>54.00</td><td>-14.65</td><td>AVG</td></tr><tr><td>2</td><td>10380.563</td><td>39.83</td><td>13.63</td><td>53.46</td><td>74.00</td><td>-20.54</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10379.211	25.72	13.63	39.35	54.00	-14.65	AVG	2	10380.563	39.83	13.63	53.46	74.00	-20.54	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10379.211	25.72	13.63	39.35	54.00	-14.65	AVG																								
2	10380.563	39.83	13.63	53.46	74.00	-20.54	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																															
Test Mode:	TX 802.11n(HT40) Mode 5190MHz (U-NII-1)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10380.081</td><td>39.92</td><td>13.63</td><td>53.55</td><td>74.00</td><td>-20.45</td><td>peak</td></tr><tr><td>2 *</td><td>10380.490</td><td>25.84</td><td>13.63</td><td>39.47</td><td>54.00</td><td>-14.53</td><td>AVG</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10380.081	39.92	13.63	53.55	74.00	-20.45	peak	2 *	10380.490	25.84	13.63	39.47	54.00	-14.53	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1	10380.081	39.92	13.63	53.55	74.00	-20.45	peak																									
2 *	10380.490	25.84	13.63	39.47	54.00	-14.53	AVG																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10459.662</td><td>40.73</td><td>13.77</td><td>54.50</td><td>74.00</td><td>-19.50</td><td>peak</td></tr><tr><td>2 *</td><td>10460.525</td><td>25.67</td><td>13.77</td><td>39.44</td><td>54.00</td><td>-14.56</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10459.662	40.73	13.77	54.50	74.00	-19.50	peak	2 *	10460.525	25.67	13.77	39.44	54.00	-14.56	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10459.662	40.73	13.77	54.50	74.00	-19.50	peak																								
2 *	10460.525	25.67	13.77	39.44	54.00	-14.56	AVG																								
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value																															




Ant. Pol.:	Vertical																															
Test Mode:	TX 802.11n(HT40) Mode 5230MHz (U-NII-1)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<p>The graph plots dBuV/m on the y-axis (from -10 to 90.0) against Frequency (MHz) on the x-axis (from 1000.000 to 40000.0). A red horizontal line at approximately 74 dBuV/m represents the FCC Part15 C - Above 1G PK limit. A green horizontal line at approximately 54 dBuV/m represents the FCC Part15 C - Above 1G AV limit. Two data points are plotted: point 1 at approximately 10459.736 MHz with a reading of 25.93 dBuV, and point 2 at approximately 10460.841 MHz with a reading of 40.83 dBuV. Both points fall well below the FCC limits.</p>																																
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10459.736</td><td>25.93</td><td>13.77</td><td>39.70</td><td>54.00</td><td>-14.30</td><td>AVG</td></tr><tr><td>2</td><td>10460.841</td><td>40.83</td><td>13.78</td><td>54.61</td><td>74.00</td><td>-19.39</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10459.736	25.93	13.77	39.70	54.00	-14.30	AVG	2	10460.841	40.83	13.78	54.61	74.00	-19.39	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	10459.736	25.93	13.77	39.70	54.00	-14.30	AVG																									
2	10460.841	40.83	13.78	54.61	74.00	-19.39	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Horizontal						
Test Mode:	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10379.823	40.57	13.63	54.20	74.00	-19.80	peak
2 *	10380.193	25.60	13.63	39.23	54.00	-14.77	AVG
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value							



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT40) Mode 5190MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10380.188</td><td>25.82</td><td>13.63</td><td>39.45</td><td>54.00</td><td>-14.55</td><td>AVG</td></tr><tr><td>2</td><td>10380.603</td><td>40.84</td><td>13.63</td><td>54.47</td><td>74.00</td><td>-19.53</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10380.188	25.82	13.63	39.45	54.00	-14.55	AVG	2	10380.603	40.84	13.63	54.47	74.00	-19.53	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10380.188	25.82	13.63	39.45	54.00	-14.55	AVG																								
2	10380.603	40.84	13.63	54.47	74.00	-19.53	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10459.535</td><td>39.73</td><td>13.77</td><td>53.50</td><td>74.00</td><td>-20.50</td><td>peak</td></tr><tr><td>2 *</td><td>10460.971</td><td>25.56</td><td>13.78</td><td>39.34</td><td>54.00</td><td>-14.66</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10459.535	39.73	13.77	53.50	74.00	-20.50	peak	2 *	10460.971	25.56	13.78	39.34	54.00	-14.66	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10459.535	39.73	13.77	53.50	74.00	-20.50	peak																								
2 *	10460.971	25.56	13.78	39.34	54.00	-14.66	AVG																								
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT40) Mode 5230MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10459.421</td><td>40.12</td><td>13.77</td><td>53.89</td><td>74.00</td><td>-20.11</td><td>peak</td></tr><tr><td>2 *</td><td>10460.961</td><td>25.44</td><td>13.78</td><td>39.22</td><td>54.00</td><td>-14.78</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10459.421	40.12	13.77	53.89	74.00	-20.11	peak	2 *	10460.961	25.44	13.78	39.22	54.00	-14.78	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10459.421	40.12	13.77	53.89	74.00	-20.11	peak																								
2 *	10460.961	25.44	13.78	39.22	54.00	-14.78	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level - Limit value</p>																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10419.005</td><td>39.67</td><td>13.70</td><td>53.37</td><td>74.00</td><td>-20.63</td><td>peak</td></tr><tr><td>2 *</td><td>10419.516</td><td>25.83</td><td>13.70</td><td>39.53</td><td>54.00</td><td>-14.47</td><td>AVG</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10419.005	39.67	13.70	53.37	74.00	-20.63	peak	2 *	10419.516	25.83	13.70	39.53	54.00	-14.47	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1	10419.005	39.67	13.70	53.37	74.00	-20.63	peak																									
2 *	10419.516	25.83	13.70	39.53	54.00	-14.47	AVG																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT80) Mode 5210MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10419.351</td><td>40.00</td><td>13.70</td><td>53.70</td><td>74.00</td><td>-20.30</td><td>peak</td></tr><tr><td>2 *</td><td>10419.466</td><td>25.95</td><td>13.70</td><td>39.65</td><td>54.00</td><td>-14.35</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10419.351	40.00	13.70	53.70	74.00	-20.30	peak	2 *	10419.466	25.95	13.70	39.65	54.00	-14.35	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10419.351	40.00	13.70	53.70	74.00	-20.30	peak																								
2 *	10419.466	25.95	13.70	39.65	54.00	-14.35	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5260MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10520.033</td><td>40.24</td><td>13.89</td><td>54.13</td><td>74.00</td><td>-19.87</td><td>peak</td></tr><tr><td>2 *</td><td>10520.997</td><td>25.47</td><td>13.89</td><td>39.36</td><td>54.00</td><td>-14.64</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10520.033	40.24	13.89	54.13	74.00	-19.87	peak	2 *	10520.997	25.47	13.89	39.36	54.00	-14.64	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10520.033	40.24	13.89	54.13	74.00	-19.87	peak																								
2 *	10520.997	25.47	13.89	39.36	54.00	-14.64	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical
Test Mode:	TX 802.11a Mode 5260MHz (U-NII-2A)
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10520.000	39.71	13.89	53.60	74.00	-20.40	peak
2 *	10520.000	24.45	13.89	38.34	54.00	-15.66	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11a Mode 5280MHz (U-NII-2A)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
 The graph plots dBuV/m on the y-axis (from -10 to 90) against MHz on the x-axis (from 1000.000 to 40000.0). A red horizontal line at ~75 dBuV/m is labeled "FCC Part15 C - Above 1G PK". A green horizontal line at ~54 dBuV/m is labeled "FCC Part15 C - Above 1G AV". Two data points are marked: point 1 at ~40 dBuV/m and point 2 at ~53 dBuV/m.																																
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10559.147</td><td>25.29</td><td>13.97</td><td>39.26</td><td>54.00</td><td>-14.74</td><td>AVG</td></tr><tr><td>2</td><td>10559.497</td><td>39.30</td><td>13.97</td><td>53.27</td><td>74.00</td><td>-20.73</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10559.147	25.29	13.97	39.26	54.00	-14.74	AVG	2	10559.497	39.30	13.97	53.27	74.00	-20.73	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	10559.147	25.29	13.97	39.26	54.00	-14.74	AVG																									
2	10559.497	39.30	13.97	53.27	74.00	-20.73	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5280MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10560.000</td><td>39.62</td><td>13.97</td><td>53.59</td><td>74.00</td><td>-20.41</td><td>peak</td></tr><tr><td>2 *</td><td>10560.000</td><td>24.45</td><td>13.97</td><td>38.42</td><td>54.00</td><td>-15.58</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10560.000	39.62	13.97	53.59	74.00	-20.41	peak	2 *	10560.000	24.45	13.97	38.42	54.00	-15.58	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10560.000	39.62	13.97	53.59	74.00	-20.41	peak																								
2 *	10560.000	24.45	13.97	38.42	54.00	-15.58	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5320MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10639.577</td><td>25.37</td><td>14.16</td><td>39.53</td><td>54.00</td><td>-14.47</td><td>AVG</td></tr><tr><td>2</td><td>10640.561</td><td>39.72</td><td>14.16</td><td>53.88</td><td>74.00</td><td>-20.12</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10639.577	25.37	14.16	39.53	54.00	-14.47	AVG	2	10640.561	39.72	14.16	53.88	74.00	-20.12	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10639.577	25.37	14.16	39.53	54.00	-14.47	AVG																								
2	10640.561	39.72	14.16	53.88	74.00	-20.12	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5320MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10640.000</td><td>40.30</td><td>14.16</td><td>54.46</td><td>74.00</td><td>-19.54</td><td>peak</td></tr><tr><td>2 *</td><td>10640.000</td><td>24.22</td><td>14.16</td><td>38.38</td><td>54.00</td><td>-15.62</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10640.000	40.30	14.16	54.46	74.00	-19.54	peak	2 *	10640.000	24.22	14.16	38.38	54.00	-15.62	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10640.000	40.30	14.16	54.46	74.00	-19.54	peak																								
2 *	10640.000	24.22	14.16	38.38	54.00	-15.62	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5260MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10519.109</td><td>25.86</td><td>13.89</td><td>39.75</td><td>54.00</td><td>-14.25</td><td>AVG</td></tr><tr><td>2</td><td>10520.280</td><td>40.14</td><td>13.89</td><td>54.03</td><td>74.00</td><td>-19.97</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10519.109	25.86	13.89	39.75	54.00	-14.25	AVG	2	10520.280	40.14	13.89	54.03	74.00	-19.97	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10519.109	25.86	13.89	39.75	54.00	-14.25	AVG																								
2	10520.280	40.14	13.89	54.03	74.00	-19.97	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5260MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 The plot shows a grid from -10 to 90.0 dBuV/m on the y-axis and 1000.000 to 40000.0 MHz on the x-axis. A red line at approximately 74 dBuV/m is labeled "FCC Part15 C - Above 1G PK". A green line at approximately 54 dBuV/m is labeled "FCC Part15 C - Above 1G AV". Two data points are marked: point 1 at 10520.000 MHz with a reading of 40.04 dBuV, and point 2 at 10520.000 MHz with a reading of 24.68 dBuV.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10520.000</td><td>40.04</td><td>13.89</td><td>53.93</td><td>74.00</td><td>-20.07</td><td>peak</td></tr><tr><td>2 *</td><td>10520.000</td><td>24.68</td><td>13.89</td><td>38.57</td><td>54.00</td><td>-15.43</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10520.000	40.04	13.89	53.93	74.00	-20.07	peak	2 *	10520.000	24.68	13.89	38.57	54.00	-15.43	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10520.000	40.04	13.89	53.93	74.00	-20.07	peak																								
2 *	10520.000	24.68	13.89	38.57	54.00	-15.43	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5280MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10560.192</td><td>25.42</td><td>13.97</td><td>39.39</td><td>54.00</td><td>-14.61</td><td>AVG</td></tr><tr><td>2</td><td>10560.405</td><td>40.24</td><td>13.97</td><td>54.21</td><td>74.00</td><td>-19.79</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10560.192	25.42	13.97	39.39	54.00	-14.61	AVG	2	10560.405	40.24	13.97	54.21	74.00	-19.79	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10560.192	25.42	13.97	39.39	54.00	-14.61	AVG																								
2	10560.405	40.24	13.97	54.21	74.00	-19.79	peak																								
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5280MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10560.000</td><td>39.72</td><td>13.97</td><td>53.69</td><td>74.00</td><td>-20.31</td><td>peak</td></tr><tr><td>2 *</td><td>10560.000</td><td>24.24</td><td>13.97</td><td>38.21</td><td>54.00</td><td>-15.79</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10560.000	39.72	13.97	53.69	74.00	-20.31	peak	2 *	10560.000	24.24	13.97	38.21	54.00	-15.79	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10560.000	39.72	13.97	53.69	74.00	-20.31	peak																								
2 *	10560.000	24.24	13.97	38.21	54.00	-15.79	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<p>The graph displays the spectral power density in dBuV/m across a frequency range from 1000.000 MHz to 40000.0 MHz. A green line represents the measured level, showing two distinct peaks labeled '1' and '2'. A red horizontal line at approximately 74 dBuV/m represents the FCC Part 15 C - Above 1G Peak limit. A blue horizontal line at approximately 54 dBuV/m represents the FCC Part 15 C - Above 1G Average limit. The margin is calculated as the difference between the level and the limit.</p>																																
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10639.333</td><td>25.54</td><td>14.16</td><td>39.70</td><td>54.00</td><td>-14.30</td><td>AVG</td></tr><tr><td>2</td><td>10639.779</td><td>39.43</td><td>14.16</td><td>53.59</td><td>74.00</td><td>-20.41</td><td>peak</td></tr></tbody></table> <p>Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10639.333	25.54	14.16	39.70	54.00	-14.30	AVG	2	10639.779	39.43	14.16	53.59	74.00	-20.41	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	10639.333	25.54	14.16	39.70	54.00	-14.30	AVG																									
2	10639.779	39.43	14.16	53.59	74.00	-20.41	peak																									



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10640.000</td><td>40.56</td><td>14.16</td><td>54.72</td><td>74.00</td><td>-19.28</td><td>peak</td></tr><tr><td>2 *</td><td>10640.000</td><td>24.52</td><td>14.16</td><td>38.68</td><td>54.00</td><td>-15.32</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10640.000	40.56	14.16	54.72	74.00	-19.28	peak	2 *	10640.000	24.52	14.16	38.68	54.00	-15.32	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10640.000	40.56	14.16	54.72	74.00	-19.28	peak																								
2 *	10640.000	24.52	14.16	38.68	54.00	-15.32	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10519.338</td><td>25.73</td><td>13.89</td><td>39.62</td><td>54.00</td><td>-14.38</td><td>AVG</td></tr><tr><td>2</td><td>10519.773</td><td>41.03</td><td>13.89</td><td>54.92</td><td>74.00</td><td>-19.08</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10519.338	25.73	13.89	39.62	54.00	-14.38	AVG	2	10519.773	41.03	13.89	54.92	74.00	-19.08	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10519.338	25.73	13.89	39.62	54.00	-14.38	AVG																								
2	10519.773	41.03	13.89	54.92	74.00	-19.08	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5260MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10519.336</td><td>39.45</td><td>13.89</td><td>53.34</td><td>74.00</td><td>-20.66</td><td>peak</td></tr><tr><td>2 *</td><td>10520.151</td><td>25.68</td><td>13.89</td><td>39.57</td><td>54.00</td><td>-14.43</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10519.336	39.45	13.89	53.34	74.00	-20.66	peak	2 *	10520.151	25.68	13.89	39.57	54.00	-14.43	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10519.336	39.45	13.89	53.34	74.00	-20.66	peak																								
2 *	10520.151	25.68	13.89	39.57	54.00	-14.43	AVG																								
<p>Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10559.586</td><td>40.00</td><td>13.97</td><td>53.97</td><td>74.00</td><td>-20.03</td><td>peak</td></tr><tr><td>2 *</td><td>10560.394</td><td>25.41</td><td>13.97</td><td>39.38</td><td>54.00</td><td>-14.62</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10559.586	40.00	13.97	53.97	74.00	-20.03	peak	2 *	10560.394	25.41	13.97	39.38	54.00	-14.62	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10559.586	40.00	13.97	53.97	74.00	-20.03	peak																								
2 *	10560.394	25.41	13.97	39.38	54.00	-14.62	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5280MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10559.168</td><td>39.80</td><td>13.97</td><td>53.77</td><td>74.00</td><td>-20.23</td><td>peak</td></tr><tr><td>2 *</td><td>10560.485</td><td>25.29</td><td>13.97</td><td>39.26</td><td>54.00</td><td>-14.74</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10559.168	39.80	13.97	53.77	74.00	-20.23	peak	2 *	10560.485	25.29	13.97	39.26	54.00	-14.74	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10559.168	39.80	13.97	53.77	74.00	-20.23	peak																								
2 *	10560.485	25.29	13.97	39.26	54.00	-14.74	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5320MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10639.727</td><td>25.48</td><td>14.16</td><td>39.64</td><td>54.00</td><td>-14.36</td><td>AVG</td></tr><tr><td>2</td><td>10639.883</td><td>39.75</td><td>14.16</td><td>53.91</td><td>74.00</td><td>-20.09</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10639.727	25.48	14.16	39.64	54.00	-14.36	AVG	2	10639.883	39.75	14.16	53.91	74.00	-20.09	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10639.727	25.48	14.16	39.64	54.00	-14.36	AVG																								
2	10639.883	39.75	14.16	53.91	74.00	-20.09	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5320MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10639.027</td><td>25.59</td><td>14.15</td><td>39.74</td><td>54.00</td><td>-14.26</td><td>AVG</td></tr><tr><td>2</td><td>10639.349</td><td>39.56</td><td>14.16</td><td>53.72</td><td>74.00</td><td>-20.28</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10639.027	25.59	14.15	39.74	54.00	-14.26	AVG	2	10639.349	39.56	14.16	53.72	74.00	-20.28	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10639.027	25.59	14.15	39.74	54.00	-14.26	AVG																								
2	10639.349	39.56	14.16	53.72	74.00	-20.28	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11n(HT40) Mode 5270MHz (U-NII-2A)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10539.337</td><td>25.12</td><td>13.93</td><td>39.05</td><td>54.00</td><td>-14.95</td><td>AVG</td></tr><tr><td>2</td><td>10540.780</td><td>40.10</td><td>13.93</td><td>54.03</td><td>74.00</td><td>-19.97</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10539.337	25.12	13.93	39.05	54.00	-14.95	AVG	2	10540.780	40.10	13.93	54.03	74.00	-19.97	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	10539.337	25.12	13.93	39.05	54.00	-14.95	AVG																									
2	10540.780	40.10	13.93	54.03	74.00	-19.97	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																																




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT40) Mode 5270MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10539.486</td><td>39.67</td><td>13.93</td><td>53.60</td><td>74.00</td><td>-20.40</td><td>peak</td></tr><tr><td>2 *</td><td>10540.621</td><td>25.25</td><td>13.93</td><td>39.18</td><td>54.00</td><td>-14.82</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10539.486	39.67	13.93	53.60	74.00	-20.40	peak	2 *	10540.621	25.25	13.93	39.18	54.00	-14.82	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10539.486	39.67	13.93	53.60	74.00	-20.40	peak																								
2 *	10540.621	25.25	13.93	39.18	54.00	-14.82	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal						
Test Mode:	TX 802.11n(HT40) Mode 5310MHz (U-NII-2A)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
 Detailed description: The figure is a line graph with a grid. The x-axis is labeled '(MHz)' and has major ticks at 1000.000, 4900.00, 8800.00, 12700.00, 16600.00, 24400.00, 28300.00, 32200.00, 36100.00, and 40000.0. The y-axis is labeled 'dBuV/m' and ranges from -10 to 90.0 in increments of 10. A red horizontal line is drawn at approximately 74 dBuV/m, labeled 'FCC Part15 C - Above 1G PK'. A green horizontal line is drawn at approximately 54 dBuV/m, labeled 'FCC Part15 C - Above 1G AV'. Two data points are plotted: point 1 is marked with a downward arrow and labeled '1' at approximately 10540.780 MHz with a reading of about 40.10 dBuV; point 2 is marked with a downward arrow and labeled '2' at approximately 10619.440 MHz with a reading of about 25.15 dBuV.							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	10540.780	40.10	13.93	54.03	74.00	-19.97	peak
2 *	10619.440	25.15	14.11	39.26	54.00	-14.74	AVG
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value							



Ant. Pol.:	Vertical
Test Mode:	TX 802.11n(HT40) Mode 5310MHz (U-NII-1)
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	10619.427	25.11	14.11	39.22	54.00	-14.78	AVG
2	10620.111	39.76	14.11	53.87	74.00	-20.13	peak

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT40) Mode 5270MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10539.491</td><td>40.09</td><td>13.93</td><td>54.02</td><td>74.00</td><td>-19.98</td><td>peak</td></tr><tr><td>2 *</td><td>10540.712</td><td>25.09</td><td>13.93</td><td>39.02</td><td>54.00</td><td>-14.98</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10539.491	40.09	13.93	54.02	74.00	-19.98	peak	2 *	10540.712	25.09	13.93	39.02	54.00	-14.98	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10539.491	40.09	13.93	54.02	74.00	-19.98	peak																								
2 *	10540.712	25.09	13.93	39.02	54.00	-14.98	Avg																								
<p>Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																															
Test Mode:	TX 802.11ac(VHT40) Mode 5270MHz (U-NII-2A)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10539.525</td><td>25.08</td><td>13.93</td><td>39.01</td><td>54.00</td><td>-14.99</td><td>AVG</td></tr><tr><td>2</td><td>10540.440</td><td>40.55</td><td>13.93</td><td>54.48</td><td>74.00</td><td>-19.52</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10539.525	25.08	13.93	39.01	54.00	-14.99	AVG	2	10540.440	40.55	13.93	54.48	74.00	-19.52	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	10539.525	25.08	13.93	39.01	54.00	-14.99	AVG																									
2	10540.440	40.55	13.93	54.48	74.00	-19.52	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11ac(VHT40) Mode 5310MHz (U-NII-2A)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10620.430</td><td>39.65</td><td>14.11</td><td>53.76</td><td>74.00</td><td>-20.24</td><td>peak</td></tr><tr><td>2 *</td><td>10620.819</td><td>25.01</td><td>14.11</td><td>39.12</td><td>54.00</td><td>-14.88</td><td>AVG</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10620.430	39.65	14.11	53.76	74.00	-20.24	peak	2 *	10620.819	25.01	14.11	39.12	54.00	-14.88	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1	10620.430	39.65	14.11	53.76	74.00	-20.24	peak																									
2 *	10620.819	25.01	14.11	39.12	54.00	-14.88	AVG																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Vertical																															
Test Mode:	TX 802.11ac(VHT40) Mode 5310MHz (U-NII-2A)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
																																
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10619.185</td><td>25.36</td><td>14.11</td><td>39.47</td><td>54.00</td><td>-14.53</td><td>AVG</td></tr><tr><td>2</td><td>10619.996</td><td>39.98</td><td>14.11</td><td>54.09</td><td>74.00</td><td>-19.91</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10619.185	25.36	14.11	39.47	54.00	-14.53	AVG	2	10619.996	39.98	14.11	54.09	74.00	-19.91	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	10619.185	25.36	14.11	39.47	54.00	-14.53	AVG																									
2	10619.996	39.98	14.11	54.09	74.00	-19.91	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																




Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT80) Mode 5290MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 Detailed description: This is a spectral plot showing the measured emissions of a device against FCC Part 15 C limits. The vertical axis represents the signal strength in dBuV/m, ranging from -10 to 90.0. The horizontal axis represents frequency in MHz, ranging from 1000.000 to 40000.0. A red horizontal line at approximately 74 dBuV/m represents the 'FCC Part15 C - Above 1G PK' limit. A green horizontal line at approximately 54 dBuV/m represents the 'FCC Part15 C - Above 1G AV' limit. Two data points are plotted: point 1 is at approximately 8800.00 MHz with a reading of about 40 dBuV/m, and point 2 is at approximately 10580.567 MHz with a reading of about 24.92 dBuV/m. Both points are well above the FCC limits.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>10580.567</td><td>24.92</td><td>14.02</td><td>38.94</td><td>54.00</td><td>-15.06</td><td>AVG</td></tr><tr><td>2</td><td>10580.767</td><td>39.78</td><td>14.02</td><td>53.80</td><td>74.00</td><td>-20.20</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	10580.567	24.92	14.02	38.94	54.00	-15.06	AVG	2	10580.767	39.78	14.02	53.80	74.00	-20.20	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	10580.567	24.92	14.02	38.94	54.00	-15.06	AVG																								
2	10580.767	39.78	14.02	53.80	74.00	-20.20	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT80) Mode 5290MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10579.444</td><td>39.07</td><td>14.02</td><td>53.09</td><td>74.00</td><td>-20.91</td><td>peak</td></tr><tr><td>2 *</td><td>10580.135</td><td>25.28</td><td>14.02</td><td>39.30</td><td>54.00</td><td>-14.70</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10579.444	39.07	14.02	53.09	74.00	-20.91	peak	2 *	10580.135	25.28	14.02	39.30	54.00	-14.70	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10579.444	39.07	14.02	53.09	74.00	-20.91	peak																								
2 *	10580.135	25.28	14.02	39.30	54.00	-14.70	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5500MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11000.303</td><td>25.53</td><td>14.97</td><td>40.50</td><td>54.00</td><td>-13.50</td><td>AVG</td></tr><tr><td>2</td><td>11000.758</td><td>39.22</td><td>14.97</td><td>54.19</td><td>74.00</td><td>-19.81</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11000.303	25.53	14.97	40.50	54.00	-13.50	AVG	2	11000.758	39.22	14.97	54.19	74.00	-19.81	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11000.303	25.53	14.97	40.50	54.00	-13.50	AVG																								
2	11000.758	39.22	14.97	54.19	74.00	-19.81	peak																								
<p>Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															





Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5580MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11159.300</td><td>25.91</td><td>14.98</td><td>40.89</td><td>54.00</td><td>-13.11</td><td>AVG</td></tr><tr><td>2</td><td>11160.718</td><td>39.32</td><td>14.98</td><td>54.30</td><td>74.00</td><td>-19.70</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11159.300	25.91	14.98	40.89	54.00	-13.11	AVG	2	11160.718	39.32	14.98	54.30	74.00	-19.70	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11159.300	25.91	14.98	40.89	54.00	-13.11	AVG																								
2	11160.718	39.32	14.98	54.30	74.00	-19.70	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5580MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11160.000</td><td>39.56</td><td>14.98</td><td>54.54</td><td>74.00</td><td>-19.46</td><td>peak</td></tr><tr><td>2 *</td><td>11160.000</td><td>24.65</td><td>14.98</td><td>39.63</td><td>54.00</td><td>-14.37</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11160.000	39.56	14.98	54.54	74.00	-19.46	peak	2 *	11160.000	24.65	14.98	39.63	54.00	-14.37	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11160.000	39.56	14.98	54.54	74.00	-19.46	peak																								
2 *	11160.000	24.65	14.98	39.63	54.00	-14.37	AVG																								
<p>Remarks:</p> <p>1.Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2.Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5700MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11399.585</td><td>24.85</td><td>14.99</td><td>39.84</td><td>54.00</td><td>-14.16</td><td>AVG</td></tr><tr><td>2</td><td>11400.219</td><td>39.34</td><td>14.99</td><td>54.33</td><td>74.00</td><td>-19.67</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11399.585	24.85	14.99	39.84	54.00	-14.16	AVG	2	11400.219	39.34	14.99	54.33	74.00	-19.67	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11399.585	24.85	14.99	39.84	54.00	-14.16	AVG																								
2	11400.219	39.34	14.99	54.33	74.00	-19.67	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5700MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11400.000</td><td>40.47</td><td>14.99</td><td>55.46</td><td>74.00</td><td>-18.54</td><td>peak</td></tr><tr><td>2 *</td><td>11400.000</td><td>23.40</td><td>14.99</td><td>38.39</td><td>54.00</td><td>-15.61</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11400.000	40.47	14.99	55.46	74.00	-18.54	peak	2 *	11400.000	23.40	14.99	38.39	54.00	-15.61	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11400.000	40.47	14.99	55.46	74.00	-18.54	peak																								
2 *	11400.000	23.40	14.99	38.39	54.00	-15.61	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5500MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10999.704</td><td>39.91</td><td>14.97</td><td>54.88</td><td>74.00</td><td>-19.12</td><td>peak</td></tr><tr><td>2 *</td><td>11000.453</td><td>25.41</td><td>14.97</td><td>40.38</td><td>54.00</td><td>-13.62</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10999.704	39.91	14.97	54.88	74.00	-19.12	peak	2 *	11000.453	25.41	14.97	40.38	54.00	-13.62	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10999.704	39.91	14.97	54.88	74.00	-19.12	peak																								
2 *	11000.453	25.41	14.97	40.38	54.00	-13.62	Avg																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5500MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11000.000</td><td>40.28</td><td>14.97</td><td>55.25</td><td>74.00</td><td>-18.75</td><td>peak</td></tr><tr><td>2 *</td><td>11000.000</td><td>24.65</td><td>14.97</td><td>39.62</td><td>54.00</td><td>-14.38</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11000.000	40.28	14.97	55.25	74.00	-18.75	peak	2 *	11000.000	24.65	14.97	39.62	54.00	-14.38	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11000.000	40.28	14.97	55.25	74.00	-18.75	peak																								
2 *	11000.000	24.65	14.97	39.62	54.00	-14.38	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5580MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11159.862</td><td>39.65</td><td>14.98</td><td>54.63</td><td>74.00</td><td>-19.37</td><td>peak</td></tr><tr><td>2 *</td><td>11160.083</td><td>25.69</td><td>14.98</td><td>40.67</td><td>54.00</td><td>-13.33</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11159.862	39.65	14.98	54.63	74.00	-19.37	peak	2 *	11160.083	25.69	14.98	40.67	54.00	-13.33	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11159.862	39.65	14.98	54.63	74.00	-19.37	peak																								
2 *	11160.083	25.69	14.98	40.67	54.00	-13.33	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5580MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11160.000</td><td>39.99</td><td>14.98</td><td>54.97</td><td>74.00</td><td>-19.03</td><td>peak</td></tr><tr><td>2 *</td><td>11160.000</td><td>24.78</td><td>14.98</td><td>39.76</td><td>54.00</td><td>-14.24</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11160.000	39.99	14.98	54.97	74.00	-19.03	peak	2 *	11160.000	24.78	14.98	39.76	54.00	-14.24	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11160.000	39.99	14.98	54.97	74.00	-19.03	peak																								
2 *	11160.000	24.78	14.98	39.76	54.00	-14.24	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal						
Test Mode:	TX 802.11n(HT20) Mode 5700MHz (U-NII-2C)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
							
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	11399.745	24.88	14.99	39.87	54.00	-14.13	AVG
2	11400.404	39.78	14.99	54.77	74.00	-19.23	peak
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value							




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5700MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11399.373</td><td>39.83</td><td>14.99</td><td>54.82</td><td>74.00</td><td>-19.18</td><td>peak</td></tr><tr><td>2 *</td><td>11400.935</td><td>24.73</td><td>14.99</td><td>39.72</td><td>54.00</td><td>-14.28</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11399.373	39.83	14.99	54.82	74.00	-19.18	peak	2 *	11400.935	24.73	14.99	39.72	54.00	-14.28	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11399.373	39.83	14.99	54.82	74.00	-19.18	peak																								
2 *	11400.935	24.73	14.99	39.72	54.00	-14.28	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5500MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11000.463</td><td>40.48</td><td>14.97</td><td>55.45</td><td>74.00</td><td>-18.55</td><td>peak</td></tr><tr><td>2 *</td><td>11000.931</td><td>25.50</td><td>14.97</td><td>40.47</td><td>54.00</td><td>-13.53</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11000.463	40.48	14.97	55.45	74.00	-18.55	peak	2 *	11000.931	25.50	14.97	40.47	54.00	-13.53	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11000.463	40.48	14.97	55.45	74.00	-18.55	peak																								
2 *	11000.931	25.50	14.97	40.47	54.00	-13.53	Avg																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5500MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>10999.605</td><td>39.90</td><td>14.97</td><td>54.87</td><td>74.00</td><td>-19.13</td><td>peak</td></tr><tr><td>2 *</td><td>10999.905</td><td>25.51</td><td>14.97</td><td>40.48</td><td>54.00</td><td>-13.52</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	10999.605	39.90	14.97	54.87	74.00	-19.13	peak	2 *	10999.905	25.51	14.97	40.48	54.00	-13.52	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	10999.605	39.90	14.97	54.87	74.00	-19.13	peak																								
2 *	10999.905	25.51	14.97	40.48	54.00	-13.52	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5580MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11159.554</td><td>25.76</td><td>14.98</td><td>40.74</td><td>54.00</td><td>-13.26</td><td>AVG</td></tr><tr><td>2</td><td>11160.517</td><td>40.88</td><td>14.98</td><td>55.86</td><td>74.00</td><td>-18.14</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11159.554	25.76	14.98	40.74	54.00	-13.26	AVG	2	11160.517	40.88	14.98	55.86	74.00	-18.14	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11159.554	25.76	14.98	40.74	54.00	-13.26	AVG																								
2	11160.517	40.88	14.98	55.86	74.00	-18.14	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																															
Test Mode:	TX 802.11ac(VHT20) Mode 5580MHz (U-NII-2C)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
 Y-axis: dBuV/m (from -10 to 90.0). X-axis: MHz (from 1000.000 to 40000.0). The plot shows a flat spectrum across the measured band.																																
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11160.030</td><td>25.51</td><td>14.98</td><td>40.49</td><td>54.00</td><td>-13.51</td><td>AVG</td></tr><tr><td>2</td><td>11160.442</td><td>40.57</td><td>14.98</td><td>55.55</td><td>74.00</td><td>-18.45</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11160.030	25.51	14.98	40.49	54.00	-13.51	AVG	2	11160.442	40.57	14.98	55.55	74.00	-18.45	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	11160.030	25.51	14.98	40.49	54.00	-13.51	AVG																									
2	11160.442	40.57	14.98	55.55	74.00	-18.45	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																																





Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5700MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11400.369</td><td>24.74</td><td>14.99</td><td>39.73</td><td>54.00</td><td>-14.27</td><td>AVG</td></tr><tr><td>2</td><td>11400.727</td><td>39.42</td><td>14.99</td><td>54.41</td><td>74.00</td><td>-19.59</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11400.369	24.74	14.99	39.73	54.00	-14.27	AVG	2	11400.727	39.42	14.99	54.41	74.00	-19.59	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11400.369	24.74	14.99	39.73	54.00	-14.27	AVG																								
2	11400.727	39.42	14.99	54.41	74.00	-19.59	peak																								
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT40) Mode 5510MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11019.160</td><td>39.56</td><td>14.97</td><td>54.53</td><td>74.00</td><td>-19.47</td><td>peak</td></tr><tr><td>2 *</td><td>11019.433</td><td>25.51</td><td>14.97</td><td>40.48</td><td>54.00</td><td>-13.52</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11019.160	39.56	14.97	54.53	74.00	-19.47	peak	2 *	11019.433	25.51	14.97	40.48	54.00	-13.52	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11019.160	39.56	14.97	54.53	74.00	-19.47	peak																								
2 *	11019.433	25.51	14.97	40.48	54.00	-13.52	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT40) Mode 5510MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<p>FCC Part15 C - Above 1G PK</p> <p>FCC Part15 C - Above 1G AV</p>																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11020.135</td><td>38.90</td><td>14.97</td><td>53.87</td><td>74.00</td><td>-20.13</td><td>peak</td></tr><tr><td>2 *</td><td>11020.745</td><td>25.38</td><td>14.97</td><td>40.35</td><td>54.00</td><td>-13.65</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11020.135	38.90	14.97	53.87	74.00	-20.13	peak	2 *	11020.745	25.38	14.97	40.35	54.00	-13.65	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11020.135	38.90	14.97	53.87	74.00	-20.13	peak																								
2 *	11020.745	25.38	14.97	40.35	54.00	-13.65	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT40) Mode 5550MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11099.388</td><td>41.50</td><td>14.98</td><td>56.48</td><td>74.00</td><td>-17.52</td><td>peak</td></tr><tr><td>2 *</td><td>11100.198</td><td>25.88</td><td>14.98</td><td>40.86</td><td>54.00</td><td>-13.14</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11099.388	41.50	14.98	56.48	74.00	-17.52	peak	2 *	11100.198	25.88	14.98	40.86	54.00	-13.14	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11099.388	41.50	14.98	56.48	74.00	-17.52	peak																								
2 *	11100.198	25.88	14.98	40.86	54.00	-13.14	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT40) Mode 5550MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<p>FCC Part15 C - Above 1G PK</p> <p>FCC Part15 C - Above 1G AV</p>																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11100.012</td><td>40.19</td><td>14.98</td><td>55.17</td><td>74.00</td><td>-18.83</td><td>peak</td></tr><tr><td>2 *</td><td>11100.568</td><td>25.35</td><td>14.98</td><td>40.33</td><td>54.00</td><td>-13.67</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11100.012	40.19	14.98	55.17	74.00	-18.83	peak	2 *	11100.568	25.35	14.98	40.33	54.00	-13.67	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11100.012	40.19	14.98	55.17	74.00	-18.83	peak																								
2 *	11100.568	25.35	14.98	40.33	54.00	-13.67	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level - Limit value</p>																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11n(HT40) Mode 5670MHz (U-NII-2C)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11339.110</td><td>25.01</td><td>14.99</td><td>40.00</td><td>54.00</td><td>-14.00</td><td>AVG</td></tr><tr><td>2</td><td>11340.830</td><td>39.61</td><td>14.99</td><td>54.60</td><td>74.00</td><td>-19.40</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11339.110	25.01	14.99	40.00	54.00	-14.00	AVG	2	11340.830	39.61	14.99	54.60	74.00	-19.40	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	11339.110	25.01	14.99	40.00	54.00	-14.00	AVG																									
2	11340.830	39.61	14.99	54.60	74.00	-19.40	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT40) Mode 5670MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11339.081</td><td>39.74</td><td>14.99</td><td>54.73</td><td>74.00</td><td>-19.27</td><td>peak</td></tr><tr><td>2 *</td><td>11339.712</td><td>24.84</td><td>14.99</td><td>39.83</td><td>54.00</td><td>-14.17</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11339.081	39.74	14.99	54.73	74.00	-19.27	peak	2 *	11339.712	24.84	14.99	39.83	54.00	-14.17	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11339.081	39.74	14.99	54.73	74.00	-19.27	peak																								
2 *	11339.712	24.84	14.99	39.83	54.00	-14.17	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT40) Mode 5510MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11019.751</td><td>25.27</td><td>14.97</td><td>40.24</td><td>54.00</td><td>-13.76</td><td>AVG</td></tr><tr><td>2</td><td>11020.717</td><td>39.68</td><td>14.97</td><td>54.65</td><td>74.00</td><td>-19.35</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11019.751	25.27	14.97	40.24	54.00	-13.76	AVG	2	11020.717	39.68	14.97	54.65	74.00	-19.35	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11019.751	25.27	14.97	40.24	54.00	-13.76	AVG																								
2	11020.717	39.68	14.97	54.65	74.00	-19.35	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																															
Test Mode:	TX 802.11ac(VHT40) Mode 5510MHz (U-NII-2C)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11019.969</td><td>39.45</td><td>14.97</td><td>54.42</td><td>74.00</td><td>-19.58</td><td>peak</td></tr><tr><td>2 *</td><td>11020.533</td><td>25.88</td><td>14.97</td><td>40.85</td><td>54.00</td><td>-13.15</td><td>AVG</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11019.969	39.45	14.97	54.42	74.00	-19.58	peak	2 *	11020.533	25.88	14.97	40.85	54.00	-13.15	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1	11019.969	39.45	14.97	54.42	74.00	-19.58	peak																									
2 *	11020.533	25.88	14.97	40.85	54.00	-13.15	AVG																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Horizontal						
Test Mode:	TX 802.11ac(VHT40) Mode 5550MHz (U-NII-2C)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	11099.447	25.36	14.98	40.34	54.00	-13.66	AVG
2	11101.000	39.18	14.98	54.16	74.00	-19.84	peak
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value							



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT40) Mode 5550MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 Detailed description: The plot shows a grid from 1000.000 to 40000.0 MHz on the x-axis and -10 to 90.0 dBuV/m on the y-axis. A red line at approximately 74 dBuV/m is labeled 'FCC Part15 C- Above 1G PK'. A green line at approximately 55 dBuV/m is labeled 'FCC Part15 C - Above 1G AV'. Two data points are plotted: point 1 at 11099.043 MHz with a reading of 40.18 dBuV and a factor of 14.98 dB/m; point 2 at 11100.149 MHz with a reading of 25.07 dBuV and a factor of 14.98 dB/m.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11099.043</td><td>40.18</td><td>14.98</td><td>55.16</td><td>74.00</td><td>-18.84</td><td>peak</td></tr><tr><td>2 *</td><td>11100.149</td><td>25.07</td><td>14.98</td><td>40.05</td><td>54.00</td><td>-13.95</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11099.043	40.18	14.98	55.16	74.00	-18.84	peak	2 *	11100.149	25.07	14.98	40.05	54.00	-13.95	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11099.043	40.18	14.98	55.16	74.00	-18.84	peak																								
2 *	11100.149	25.07	14.98	40.05	54.00	-13.95	Avg																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT40) Mode 5670MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11339.841</td><td>25.03</td><td>14.99</td><td>40.02</td><td>54.00</td><td>-13.98</td><td>AVG</td></tr><tr><td>2</td><td>11340.559</td><td>39.78</td><td>14.99</td><td>54.77</td><td>74.00</td><td>-19.23</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11339.841	25.03	14.99	40.02	54.00	-13.98	AVG	2	11340.559	39.78	14.99	54.77	74.00	-19.23	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11339.841	25.03	14.99	40.02	54.00	-13.98	AVG																								
2	11340.559	39.78	14.99	54.77	74.00	-19.23	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT40) Mode 5670MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11339.578</td><td>25.33</td><td>14.99</td><td>40.32</td><td>54.00</td><td>-13.68</td><td>AVG</td></tr><tr><td>2</td><td>11340.597</td><td>39.56</td><td>14.99</td><td>54.55</td><td>74.00</td><td>-19.45</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11339.578	25.33	14.99	40.32	54.00	-13.68	AVG	2	11340.597	39.56	14.99	54.55	74.00	-19.45	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11339.578	25.33	14.99	40.32	54.00	-13.68	AVG																								
2	11340.597	39.56	14.99	54.55	74.00	-19.45	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT80) Mode 5530MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11059.801</td><td>25.40</td><td>14.98</td><td>40.38</td><td>54.00</td><td>-13.62</td><td>AVG</td></tr><tr><td>2</td><td>11060.764</td><td>39.44</td><td>14.98</td><td>54.42</td><td>74.00</td><td>-19.58</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11059.801	25.40	14.98	40.38	54.00	-13.62	AVG	2	11060.764	39.44	14.98	54.42	74.00	-19.58	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11059.801	25.40	14.98	40.38	54.00	-13.62	AVG																								
2	11060.764	39.44	14.98	54.42	74.00	-19.58	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT80) Mode 5530MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11060.100</td><td>39.50</td><td>14.98</td><td>54.48</td><td>74.00</td><td>-19.52</td><td>peak</td></tr><tr><td>2 *</td><td>11060.560</td><td>25.28</td><td>14.98</td><td>40.26</td><td>54.00</td><td>-13.74</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11060.100	39.50	14.98	54.48	74.00	-19.52	peak	2 *	11060.560	25.28	14.98	40.26	54.00	-13.74	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11060.100	39.50	14.98	54.48	74.00	-19.52	peak																								
2 *	11060.560	25.28	14.98	40.26	54.00	-13.74	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT80) Mode 5610MHz (U-NII-2C)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11219.789</td><td>25.73</td><td>14.98</td><td>40.71</td><td>54.00</td><td>-13.29</td><td>AVG</td></tr><tr><td>2</td><td>11220.688</td><td>39.62</td><td>14.98</td><td>54.60</td><td>74.00</td><td>-19.40</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11219.789	25.73	14.98	40.71	54.00	-13.29	AVG	2	11220.688	39.62	14.98	54.60	74.00	-19.40	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11219.789	25.73	14.98	40.71	54.00	-13.29	AVG																								
2	11220.688	39.62	14.98	54.60	74.00	-19.40	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																													
Test Mode:	TX 802.11ac(VHT80) Mode 5610MHz (U-NII-2C)																													
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																													
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11219.043</td><td>26.00</td><td>14.98</td><td>40.98</td><td>54.00</td><td>-13.02</td><td>AVG</td></tr><tr><td>2</td><td>11220.155</td><td>39.65</td><td>14.98</td><td>54.63</td><td>74.00</td><td>-19.37</td><td>peak</td></tr></tbody></table>							No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11219.043	26.00	14.98	40.98	54.00	-13.02	AVG	2	11220.155	39.65	14.98	54.63	74.00	-19.37	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																							
1 *	11219.043	26.00	14.98	40.98	54.00	-13.02	AVG																							
2	11220.155	39.65	14.98	54.63	74.00	-19.37	peak																							
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value																														



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5745MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11490.453</td><td>24.94</td><td>15.01</td><td>39.95</td><td>54.00</td><td>-14.05</td><td>AVG</td></tr><tr><td>2</td><td>11490.982</td><td>39.63</td><td>15.01</td><td>54.64</td><td>74.00</td><td>-19.36</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11490.453	24.94	15.01	39.95	54.00	-14.05	AVG	2	11490.982	39.63	15.01	54.64	74.00	-19.36	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11490.453	24.94	15.01	39.95	54.00	-14.05	AVG																								
2	11490.982	39.63	15.01	54.64	74.00	-19.36	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical
Test Mode:	TX 802.11a Mode 5745MHz (U-NII-3)
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11490.000	39.00	15.00	54.00	74.00	-20.00	peak
2 *	11490.000	24.05	15.00	39.05	54.00	-14.95	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5785MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11569.459</td><td>25.43</td><td>15.06</td><td>40.49</td><td>54.00</td><td>-13.51</td><td>AVG</td></tr><tr><td>2</td><td>11570.463</td><td>39.44</td><td>15.07</td><td>54.51</td><td>74.00</td><td>-19.49</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11569.459	25.43	15.06	40.49	54.00	-13.51	AVG	2	11570.463	39.44	15.07	54.51	74.00	-19.49	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11569.459	25.43	15.06	40.49	54.00	-13.51	AVG																								
2	11570.463	39.44	15.07	54.51	74.00	-19.49	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5785MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11570.000</td><td>39.80</td><td>15.06</td><td>54.86</td><td>74.00</td><td>-19.14</td><td>peak</td></tr><tr><td>2 *</td><td>11570.000</td><td>24.55</td><td>15.06</td><td>39.61</td><td>54.00</td><td>-14.39</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11570.000	39.80	15.06	54.86	74.00	-19.14	peak	2 *	11570.000	24.55	15.06	39.61	54.00	-14.39	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11570.000	39.80	15.06	54.86	74.00	-19.14	peak																								
2 *	11570.000	24.55	15.06	39.61	54.00	-14.39	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11650.207</td><td>40.11</td><td>15.14</td><td>55.25</td><td>74.00</td><td>-18.75</td><td>peak</td></tr><tr><td>2 *</td><td>11650.919</td><td>25.12</td><td>15.14</td><td>40.26</td><td>54.00</td><td>-13.74</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11650.207	40.11	15.14	55.25	74.00	-18.75	peak	2 *	11650.919	25.12	15.14	40.26	54.00	-13.74	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11650.207	40.11	15.14	55.25	74.00	-18.75	peak																								
2 *	11650.919	25.12	15.14	40.26	54.00	-13.74	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical
Test Mode:	TX 802.11a Mode 5825MHz (U-NII-3)
Remark:	No report for the emission which more than 10 dB below the prescribed limit.



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11650.000	39.55	15.13	54.68	74.00	-19.32	peak
2 *	11650.000	24.29	15.13	39.42	54.00	-14.58	AVG

Remarks:


1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.:	Horizontal						
Test Mode:	TX 802.11n(HT20) Mode 5745MHz (U-NII-3)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1 *	11489.189	24.88	15.00	39.88	54.00	-14.12	AVG
2	11490.525	40.34	15.01	55.35	74.00	-18.65	peak
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value							



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5745MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11489.293</td><td>39.37</td><td>15.00</td><td>54.37</td><td>74.00</td><td>-19.63</td><td>peak</td></tr><tr><td>2 *</td><td>11490.845</td><td>25.40</td><td>15.01</td><td>40.41</td><td>54.00</td><td>-13.59</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11489.293	39.37	15.00	54.37	74.00	-19.63	peak	2 *	11490.845	25.40	15.01	40.41	54.00	-13.59	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11489.293	39.37	15.00	54.37	74.00	-19.63	peak																								
2 *	11490.845	25.40	15.01	40.41	54.00	-13.59	Avg																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															





Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5785MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11570.186</td><td>25.24</td><td>15.07</td><td>40.31</td><td>54.00</td><td>-13.69</td><td>AVG</td></tr><tr><td>2</td><td>11570.690</td><td>40.48</td><td>15.07</td><td>55.55</td><td>74.00</td><td>-18.45</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11570.186	25.24	15.07	40.31	54.00	-13.69	AVG	2	11570.690	40.48	15.07	55.55	74.00	-18.45	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11570.186	25.24	15.07	40.31	54.00	-13.69	AVG																								
2	11570.690	40.48	15.07	55.55	74.00	-18.45	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT20) Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11649.294</td><td>39.28</td><td>15.13</td><td>54.41</td><td>74.00</td><td>-19.59</td><td>peak</td></tr><tr><td>2 *</td><td>11650.553</td><td>25.15</td><td>15.14</td><td>40.29</td><td>54.00</td><td>-13.71</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11649.294	39.28	15.13	54.41	74.00	-19.59	peak	2 *	11650.553	25.15	15.14	40.29	54.00	-13.71	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11649.294	39.28	15.13	54.41	74.00	-19.59	peak																								
2 *	11650.553	25.15	15.14	40.29	54.00	-13.71	Avg																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11649.072</td><td>25.10</td><td>15.13</td><td>40.23</td><td>54.00</td><td>-13.77</td><td>AVG</td></tr><tr><td>2</td><td>11649.335</td><td>39.97</td><td>15.13</td><td>55.10</td><td>74.00</td><td>-18.90</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11649.072	25.10	15.13	40.23	54.00	-13.77	AVG	2	11649.335	39.97	15.13	55.10	74.00	-18.90	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11649.072	25.10	15.13	40.23	54.00	-13.77	AVG																								
2	11649.335	39.97	15.13	55.10	74.00	-18.90	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11489.472</td><td>24.86</td><td>15.00</td><td>39.86</td><td>54.00</td><td>-14.14</td><td>AVG</td></tr><tr><td>2</td><td>11490.820</td><td>39.23</td><td>15.01</td><td>54.24</td><td>74.00</td><td>-19.76</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11489.472	24.86	15.00	39.86	54.00	-14.14	AVG	2	11490.820	39.23	15.01	54.24	74.00	-19.76	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11489.472	24.86	15.00	39.86	54.00	-14.14	AVG																								
2	11490.820	39.23	15.01	54.24	74.00	-19.76	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5745MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11489.211</td><td>39.68</td><td>15.00</td><td>54.68</td><td>74.00</td><td>-19.32</td><td>peak</td></tr><tr><td>2 *</td><td>11490.667</td><td>25.25</td><td>15.01</td><td>40.26</td><td>54.00</td><td>-13.74</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11489.211	39.68	15.00	54.68	74.00	-19.32	peak	2 *	11490.667	25.25	15.01	40.26	54.00	-13.74	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11489.211	39.68	15.00	54.68	74.00	-19.32	peak																								
2 *	11490.667	25.25	15.01	40.26	54.00	-13.74	AVG																								
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level - Limit value																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11569.277</td><td>25.24</td><td>15.06</td><td>40.30</td><td>54.00</td><td>-13.70</td><td>AVG</td></tr><tr><td>2</td><td>11570.740</td><td>40.44</td><td>15.07</td><td>55.51</td><td>74.00</td><td>-18.49</td><td>peak</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11569.277	25.24	15.06	40.30	54.00	-13.70	AVG	2	11570.740	40.44	15.07	55.51	74.00	-18.49	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1 *	11569.277	25.24	15.06	40.30	54.00	-13.70	AVG																									
2	11570.740	40.44	15.07	55.51	74.00	-18.49	peak																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5785MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11570.170</td><td>25.24</td><td>15.07</td><td>40.31</td><td>54.00</td><td>-13.69</td><td>AVG</td></tr><tr><td>2</td><td>11570.954</td><td>39.54</td><td>15.07</td><td>54.61</td><td>74.00</td><td>-19.39</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11570.170	25.24	15.07	40.31	54.00	-13.69	AVG	2	11570.954	39.54	15.07	54.61	74.00	-19.39	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11570.170	25.24	15.07	40.31	54.00	-13.69	AVG																								
2	11570.954	39.54	15.07	54.61	74.00	-19.39	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11649.290</td><td>39.94</td><td>15.13</td><td>55.07</td><td>74.00</td><td>-18.93</td><td>peak</td></tr><tr><td>2 *</td><td>11650.465</td><td>25.37</td><td>15.14</td><td>40.51</td><td>54.00</td><td>-13.49</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11649.290	39.94	15.13	55.07	74.00	-18.93	peak	2 *	11650.465	25.37	15.14	40.51	54.00	-13.49	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11649.290	39.94	15.13	55.07	74.00	-18.93	peak																								
2 *	11650.465	25.37	15.14	40.51	54.00	-13.49	AVG																								
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT20) Mode 5825MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11649.141</td><td>25.34</td><td>15.13</td><td>40.47</td><td>54.00</td><td>-13.53</td><td>AVG</td></tr><tr><td>2</td><td>11650.302</td><td>39.35</td><td>15.14</td><td>54.49</td><td>74.00</td><td>-19.51</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11649.141	25.34	15.13	40.47	54.00	-13.53	AVG	2	11650.302	39.35	15.14	54.49	74.00	-19.51	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11649.141	25.34	15.13	40.47	54.00	-13.53	AVG																								
2	11650.302	39.35	15.14	54.49	74.00	-19.51	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11509.212</td><td>39.83</td><td>15.00</td><td>54.83</td><td>74.00</td><td>-19.17</td><td>peak</td></tr><tr><td>2 *</td><td>11509.578</td><td>25.16</td><td>15.00</td><td>40.16</td><td>54.00</td><td>-13.84</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11509.212	39.83	15.00	54.83	74.00	-19.17	peak	2 *	11509.578	25.16	15.00	40.16	54.00	-13.84	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11509.212	39.83	15.00	54.83	74.00	-19.17	peak																								
2 *	11509.578	25.16	15.00	40.16	54.00	-13.84	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT40) Mode 5755MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11509.052</td><td>24.98</td><td>15.00</td><td>39.98</td><td>54.00</td><td>-14.02</td><td>AVG</td></tr><tr><td>2</td><td>11509.435</td><td>39.68</td><td>15.00</td><td>54.68</td><td>74.00</td><td>-19.32</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11509.052	24.98	15.00	39.98	54.00	-14.02	AVG	2	11509.435	39.68	15.00	54.68	74.00	-19.32	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11509.052	24.98	15.00	39.98	54.00	-14.02	AVG																								
2	11509.435	39.68	15.00	54.68	74.00	-19.32	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11n(HT40) Mode 5795MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11589.708</td><td>39.74</td><td>15.08</td><td>54.82</td><td>74.00</td><td>-19.18</td><td>peak</td></tr><tr><td>2 *</td><td>11590.593</td><td>24.93</td><td>15.09</td><td>40.02</td><td>54.00</td><td>-13.98</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11589.708	39.74	15.08	54.82	74.00	-19.18	peak	2 *	11590.593	24.93	15.09	40.02	54.00	-13.98	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11589.708	39.74	15.08	54.82	74.00	-19.18	peak																								
2 *	11590.593	24.93	15.09	40.02	54.00	-13.98	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical
Test Mode:	TX 802.11n(HT40) Mode 5795MHz (U-NII-3)
Remark:	No report for the emission which more than 10 dB below the prescribed limit.




No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	11589.266	39.28	15.08	54.36	74.00	-19.64	peak
2 *	11590.299	24.91	15.09	40.00	54.00	-14.00	AVG

Remarks:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
2. Margin value = Level -Limit value



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11510.455</td><td>39.73</td><td>15.01</td><td>54.74</td><td>74.00</td><td>-19.26</td><td>peak</td></tr><tr><td>2 *</td><td>11510.895</td><td>24.95</td><td>15.01</td><td>39.96</td><td>54.00</td><td>-14.04</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11510.455	39.73	15.01	54.74	74.00	-19.26	peak	2 *	11510.895	24.95	15.01	39.96	54.00	-14.04	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11510.455	39.73	15.01	54.74	74.00	-19.26	peak																								
2 *	11510.895	24.95	15.01	39.96	54.00	-14.04	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT40) Mode 5755MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
 <table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11509.394</td><td>39.41</td><td>15.00</td><td>54.41</td><td>74.00</td><td>-19.59</td><td>peak</td></tr><tr><td>2 *</td><td>11510.467</td><td>25.09</td><td>15.01</td><td>40.10</td><td>54.00</td><td>-13.90</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11509.394	39.41	15.00	54.41	74.00	-19.59	peak	2 *	11510.467	25.09	15.01	40.10	54.00	-13.90	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11509.394	39.41	15.00	54.41	74.00	-19.59	peak																								
2 *	11510.467	25.09	15.01	40.10	54.00	-13.90	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11ac(VHT40) Mode 5795MHz (U-NII-3)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11509.487</td><td>39.83</td><td>15.00</td><td>54.83</td><td>74.00</td><td>-19.17</td><td>peak</td></tr><tr><td>2 *</td><td>11509.820</td><td>25.30</td><td>15.00</td><td>40.30</td><td>54.00</td><td>-13.70</td><td>AVG</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11509.487	39.83	15.00	54.83	74.00	-19.17	peak	2 *	11509.820	25.30	15.00	40.30	54.00	-13.70	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1	11509.487	39.83	15.00	54.83	74.00	-19.17	peak																									
2 *	11509.820	25.30	15.00	40.30	54.00	-13.70	AVG																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																																




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT40) Mode 5795MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<p>The graph plots dBuV/m on the y-axis (from -10 to 90.0) against MHz on the x-axis (from 1000.000 to 40000.0). A red horizontal line at approximately 74 dBuV/m is labeled "FCC Part15 C - Above 1G PK". A green horizontal line at approximately 54 dBuV/m is labeled "FCC Part15 C - Above 1G AV". Two data points are plotted: point 1 at approximately 41 dBuV/m and point 2 at approximately 56 dBuV/m.</p>																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1 *</td><td>11589.028</td><td>24.84</td><td>15.08</td><td>39.92</td><td>54.00</td><td>-14.08</td><td>AVG</td></tr><tr><td>2</td><td>11590.761</td><td>39.67</td><td>15.09</td><td>54.76</td><td>74.00</td><td>-19.24</td><td>peak</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1 *	11589.028	24.84	15.08	39.92	54.00	-14.08	AVG	2	11590.761	39.67	15.09	54.76	74.00	-19.24	peak
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1 *	11589.028	24.84	15.08	39.92	54.00	-14.08	AVG																								
2	11590.761	39.67	15.09	54.76	74.00	-19.24	peak																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11549.245</td><td>39.91</td><td>15.04</td><td>54.95</td><td>74.00</td><td>-19.05</td><td>peak</td></tr><tr><td>2 *</td><td>11549.851</td><td>25.23</td><td>15.04</td><td>40.27</td><td>54.00</td><td>-13.73</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11549.245	39.91	15.04	54.95	74.00	-19.05	peak	2 *	11549.851	25.23	15.04	40.27	54.00	-13.73	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11549.245	39.91	15.04	54.95	74.00	-19.05	peak																								
2 *	11549.851	25.23	15.04	40.27	54.00	-13.73	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11ac(VHT80) Mode 5775MHz (U-NII-3)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>11550.487</td><td>40.20</td><td>15.05</td><td>55.25</td><td>74.00</td><td>-18.75</td><td>peak</td></tr><tr><td>2 *</td><td>11550.721</td><td>25.27</td><td>15.05</td><td>40.32</td><td>54.00</td><td>-13.68</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	11550.487	40.20	15.05	55.25	74.00	-18.75	peak	2 *	11550.721	25.27	15.05	40.32	54.00	-13.68	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	11550.487	40.20	15.05	55.25	74.00	-18.75	peak																								
2 *	11550.721	25.27	15.05	40.32	54.00	-13.68	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															

3.3. Band Edge Emissions

Limit

Limits of unwanted emission out of the restricted bands

FCC CFR Title 47 Part 15 Subpart C Section 15.407(b)/ RSS-247 6.2.1.2 & RSS-247 6.2.4.2


Frequency (MHz)	EIRP Limits (dBm)	Equivalent Field Strength at 3m (dBuV/m)
5150~5250	-27	68.2
5250~5350	-27	68.2
5470~5725	-27	68.2
5725~5825	-27(Note 2)	68.2
	10(Note 2)	105.2
	15.6(Note 2)	110.8
	27(Note 2)	122.2

Note: 1. The following formula is used to convert the equipment isotropic radiated power (eirp) to field

$$\text{strength: } E = \frac{1000000\sqrt{30P}}{3} \text{ uV/m, where P is the eirp (Watts)}$$

2. According to FCC 16-24, All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27dBm/MHz at the band edge.

Test Configuration



Test Procedure

1. The EUT was setup and tested according to ANSI C63.10:2013 requirements.
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

[Http://www.sz-ctc.org.cn](http://www.sz-ctc.org.cn)



5. The receiver set as follow:

RBW=1MHz, VBW=3MHz PEAK detector for Peak value.

RBW=1MHz, VBW see note 1 with Peak Detector for Average Value.


Note 1: For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause Appendix E: Duty Cycle

Test Mode


Please refer to the clause 2.4.

Test Results


Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>5150.000</td><td>58.46</td><td>2.93</td><td>61.39</td><td>74.00</td><td>-12.61</td><td>peak</td></tr><tr><td>2 *</td><td>5150.000</td><td>47.12</td><td>2.93</td><td>50.05</td><td>54.00</td><td>-3.95</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	5150.000	58.46	2.93	61.39	74.00	-12.61	peak	2 *	5150.000	47.12	2.93	50.05	54.00	-3.95	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	5150.000	58.46	2.93	61.39	74.00	-12.61	peak																								
2 *	5150.000	47.12	2.93	50.05	54.00	-3.95	Avg																								
<p>Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															






Ant. Pol.:	Horizontal																														
Test Mode:	TX 802.11a Mode 5320MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>5350.000</td><td>47.59</td><td>3.43</td><td>51.02</td><td>74.00</td><td>-22.98</td><td>peak</td></tr><tr><td>2 *</td><td>5350.000</td><td>43.30</td><td>3.43</td><td>46.73</td><td>54.00</td><td>-7.27</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	5350.000	47.59	3.43	51.02	74.00	-22.98	peak	2 *	5350.000	43.30	3.43	46.73	54.00	-7.27	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	5350.000	47.59	3.43	51.02	74.00	-22.98	peak																								
2 *	5350.000	43.30	3.43	46.73	54.00	-7.27	Avg																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															




Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11a Mode 5320MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>5350.000</td><td>50.02</td><td>3.43</td><td>53.45</td><td>74.00</td><td>-20.55</td><td>peak</td></tr><tr><td>2 *</td><td>5350.000</td><td>39.31</td><td>3.43</td><td>42.74</td><td>54.00</td><td>-11.26</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	5350.000	50.02	3.43	53.45	74.00	-20.55	peak	2 *	5350.000	39.31	3.43	42.74	54.00	-11.26	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	5350.000	50.02	3.43	53.45	74.00	-20.55	peak																								
2 *	5350.000	39.31	3.43	42.74	54.00	-11.26	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																															





Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5180MHz (U-NII-1)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>5150.000</td><td>53.75</td><td>2.93</td><td>56.68</td><td>74.00</td><td>-17.32</td><td>peak</td></tr><tr><td>2 *</td><td>5150.000</td><td>47.86</td><td>2.93</td><td>50.79</td><td>54.00</td><td>-3.21</td><td>Avg</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	5150.000	53.75	2.93	56.68	74.00	-17.32	peak	2 *	5150.000	47.86	2.93	50.79	54.00	-3.21	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	5150.000	53.75	2.93	56.68	74.00	-17.32	peak																								
2 *	5150.000	47.86	2.93	50.79	54.00	-3.21	Avg																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level - Limit value</p>																															





Ant. Pol.:	Vertical																														
Test Mode:	TX 802.11n(HT20) Mode 5320MHz (U-NII-2A)																														
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																														
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>5350.000</td><td>45.57</td><td>3.43</td><td>49.00</td><td>74.00</td><td>-25.00</td><td>peak</td></tr><tr><td>2 *</td><td>5350.000</td><td>40.21</td><td>3.43</td><td>43.64</td><td>54.00</td><td>-10.36</td><td>AVG</td></tr></tbody></table>								No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	5350.000	45.57	3.43	49.00	74.00	-25.00	peak	2 *	5350.000	40.21	3.43	43.64	54.00	-10.36	AVG
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																								
1	5350.000	45.57	3.43	49.00	74.00	-25.00	peak																								
2 *	5350.000	40.21	3.43	43.64	54.00	-10.36	AVG																								
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level -Limit value</p>																															



Ant. Pol.:	Horizontal																															
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1)																															
Remark:	No report for the emission which more than 10 dB below the prescribed limit.																															
<table border="1"><thead><tr><th>No.</th><th>Frequency (MHz)</th><th>Reading (dBuV)</th><th>Factor (dB/m)</th><th>Level (dBuV/m)</th><th>Limit (dBuV/m)</th><th>Margin (dB)</th><th>Detector</th></tr></thead><tbody><tr><td>1</td><td>5150.000</td><td>53.09</td><td>2.93</td><td>56.02</td><td>74.00</td><td>-17.98</td><td>peak</td></tr><tr><td>2 *</td><td>5150.000</td><td>48.13</td><td>2.93</td><td>51.06</td><td>54.00</td><td>-2.94</td><td>Avg</td></tr></tbody></table>									No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	1	5150.000	53.09	2.93	56.02	74.00	-17.98	peak	2 *	5150.000	48.13	2.93	51.06	54.00	-2.94	Avg
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector																									
1	5150.000	53.09	2.93	56.02	74.00	-17.98	peak																									
2 *	5150.000	48.13	2.93	51.06	54.00	-2.94	Avg																									
<p>Remarks:</p> <p>1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor</p> <p>2. Margin value = Level -Limit value</p>																																



Ant. Pol.:	Vertical						
Test Mode:	TX 802.11ac(VHT20) Mode 5180MHz (U-NII-1)						
Remark:	No report for the emission which more than 10 dB below the prescribed limit.						
No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	5150.000	50.82	2.93	53.75	74.00	-20.25	peak
2 *	5150.000	46.54	2.93	49.47	54.00	-4.53	AVG
Remarks: 1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor 2. Margin value = Level - Limit value							

