



FCC Part 15, Subpart B, Class B

ARTIKA FOR LIVING INC

Capa pendant

Test Model: PDT-CPC-WT

Additional Model No.: PDT-CPC-XXXXXX ("XXXXXX" can be A to Z and/or 0 to 9 and/or blank (commercial code))

Prepared for : ARTIKA FOR LIVING INC  
Address : 1756 50th avenue, Lachine, Qc, Canada H8T 2V5  
Lachine Canada

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park  
Yabianxueziwei, Shajing Street, Baoan District,  
Shenzhen, 518000, China  
Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : September 08, 2022  
Number of tested samples : 2  
Sample No. : A082322200  
Serial number : Prototype  
Date of Test : September 08, 2022~ September 15, 2022  
Date of Report : September 15, 2022





FCC Part 15, Subpart B, Class B
FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014

Report Reference No. .... : LCSA082322200EA

Date Of Issue ..... : September 15, 2022

Testing Laboratory Name .... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Address ..... : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park
Yabianxueziwei, Shajing Street, Baoan District, Shenzhen,
518000, China

Testing Location/ Procedure... : Full application of Harmonised standards ■
Partial application of Harmonised standards □
Other standard testing method □

Applicant's Name..... : ARTIKA FOR LIVING INC

Address ..... : 1756 50th avenue, Lachine, Qc, CanadaH8T 2V5 Lachine
Canada

Test Specification

Standard..... : FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4
-2014

Test Report Form No..... : LCSEMC-1.0

TRF Originator..... : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF..... : Dated 2011-03

SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long
as the SHENZHEN LCS COMPLIANCE TESTING LABORATORY LTD. is acknowledged as
copyright owner and source of the material. SHENZHEN LCS COMPLIANCE TESTING
LABORATORY LTD. takes no responsibility for and will not assume liability for damages
resulting from the reader's interpretation of the reproduced material due to its placement and
context.

Test Item Description..... : Capa pendant

Test Model ..... : PDT-CPC-WT

Trade Mark ..... : Artika

Ratings ..... : Input: AC 120V, 60Hz, 26W

Result ..... : Positive

Compiled by:

Vera Deng

Vera Deng/ Administrator

Supervised by:

Cary Luo

Cary Luo/ Technique principal

Approved by:

Gavin Liang

Gavin Liang/ Manager





### FCC -- TEST REPORT

<b>Test Report No. : LCSA082322200EA</b>	<u>September 15, 2022</u> Date of issue
--	--

Test Model .....	: PDT-CPC-WT
EUT.....	: Capa pendant
<b>Applicant.....</b>	<b>: ARTIKA FOR LIVING INC</b>
Address.....	: 1756 50th avenue, Lachine, Qc, CanadaH8T 2V5 Lachine Canada
Telephone.....	: /
Fax.....	: /
<b>Manufacturer.....</b>	<b>: ZHONGSHAN C5 LIGHTING CO., LTD</b>
Address.....	: 1# Henglong Road, Tongyi Industrial Area, Cao San, Guzhen, Zhongshan, Guangdong, China.
Telephone.....	: /
Fax.....	: /
<b>Factory.....</b>	<b>: ZHONGSHAN C5 LIGHTING CO., LTD</b>
Address.....	: 1# Henglong Road, Tongyi Industrial Area, Cao San, Guzhen, Zhongshan, Guangdong, China.
Telephone.....	: /
Fax.....	: /

**Test Result** according to the standards on page 6: **Positive**

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.





### Revision History

Report Version	Issue Date	Revision Content	Revised By
000	September 15, 2022	Initial Issue	--





# TABLE OF CONTENTS

Test Report Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS .....</b>	<b>6</b>
1.1. Description of Standards and Results .....	6
<b>2. GENERAL INFORMATION .....</b>	<b>7</b>
2.1. Description of Device (EUT).....	7
2.2. Support Equipment List.....	7
2.3. Description of Test Facility .....	8
2.4. Statement of the Measurement Uncertainty.....	8
2.5. Measurement Uncertainty.....	8
<b>3. TEST RESULTS .....</b>	<b>9</b>
3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT .....	9
3.2. Radiated emission Measurement.....	13
<b>4. TEST SETUP PHOTOGRAPHS OF EUT .....</b>	<b>17</b>
<b>5. EXTERIOR PHOTOGRAPHS OF THE EUT .....</b>	<b>17</b>
<b>6. INTERIOR PHOTOGRAPHS OF THE EUT.....</b>	<b>17</b>





# 1. SUMMARY OF STANDARDS AND RESULTS

## 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION			
Description of Test Item	Standard	Limits	Results
Conducted disturbance at mains terminals	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
Radiated disturbance	FCC 47 CFR Part 15 Subpart B, Class B, ANSI C63.4 -2014	Class B	PASS
N/A is an abbreviation for Not Applicable.			

Test mode:		
Mode 1	Lighting	Record





## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

- EUT : Capa pendant
- Trade Mark : Artika
- Test Model : PDT-CPC-WT
- Additional Model No. : PDT-CPC-XXXXXX (“XXXXXX” can be A to Z and/or 0 to 9 and/or blank (commercial code))
- Model Declaration : PCB board, structure and internal of these model(s) are the same, So no additional models were tested
- Power Supply : Input: AC 120V, 60Hz, 26W
- Highest internal frequency (Fx) :  $F_x \leq 108 \text{ MHz}$

Highest internal frequency (Fx)	Highest measured frequency
$F_x \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} < F_x \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} < F_x \leq 1 \text{ GHz}$	5 GHz
$F_x > 1 \text{ GHz}$	$5 \times F_x$ up to a maximum of 6 GHz

NOTE 1 For FM and TV broadcast receivers,  $F_x$  is determined from the highest frequency generated or used excluding the local oscillator and tuned frequencies.  
Where  $F_x$  is unknown, the radiated emission measurements shall be performed up to 6 GHz.

### 2.2. Support Equipment List

Name	Manufacturers	M/N	S/N
--	--	--	--





### 2.3. Description of Test Facility

#### Site Description

EMC Lab. : NVLAP Accreditation Code is 600167-0.  
 FCC Designation Number is CN5024.  
 CAB identifier is CN0071.  
 CNAS Registration Number is L4595.  
 FCC Test Firm Registration Number: 254912

### 2.4. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

### 2.5. Measurement Uncertainty

Test	Parameters	Expanded Uncertainty (Ulab)	Expanded Uncertainty (Ucisp)
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	± 2.63 dB ± 2.35 dB	± 3.8 dB ± 3.4 dB
Radiated Emission	Level accuracy (30MHz to 1000MHz)	± 3.48 dB	± 5.3 dB
Radiated Emission	Level accuracy (above 1000MHz)	± 3.90 dB	± 5.2 dB

(1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

(2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.





### 3. TEST RESULTS


#### 3.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

##### 3.1.1. Test Equipment

The following test equipments are used during the power line conducted measurement:

Item	Equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	EMI Test Receiver	R&S	ESR3	102312	2022-02-18	2023-02-17
3	Artificial Mains	R&S	ENV216	101288	2022-06-16	2023-06-15
4	Pulse Limiter	R&S	ESH3-Z2	102750-NB	2022-08-18	2023-08-17
5	Impedance Stabilization Network	TESEQ	ISN T800	45130	2021-11-16	2022-11-15

##### 3.1.2. Block Diagram of Test Setup



##### 3.1.3. Test Standard

###### Power Line Conducted Emission Limits (Class B)

Frequency (MHz)			Limit (dB $\mu$ V)	
			Quasi-peak Level	Average Level
0.15	~	0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50	~	5.00	56.0	46.0
5.00	~	30.00	60.0	50.0

NOTE1-The lower limit shall apply at the transition frequencies.

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.





### 3.1.4.EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the commission requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

### 3.1.5.Operating Condition of EUT

3.1.5.1.Setup the EUT as shown on Section 3.1.2

3.1.5.2.Turn on the power of all equipments.

3.1.5.3.Let the EUT work in measuring Lighting and measure it.

### 3.1.6.Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC/ANSI C63.4-2014 on Conducted Emission Measurement.

The bandwidth of the test receiver is set at 9kHz.

The frequency range from 150kHz to 30MHz is investigated

### 3.1.7.Test Results


**PASS.**

The test result please refer to the next page.





<b>Test Model</b>	PDT-CPC-WT	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	23.2°C, 53.4% RH	<b>Test Engineer</b>	Nick Peng
<b>Pol</b>	Line	<b>Test Voltage</b>	AC 120V/60Hz




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1580	37.41	19.63	57.04	65.57	-8.53	QP	
2		0.1580	19.08	19.63	38.71	55.57	-16.86	AVG	
3		0.3090	30.58	19.63	50.21	60.00	-9.79	QP	
4		0.3090	8.51	19.63	28.14	50.00	-21.86	AVG	
5		1.0546	28.03	19.65	47.68	56.00	-8.32	QP	
6		1.0636	10.84	19.65	30.49	46.00	-15.51	AVG	
7	*	2.9176	32.97	19.68	52.65	56.00	-3.35	QP	
8		2.9896	19.62	19.68	39.30	46.00	-6.70	AVG	
9		3.4950	29.52	19.70	49.22	56.00	-6.78	QP	
10		3.4950	17.91	19.70	37.61	46.00	-8.39	AVG	
11		5.3701	33.23	19.70	52.93	60.00	-7.07	QP	
12		5.4286	21.19	19.70	40.89	50.00	-9.11	AVG	





<b>Test Model</b>	PDT-CPC-WT	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	22.5°C, 53.7% RH	<b>Test Engineer</b>	Nick Peng
<b>Pol</b>	Neutral	<b>Test Voltage</b>	AC 120V/60Hz



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Margin dB	Detector	Comment
1		0.1600	36.94	19.63	56.57	65.46	-8.89	QP	
2		0.1600	18.39	19.63	38.02	55.46	-17.44	AVG	
3		0.2540	33.28	19.63	52.91	61.63	-8.72	QP	
4		0.2540	17.77	19.63	37.40	51.63	-14.23	AVG	
5		0.2840	33.66	19.63	53.29	60.70	-7.41	QP	
6		0.2840	18.70	19.63	38.33	50.70	-12.37	AVG	
7	*	0.4921	34.30	19.64	53.94	56.13	-2.19	QP	
8		0.5146	17.69	19.65	37.34	46.00	-8.66	AVG	
9		3.3230	27.94	19.77	47.71	56.00	-8.29	QP	
10		3.3230	17.63	19.77	37.40	46.00	-8.60	AVG	
11		5.3745	33.08	19.80	52.88	60.00	-7.12	QP	
12		5.4691	18.73	19.80	38.53	50.00	-11.47	AVG	

\*\*\*Note: 1) Pre-scan all modes and recorded the worst case results in this report.

2) Margin=Reading level + Correct - Limit




### 3.2. Radiated emission Measurement

#### 3.2.1. Test Equipment


The following test equipments are used during the radiated emission measurement:

Item	Test equipment	Manufacturer	Model No.	Serial No.	Cal Date	Due Date
1	EMI Test Software	AUDIX	E3	/	N/A	N/A
2	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2021-09-12	2024-09-11
3	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2021-09-05	2024-09-04
4	EMI Test Receiver	R&S	ESR3	102311	2022-08-18	2023-08-17
5	Broadband Preamplifier	/	BP-01M18G	P190501	2022-06-16	2023-06-15
6	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2021-11-15	2022-11-14
7	EMI Test Receiver	R&S	ESPI	101940	2022-08-18	2023-08-17
8	EMI Test Software	AUDIX	E3	/	N/A	N/A

#### 3.2.2. Block Diagram of Test Setup



Below 1GHz



Above 1GHz





### 3.2.3. Radiated Emission Limit (Class B)

Limits for Radiated Disturbance Below 1GHz

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46
960 ~ 1000	3	500	54

Remark: (1) Emission level (dB)μV = 20 log Emission level μV/m  
 (2) The smaller limit shall apply at the cross point between two frequency bands.  
 (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

Limits for Radiated Emission Above 1GHz

Frequency (MHz)	Distance (Meters)	Peak Limit (dBμV/m)	Average Limit (dBμV/m)
Above 1000	3	74	54

\*\*\*Note: The lower limit applies at the transition frequency.

### 3.2.4. EUT Configuration on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 3.2.5. Operating Condition of EUT

3.2.5.1. Setup the EUT as shown in Section 3.2.2.

3.2.5.2. Let the EUT work in test Lighting and measure it.

### 3.2.6. Test Procedure

EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated by-log antenna) is used as receiving antenna. Both horizontal and vertical polarization of the antenna is set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.4-2014 on radiated emission measurement.

The bandwidth of the EMI test receiver is set at 120kHz, 300kHz. The frequency range from 30MHz to 1000MHz is checked.

### 3.2.7. Radiated Emission Noise Measurement Result


**PASS.**

The scanning waveforms please refer to the next page.





<b>Test Model</b>	PDT-CPC-WT	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	22.3°C, 53.6% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Vertical	<b>Distance</b>	3m
<b>Test Engineer</b>	Nick Peng	<b>Test Voltage</b>	AC 120V/60Hz



pol:

VERTICAL


	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	55.22	21.47	0.63	12.55	34.65	40.00	-5.35	QP
2	73.10	23.85	0.71	10.07	34.63	40.00	-5.37	QP
3	116.95	21.33	0.89	10.84	33.06	43.50	-10.44	QP
4	161.47	20.89	1.08	9.28	31.25	43.50	-12.25	QP
5	408.95	15.86	1.41	15.03	32.30	46.00	-13.70	QP
6	758.04	20.37	1.92	19.72	42.01	46.00	-3.99	QP

- Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that are 20db below the official limit are not reported





<b>Test Model</b>	PDT-CPC-WT	<b>Test Mode</b>	Lighting
<b>Environmental Conditions</b>	22.3°C, 53.6% RH	<b>Detector Function</b>	Quasi-peak
<b>Pol</b>	Horizontal	<b>Distance</b>	3m
<b>Test Engineer</b>	Nick Peng	<b>Test Voltage</b>	AC 120V/60Hz



pol:

HORIZONTAL

	Freq	Reading	CabLos	Antfac	Measured	Limit	Over	Remark
	MHz	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	54.26	18.50	0.62	12.56	31.68	40.00	-8.32	QP
2	64.89	19.81	0.68	11.33	31.82	40.00	-8.18	QP
3	124.57	23.52	0.93	10.04	34.49	43.50	-9.01	QP
4	348.03	15.98	1.36	14.79	32.13	46.00	-13.87	QP
5	597.22	14.76	1.50	19.21	35.47	46.00	-10.53	QP
6	881.41	15.75	2.08	21.23	39.06	46.00	-6.94	QP

- Note: 1. All readings are Quasi-peak values.  
 2. Measured= Reading + Antenna Factor + Cable Loss  
 3. The emission that are 20db below the official limit are not reported

Note:1).Pre-Scan all mode, Thus record worse case mode result in this report.

2) Margin=Reading level + Correct - Limit







#### 4. TEST SETUP PHOTOGRAPHS OF EUT

Please refer to separated files for Test Setup Photos of the EUT.

#### 5. EXTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for External Photos of the EUT.

#### 6. INTERIOR PHOTOGRAPHS OF THE EUT

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF TEST REPORT-----

