



FCC RF Test Report

APPLICANT : Honor Device Co., Ltd.
EQUIPMENT : Smart Phone
BRAND NAME : HONOR
MODEL NAME : FNE-NX9
FCC ID : 2AYGCFNE-NX9
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DSS) Spread Spectrum Transmitter
TEST DATE(S) : May 26, 2022 ~ Jul. 07, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (ShenZhen).

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1 GENERAL DESCRIPTION..... 5

 1.1 Applicant 5

 1.2 Manufacturer 5

 1.3 Product Feature of Equipment Under Test..... 5

 1.4 Product Specification of Equipment Under Test..... 6

 1.5 Modification of EUT 6

 1.6 Testing Location 7

 1.7 Test Software 8

 1.8 Applicable Standards..... 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST..... 9

 2.1 Carrier Frequency Channel 9

 2.2 Test Mode 10

 2.3 Connection Diagram of Test System 11

 2.4 Support Unit used in test configuration and system 11

 2.5 EUT Operation Test Setup 12

 2.6 Measurement Results Explanation Example..... 12

3 TEST RESULT 13

 3.1 Number of Channel Measurement 13

 3.2 Hopping Channel Separation Measurement 16

 3.3 Dwell Time Measurement 27

 3.4 20dB and 99% Bandwidth Measurement 30

 3.5 Output Power Measurement..... 49

 3.6 Conducted Band Edges Measurement..... 50

 3.7 Conducted Spurious Emission Measurement 63

 3.8 Radiated Band Edges and Spurious Emission Measurement 82

 3.9 AC Conducted Emission Measurement..... 86

 3.10 Antenna Requirements 88

4 LIST OF MEASURING EQUIPMENT..... 89

5 UNCERTAINTY OF EVALUATION..... 90

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. AC CONDUCTED EMISSION TEST RESULT

APPENDIX C. RADIATED SPURIOUS EMISSION

APPENDIX D. DUTY CYCLE PLOTS

APPENDIX E. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR242802A	Rev. 01	Initial issue of report	Jul. 08, 2022



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	Number of Channels	≥ 15Chs	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	≥ 2/3 of 20dB BW	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	≤ 0.4sec in 31.6sec period	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	-	Report only	-
3.4	-	99% Bandwidth	-	Report only	-
3.5	15.247(b)(1)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	Conducted Band Edges	≤ 20dBc	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	≤ 20dBc	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 10.25 dB at 48.430 MHz
3.9	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 8.86 dB at 0.170 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Honor Device Co., Ltd.

Shum Yip Sky Park, No. 8089, Hongli West Road, Shenzhen, China

1.2 Manufacturer

Honor Device Co., Ltd.

Shum Yip Sky Park, No. 8089, Hongli West Road, Shenzhen, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smart Phone
Brand Name	HONOR
Model Name	FNE-NX9
IMEI Code	Conducted: 865911060050962/865911060054162 Conduction: 865911060030063/865911060037068 Radiation: 865911060029461/865911060036466
FCC ID	2AYGCFNE-NX9
HW Version	HN2FNEM02
SW Version	6.1.0.116(C900E100R1P1)
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Maximum Output Power to Antenna	<Ant 1> Bluetooth BR(1Mbps) : 16.13 dBm (0.0410 W) Bluetooth EDR (2Mbps) : 15.54 dBm (0.0358 W) Bluetooth EDR (3Mbps) : 15.61 dBm (0.0364 W) <Ant 2> Bluetooth BR(1Mbps) : 16.26 dBm (0.0423 W) Bluetooth EDR (2Mbps) : 15.64 dBm (0.0366 W) Bluetooth EDR (3Mbps) : 15.73 dBm (0.0374 W)
99% Occupied Bandwidth	<Ant 1> Bluetooth BR(1Mbps) : 0.848MHz Bluetooth EDR (2Mbps) : 1.166MHz Bluetooth EDR (3Mbps) : 1.149MHz <Ant 2> Bluetooth BR(1Mbps) : 0.836MHz Bluetooth EDR (2Mbps) : 1.169MHz Bluetooth EDR (3Mbps) : 1.152MHz
Antenna Type / Gain	<Ant 1> Built-in Antenna type with gain -1.90 dBi <Ant 2> Built-in Antenna type with gain -2.30 dBi
Type of Modulation	Bluetooth BR (1Mbps) : GFSK Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK Bluetooth EDR (3Mbps) : 8-DPSK

Note:

1. BT Ant. 1/2 corresponding to EUT Photo Ant. 8/11.
2. BT Ant. 1/2 does not support MIMO mode.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH05-KS TH01-KS	CN1257	314309

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-SZ	CN1256	421272



1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH05-KS	AUDIX	E3	6.2009-8-24al
2.	CO01-SZ	AUDIX	E3	6.120613b

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-




2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps π/4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
Mode 3: CH78_2480 MHz			
AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable 1(Charging from Adapter3) + Battery 1		
Remark: <ol style="list-style-type: none"> For radiated test cases, the worst mode data rate 3Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission. For Radiated Test Cases, The tests were performed with Adapter 3, Battery1 and USB Cable1. 			

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	Dlink	DIR-820L	KA2IR820LA1	N/A	Unshielded,1.8m
3.	NOTE BOOK	Lenovo	E540	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
4.	Bluetooth Earphone	Samsung	EO-MG900	PYAHS-107W	N/A	N/A



2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 5.0 dB.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} . \\ &= 5.0 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup






3.1.5 Test Result of Number of Hopping Frequency


For Ant 1

Number of Hopping Channel Plot on Channel 00



Date: 26.JUN.2022 07:26:08

Number of Hopping Channel Plot on Channel 78




Date: 26.JUN.2022 07:26:41




For Ant 2

Number of Hopping Channel Plot on Channel 00



Date: 29.JUN.2022 17:04:14

Number of Hopping Channel Plot on Channel 78



Date: 29.JUN.2022 17:04:30

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup






3.2.5 Test Result of Hopping Channel Separation

For Ant 1


<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 28.JUN.2022 06:46:32


Channel Separation Plot on Channel 39 - 40



Date: 28.JUN.2022 06:51:06




Channel Separation Plot on Channel 77 - 78



Date: 28.JUN.2022 08:13:53

<2Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 28.JUN.2022 07:01:30




Channel Separation Plot on Channel 39 - 40



Date: 28.JUN.2022 07:05:50

Channel Separation Plot on Channel 77 - 78




Date: 28.JUN.2022 08:15:15




<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 28.JUN.2022 07:17:00


Channel Separation Plot on Channel 39 - 40



Date: 28.JUN.2022 07:20:52



Channel Separation Plot on Channel 77 - 78




Date: 28.JUN.2022 07:24:54



For Ant 2


<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 29.JUN.2022 16:50:07


Channel Separation Plot on Channel 39 - 40



Date: 29.JUN.2022 16:40:00




Channel Separation Plot on Channel 77 - 78



Date: 29.JUN.2022 17:02:13

<2Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 29.JUN.2022 17:16:50




Channel Separation Plot on Channel 39 - 40



Date: 29.JUN.2022 17:24:53

Channel Separation Plot on Channel 77 - 78




Date: 29.JUN.2022 17:30:12




<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 29.JUN.2022 18:26:08


Channel Separation Plot on Channel 39 - 40



Date: 29.JUN.2022 18:32:05



Channel Separation Plot on Channel 77 - 78



Date: 29.JUN.2022 18:38:02

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup






3.3.5 Test Result of Dwell Time

Please refer to Appendix A.


For Ant 1:

Package Transfer Time Plot



For Ant 2:

Package Transfer Time Plot





Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots (5 Transmit and 1 Receive slot) in 79 hopping channels.
With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s),
Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.
With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s),
Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;
Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup






3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

For Ant 1:


<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 7.JUL.2022 21:24:15


20 dB Bandwidth Plot on Channel 39



Date: 7.JUL.2022 21:26:30




20 dB Bandwidth Plot on Channel 78



Date: 7.JUL.2022 21:28:27

<2Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 7.JUL.2022 21:30:54




20 dB Bandwidth Plot on Channel 39



Date: 7 JUL 2022 21:32:29

20 dB Bandwidth Plot on Channel 78




Date: 7 JUL 2022 21:34:09




<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 7.JUL.2022 21:38:58


20 dB Bandwidth Plot on Channel 39



Date: 7.JUL.2022 21:36:34



20 dB Bandwidth Plot on Channel 78




Date: 7.JUL.2022 21:35:27

For Ant 2:

<1Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 7.JUL.2022 21:44:52




20 dB Bandwidth Plot on Channel 39



Date: 7.JUL.2022 21:45:58

20 dB Bandwidth Plot on Channel 78




Date: 7.JUL.2022 21:47:00




<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 7.JUL.2022 21:50:28


20 dB Bandwidth Plot on Channel 39



Date: 7.JUL.2022 21:49:05




20 dB Bandwidth Plot on Channel 78



Date: 7.JUL.2022 21:47:54

<3Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 7.JUL.2022 21:51:28




20 dB Bandwidth Plot on Channel 39



Date: 7.JUL.2022 21:52:19

20 dB Bandwidth Plot on Channel 78



Date: 7.JUL.2022 21:53:21



3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

For Ant 1:


<1Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 28 JUN, 2022 06:43:32


99% Occupied Bandwidth Plot on Channel 39



Date: 28 JUN, 2022 06:49:04




99% Occupied Bandwidth Plot on Channel 78



Date: 28.JUN.2022 06:51:52

<2Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 28.JUN.2022 06:59:41




99% Occupied Bandwidth Plot on Channel 39



Date: 28.JUN.2022 07:04:07

99% Occupied Bandwidth Plot on Channel 78




Date: 28.JUN.2022 07:07:51




<3Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 28.JUN.2022 07:15:14


99% Occupied Bandwidth Plot on Channel 39



Date: 28.JUN.2022 07:17:45



99% Occupied Bandwidth Plot on Channel 78




Date: 28.JUN.2022 07:21:42

For Ant 2

<1Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 29.JUN.2022 16:45:54




99% Occupied Bandwidth Plot on Channel 39



Date: 29.JUN.2022 16:31:43

99% Occupied Bandwidth Plot on Channel 78




Date: 29.JUN.2022 16:54:57




<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 29.JUN.2022 17:13:46


99% Occupied Bandwidth Plot on Channel 39



Date: 29.JUN.2022 17:22:15




99% Occupied Bandwidth Plot on Channel 78



Date: 29.JUN.2022 17:27:12

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 29.JUN.2022 17:33:54




99% Occupied Bandwidth Plot on Channel 39



Date: 29.JUN.2022 18:28:43

99% Occupied Bandwidth Plot on Channel 78



Date: 29.JUN.2022 18:34:32

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup






3.6.5 Test Result of Conducted Band Edges

For Ant 1


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 28.JUN.2022 06:42:27

High Band Edge Plot on Channel 78




Date: 28.JUN.2022 06:53:08




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 28.JUN.2022 06:59:07

High Band Edge Plot on Channel 78




Date: 28.JUN.2022 07:07:14




<3Mbps>

Low Band Edge Plot on Channel 00



Date: 28.JUN.2022 07:14:36

High Band Edge Plot on Channel 78




Date: 28.JUN.2022 07:23:10



For Ant 2


<1Mbps>

Low Band Edge Plot on Channel 00



Date: 29.JUN.2022 16:45:06

High Band Edge Plot on Channel 78




Date: 29.JUN.2022 16:54:20




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 29.JUN.2022 17:13:05

High Band Edge Plot on Channel 78




Date: 29.JUN.2022 17:26:35




<3Mbps>

Low Band Edge Plot on Channel 00



Date: 29.JUN.2022 17:33:18

High Band Edge Plot on Channel 78



Date: 29.JUN.2022 18:33:50