

FCC Radio Partial Test Report

FCC ID: 2AYGCLGE-NX9

This report concerns: Original Grant

Project No. : 2203G019
Equipment : Smart Phone
Brand Name : HONOR
Test Model : LGE-NX9
Series Model : N/A
Applicant : Honor Device Co., Ltd.
Address : Shum Yip Sky Park, No. 8089, Hongli West Road, Shenzhen, China
Manufacturer : Honor Device Co., Ltd.
Address : Shum Yip Sky Park, No. 8089, Hongli West Road, Shenzhen, China
Date of Receipt : Feb. 11, 2022
Date of Test : Feb. 13, 2022 ~ Apr. 19, 2022
Issued Date : Apr. 22, 2022
Report Version : R00
Standard(s) : FCC CFR Title 47, Part 15, Subpart E
FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01
ANSI C63.10-2013

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Grani Zhou

Prepared by : Grani Zhou

Steven Lu

Approved by : Steven Lu



TESTING CERT #5123.02

Add: No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792

People's Republic of China.

Tel: +86-769-8318-3000

Web: www.newbtl.com

Declaration

BTL represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

BTL's reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

BTL's laboratory quality assurance procedures are in compliance with the **ISO/IEC 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

BTL is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

Limitation

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

Table of Contents	Page
REPORT ISSUED HISTORY	5
1 . SUMMARY OF TEST RESULTS	6
1.1 TEST FACILITY	7
1.2 MEASUREMENT UNCERTAINTY	7
1.3 TEST ENVIRONMENT CONDITIONS	7
2 . GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 PARAMETERS OF TEST SOFTWARE	12
3 . BANDWIDTH	16
3.1 LIMIT	16
3.2 TEST PROCEDURE	16
3.3 DEVIATION FROM STANDARD	16
3.4 TEST SETUP	16
3.5 EUT OPERATION CONDITIONS	16
3.6 TEST RESULTS	16
4 . MAXIMUM OUTPUT POWER	17
4.1 limit	17
4.2 TEST PROCEDURE	17
4.3 DEVIATION FROM STANDARD	17
4.4 TEST SETUP	17
4.5 EUT OPERATION CONDITIONS	17
4.6 TEST RESULTS	17
5 . Band Edge Measurements & Conducted Spurious Emission	18
5.1 LIMIT	18
5.2 TEST PROCEDURE	19
5.3 DEVIATION FROM STANDARD	19
5.4 TEST SETUP	19
5.5 TEST RESULTS	19
6 . POWER SPECTRAL DENSITY	20
6.1 LIMIT	20
6.2 TEST PROCEDURE	20
6.3 DEVIATION FROM STANDARD	20
6.4 TEST SETUP	21

Table of Contents	Page
6.5 EUT OPERATION CONDITIONS	21
6.6 TEST RESULTS	21
7 . FREQUENCY STABILITY	22
7.1 LIMIT	22
7.2 TEST PROCEDURE	22
7.3 DEVIATION FROM STANDARD	22
7.4 TEST SETUP	22
7.5 EUT OPERATION CONDITIONS	22
7.6 TEST RESULTS	22
8 . MEASUREMENT INSTRUMENTS LIST	23

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-11-2203G019	R00	Original Report.	Apr. 22, 2022	Valid

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

FCC CFR Title 47, Part 15, Subpart E				
Standard(s) Section	Test Item		Judgment	Remark
15.407(a) 15.407(e)	Bandwidth	6 & 26 dB Bandwidth	PASS	-----
		99% Emission Bandwidth		
15.407(a)	Maximum Output Power		Pass	-----
15.407(a)	Power Spectral Density		Pass	-----
15.407(g)	Frequency Stability		Pass	-----
15.407(b) 15.209	Band Edge Measurements		Pass	-----
15.407(b) 15.209	Conducted Spurious Emission		Pass	-----
15.203	Antenna Requirements		PASS	NOTE (2)
15.407(c)	Automatically Discontinue Transmission		PASS	NOTE (3)

Note:

- (1) "N/A" denotes test is not applicable in this test report.
- (2) The device what use a permanently attached antenna were considered sufficient to comply with the provisions of 15.203.
- (3) During no any information transmission, the EUT can automatically discontinue transmission and become standby mode for power saving. the EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.
- (4) For UNII-1 this device was functioned as a
 - Outdoor access point device
 - Indoor access point device
 - Fixed point-to-point access points device
 - Client device

1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

BTL's Registration Number for FCC: 357015
 BTL's Designation Number for FCC: CN1240

1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

The BTL measurement uncertainty as below table:

Test Item	Extended Uncertainty
Transmit Output Power Data	U = 0.56 dB
RF Power Density, Conducted	U = 0.66 dB
Bandwidth	20MHz: U=41.78kHz 40MHz: U=82.12kHz 80MHz: U=163.5kHz
Band Edge Compliance	U = 0.9 dB
Spurious Emissions, Conducted	20MHz~3.6GHz: U=0.92dB 3.6GHz~8.4GHz: U=1.22dB 8.4GHz~13.6GHz: U=1.44dB 8.4GHz~17.1GHz: U=1.58dB 17.1GHz~22GHz: U=1.98dB 22GHz~26.5GHz: U=2.18dB
Frequency Stability	2500MHz: U=41.58Hz 5800MHz: U=82.24Hz
Duty Cycle	U=2.06 %




Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

1.3 TEST ENVIRONMENT CONDITIONS

Test Item	Temperature	Humidity	Test Voltage	Tested By
Bandwidth	15 ~ 35°C	20 ~ 75%	DC 3.87V	Jesse Wang
Maximum Output Power	15 ~ 35°C	20 ~ 75%	DC 3.87V	Jesse Wang
Power Spectral Density	15 ~ 35°C	20 ~ 75%	DC 3.87V	Jesse Wang
Band Edge Measurements	15 ~ 35°C	20 ~ 75%	DC 3.87V	Jesse Wang
Conducted Spurious Emission	15 ~ 35°C	20 ~ 75%	DC 3.87V	Jesse Wang
Frequency Stability	Normal & Extreme	20 ~ 75%	Normal & Extreme	Jesse Wang

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Smart Phone
Brand Name	HONOR
Test Model	LGE-NX9
Series Model	N/A
Model Difference(s)	N/A
Hardware Version	HN1LGEHM
Software Version	6.0.0.108(C900E103R1P3)
Power Source	1# DC voltage supplied from AC adapter. 2# Supplied from battery.
Power Rating	1# I/P: 100-240V~ 50/60Hz 1.6A O/P: 5V  2A or 10V  4A or 20V  5A Max 2# DC 3.87V, Rated Capacity:4500mAh
Operation Frequency Band(s)	UNII-1: 5150 MHz ~ 5250 MHz UNII-2A: 5250 MHz ~ 5350 MHz UNII-2C: 5470 MHz ~ 5725 MHz UNII-3: 5725 MHz ~ 5850 MHz
Modulation Type	IEEE 802.11a/n/ac: OFDM IEEE 802.11ax: OFDMA
Bit Rate of Transmitter	IEEE 802.11a: 54/48/36/24/18/12/9/6 Mbps IEEE 802.11n: up to 300 Mbps IEEE 802.11ac: up to 1733.4 Mbps IEEE 802.11ax: up to 2402 Mbps
Maximum Output Power UNII-1	IEEE 802.11a: 19.96 dBm (99.08 mW)
Maximum Output Power UNII-2A	IEEE 802.11a: 19.72 dBm (93.76 mW)
Maximum Output Power UNII-2C	IEEE 802.11a: 20.31 dBm (107.40 mW)
Maximum Output Power UNII-3	IEEE 802.11a: 20.93 dBm (123.88 mW)
Antenna Smart System	SISO, CDD, MIMO

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20)		IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40)		IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80)	
UNII-1		UNII-1		UNII-1	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20)		IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40)		IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80)	
UNII-2A		UNII-2A		UNII-2A	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
52	5260	54	5270	58	5290
56	5280	62	5310		
60	5300				
64	5320				

IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20)		IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40)		IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80)	
UNII-2C		UNII-2C		UNII-2C	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
100	5500	102	5510	106	5530
104	5520	110	5550	122	5610
108	5540	118	5590		
112	5560	126	5630		
116	5580	134	5670		
120	5600				
124	5620				
128	5640				
132	5660				
136	5680				
140	5700				

IEEE 802.11a IEEE 802.11n(HT20) IEEE 802.11ac(VHT20) IEEE 802.11ax(HE20)		IEEE 802.11n(HT40) IEEE 802.11ac(VHT40) IEEE 802.11ax(HE40)		IEEE 802.11ac(VHT80) IEEE 802.11ax(HE80)	
UNII-3		UNII-3		UNII-3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

IEEE 802.11ac(VHT160) IEEE 802.11ax(HE160)	
Channel	Frequency (MHz)
50	5250
114	5570

IEEE 802.11ax (HE20)					
26 Tone(2M)		52 Tone(4M)		106 Tone(8M)	
Band 1		Band 2		Band 3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	52	5260	100	5500
40	5200	56	5280	104	5520
44	5220	60	5300	108	5540
48	5240	64	5320	112	5560
				116	5580
				120	5600
				124	5620
				128	5640
				132	5660
				136	5680
				140	5700

IEEE 802.11ax (HE40)					
242 Tone(20M)					
Band 1		Band 2		Band 3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
38	5190	54	5270	102	5510
46	5230	62	5310	110	5550
				118	5590
				126	5630
				134	5670

IEEE 802.11ax (HE80)					
484 Tone(40M)					
Band 1		Band 2		Band 3	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	5210	58	5290	106	5530
				122	5610

IEEE 802.11ax (HE160)		
996 Tone(80M)		
Band 1	Band 2	Band 3
Channel	Frequency (MHz)	
50	5250	
114	5570	

3. Antenna Specification:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	Note
Ant 1	N/A	N/A	Integrated	N/A	-2.4	UNII-1
						UNII-2A
						UNII-2C
						UNII-3
Ant 2	N/A	N/A	Integrated	N/A	-2.2	UNII-1
						UNII-2A
						UNII-2C
						UNII-3




Note:

- This EUT supports CDD/MIMO, any transmit signals are correlated with each other, so Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N]$ dBi, that is Directional gain = $10 \log[(10^{-2.4/20} + 10^{-2.2/20})^2 / 2]$ dBi = 0.71.
- The antenna gain is provided by the manufacturer.

4. Table for Antenna Configuration:

Operating Mode	TX Mode	1TX	2TX
		IEEE 802.11a	V (SISO)
IEEE 802.11n(HT20)	V (SISO)	V (MIMO)	
IEEE 802.11n(HT40)	V (SISO)	V (MIMO)	
IEEE 802.11ac(VHT20)	V (SISO)	V (MIMO)	
IEEE 802.11ac(VHT40)	V (SISO)	V (MIMO)	
IEEE 802.11ac(VHT80)	V (SISO)	V (MIMO)	
IEEE 802.11ac(VHT160)	V (SISO)	V (MIMO)	
IEEE 802.11ax(HE20)	V (SISO)	V (MIMO)	
IEEE 802.11ax(HE40)	V (SISO)	V (MIMO)	
IEEE 802.11ax(HE80)	V (SISO)	V (MIMO)	
IEEE 802.11ax(HE160)	V (SISO)	V (MIMO)	

5. The EUT contains following accessory devices

Object / Part No.	Manufacturer / Trademark	Type / Model Name	Technical Data
Adapter	HONOR Device Co., Ltd.	HN-200500E01	I/P: 100-240V ~50/60Hz, 1.6A O/P: 5V  2A or 10V  4A or 20V  5A Max
		HN-200500U01	
		HN-200500B01	
Battery	Shenzhen Sunwoda Intelligence Technology Co., Ltd.	HB586680EFW	Rated capacity: 4500 mAh Nominal Voltage: +3.87V Charging Voltage: +4.45V
	Scud (Fujian) Electronics Co., Ltd.		

2.2 PARAMETERS OF TEST SOFTWARE

UNII-1				
Test Software Version	N/A			
Frequency (MHz)	5180	5200	5220	5240
IEEE 802.11a	15	17	17	17
IEEE 802.11n(HT20)	14.5	17	17	17
IEEE 802.11ac(VHT20)	14.5	17	17	17
IEEE 802.11ax(HE20)	14.5	17	17	17
IEEE 802.11ax(HE20)_106Tone_SISO	14.5	17	17	17
IEEE 802.11ax(HE20)_106Tone_MIMO	14.5	15	15	15
Frequency (MHz)	5190		5230	
IEEE 802.11n(HT40)	14		16	
IEEE 802.11ac(VHT40)	14		16	
IEEE 802.11ax(HE40)	14		16	
IEEE 802.11ax(HE40)_242Tone_MIMO	14		16	
Frequency (MHz)	5180-5700			
IEEE 802.11ax(HE20)_26Tone_SISO	11.5			
IEEE 802.11ax(HE20)_52Tone_SISO	14.5			
IEEE 802.11ax(HE20)_26Tone_MIMO	9			
IEEE 802.11ax(HE20)_52Tone_MIMO	12			
Frequency (MHz)	5210			
IEEE 802.11ac(VHT80)	13.5			
IEEE 802.11ax(HE80)	13.5			
IEEE 802.11ax(HE80)_484Tone_MIMO	13.5			
Frequency (MHz)	5250			
IEEE 802.11ac(VHT160)	12			
IEEE 802.11ax(HE160)	12			
IEEE 802.11ax(HE160)_996Tone_MIMO	12			

UNII-2A			
Test Software Version	N/A		
Frequency (MHz)	5260	5300	5320
IEEE 802.11a	17	17	16.5
IEEE 802.11n(HT20)	17	17	14.5
IEEE 802.11ac(VHT20)	17	17	14.5
IEEE 802.11ax(HE20)	17	17	14.5
IEEE 802.11ax(HE20)_106Tone_SISO	17	17	14.5
IEEE 802.11ax(HE20)_106Tone_MIMO	15	15	14.5
Frequency (MHz)	5270		5310
IEEE 802.11n(HT40)	16		13
IEEE 802.11ac(VHT40)	16		13
IEEE 802.11ax(HE40)	17		17
IEEE 802.11ax(HE40)_242Tone_SISO	16		13
IEEE 802.11ax(HE40)_242Tone_MIMO	16		13
Frequency (MHz)	5180-5700		
IEEE 802.11ax(HE20)_26Tone_SISO	11.5		
IEEE 802.11ax(HE20)_52Tone_SISO	14.5		
IEEE 802.11ax(HE20)_26Tone_MIMO	9		
IEEE 802.11ax(HE20)_52Tone_MIMO	12		
Frequency (MHz)	5290		
IEEE 802.11ac(VHT80)	12.5		
IEEE 802.11ax(HE80)	12.5		
IEEE 802.11ax(HE80)_484Tone_SISO	12.5		
IEEE 802.11ax(HE80)_484Tone_MIMO	12.5		
Frequency (MHz)	5250		
IEEE 802.11ac(VHT160)	12		
IEEE 802.11ax(HE160)	12		
IEEE 802.11ax(HE160)_996Tone_SISO	12		
IEEE 802.11ax(HE160)_996Tone_MIMO	12		

UNII-2C							
Test Software Version	N/A						
Frequency (MHz)	5500	5520	5580	5680	5700	5720	5720 UNII-2C
IEEE 802.11a	16	17	17	17	14.5	18	18
IEEE 802.11n(HT20)	14.5	17	17	17	14	15.5	15.5
IEEE 802.11ac(VHT20)	14.5	17	17	17	14	17	17
Frequency (MHz)	5500	5520	5580	5680	5700	5720 UNII-2C	
IEEE 802.11ax(HE20)	14.5	17	17	17	14	17	
IEEE 802.11ax(HE20) _106Tone_SISO	14.5	17	17	17	14	17	
IEEE 802.11ax(HE20) _106Tone_MIMO	14.5	15	15	15	14	17	
Frequency (MHz)	5510	5550	5630	5670	5710	5710 UNII-2C	
IEEE 802.11n(HT40)	13.5	16	16	16	15.5	15.5	
IEEE 802.11ac(VHT40)	13.5	16	16	16	15.5	15.5	
Frequency (MHz)	5510	5550	5630	5670	5710 UNII-2C		
IEEE 802.11ax(HE40)	13.5	16	16	16	15.5		
IEEE 802.11ax(HE40) _242Tone_SISO	13.5	16	16	16	15.5		
IEEE 802.11ax(HE40) _242Tone_MIMO	13.5	16	16	16	15.5		
Frequency (MHz)	5530		5610		5690_UNII-2C		
IEEE 802.11ac(VHT80)	13		16		16		
IEEE 802.11ax(HE80)	13		16		16		
IEEE 802.11ax(HE80) _484Tone_SISO	13		16		17		
IEEE 802.11ax(HE80) _484Tone_MIMO	13		16		17		
Frequency (MHz)	5180-5700			5720			
IEEE 802.11ax(HE20) _26Tone_SISO	11.5			11.5			
IEEE 802.11ax(HE20) _52Tone_MIMO	14.5			14.5			
IEEE 802.11ax(HE20) _26Tone_SISO	9			9			
IEEE 802.11ax(HE20) _52Tone_MIMO	12			12			
Frequency (MHz)	5570						
IEEE 802.11ac(VHT160)	13.5						
IEEE 802.11ax(HE160)	13.5						
IEEE 802.11ax(HE160)- _996Tone_SISO	13.5						
IEEE 802.11ax(HE160)- _996Tone_MIMO	13.5						

UNII-3				
Test Software Version	N/A			
Frequency (MHz)	5720_UNII-3	5745	5785	5825
IEEE 802.11a	18	18	18	18
IEEE 802.11n(HT20)	15.5	17.5	17.5	17.5
IEEE 802.11ac(VHT20)	17	17	17	17
IEEE 802.11ax(HE20)	17	17	17	17
IEEE 802.11ax(HE20) _106Tone_SISO	17	17	17	17
IEEE 802.11ax(HE20) _106Tone_MIMO	17	17	17	17
Frequency (MHz)	5710_UNII-3	5755	5795	
IEEE 802.11n(HT40)	15.5	17.5	17.5	
IEEE 802.11ac(VHT40)	15.5	17	17	
IEEE 802.11ax(HE40)	15.5	17	17	
IEEE 802.11ax(HE40) _242Tone_SISO	15.5	17	17	
IEEE 802.11ax(HE40) _242Tone_MIMO	15.5	17	17	
Frequency (MHz)	5690_UNII-3		5775	
IEEE 802.11ax(HE80) _484Tone_SISO	17		17	
IEEE 802.11ax(HE80) _484Tone_MIMO	17		17	
IEEE 802.11ac(VHT80)	16		17	
IEEE 802.11ax(HE80)	16		17	
Frequency (MHz)	5725-5825			
IEEE 802.11ax(HE20) _26Tone_SISO	17			
IEEE 802.11ax(HE20) _52Tone_SISO	17			
IEEE 802.11ax(HE20) _26Tone_MIMO	17			
IEEE 802.11ax(HE20) _52Tone_MIMO	17			

3. BANDWIDTH

3.1 LIMIT

Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.407(a) FCC 15.407(e)	26 dB Bandwidth	-	5150-5250
	26 dB Bandwidth	-	5250-5350
	26 dB Bandwidth	-	5470-5725
	6 dB Bandwidth	Minimum 500 kHz	5725-5850

3.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below
- b. Spectrum Setting:
For UNII-1, UNII-2A, UNII-2C:

Spectrum Parameter	Setting
Span Frequency	> 26 dB Bandwidth
RBW	Appromiximately 1% of the emission bandwidth
VBW	> RBW
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

For UNII-3:

Spectrum Parameter	Setting
Span Frequency	> 6 dB Bandwidth
RBW	100 kHz
VBW	300 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

- c. Measured the spectrum width with power higher than 26 dB / 6 dB below carrier.

3.3 DEVIATION FROM STANDARD

No deviation.

3.4 TEST SETUP



3.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

3.6 TEST RESULTS

Please refer to the APPENDIX.

4. MAXIMUM OUTPUT POWER

4.1 limit

Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.407(a)	Maximum Output Power	AP device: 1 Watt (30 dBm) Client device: 250 mW (23.98 dBm)	5150-5250
		250 mW (23.98 dBm)	5250-5350
		250 mW (23.98 dBm)	5470-5725
		1 Watt (30dBm)	5725-5850

Note:

- a. For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
- b. For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or 11 dBm + 10log B, where B is the 26dB Bandwidth in megahertz.


4.2 TEST PROCEDURE

- a. The EUT was directly connected to the power meter and antenna output port as show in the block diagram below.
- b. Test test was performed in accordance with method of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



4.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

4.6 TEST RESULTS

Please refer to the APPENDIX.

5. Band Edge Measurements & Conducted Spurious Emission

5.1 LIMIT

Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.407(b) FCC 15.209	Band Edge Measurements & Conducted Spurious Emission	F<1GHz: §15.209/§ RSS-gen, §8.9 limit (QP). F≥1GHz & out-restricted: <-27dBm/MHz PK e.i.r.p. (exl. 5.15-5.35GHz).	5150-5250
		F<1GHz: §15.209 /RSS-gen, §8.9 limit (QP). F≥1GHz & out-restricted: <-27dBm/MHz PK e.i.r.p. (exl. 5.25-5.35GHz).	5250-5350
		F<1GHz: §15.209/ RSS-gen, §8.9 limit (QP). F≥1GHz & out-restricted: <-27dBm/MHz PK e.i.r.p. (exl. 5.47-5.725GHz).	5470-5725
		F<1GHz: §15.209/ RSS-gen, §8.9 limit (QP) F≥1GHz &out-restricted:(QP) a) 27 dBm/MHz at frequencies from the band edges decreasing linearly to 15.6 dBm/MHz at 5 MHz above or below the band edges; b) 15.6 dBm/MHz at 5 MHz above or below the band edges decreasing linearly to 10 dBm/MHz at 25 MHz above or below the band edges; c) 10 dBm/MHz at 25 MHz above or below the band edges decreasing linearly to -27 dBm/MHz at 75 MHz above or below the band edges; and d) -27 dBm/MHz at frequencies more than 75 MHz above or below the band edges.	5725-5850

5.2 TEST PROCEDURE

The following table is the setting of the receiver:

Spectrum Parameters	Setting
Start ~ Stop Frequency	30 MHz~1000 MHz for RBW 100 kHz


Spectrum Parameters	Setting
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic or 40 GHz, whichever is lower
RBW / VBW (Emission in restricted band)	1 MHz / 3 MHz for PK value 1 MHz / 1/T Hz for AVG value

Receiver Parameters	Setting
Start ~ Stop Frequency	30 MHz~1000 MHz for QP detector
Start ~ Stop Frequency	1 GHz~40 GHz for PK/AVG detector

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 TEST RESULTS

Please refer to the APPENDIX.

6. POWER SPECTRAL DENSITY

6.1 LIMIT

Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.407(a)	Power Spectral Density	AP device: 17 dBm/MHz Client device: 11 dBm/MHz	5150-5250
		11 dBm/MHz	5250-5350
		11 dBm/MHz	5470-5725
		30 dBm/500 kHz	5725-5850

6.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting:

For UNII-1, UNII-2A, UNII-2C:

Spectrum Parameter	Setting
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	1 MHz.
VBW	3 MHz.
Detector	RMS
Trace average	100 trace
Sweep Time	Auto

For UNII-3:

Spectrum Parameter	Setting
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RBW	100 kHz.
VBW	300 kHz.
Detector	RMS
Trace average	100 trace
Sweep Time	Auto

Note:

- For UNII-3, according to KDB publication 789033 D02 General UNII Test Procedures New Rules v02r01, section II.F.5., it is acceptable to set RBW at 100kHz and VBW at 300kHz if the spectrum analyzer does not have 500 kHz RBW. Then, add $10 \log (500 \text{ kHz}/100 \text{ kHz})$ to the measured result, i.e. 7 dB.
- During the test of U-NII 3 PSD, the measurement result with RBW=100kHz has been added 7 dB by compensating offset. For example, the cable loss is 13 dB, and the final offset is $13 + 7 = 20$ dB when RBW=100kHz is used.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP**6.5 EUT OPERATION CONDITIONS**

The EUT was programmed to be in continuously transmitting mode.

6.6 TEST RESULTS

Please refer to the APPENDIX.

7. FREQUENCY STABILITY

7.1 LIMIT

Section	Test Item	Limit	Frequency Range (MHz)
FCC 15.407(g)	Frequency Stability	An emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.	5150-5250
			5250-5350
			5470-5725
			5725-5850

7.2 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting:


Spectrum Parameter	Setting
Span Frequency	Entire absence of modulation emissions bandwidth
RBW	10 kHz
VBW	10 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

- c. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value.
- d. User manual temperature is -20°C~75°C.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

7.6 TEST RESULTS

Please refer to the APPENDIX.

8. MEASUREMENT INSTRUMENTS LIST

Conducted Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Power Meter	R&S	NRX	102795	Sep. 26, 2022
2	Power Sensor	R&S	NRP6A	103126	May 14, 2022
3	Power Sensor	R&S	NRP6A	103127	May 14, 2022
4	Spectrum Analyzer	R&S	FSW43	101625	May 13, 2022
5	Temperature Chamber	WEISS	WKL64/40	56246014990010	May 24, 2022
6	Universal Radio Communication Tester	R&S	CMW500	164699	May 13, 2022
7	Universal Radio Communication Tester	R&S	CMW500	164543	May 13, 2022
8	Vector Signal Generator	R&S	SMW200A	107864	May 13, 2022

Remark: "N/A" denotes no model name, serial no. or calibration specified.

All calibration period of equipment list is one year.

End of Test Report