



**MPE ESTIMATION  
FCC ID: 2AYGI-C6S**

**1, Limit for General Population/ Uncontrolled Exposures**

Frequency	Power density (mW/ cm <sup>2</sup> )	Averaging time(minutes)
300MHz----1.5GHz	F/1500	30
1.5GHz---100GHz	1.0	30

**2, Estimation Result**

**For 2.4G WIFI:**

Mode	Max PK Output power(dBm)	Tune Up Power(dBm)	Max Tune Up power(mW)	Antenna Gain(dBi)	Antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )
WIFI	21.25	21±1(22)	158.49	5	3.16228	0.09976
$Pd = \frac{Pout * G}{4\pi r^2}$ ;						
Note:						
Note: The estimation distance is 20cm The device could not transmit simultaneously in 2.4G.						
Note: PK Output power= conducted power. Conducted power see the test report HK2012103871-E. Gantenna gain=5dBi						

when the minimum test separation distance is >20 cm, a distance of 20 cm is applied to determine RF Exposure test exclusion. The test exclusion threshold is 0.09976mW/cm<sup>2</sup> which is < 1.0mW/cm<sup>2</sup>, RF Exposure testing is not required.

Note: the device could not transmit simultaneously in 2.4G.

-----The End-----