



# FCC - TEST REPORT

Report Number : **709502307650-00B** Date of Issue: December 4, 2023

Model : RH50R

Product Type : RICO 2 THERMAL IMAGING SCOPE

Applicant : IRay Technology Co., Ltd.

Address : 11 Guiyang Street, YEDA, Yantai 264006, P.R. China

Manufacturer : IRay Technology Co., Ltd.

Address : 11 Guiyang Street, YEDA, Yantai 264006, P.R. China

Test Result :  **Positive**       **Negative**

Total pages including Appendices : 67

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.*



# 1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards .....	5
5	Summary of Test Results.....	6
6	General Remarks.....	7
7	Test Setups .....	8
8	Systems test configuration .....	11
9	Technical Requirement.....	12
9.1	Conducted Emission .....	12
9.2	Conducted peak(average) output power .....	17
9.3	6dB bandwidth .....	30
9.4	Power spectral density .....	34
9.5	Spurious RF conducted emissions.....	38
9.6	Band edge.....	48
9.7	Spurious radiated emissions for transmitter .....	55
10	Test Equipment List.....	64
11	System Measurement Uncertainty .....	65
12	Photographs of Test Set-ups .....	66
13	Photographs of EUT .....	67



## 2 Details about the Test Laboratory

### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch  
No.16 Lane, 1951 Du Hui Road,  
Shanghai 201108,  
P.R. China

Test Firm FCC  
Registration  
Number: 820234

Designation  
number: CN1183

IC Company  
Number: 31668

CAB identifier: CN0101

Telephone: +86 21 6141 0123  
Fax: +86 21 6140 8600

### 3 Description of the Equipment under Test

#### Description of the Equipment Under Test

Product: RICO 2 THERMAL IMAGING SCOPE

Model no.: RH50R

FCC ID: 2AYGT-4C-00

Rating: 3-4.2V DC (rechargeable lithium-ion battery)  
USB 5V input (type C)

RF Transmission Frequency: For 802.11b/g/n-HT20: 2412~2462 MHz

No. of Operated Channel: 2.4GHz WIFI: 11 for 802.11b/802.11g/802.11(H20)

Modulation: For 2.4GHz WIFI:  
Direct Sequence Spread Spectrum (DSSS) for 802.11b  
Orthogonal Frequency Division Multiplexing (OFDM) for 802.11g/n

Channel list:

802.11b/g/n(HT20)			
Ch	Fre(MHz)	Ch	Fre(MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437		

Antenna Type: FPC antenna

Antenna Gain: 3.5dBi

Description of the EUT: The Equipment Under Test (EUT) is a RICO 2 THERMAL IMAGING SCOPE which support 2.4GHz Wi-Fi. We tested it and listed the worst data in this report.

Test sample no.:

SHA-762139-2 (RF radiated); SHA-762139-3 (RF conducted)

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment or any information supplied.



## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 Measurement Guidance and ANSI C63.10-2020.

## 5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition		Pages	Test Site	Test Result		
				Pass	Fail	N/A
§15.207	Conducted emission AC power port	13-16	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247 (b) (1)	Conducted peak output power	17-29	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1)	20dB bandwidth	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)	Carrier frequency separation	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii)	Number of hopping frequencies	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii)	Dwell Time	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(2)	6dB bandwidth	30-33	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(e)	Power spectral density	34-37	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Spurious RF conducted emissions	38-47	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d)	Band edge	48-54	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & §15.209	Spurious radiated emissions for transmitter	55-63	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.203	Antenna requirement	See note 1		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses FPC antenna, which gain is 3.5dBi. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.



## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: 2AYGT-4C-00, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

### SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: October 19, 2023

Testing Start Date: October 19, 2023

Testing End Date: November 23, 2023

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:




Hui TONG  
Review Engineer

Jiayi XU  
Project Engineer

Cheng Huali  
Test Engineer


## 7 Test Setups

### 7.1 AC Power Line Conducted Emission test setups




### 7.2 Radiated test setups

#### 9kHz ~ 30MHz Test Setup:







30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



18GHz ~ 25GHz Test Setup:



7.3 Conducted RF test setups



## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenovo	E470	PF-OU5TS7 17/09
AC/DC adapter	SHENZHEN KEYU POWER	KA12C-0502000US	N/A

Test software: adb commend

Test Mode Applicability and Tested Channel Detail:

Mode	Tested Channel	Data Rate (Mbps)	Modulation	(Power level setting
802.11b	1	1	CCK	13
	6	1	CCK	13
	11	1	CCK	13
802.11g	1	6	OFDM	13
	6	6	OFDM	13
	11	6	OFDM	13
802.11n HT20	1	MCS0	OFDM	13
	6	MCS0	OFDM	13
	11	MCS0	OFDM	13

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

## 9 Technical Requirement

### 9.1 Conducted Emission

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

#### Limit

According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency

**Conducted Emission**

# 150k-30MHz Conducted Emission Test


## EUT Information

EUT Name:	RICO 2 THERMAL IMAGING SCOPE
Model:	RH50R
Client:	IRay Technology Co., Ltd
Op Cond:	Transmitting,802.11g_TX_2462MHz, AC 120V/60Hz, T20.2, H42.1%, P102.3kPa
Operator:	Cheng Huali
Standard:	FCC Part 15.207(a)
Comment:	Phase L
Sample No.:	SHA-762139-2

## Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup:	Voltage with 2-Line-LISN
Receiver:	[ESR 3]
Level Unit:	dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB



## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.186000	47.63	---	64.21	16.58	1000.0	9.000	L1	19.4
0.303000	---	33.05	50.16	17.11	1000.0	9.000	L1	19.5
0.366000	41.36	---	58.59	17.23	1000.0	9.000	L1	19.5
0.424500	---	34.31	47.36	13.05	1000.0	9.000	L1	19.5
0.888000	38.97	---	56.00	17.03	1000.0	9.000	L1	19.5
0.969000	---	32.28	46.00	13.72	1000.0	9.000	L1	19.5
2.157000	---	26.09	46.00	19.91	1000.0	9.000	L1	19.5
2.188500	32.72	---	56.00	23.28	1000.0	9.000	L1	19.5
5.266500	25.50	---	60.00	34.50	1000.0	9.000	L1	19.6
5.433000	---	19.17	50.00	30.83	1000.0	9.000	L1	19.6
22.290000	25.80	---	60.00	34.20	1000.0	9.000	L1	20.7
25.066500	---	18.68	50.00	31.32	1000.0	9.000	L1	20.9

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)  
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator

# 150k-30MHz Conducted Emission Test


## EUT Information

EUT Name: RICO 2 THERMAL IMAGING SCOPE  
 Model: RH50R  
 Client: IRay Technology Co., Ltd  
 Op Cond: Transmitting,802.11g\_TX\_2462MHz, AC 120V/60Hz, T20.2, H42.1%,  
 Operator: Cheng Huali  
 Standard: FCC Part 15.207(a)  
 Comment: Phase N  
 Sample No.: SHA-762139-2

## Scan Setup: Voltage with 2-Line-LISN pre [EMI conducted]

Hardware Setup: Voltage with 2-Line-LISN  
 Receiver: [ESR 3]  
 Level Unit: dBuV

Subrange	Step Size	Detectors	IF BW	Meas. Time	Preamp
9 kHz - 150 kHz	100 Hz	PK+	200 Hz	0.02 s	0 dB
150 kHz - 30 MHz	4.5 kHz	PK+; AVG	9 kHz	0.01 s	0 dB



## Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.357000	41.88	---	58.80	16.92	1000.0	9.000	N	19.5
0.361500	---	31.52	48.69	17.17	1000.0	9.000	N	19.5
0.483000	---	34.02	46.29	12.27	1000.0	9.000	N	19.5
0.487500	43.28	---	56.21	12.93	1000.0	9.000	N	19.5
0.973500	---	30.57	46.00	15.43	1000.0	9.000	N	19.5
0.978000	40.58	---	56.00	15.42	1000.0	9.000	N	19.5
2.148000	---	27.22	46.00	18.78	1000.0	9.000	N	19.5
2.157000	35.94	---	56.00	20.06	1000.0	9.000	N	19.5
6.391500	---	21.32	50.00	28.68	1000.0	9.000	N	19.6
6.418500	29.72	---	60.00	30.28	1000.0	9.000	N	19.6
22.524000	---	23.15	50.00	26.85	1000.0	9.000	N	20.5
23.847000	31.60	---	60.00	28.40	1000.0	9.000	N	20.5

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator



## 9.2 Conducted peak(average) output power

### Test Method

1. Measure the duty cycle D of the transmitter output signal.
2. Set span to at least 1.5 times the OBW.
3. Set RBW = 1% to 5% of the OBW, not to exceed 1 MHz.
4. Set VBW  $\geq [3 \times \text{RBW}]$ .
5. Number of points in sweep  $\geq [2 \times \text{span} / \text{RBW}]$ . (This gives bin-to-bin spacing  $\leq \text{RBW} / 2$ , so that narrowband signals are not lost between frequency bins.)
6. Sweep time = auto.
7. Detector = RMS (i.e., power averaging), if available. Otherwise, use the sample detector mode.
8. Do not use sweep triggering. Allow the sweep to "free run."
9. Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
10. Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function with band limits set equal to the OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.
11. Add  $[10 \log (1 / D)]$ , where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission).

### Limits

According to §15.247 (b) (1) conducted peak (average) output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	$\leq 1$	$\leq 30$



Test result as below table

802.11b

Frequency (MHz)	Duty cycle Factor (dB)	Conducted Power (dBm)	Total Power(average) (dBm)	Result
Low channel 2412MHz	0	11.98	11.98	Pass
Middle channel 2437MHz	0	12.22	12.22	Pass
High channel 2462MHz	0	12.54	12.54	Pass

802.11g



Frequency (MHz)	Duty cycle Factor (dB)	Conducted Power (dBm)	Total Power(average) (dBm)	Result
Low channel 2412MHz	1.94	10.72	12.66	Pass
Middle channel 2437MHz	1.95	10.89	12.84	Pass
High channel 2462MHz	1.95	11.23	13.18	Pass



802.11n(HT20)



Frequency (MHz)	Duty cycle Factor (dB)	Conducted Power (dBm)	Total Power(average) (dBm)	Result
Low channel 2412MHz	2.07	10.53	12.60	Pass
Middle channel 2437MHz	2.01	10.81	12.82	Pass
High channel 2462MHz	2.01	11.14	13.15	Pass



## Duty Cycle

Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)
NVNT	b	2412	Ant1	98.9	0
NVNT	b	2437	Ant1	98.87	0
NVNT	b	2462	Ant1	98.9	0
NVNT	g	2412	Ant1	64.03	1.94
NVNT	g	2437	Ant1	63.77	1.95
NVNT	g	2462	Ant1	63.77	1.95
NVNT	n20	2412	Ant1	62.12	2.07
NVNT	n20	2437	Ant1	62.88	2.01
NVNT	n20	2462	Ant1	62.88	2.01























# Conducted power













### 9.3 6dB bandwidth

#### Test Method

1. The RF output of EUT was connected to the spectrum analyzer. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting, the instrument center frequency is set to the nominal EUT channel center frequency enable the EUT transmit continuously.
3. Use the following spectrum analyzer settings:  
RBW=100KHz, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
4. Use the automatic bandwidth measurement capability of an instrument, use the X dB bandwidth mode with X set to 6 dB.
5. Allow the trace to stabilize, record the 6 dB Bandwidth value.

#### Limit

Limit [kHz]

≥500

#### Test result

Test Mode	Frequency MHz	6dB bandwidth (MHz)		Result
		result	limit	verdict
802.11b	2412	8.056	≥0.5	Pass
	2437	9.053	≥0.5	Pass
	2462	8.533	≥0.5	Pass
802.11g	2412	16.337	≥0.5	Pass
	2437	16.345	≥0.5	Pass
	2462	16.231	≥0.5	Pass
802.11n(HT20)	2412	17.531	≥0.5	Pass
	2437	17.588	≥0.5	Pass
	2462	17.688	≥0.5	Pass