



# RF EXPOSURE REPORT

**Report No.:** 20230917G12781X-W4

**Product Name:** Smart Thermostat

**Model No.:** WT201-915M, NN201-915M, WT201-9M, NN201-9M, WT201, NN201

**FCC ID:** 2AYHY-WT201

**Applicant:** Xiamen Milesight IoT Co., Ltd.

**Address:** Building C09, Software Park Phase III, Xiamen 361024, Fujian, China

**Dates of Testing:** 09/26/2023 - 10/09/2023

**Issued by:** CCIC Southern Testing Co., Ltd.

**Lab Location:** Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China.

**Tel:** 86 755 26627338    **Fax:** 86 755 26627238

This test report consists of 8 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



### Test Report

**Product**.....: Smart Thermostat  
**Brand Name**.....: Milesight  
**Trade Name** .....: Milesight  
**Applicant**.....: Xiamen Milesight IoT Co., Ltd.  
**Applicant Address**.....: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China  
**Manufacturer**.....: Xiamen Milesight IoT Co., Ltd.  
**Manufacturer Address**.....: Building C09, Software Park Phase III, Xiamen 361024, Fujian, China  
**Test Standards**.....: 47 CFR Part 2.1091  
**Test Result**.....: Pass

**Tested by** .....: Chuiwang Zhang 2023.10.10  
 Chuiwang Zhang, Test Engineer

**Reviewed by**.....: Chris You 2023.10.10  
 Chris You, Senior Engineer

**Approved by**.....: Yang Fan 2023.10.10  
 Yang Fan, Manager



## Table of Contents

<b>1. GENERAL INFORMATION.....</b>	<b>5</b>
1.1. EUT Description.....	5
1.2. EUT Description.....	6
1.3. Laboratory Facilities.....	6
1.4. Laboratory Location.....	6
<b>2. TECHNICAL REQUIREMENTS SPECIFICATION IN CFR TITLE 47 PART 2.1091 .....</b>	<b>7</b>
2.1. Evaluation method.....	7
2.2. Predication of MPE limit at a given distance.....	7
2.3. Evaluation Results.....	8
2.4. Conclusion.....	8



Change History		
Issue	Date	Reason for change
1.0	2023.10.10	First edition

## 1. GENERAL INFORMATION

### 1.1. EUT Description

Product Name	Smart Thermostat
Device Type	Fixed devices
Frequency Range	LoRaWAN: 902MHz~928MHz
Modulation Type	LoRa
Antenna Type	PCB Antenna
Antenna Gain	1.49dBi

Note 1: The information of antenna gain and cable loss is provided by the manufacturer and our lab is not responsible for the accuracy of the antenna gain and cable loss information.

Note 2: Model No.: WT201-915M(Main model), NN201-915M, WT201-9M, NN201-9M, WT201, NN201 with the same electromagnetic emissions and electromagnetic compatibility characteristics.

Their differences are as follows:

The models have same software.

All the above models share one PCB board.

These models differ only by model.



## 1.2. EUT Description

EUT has been tested according to the following standards.

No.	Identity	Document Title
1	47 CFR Part 1	Practice and Procedure
2	47 CFR Part 2	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
3	KDB 447498 D01 General RF Exposure Guidance v06	RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices
4	OET Bulletin 65 Edition 97-01	Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields

## 1.3. Laboratory Facilities

### FCC-Registration No.: 406086

CCIC Southern Testing Co., Ltd EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Designation Number: CN1283, valid time is until Oct. 30th, 2023.

### ISED Registration: 11185A

CCIC Southern Testing Co., Ltd. EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 11185A on Aug. 04, 2016, valid time is until Oct. 30th, 2023.

### CAB number: CN0064

### A2LA Code: 5721.01

CCIC-SET is a third party testing organization accredited by A2LA according to ISO/IEC 17025. The accreditation certificate number is 5721.01.

## 1.4. Laboratory Location

Company Name:	CCIC Southern Testing Co., Ltd.
Address:	Electronic Testing Building, No. 43 Shahe Road, Xili Street, Nanshan District, Shenzhen, Guangdong, China

## 2. Technical Requirements Specification in CFR Title 47 Part 2.1091

### 2.1. Evaluation method

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

**Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)**

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	< 6
3.0-30	1824/f	4.89/f	*(900/f <sup>2</sup> )	< 6
30-300	61.4	0.163	1.0	< 6
300-1500	/	/	f/300	< 6
1500-100,000	/	/	5	< 6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	< 30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	< 30
30-300	27.5	0.073	0.2	< 30
300-1500	/	/	f/1500	< 30
1500-100,000	/	/	1.0	< 30
Note: f = frequency in MHz. * = Plane-wave equivalent power density.				

### 2.2. Predication of MPE limit at a given distance

Refer to formulas on page 19 of OET Bulletin 65, Edition 97-01.

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = numeric gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the centre of radiation of the antenna (appropriate units, e.g., cm)



## 2.3. Evaluation Results

### Worst-Case mode Conducted Output Power Results for LoRa

Operation Mode	Frequency (MHz)	Maximum Output power (dBm)	Max Tune up power (dBm)	Max Tune up power (mW)
LoRa-DTS	903.0	11.215	12 ± 1	19.95
LoRa-DSS	902.3	11.281	12 ± 1	19.95

### Calculation results: Worst-Case mode

Operation Mode	Antenna Gain (dBi)	Antenna Gain (numeric)	Distance (cm)	Result (mW/cm <sup>2</sup> )	Power Density (mW/cm <sup>2</sup> )
LoRa-DTS	1.49	2.84	20	0.006	0.60
LoRa-DSS	1.49	2.84	20	0.006	0.60

## 2.4. Conclusion

According to the KDB 447498 D01 General RF Exposure Guidance v06 section 7.2 determine the device is exclusion from SAR test.

**\*\* END OF REPORT \*\***