

**FCC ID: 2AYJD-DZ2101**

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHZ})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

2.4GWIFI:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
802.11b	2.412	7.222	5.27	8±1	9.00	7.94	<5	2.46728	3.00	YES
	2.437	7.681	5.86	8±1	9.00	7.94	<5	2.48003	3.00	YES
	2.462	7.33	5.41	8±1	9.00	7.94	<5	2.49272	3.00	YES
802.11g	2.412	6.427	4.39	7±1	8.00	6.31	<5	1.95983	3.00	YES
	2.437	6.527	4.49	7±1	8.00	6.31	<5	1.96996	3.00	YES
	2.462	6.595	4.57	7±1	8.00	6.31	<5	1.98004	3.00	YES
802.11n(HT20)	2.412	6.441	4.41	7±1	8.00	6.31	<5	1.95983	3.00	YES
	2.437	6.561	4.53	7±1	8.00	6.31	<5	1.96996	3.00	YES
	2.462	6.498	4.46	7±1	8.00	6.31	<5	1.98004	3.00	YES
802.11n(HT40)	2.422	5.514	3.56	6±1	7.00	5.01	<5	1.55997	3.00	YES
	2.437	5.41	3.48	6±1	7.00	5.01	<5	1.56480	3.00	YES
	2.452	5.237	3.34	6±1	7.00	5.01	<5	1.56960	3.00	YES

**Conclusion:**

For the max result :  $2.49272 \leq$  FCC Limit 3.0 for 1g SAR.