

FCC Test Report

Report No.: AGC11143221003FE02

FCC ID	:	2AYLN-N104			
APPLICATION PURPOSE	:	Original Equipment			
PRODUCT DESIGNATION	:	NewCube Mini PC			
BRAND NAME	:	JWIPC			
MODEL NAME	:	N104, N1040, N********(*=A-Z, 0-9, character or blank)			
APPLICANT	:	JWIPC TECHNOLOGY CO., LTD.			
DATE OF ISSUE	:	Nov. 11, 2022			
STANDARD(S)	:	FCC Part 15.247			
REPORT VERSION	:	V1.0			
Attestation of Global Compliance (Shenzhen) Co., Ltd					





REPORT REVISE RECORD

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Nov. 11, 2022	Valid	Initial Release



TABLE OF CONTENTS

1. VERIFICATION OF COMPLIANCE	5
2. GENERAL INFORMATION	6
2.1. PRODUCT DESCRIPTION	6
2.2. TABLE OF CARRIER FREQUENCYS	6
2.3. RELATED SUBMITTAL(S)/GRANT(S)	7
2.4. TEST METHODOLOGY	7
2.5. SPECIAL ACCESSORIES	7
2.6. EQUIPMENT MODIFICATIONS	7
2.7. ANTENNA REQUIREMENT	7
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	
5.1. CONFIGURATION OF TESTED SYSTEM	
5.2. EQUIPMENT USED IN TESTED SYSTEM	
5.3. SUMMARY OF TEST RESULTS	
6. TEST FACILITY	
7. PEAK OUTPUT POWER	
7.1. MEASUREMENT PROCEDURE	
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
7.3. LIMITS AND MEASUREMENT RESULT	
8. BANDWIDTH	
8.1. MEASUREMENT PROCEDURE	
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
8.3. LIMITS AND MEASUREMENT RESULTS	
9. CONDUCTED SPURIOUS EMISSION	24
9.1. MEASUREMENT PROCEDURE	
9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	
9.3. MEASUREMENT EQUIPMENT USED	
9.4. LIMITS AND MEASUREMENT RESULT	24
10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY	
10.1. MEASUREMENT PROCEDURE	
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)	



10.3. MEASUREMENT EQUIPMENT USED	37
10.4. LIMITS AND MEASUREMENT RESULT	37
11. RADIATED EMISSION	39
11.1. MEASUREMENT PROCEDURE	41
11.2. TEST SETUP	42
11.3. LIMITS AND MEASUREMENT RESULT	43
11.4. TEST RESULT	43
12. LINE CONDUCTED EMISSION TEST	62
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	62
12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST	62
12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST	63
12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST	63
12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST	63
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	68
APPENDIX B: PHOTOGRAPHS OF EUT	68



1. VERIFICATION OF COMPLIANCE

Applicant	JWIPC TECHNOLOGY CO., LTD.	
Address	13/F, Building B, Haisong Edifice, Tairan 9th Road, Futian District, Shenzhen, China	
Manufacturer	JWIPC TECHNOLOGY CO., LTD.	
Address	13/F, Building B, Haisong Edifice, Tairan 9th Road, Futian District, Shenzhen, China	
Factory	DONGGUAN SCD TECHNOLOGY CO., LTD.	
Address	No.1 Longcheng 2nd Street, Qingxi Town, Dongguan City, Guangdong Province, China	
Product Designation	NewCube Mini PC	
Brand Name	JWIPC	
Test Model	N104	
Series Model	N1040, N********(*=A-Z, 0-9, character or blank)	
Declaration of Difference	Different CPU models, memory hard disk capacity is different	
Date of receipt of test item	Oct. 08, 2022	
Date of Test	Oct. 08, 2022~Nov. 11, 2022	
Deviation	No any deviation from the test method	
Condition of Test Sample	Normal	
Test Result	Pass	
Report Template	AGCRT-US-BLE/RF	

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC part 15.247.

Bibo zhang Prepared By **Bibo Zhang** Nov. 11, 2022 (Project Engineer) alin Lin ^u sr) Reviewed By Calvin Liu Nov. 11, 2022 (Reviewer) Max Zhan Approved By Max Zhang Nov. 11, 2022 Authorized Officer

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

 Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com

 Web: http://www.agccert.com/



2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

The EUT is designed as a "NewCube Mini PC". It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	1Mbps:4.526dBm (Max) 2Mbps:4.548dBm (Max)
Bluetooth Version	V5.1
Modulation	BR □GFSK, EDR □π /4-DQPSK, □8DPSK BLE ⊠GFSK 1Mbps ⊠GFSK 2Mbps
Number of channels	40 Channel
Antenna Designation	PIFA Antenna (Comply with requirements of the FCC part 15.203)
Antenna Gain	2.20dBi
Hardware Version	IADPNS02-00
Software Version	Windows 11
Power Supply	DC 19V

Note: Three adapters (DA-90J19, NB-65B19, SOY-1900342-327) and four CPU (I5-1235U, I3-1215U, I5-1240P, I7-1255U) were tested. The test records reported below are the worst results compared with other modes (DA-90J19 and I7-1255U).

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
	0	2402 MHz
2400~2483.5MHz	1	2404 MHz
	:	:
	38	2478 MHz
	39	2480 MHz



2.3. RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for FCC ID: 2AYLN-N104 filing to comply with the FCC Part 15.247 requirements.

2.4. TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

2.5. SPECIAL ACCESSORIES

Refer to section 5.2.

2.6. EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2.7. ANTENNA REQUIREMENT

This intentional radiator is designed with a permanently attached antenna of an antenna to ensure that no antenna other than that furnished by the responsible party shall be used with the device. For more information of the antenna, please refer to the APPENDIX B: PHOTOGRAPHS OF EUT.



3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y $\pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.

Item	Measurement Uncertainty
Uncertainty of Conducted Emission for AC Port	$U_c = \pm 3.1 \text{ dB}$
Uncertainty of Radiated Emission below 1GHz	$U_c = \pm 4.0 \text{ dB}$
Uncertainty of Radiated Emission above 1GHz	$U_c = \pm 4.8 \text{ dB}$
Uncertainty of total RF power, conducted	$U_c = \pm 0.8 \text{ dB}$
Uncertainty of RF power density, conducted	$U_c = \pm 2.6 \text{ dB}$
Uncertainty of spurious emissions, conducted	$U_c = \pm 2 \%$
Uncertainty of Occupied Channel Bandwidth	$U_c = \pm 2 \%$



4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel TX_CH00
2	Middle channel TX_CH19
3	High channel TX_CH39

Note:

- 1. Only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.

Software Setting

 Iocalhost:87 	38/bt/modulatedTxLowEnergy			
			intel(R) Wi-Fi 6 AX201 160MHz	Con
owEnergy				
	Packet Type		35 2472	
	2M Bandwidth -		36 2474	
	Payload Length		37 2476	
	- 37 bytes		. 38 2478	
	Payload Pattern	4	2480 39 2480	
	PRBS9 -			
	START STO	ЭP	C DEFAULT	
	© Intel Corpo	oratio	n	
			e 🔒 🔳	へ 身



5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF TESTED SYSTEM

Radiated Emission Configure:

EUT

Conducted Emission Configure:

EUT	AE

5.2. EQUIPMENT USED IN TESTED SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	NewCube Mini PC	N104	2AYLN-N104	EUT
2	Adapter 1	DA-90J19	Input: AC 100-240V 50-60Hz, 1.5A Max Output: DC 19V 4.74A	AE
3	Adapter 2	NB-65B19	Input: AC 100-240V 50-60Hz, 1.5A Max Output: DC 19V 3.42A	AE
4	Adapter 3	SOY-1900342-327	Input: AC 100-240V 50-60Hz, 1.5A Max Output: DC 19V 3.42A	AE

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant



6. TEST FACILITY

Test Site	Attestation of C	Attestation of Global Compliance (Shenzhen) Co., Ltd				
Location		1-2/F, Building 19, Junfeng Industrial Park, Chongqing Road, Heping Community, Fuhai Street, Bao'an District, Shenzhen, Guangdong, China				
Designation Number	CN1259	CN1259				
FCC Test Firm Registration Number	975832	975832				
A2LA Cert. No.	5054.02	5054.02				
Description	Attestation of C	Attestation of Global Compliance (Shenzhen) Co., Ltd is accredited by A2LA				
TEST EQUIPMENT OF CONDUCTED EMISSION TEST						
Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due	
TEST RECEIVER	R&S	ESPI	101206	Mar. 28, 2022	Mar. 27, 2023	
LISN	R&S	ESH2-Z5	100086	Jun. 08, 2022	Jun. 07, 2023	
Test software	R&S	ES-K1	Ver.V1.71	N/A	N/A	

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Mar. 28, 2022	Mar. 27, 2023
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Nov. 17, 2021	Nov. 16, 2022
2.4GHz Filter	EM Electronics	2400-2500MHz	N/A	N/A	N/A
Attenuator	ZHINAN	E-002	N/A	Sep. 01, 2022	Aug. 31, 2023
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Oct. 31, 2021	Oct. 30, 2023
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Mar. 12, 2022	Mar. 11, 2024
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	Apr. 23, 2021	Apr. 22, 2023
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Sep. 01, 2022	Aug. 31, 2023
ANTENNA	SCHWARZBECK	VULB9168	494	Jan. 08, 2021	Jan. 07, 2023
Test software	Tonscend	JS32-RE	Ver.2.5	N/A	N/A



7. PEAK OUTPUT POWER


7.1. MEASUREMENT PROCEDURE

For peak power test:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. RBW≥DTS bandwidth
- 3. VBW≥3*RBW.
- 4. SPAN≥VBW.
- 5. Sweep: Auto.
- 6. Detector function: Peak.
- 7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) PEAK POWER TEST SETUP







7.3. LIMITS AND MEASUREMENT RESULT

Test Data of Conducted Output Power				
Test Mode	Test Channel (MHz)	Peak Power (dBm)	Limits (dBm)	Pass or Fail
	2402	3.827	≤30	Pass
GFSK 1M	2440	4.526	≪30	Pass
	2480	4.358	≤30	Pass
GFSK 2M	2402	3.877	≪30	Pass
	2440	4.548	≪30	Pass
	2480	4.351	≪30	Pass


Test Graphs of Conducted Output Power












Test Graphs of Conducted Output Power







8. BANDWIDTH

8.1. MEASUREMENT PROCEDURE

6dB bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 kHz, VBW \ge 3×RBW.
- 4. Set SPA Trace 1 Max hold, then View.

Occupied bandwidth:

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hoping channel The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW; Sweep = auto; Detector function = peak

4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.


8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.


Test Data of Occupied Bandwidth and DTS Bandwidth					
Test Mode	Test Channel (MHz)	99% Occupied Bandwidth (MHz)	-6dB Bandwidth (MHz)	Limits (MHz)	Pass or Fail
	2402	1.047	0.671	≥0.5	Pass
GFSK 1M	2440	1.043	0.679	≥0.5	Pass
	2480	1.044	0.685	≥0.5	Pass
GFSK 2M	2402	2.043	1.119	≥0.5	Pass
	2440	2.043	1.127	≥0.5	Pass
	2480	2.044	1.133	≥0.5	Pass

8.3. LIMITS AND MEASUREMENT RESULTS






Test Graphs of Occupied Bandwidth









Test_Graph_LE1M_ANT1_2480_1Mbps_OBW





















Test_Graph_LE2M_ANT1_2480_2Mbps_OBW









9. CONDUCTED SPURIOUS EMISSION

9.1. MEASUREMENT PROCEDURE

- 1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- 2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

9.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

9.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

9.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT				
Anniisekis Limite	Measurement Result			
Applicable Limits	Test Data	Criteria		
In any 100 kHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS		






Test Graphs of Spurious Emissions in Non-Restricted Frequency Bands
























Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands

























Test Graphs of Band Edge Emissions in Non-Restricted Frequency Bands

Test_Graph_LE2M_ANT1_2402_2Mbps_Lower Band Edge Emissions

Log

Lin







10. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

10.1. MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set the SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 8.4 was used in this testing.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer to Section 7.2.


10.3. MEASUREMENT EQUIPMENT USED

Refer to Section 6.

10.4. LIMITS AND MEASUREMENT RESULT


	Test Data of Conducted Output Power Spectral Density								
Test Mode	Test Channel (MHz)	Power density (dBm/3kHz)	Limit (dBm/3kHz)	Pass or Fail					
	2402	-11.342	≤8	Pass					
GFSK 1M	2440	-10.863	≪8	Pass					
	2480	-11.119	≪8	Pass					
	2402	-13.925	≪8	Pass					
GFSK 2M	2440	-13.285	≪8	Pass					
	2480	-13.493	≪8	Pass					






Test Graphs of Conducted Output Power Spectral Density












11. RADIATED EMISSION

11.1. MEASUREMENT PROCEDURE

- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emission, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.



11.2. TEST SETUP





11.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested for restricted band radiated emission, the test records reported below are the worst result compared to other modes.

11.4. TEST RESULT


Radiated emission below 30MHz

The amplitude of spurious emissions from 9kHz to 30MHz which are attenuated more than 20 dB below the permissible value need not be reported.



EUT	NewCube Mini PC	Model Name	N104						
Temperature	25° C	Relative Humidity	55.4%						
Pressure	960hPa	Test Voltage	Normal Voltage						
Test Mode	Mode 3	Antenna	Horizontal						

Radiated emission from 30MHz to 1000MHz-1M



No.	М	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		65.8031	11.82	13.68	25.50	40.00	-14.50	peak
2	*	198.5880	18.77	10.99	29.76	43.50	-13.74	peak
3		313.2760	13.53	18.06	31.59	46.00	-14.41	peak
4		459.1144	5.57	23.14	28.71	46.00	-17.29	peak
5		622.8900	6.55	20.84	27.39	46.00	-18.61	peak
6		925.7563	6.02	25.60	31.62	46.00	-14.38	peak

RESULT: PASS



EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		32.0667	22.68	9.19	31.87	40.00	-8.13	peak
2		59.6493	17.70	11.84	29.54	40.00	-10.46	peak
3	*	87.1117	20.93	11.71	32.64	40.00	-7.36	peak
4		102.0014	20.25	11.18	31.43	43.50	-12.07	peak
5	:	210.0482	20.21	11.65	31.86	43.50	-11.64	peak
6		1000.000	12.01	28.36	40.37	54.00	-13.63	peak

RESULT: PASS

Note:

- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. All test modes had been tested. The mode 3 is the worst case and recorded in the report.



EUT	NewCube Mini PC	Model Name	N104					
Temperature	25° C	Relative Humidity	55.4%					
Pressure	960hPa	Test Voltage	Normal Voltage					
Test Mode	Mode 3	Antenna	Horizontal					

Radiated emission from 30MHz to 1000MHz-2M

										Lin Ma	nit: Irgin:	
												F
					_							
12			1			Amerika Marina	MM Marine	June The	Turken week	Ame	e strate gard	1. J. W. W.
national	r.m.h.duluqhu	,um (produce)	Jon My	White	2 Any MA	Monune State ()				•••		
30.000	40 50) 60	70	80		(MHz)	300	400	500	600	700	1000.0

No.	Mk	. Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		71.8320	13.17	12.91	26.08	40.00	-13.92	peak
2		106.7587	8.51	12.10	20.61	43.50	-22.89	peak
3	*	197.8928	19.23	10.95	30.18	43.50	-13.32	peak
4		313.2760	14.14	18.06	32.20	46.00	-13.80	peak
5		419.1081	9.03	20.51	29.54	46.00	-16.46	peak
6		942.1305	6.49	25.49	31.98	46.00	-14.02	peak


RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/



EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		58.4074	19.26	11.65	30.91	40.00	-9.09	peak
2	*	87.1117	19.48	11.71	31.19	40.00	-8.81	peak
3	1	103.0800	19.33	11.23	30.56	43.50	-12.94	peak
4	1	170.1948	14.47	12.67	27.14	43.50	-16.36	peak
5	2	211.5265	18.11	11.59	29.70	43.50	-13.80	peak
6	3	321.0608	12.40	15.96	28.36	46.00	-17.64	peak

RESULT: PASS Note:

- 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
- 2. All test modes had been tested. The mode 3 is the worst case and recorded in the report.



Test Mode

Vertical

Radiated emission above 1GHz-1M

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4804.011	48.69	0.08	48.77	74.00	-25.23	peak
4804.011	42.12	0.08	42.20	54.00	-11.80	AVG
7206.022	48.35	2.21	50.56	74.00	-23.44	peak
7206.022	40.27	2.21	42.48	54.00	-11.52	AVG
Remark:						
emain.						
actor = Anter	nna Factor + Cable	Loss – Pre-	amplifier.			

EUTNewCube Mini PCModel NameN104Temperature25° CRelative Humidity55.4%Pressure960hPaTest VoltageNormal Voltage

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4804.011	49.33	0.08	49.41	74.00	-24.59	peak
4804.011	41.17	0.08	41.25	54.00	-12.75	AVG
7206.022	48.34	2.21	50.55	74.00	-23.45	peak
7206.022	40.12	2.21	42.33	54.00	-11.67	AVG
emark:						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			

Antenna

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Mode 3



Report No.: AGC11143221003FE02 Page 49 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.005	51.02	0.14	51.16	74.00	-22.84	peak
4880.005	42.34	0.14	42.48	54.00	-11.52	AVG
7320.140	46.37	2.36	48.73	74.00	-25.27	peak
7320.140	40.39	2.36	42.75	54.00	-11.25	AVG
emark:						
actor = Anter	nna Factor + Cable	Loss - Pre-	amplifier.			

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4880.050	50.25	0.14	50.39	74.00	-23.61	peak
4880.050	43.57	0.14	43.71	54.00	-10.29	AVG
7320.080	46.35	2.36	48.71	74.00	-25.29	peak
7320.080	41.12	2.36	43.48	54.00	-10.52	AVG
) om ork:						
lemark:						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			



Report No.: AGC11143221003FE02 Page 50 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4960.012	50.25	0.22	50.47	74.00	-23.53	peak
4960.012	38.34	0.22	38.56	54.00	-15.44	AVG
7440.027	48.33	2.64	50.97	74.00	-23.03	peak
7440.027	38.24	2.64	40.88	54.00	-13.12	AVG
Remark:						
actor = Anter	na Factor + Cabl	e Loss – Pre-	amplifier.			

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4960.013	49.35	0.22	49.57	74	-24.43	peak
4960.013	43.31	0.22	43.53	54	-10.47	AVG
7440.027	46.15	2.64	48.79	74	-25.21	peak
7440.027	38.52	2.64	41.16	54	-12.84	AVG
Remark:						
actor = Anter	nna Factor + Cable	Loss – Pre-	amplifier.			

RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



Radiated emission above 1GHz-1M

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.011	49.58	0.08	49.66	74.00	-24.34	peak
4804.011	41.33	0.08	41.41	54.00	-12.59	AVG
7206.022	49.57	2.21	51.78	74.00	-22.22	peak
7206.022	41.28	2.21	43.49	54.00	-10.51	AVG
Remark:						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			

EUT NewCube Mini PC **Model Name** N104 25° C **Relative Humidity** 55.4% **Temperature** Pressure 960hPa **Test Voltage** Normal Voltage **Test Mode** Mode 3 Antenna Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4804.011	50.27	0.08	50.35	74.00	-23.65	peak
4804.011	40.06	0.08	40.14	54.00	-13.86	AVG
7206.022	49.34	2.21	51.55	74.00	-22.45	peak
7206.022	41.28	2.21	43.49	54.00	-10.51	AVG
emark:						
emark:	na Factor + Cable	loss Pro	amplifior			



Report No.: AGC11143221003FE02 Page 52 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	
4880.005	52.33	0.14	52.47	74.00	-21.53	peak
4880.005	41.96	0.14	42.10	54.00	-11.90	AVG
7320.140	45.97	2.36	48.33	74.00	-25.67	peak
7320.140	39.74	2.36	42.10	54.00	-11.90	AVG
emark:						
actor = Anter	nna Factor + Cable	Loss – Pre-	amplifier.			

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4880.050	52.25	0.14	52.39	74.00	-21.61	peak
4880.050	44.12	0.14	44.26	54.00	-9.74	AVG
7320.080	46.33	2.36	48.69	74.00	-25.31	peak
7320.080	42.01	2.36	44.37	54.00	-9.63	AVG
Domorka						
Remark:						
actor = Anter	nna Factor + Cable	e Loss – Pre-	amplifier.			



Report No.: AGC11143221003FE02 Page 53 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.012	49.34	0.22	49.56	74.00	-24.44	peak
4960.012	39.15	0.22	39.37	54.00	-14.63	AVG
7440.027	49.27	2.64	51.91	74.00	-22.09	peak
7440.027	39.42	2.64	42.06	54.00	-11.94	AVG
lemark:						
	na Factor + Cable	e Loss – Pre-	amplifier.			

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Value Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	value Type
4960.013	48.34	0.22	48.56	74	-25.44	peak
4960.013	42.39	0.22	42.61	54	-11.39	AVG
7440.027	45.52	2.64	48.16	74	-25.84	peak
7440.027	39.51	2.64	42.15	54	-11.85	AVG
Remark:						
actor = Anter	nna Factor + Cabl	e Loss – Pre-	amplifier.			

RESULT: PASS

Note:

The amplitude of other spurious emissions from 1G to 25 GHz which are attenuated more than 20 dB below the permissible value need not be reported.

Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.


The "Factor" value can be calculated automatically by software of measurement system.




EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Test result for band edge emission at restricted bands-1M

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: PASS




Report No.: AGC11143221003FE02 Page 55 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd




Report No.: AGC11143221003FE02 Page 56 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: PASS




Report No.: AGC11143221003FE02 Page 57 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS


Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.




EUT	NewCube Mini PC	Model Name N104	
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Test result for band edge emission at restricted bands-2M

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: PASS




Report No.: AGC11143221003FE02 Page 59 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd




Report No.: AGC11143221003FE02 Page 60 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Test Graph for Peak Measurement



Test Graph for Average Measurement




RESULT: PASS




Report No.: AGC11143221003FE02 Page 61 of 68

EUT	NewCube Mini PC	Model Name	N104
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Test Graph for Peak Measurement



Test Graph for Average Measurement



RESULT: PASS

Note: The factor had been edited in the "Input Correction" of the Spectrum Analyzer.



12. LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage				
Frequency	Q.P.(dBuV)	Average(dBuV)			
150kHz~500kHz	66-56	56-46			
500kHz~5MHz	56	46			
5MHz~30MHz	60	50			

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipment received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less – 2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST







MEASUREMENT RESULT: "agc_fin"

2022/10/26 18	:51					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.178000	43.40	6.7	65	21.2	QP	L1
0.366000	33.20	5.8	59	25.4	QP	L1
0.658000	29.20	5.4	56	26.8	QP	L1
0.986000	30.80	5.4	56	25.2	QP	L1
1.390000	29.50	5.9	56	26.5	QP	L1
2.226000	31.20	6.5	56	24.8	QP	L1

MEASUREMENT RESULT: "agc fin2"

20	22/10/26 18	:50					
	Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
	0.330000	27.30	5.9	50	22.2	AV	L1
	0.362000	30.80	5.8	49	17.9	AV	L1
	0.366000	32.30	5.8	49	16.3	AV	L1
	1.022000	22.80	5.5	46	23.2	AV	L1
	1.354000	21.10	5.9	46	24.9	VA	L1
	2.222000	19.10	6.5	46	26.9	AV	L1


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

2







MEASUREMENT RESULT: "agc_fin"

2022/10/26 18	:47					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.174000	44.60	6.7	65	20.2	QP	N
0.362000	32.70	5.8	59	25.0	QP	Ν
0.366000	36.50	5.8	59	22.1	QP	N
0.662000	30.60	5.4	56	25.4	QP	N
1.022000	27.10	5.5	56	28.9	QP	N
1.934000	25.60	6.4	56	30.4	QP	N

MEASUREMENT RESULT: "agc fin2"

2022/10/26 18	:44					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.178000	28.30	6.7	55	26.3	AV	N
0.330000	28.10	5.9	50	21.4	AV	Ν
0.362000	28.80	5.8	49	19.9	AV	Ν
0.366000	31.10	5.8	49	17.5	AV	Ν
2.886000	20.60	6.5	46	25.4	AV	Ν
3.470000	19.50	6.5	46	26.5	AV	Ν


Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

2

```
Tel: +86-755 2523 4088 E-mail: agc@agccert.com Web: http://www.agccert.com/
```





Line Conducted Emission Test Line 1-L-2M

MEASUREMENT RESULT: "agc_fin"

2022/10/26 1	8:54					
Frequency	Level	Transd	Limit	Margin	Detector	Line
MHz	dBµV	dB	dBµV	dB		
0.174000	42.90	6.7	65	21.9	QP	L1
0.366000	33.10	5.8	59	25.5	QP	L1
1.018000	29.50	5.5	56	26.5	QP	L1
2.254000	29.90	6.5	56	26.1	QP	L1
2.586000	29.20	6.5	56	26.8	QP	L1
2.770000	30.00	6.5	56	26.0	QP	L1

MEASUREMENT RESULT: "agc_fin2"

2022/10/26 18:53

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.330000 0.362000 0.366000 0.694000 1.022000 1.354000	27.10 30.40 32.10 21.90 22.70 21.70	5.9 5.8 5.4 5.5 5.9	50 49 46 46 46	22.4 18.3 16.5 24.1 23.3 24.3	AV AV AV AV	L1 L1 L1 L1 L1 L1

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.


Attestation of Global Compliance(Shenzhen)Co., Ltd

 Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd

 Tel: +86-755 2523 4088
 E-mail: agc@agccert.com
 Web: http://www.agccert.com/







MEASUREMENT RESULT: "agc_fin"

2022/10/26 18:58							
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	
0.182000	44.10	6.7	64	20.3	QP	N	
0.370000	33.40	5.8	59	25.1	QP	N	
0.654000	29.40	5.4	56	25.6	QP	N	
0.706000	29.10	5.4	56	26.9	QP	N	
1.426000	29.30	6.0	56	26.7	QP	N	
2.574000	29.40	6.5	56	26.6	QP	N	

MEASUREMENT RESULT: "agc_fin2"

-	~ ~		(- L - C - L	/26	10.	E 0	
2	U.2	441	10	140	18:	20	

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line
0.178000	28.70	6.7	55	25.9	AV	N
0.330000	27.90	5.9	50	21.6	AV	N
0.362000	29.30	5.8	49	19.4	AV	Ν
0.366000	30.80	5.8	49	17.8	AV	Ν
1.970000	20.70	6.5	46	25.3	AV	Ν
2.546000	19.60	6.5	46	26.4	AV	N

Any report having not been signed by authorized approver, or having been altered without authorization, or having not been stamped by the "Dedicated Testing/Inspection Stamp" is deemed to be invalid. Copying or excerpting portion of, or altering the content of the report is not permitted without the written authorization of AGC. The test results presented in the report apply only to the tested sample. Any objections to report issued by AGC should be submitted to AGC within 15days after the issuance of the test report. Further enquiry of validity or verification of the test report should be addressed to AGC by agc01@agccert.com.

Attestation of Global Compliance(Shenzhen)Co., Ltd Attestation of Global Compliance(Shenzhen)Std & Tech Co., Ltd



APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Refer to the Report No.: AGC11143221003AP01

APPENDIX B: PHOTOGRAPHS OF EUT

Refer to the Report No.: AGC11143221003AP02

----END OF REPORT----



Conditions of Issuance of Test Reports

 All samples and goods are accepted by the Attestation of Global Compliance (Shenzhen) Co., Ltd. (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The company provides its services on the basis that such terms and conditions constitute express agreement between the company and any person, firm or company requesting its services (the "Clients").
 Any report issued by Company as a result of this application for testing services (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to its customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. In the event of the improper use of the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

5. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

6. The Company will not be liable for or accept responsibility for any loss or damage however arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

7. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

8. The Company is not responsible for recalling the electronic version of the original report when any revision is made to them. The Client assumes the responsibility to providing the revised version to any interested party who uses them.

9. Subject to the variable length of retention time for test data and report stored hereinto as otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of the test report for a period of six years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after retention period. Under no circumstances shall we be liable for damage of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.