


# RF Exposure Evaluation Report

**Application No.:** SZCR2104020343AT  
**Applicant:** Jwipc Technology Co., Ltd.  
**Address of Applicant:** 13/F, Building B, Haisong Edifice, Tairan 9th Road, Futian District, Shenzhen, China  
**Manufacturer:** Jwipc Technology Co., Ltd.  
**Address of Manufacturer:** 13/F, Building B, Haisong Edifice, Tairan 9th Road, Futian District, Shenzhen, China  
**Factory:** Dongguan Scd Technology Co., Ltd.  
**Address of Factory:** No.1 The 2nd Street, Huihuang Industrial Zone, Xiekeng Village, Qingxi Town, Dongguan, 523000 Guangdong, China  
**Equipment Under Test (EUT):**  
**Product Name:** OPS PC MODULE  
**Model No.:** S096, S0\*\*\*\*\* (\*=A-Z, 0-9, character or blank) ♣  
 ♣ Please refer to section 4.1 of this report which indicates which model was actually tested and which were electrically identical.  
**FCC ID:** 2AYLN-S096  
**Standards:** 47 CFR Part 1.1307  
 47 CFR Part 1.1310  
 47 CFR Part 2.1091  
**Date of Receipt:** 2021-04-02  
**Date of Test:** 2021-04-14 to 2021-05-10  
**Date of Issue:** 2021-05-11

<b>Test Result :</b>	<b>PASS*</b>
----------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu  
 EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8397 1443, or e-mail: CN\_Poccheck@sgs.com**

## 2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2021-05-11		Original

<b>Authorized for issue by:</b>			
		<i>Harry Wu</i>	
		_____	
		<b>Harry Wu/Project Engineer</b>	
		<i>Eric Fu</i>	
		_____	
		<b>Eric Fu/Reviewer</b>	



### 3 Contents

	Page
1 COVER PAGE .....	1
2 VERSION .....	2
3 CONTENTS .....	3
4 GENERAL INFORMATION .....	4
4.1 GENERAL DESCRIPTION OF EUT .....	4
4.2 TEST LOCATION .....	7
4.3 TEST FACILITY .....	7
4.4 DEVIATION FROM STANDARDS .....	7
4.5 ABNORMALITIES FROM STANDARD CONDITIONS .....	7
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	7
5 RF EXPOSURE EVALUATION .....	8
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT .....	8
5.1.1 Limits .....	8
5.1.2 Test Procedure .....	8
4.1.3 EUT RF EXPOSURE EVALUATION .....	9



## 4 General Information

### 4.1 General Description of EUT

Rated voltage:	Input:DC19.0V, 3.42A
<b>For BT:</b>	
Bluetooth Version:	V5.0
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK, Pi/4DQPSK, 8DPSK
Number of Channels:	79
Channel Spacing:	1MHz
Antenna Type:	Dipole Antenna
Antenna Gain:	Antenna 1: 5.67dBi
<b>For BLE:</b>	
Bluetooth Version:	V5.0
Operation Frequency:	2402MHz to 2480MHz
Modulation Type:	GFSK
Number of Channels:	40
Channel Spacing:	2MHz
Data Rate:	1Mbps, 2Mbps
Antenna Type:	Dipole Antenna
Antenna Gain:	Antenna 1: 5.67dBi
<b>For 2.4G Wifi</b>	
Operation Frequency:	802.11b/g/n/ax(HT20/HE20): 2412MHz to 2462MHz 802.11n/ax(HT40/HE40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11ax: OFDM&OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11802.11b/g/n(HT20)/ax(HE20): 11 802.11n(HT40)/ax(HE40):7
Channel Spacing:	5MHz
Antenna Type:	Dipole Antenna
Antenna Gain:	Antenna 1&2:5.67dBi Directional gain of antenna 1+2: 8.68dBi
<b>For 5GHz Wifi</b>	
DFS Function:	Slaver





# SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZCR210402034306  
Page: 5 of 11

TPC Function:	Not Support
Antenna Type:	Dipole Antenna
Antenna Gain:	Antenna 1&2:3dBi Directional gain of antenna 1+2: 6.01dBi.

Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
	UNII Band I	802.11a/n(HT20)/ac(VHT20)/ax(HE20)	5180-5240	4
		802.11n(HT40)/ac(VHT40)/ax(HE40)	5190-5230	2
		802.11ac(VHT80)/ax(HE80)	5210	1
	UNII Band II-A	802.11a/n(HT20)/ac(VHT20)/ax(HE20)	5260-5320	4
		802.11n(HT40)/ac(VHT40)/ax(HE40)	5270-5310	2
		802.11ac(VHT80)/ax(HE80)	5290	1
	UNII Band II-C	802.11ax(HE160)	5250	1
		802.11a/n(HT20)/ac(VHT20)/ax(HE20)	5500-5700	11
		802.11n(HT40)/ac(VHT40)/ax(HE40)	5510-5670	5
		802.11ac(VHT80)/ax(HE80)	5530-5610	2
	UNII Band III	802.11ax(HE160)	5570	1
		802.11a/n(HT20)/ac(VHT20)/ax(HE20)	5745-5825	5
802.11n(HT40)/ac(VHT40)/ax(HE40)		5755-5895	2	
		802.11ac(VHT80)/ax(HE80)	5775	1
Modulation Type:	802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDM&OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)			
Channel Spacing:	802.11a/n(HT20)/ac(VHT20)/ax(HE20) : 20MHz 802.11n(HT40)/ac(VHT40)/ax(HE40) : 40MHz 802.11ac(VHT80)/ax(HE80) : 80MHz 802.11ac(VHT160)/ax(HE160) : 160MHz			



SGS-CSTC Standards Technical Services Co., Ltd.  
Shenzhen Branch (CMAA) Testing Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing/inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or e-mail: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn  
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com



**Declaration of EUT Family Grouping:**

Model No.: S096, S0\*\*\*\*\* (\*=A-Z, 0-9, character or blank)

Only the model S096 was tested. According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on model No., memory capacity, hard disk capacity and CPU.

Key Component List	
CPU	i7-10700T, i5-10500T, i5-10400T and G5900T
PCH	H510 and Q570
The configurations have been considered, Configuration (CPU: i7-10700T and PCH: H510) is worst case and recorded in the report.	



## 4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China  
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

## 4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

## 4.4 Deviation from Standards

None.

## 4.5 Abnormalities from Standard Conditions

None.

## 4.6 Other Information Requested by the Customer

None.



## 5 RF Exposure Evaluation

### 5.1 RF Exposure Compliance Requirement

#### 5.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

**TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

Pd = power density in mW/cm<sup>2</sup>

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 5.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.





### 4.1.3 EUT RF Exposure Evaluation

**For BT:**

Antenna Gain: 5.67dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.69in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	EIRP (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
1	2480	10.20	38.64	0.008	1.0	PASS

Note: Refer to report No. SZCR210402034302 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.

**For BLE:**

Antenna Gain: 5.67dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.69 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	EIRP (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
1	2480	6.30	15.74	0.003	1.0	PASS

Note: Refer to report No. SZCR210402034303 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or e-mail: [CN.Doccheck@sgs.com](mailto:CN.Doccheck@sgs.com)

**For 2.4G:**

**For SISO:**

Antenna Gain: 5.67dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.69 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	EIRP (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
2	2462	14.01	92.90	0.018	1.0	PASS

**For MIMO:**

Antenna Gain: 5.67dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 3.69 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	EIRP (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
1+2	2437	15.94	144.88	0.029	1.0	PASS

Note: Refer to report No. SZCR210402034304 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Friis transmission formula is far greater than 20 cm separation requirement.



**For 5G:**

**For SISO:**

Antenna Gain: 3dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.995 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	EIRP (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
1	5600	13.34	43.05	0.009	1.0	PASS

**For MIMO:**

Antenna Gain: 3dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.995 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Antenna	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	EIRP (mW)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
1+2	5785	15.65	73.28	0.015	1.0	PASS

Note: Refer to report No. SZCR210402034305 for EUT test Max Conducted Peak Output Power value. The distance r (4th column) calculated from the Friis transmission formula is far greater than 20 cm separation requirement.

- End of the Report -

