



PRODUCT SPECIFICATION

TITLE

2.4/5GHz BALANCE FLEX ANTENNA

TABLE OF CONTENTS

- 1.0 SCOPE
- 2.0 PRODUCT DESCRIPTION
- 3.0 GENERAL SPECIFICATION
- 4.0 PRODUCT STRUCTURE INFORMATION
- 5.0 APPLICABLE DOCUMENTS
- 6.0 ANTENNA SPECIFICATION
- 7.0 MECHANICAL SPECIFICATION
- 8.0 ENVIRONMENTAL SPECIFICATION
- 9.0 PACKING

REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 1 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Stary Song 2019/06/05



PRODUCT SPECIFICATION

2.4/5GHz BALANCE FLEX ANTENNA

1.0 SCOPE

This Product Specification covers the mechanical, electrical and environmental performances specification for 2.4/5GHz Balance Flex Antenna.

2.0 PRODUCT DESCRIPTION

2.1 PRODUCT NAME AND SERIES NUMBER (S)


Product name: 2.4/5GHz Balance Flex Antenna
Series Number: 146153XXXX

2.2 DESCRIPTION

Series 146153 is a balanced, dipole-type, high efficiency antenna for 2.4/5 GHz applications, including WiFi, Bluetooth, Zigbee and others. This antenna is made from poly flexible material with small size 35*9*0.1mm and has double-sided adhesive tape for easy “peel and stick” mounting. This balanced antenna with ground plane independent design offers various cable length options for ease of integration into various devices.

2.3 FEATURES

- Ground plane independent, balanced dual band antenna
- Flex size 35 x 9 x 0.1mm (not contain solder area)
- IPEX MHF (U.FL compatible) connector (Such as MHF1/MHF4)
- Cable OD1.13mm, 6 standard length options (50/100/150/200/250/300mm)
- Cable and connector can be customized
- RoHS Compliant



Molex 1461530100 2.4/5GHz BALANCE FLEX ANTENNA MODULE 3D VIEW

REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 2 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Stary Song 2019/06/05




PRODUCT SPECIFICATION

3.0 GENERAL SPECIFICATION

Product name	2.4/5GHz Balance Flex Antenna	
Part number	146153XXXX	
Frequency	2.4GHz-2.5GHz	5.15GHz-5.85GHz
Polarization	Linear	
Operating with matching	-40°C to 85°C	
Storage with matching	-40°C to 85°C	
RF Power	2 Watts	
Impedance with matching	50 Ohms	
Antenna type	Flex	
Connector type	146153 0XXX	146153 1XXX
	Compatible MHF1	Compatible MHF4
User Implementation type	Adhesive 3M9077	
Cable diameter	Ø1.13mm	
Cable length	150 mm (P/N for 1461530150/1461531150)	


REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 3 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Stary Song 2019/06/05

4.0 PRODUCT STRUCTURE INFORMATION



Mechanical Structure Information for 1461530XXX

REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 4 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Stary Song 2019/06/05



Mechanical Structure Information for 1461531XXX

REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 5 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Sary Song 2019/06/05



PRODUCT SPECIFICATION

6.0 ANTENNA SPECIFICATION

All measurements are done of the antenna mounted on a PC/ABS material block of 1mm thickness with VNA Agilent E5071C and Over-The-Air (OTA) chamber. All measurements in this document are done with the part no.1461530100 for different cable length.

6.1 ELECTRICAL REQUIREMENT

6.1.3 ELECTRICAL REQUIREMENTS FOR CABLE LENGTH 150mm		
P/N	1461530150	
Frequency Range	2.4GHz-2.5GHz	5.15GHz-5.85GHz
Peak Gain (Max)	2.93dBi	6.82dBi
Average Total efficiency	>76%	>75%
Return Loss	< -10 dB	< -10 dB

REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 6 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Stary Song 2019/06/05



PRODUCT SPECIFICATION

6.2 CABLE LOSS

DESCRIPTION	TEST CONDITION	REQUIREMENTS	
Frequency Range	2.4GHz/5GHz	2.0GHz~3.0GHz	5.0GHz~6.0GHz
Attenuation	1m cable measured by VNA5071C	≤3.5dB/m	≤5.5dB/m

Balance antenna resonance is insensitive to cable's length, but the cable's loss will affect the total efficiency.

7.0 MECHANICAL SPECIFICATION

All measurements in this document are done with the part no.1461530100 for different cable length.

DESCRIPTION	TEST CONDITION	TEST RESULT
Pull Test	1. Test machine: Max intelligent load tester 2. Stick the flex antenna on a plastic board, pull cable in axial direction.	Pull force >8N
Un-mating force (connector)	Solder the receptacle connector to the test board ,then place the board and plug on push-on/pull-off machine, and repeat mating and un-mating 30 cycles at a speed 25±3mm/min. along the mating axis.	Un-mating force : 0.5 kgf min

REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 8 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Stary Song 2019/06/05




PRODUCT SPECIFICATION

8.0 ENVIRONMENTAL SPECIFICATION


DESCRIPTION	SPECIFICATION
Temperature /Humidity cycling	<ol style="list-style-type: none"> The device under test is kept for 30 mins in an environment with a temperature of -40 °C. Kept for 4 Hours in an environment with a temperature of 85 degrees and a relative humidity of 95%. Kept for 2 Hours in an environment with a temperature of 125 degrees and a relative humidity of 95%. The cycle is repeated until a total of 40 cycles have been completed. Hereafter the conditions are stabilized at room temperature. Transfer temperature 8°C per min. Parts should meet RF spec before and after test. No cosmetic problem (No soldering problem; No adhesion problem of glue.)
Temperature Shock	<ol style="list-style-type: none"> The device under test at -40 °C⇔125 °C by 100 cycles, Dwell of 30 mins, transition time between Dwell 30 secs (~ 61 mins / cycle) and each item should be measured after exposing them in normal temperature and humidity for 24 h. Parts should meet RF spec before and after test. No cosmetic problem (No soldering problem; No adhesion problem of glue) .
High Temperature	<ol style="list-style-type: none"> Temperature:125°C, time:1008 hours There is no substantial obstruction to air flow across and around the samples, and the samples are not touching each other Parts should meet RF spec before and after test. No cosmetic problem (No soldering problem; No adhesion problem of glue) .
Salt Mist Test	<ol style="list-style-type: none"> The device under test is exposed to a spray of a 5% (by volume) resolution of NAACL in water for 2 hours. Thereafter the device under test is left for 1 week in room temperature at a relative humidity of 95%. The cycle is repeated until a total of 2 cycles have been completed. Here after the conditions are stabilized at room temperature. Parts should meet RF spec before and after test. No visible corrosion. Discoloration acceptable.

REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 9 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Sтары Song 2019/06/05

9.0 PACKING



PET FILM



NOTES:

- 1.PRODUCTS MUST BE PACKED IN CARTONS AND SEALED UP WITH TAPE.
- 2.STICK LABEL WITH PART NUMBER AND DATE CODE
- 3.STANDARD PACKAGING QUANTITY:SEE TABLE
- 4.THIS PACKAGING SPECIFICATION TO BE USED FOR "2.4/5GHZ BALANCE FLEX ANTENNA".
5. WHEN TAKING PRODUCT FROM PET FILM, PLEASE REMOVE THE COVER TAPE FIRST, THEN PICK UP THE PART FROM FLEX NOT THE CABLE, TO AVOID SOLDER JOINT DAMAGE.

PACKAGING INFORMATION FOR 146153XXXX

REVISION: E2	ECR/ECN INFORMATION: EC No: 619345 DATE: 2019/06/20	TITLE: 2.4/5GHz Balance Flex Antenna Product Specification	SHEET No. 10 of 10
DOCUMENT NUMBER: PS-1461530100	CREATED / REVISED BY: Kang Cheng 2019/06/05	CHECKED BY: Cooper Zhou 2019/06/05	APPROVED BY: Stary Song 2019/06/05