



SAR Evaluation Report

Application No.: SZEM2101000698CR
Applicant: Yadea technology group co., Ltd.
Address of Applicant: Dongsheng Road,Dacheng Industrial Zone, Anzhen,Xishan District, Wuxi, Jiangsu, 214100, China.
Manufacturer: Yadea technology group co., Ltd.
Address of Manufacturer: Dongsheng Road,Dacheng Industrial Zone, Anzhen,Xishan District, Wuxi, Jiangsu, 214100, China.
Factory: HL CORP(SHENZHEN)
Address of Factory: Bitou third Industrial Park,Songgang Sub-district Baoan district ,Shenzhen
Equipment Under Test (EUT):
EUT Name: Electric scooter
Model No.: KS5, KS5 PRO *
 * Please refer to section 4.1 of this report which indicates which model was actually tested and which were electrically identical.
Trade Mark: 
FCC ID: 2AYR9YWTT01
Standards: 47 CFR Part 1.1307
 47 CFR Part 2.1093
 KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2021-01-18
Date of Test: 2021-01-21 to 2021-02-18
Date of Issue: 2021-03-15

| | |
|----------------------|--------------|
| Test Result : | Pass* |
|----------------------|--------------|

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
 EMC Laboratory Manager



2 Version

| Revision Record | | | | |
|-----------------|---------|------------|----------|----------|
| Version | Chapter | Date | Modifier | Remark |
| 01 | | 2021-03-15 | | Original |
| | | | | |
| | | | | |

| | | | |
|---------------------------------|--|---|--|
| Authorized for issue by: | | | |
| | |  | |
| | | <hr/> Leo Li/Project Engineer | |
| | |  | |
| | | <hr/> Eric Fu /Reviewer | |



3 Contents

| | Page |
|---|------|
| 1 COVER PAGE | 1 |
| 2 VERSION | 2 |
| 3 CONTENTS | 3 |
| 4 GENERAL INFORMATION | 4 |
| 4.1 GENERAL DESCRIPTION OF EUT | 4 |
| 4.2 TEST LOCATION | 5 |
| 4.3 TEST FACILITY | 5 |
| 4.4 DEVIATION FROM STANDARDS | 5 |
| 4.5 ABNORMALITIES FROM STANDARD CONDITIONS | 5 |
| 4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER | 5 |
| 5 SAR EVALUATION | 6 |
| 5.1 RF EXPOSURE COMPLIANCE REQUIREMENT | 6 |
| 5.1.1 <i>Standard Requirement</i> | 6 |
| 5.1.2 <i>Limits</i> | 6 |
| 5.1.3 <i>EUT RF Exposure</i> | 6 |



4 General Information

4.1 General Description of EUT

| | |
|----------------------|--|
| Power supply: | DC 36V rechargeable battery which charged from AC/DC adapter Adapter information: Model: FY-4202000 Input: AC 100-240V, 50/60Hz Output: DC 42.0V, 2.0A |
| Cable(s): | DC Cable: 100cm unshielded AC Cable: 120cm unshielded |
| Operation Frequency: | 2402MHz to 2480MHz |
| Bluetooth Version: | V4.2 LE |
| Modulation Type: | GFSK |
| Number of Channels: | 40 |
| Channel Spacing: | 2MHz |
| Antenna Type: | PCB Antenna |
| Antenna Gain: | 0dBi |

Declaration of EUT Family Grouping:

Model No.: KS5, KS5 PRO

Only the model KS5 PRO was tested, since according to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions were identical for the above models, with only difference on motor power and battery capacity, highly, length, foot distance, pole height.



4.2 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China
518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

No tests were sub-contracted.

4.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.4 Deviation from Standards

None.

4.5 Abnormalities from Standard Conditions

None.

4.6 Other Information Requested by the Customer

None.



5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

The Max. power (including tune-up tolerance) is 1.18 dBm on the highest channel 2.48 GHz (*)
 1.18 dBm logarithmic terms convert to numeric result is nearly 1.31 mW

According to the formula. calculate the test exclusion thresholds:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

$$\text{General RF Exposure} = (1.31 \text{ mW} / 5 \text{ mm}) \times \sqrt{2.48 \text{ GHz}} = 0.41 \quad (1)$$

SAR requirement:

$$S = 3.0 \quad (2)$$

$$(1) < (2)$$

So the SAR report is not required.

(*) Max. power refer to Report No.:SZEM210100069802

- End of the Report -

