




RADIO EXPOSURE TEST REPORT

FCC ID : 2AYRA-08449
Equipment : Linksys Velop Micro-Mesh 6
Brand Name : Linksys
Model Name : LN1200 v2, LN1210 v2, LN1215 v2
Applicant : Linksys USA, Inc.
121 Theory, Irvine, CA. 92617, USA
Standard : 47 CFR Part 2.1091

The product was received on Jan. 02, 2024, and testing was started from Jan. 02, 2024 and completed on Feb. 22, 2024. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1091 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....3
Summary of Test Result.....4
1 General Description5
1.1 EUT General Information5
1.2 Antenna Information6
1.3 Table for Multiple Listing8
1.4 Table for EUT Information8
1.5 Table for EUT Supports Function.....8
1.6 Accessories8
1.7 Applicable Standards9
1.8 Testing Location9
2 Maximum Permissible Exposure10
2.1 Limit of Maximum Permissible Exposure10
2.2 MPE Calculation Method.....10
2.3 MPE Exemption.....11
2.4 Calculated Result and Limit.....12

Photographs of EUT v01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Exposure evaluation	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sam Chen

Report Producer: Cathy Chiu



1 General Description

1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
2.4GHz WLAN	2400-2483.5	2412-2462	802.11b: DSSS (DBPSK, DQPSK, CCK) 802.11g/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) VHT: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
5GHz WLAN	5150-5250 5250-5350 5470-5725 5725-5850 5725-5895	5180-5250 5250-5320 5500-5720 5745-5825 5815-5885	802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM)
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK) LE: GFSK



1.2 Antenna Information

Ant.	Port			Brand	Model Name	Antenna Type	Connector	Gain (dBi)
	2.4GHz	5GHz	Bluetooth					
1	1	1	-	GALTRONICS	02102140-08042C	PCB Antenna	U.FL	Note1
2	2	-	-	GALTRONICS	02036073-07315	Embedded Antenna	N/A	
3	-	2	-	GALTRONICS	02102142-08042C	PCB Antenna	U.FL	
4	-	-	1	GALTRONICS	02036073-07315	Embedded Antenna	N/A	

Note1:

Ant.	Antenna Gain (dBi)						
	WLAN 2.4GHz	WLAN 5GHz UNII 1	WLAN 5GHz UNII 2A	WLAN 5GHz UNII 2C	WLAN 5GHz UNII 3	WLAN 5GHz UNII 4	Bluetooth
1	1.91	2.88	2.97	3.29	3.29	3.29	-
2	2.50	-	-	-	-	-	-
3	-	3.63	3.63	3.12	3.44	3.44	-
4	-	-	-	-	-	-	3.53

Note 2: The above information was declared by manufacturer.



Note 3: Directional gain information

Type	Maximum Output Power	Power Spectral Density
Non-BF	Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for N ANT ≤ 4	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left[\sum_{k=1}^{N_{ANT}} g_{j,k} \right]^2}{N_{ANT}} \right]$
BF	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left[\sum_{k=1}^{N_{ANT}} g_{j,k} \right]^2}{N_{ANT}} \right]$	$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left[\sum_{k=1}^{N_{ANT}} g_{j,k} \right]^2}{N_{ANT}} \right]$

Ex.

Directional Gain (NSS1) formula :

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{ANT}} \left[\sum_{k=1}^{N_{ANT}} g_{j,k} \right]^2}{N_{ANT}} \right]$$

$$NSS1(g1,1) = 10^{G1/20} ; NSS1(g1,2) = 10^{G2/20} ; NSS1(g1,3) = 10^{G3/20} ; NSS1(g1,4) = 10^{G4/20}$$

$$g_{j,k} = (NSS1(g1,1) + NSS1(g1,2) + NSS1(g1,3) + NSS1(g1,4))^2$$

$$DG = 10 \log \left[\frac{(NSS1(g1,1) + NSS1(g1,2) + NSS1(g1,3) + NSS1(g1,4))^2}{N_{ANT}} \right] \Rightarrow 10$$

$$\log \left[\frac{(10^{G1/20} + 10^{G2/20} + 10^{G3/20} + 10^{G4/20})^2}{N_{ANT}} \right]$$

Where ;

$$2.4G \ G1 = 1.91 \text{ dBi} ; G2 = 2.50 \text{ dBi} ;$$

$$5G \text{ UNII-1} \ G1 = 2.88 \text{ dBi} ; G2 = 3.63 \text{ dBi} ;$$

$$5G \text{ UNII-2A} \ G1 = 2.97 \text{ dBi} ; G2 = 3.63 \text{ dBi} ;$$

$$5G \text{ UNII-2C} \ G1 = 3.29 \text{ dBi} ; G2 = 3.12 \text{ dBi} ;$$

$$5G \text{ UNII-3} \ G1 = 3.29 \text{ dBi} ; G2 = 3.44 \text{ dBi} ;$$

$$5G \text{ UNII-4} \ G1 = 3.29 \text{ dBi} ; G2 = 3.44 \text{ dBi} ;$$

$$2.4G \ DG = 5.22 \text{ dBi}$$

$$5G \text{ UNII-1} \ DG = 6.27 \text{ dBi}$$

$$5G \text{ UNII-2A} \ DG = 6.32 \text{ dBi}$$

$$5G \text{ UNII-2C} \ DG = 6.22 \text{ dB}$$

$$5G \text{ UNII-3} \ DG = 6.38 \text{ dBi}$$

$$5G \text{ UNII-4} \ DG = 6.38 \text{ dBi}$$

<For 2.4GHz function>

For IEEE 802.11b/g/n/VHT/ax (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For 5GHz function>

For IEEE 802.11a/n/ac/ax (2TX/2RX):

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

<For Bluetooth function> (1TX/1RX):

Only Port 1 can be used as transmitting/receiving antenna.

Port 1 could transmit/receive simultaneously.



1.3 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description
LN1200 v2	For retail
LN1210 v2	For e-commerce
LN1215 v2	For Warehouse

Note 1: From the above models, model: LN1200 v2 was selected as representative model for the test and its data was recorded in this report.

Note 2: The above information was declared by manufacturer.

1.4 Table for EUT Information

EUT	Description
EUT 1	With Conductive Fabric
EUT 2	Without Conductive Fabric

Note 1: From the above EUTs, EUT 1 was selected as representative EUT for the test and its data was recorded in this report.

Note 2: The above information was declared by manufacturer.

1.5 Table for EUT Supports Function

Function
AP
Mesh

Note: The above information was declared by manufacturer.

1.6 Accessories

Accessories			
Equipment Name	Brand Name	Model Name	Rating
Adapter 1	Ktec	KSA-18W-050300VU	INPUT: 100-240V~50/60Hz, 0.5A OUTPUT: 5.0V, 3.0A
Adapter 2	MOSO	MSA-C3000IC5.0-18P-US	INPUT: 100-240V~50/60Hz, 0.7A max. OUTPUT: 5.0V, 3A
Adapter 3	Ktec	KSA-18W-050300D5	INPUT: 100-240V ~ 50/60Hz, 0.5A OUTPUT: 5.0V, 3.0A
Other			
US Plug*1 (Equip with Adapter 3 use only)			



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.8 Testing Location

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)
(TAF: 3787)	TEL: 886-3-656-9065 FAX: 886-3-656-9085
	Test site Designation No. TW3787 with FCC.
	Conformity Assessment Body Identifier (CABID) TW3787 with ISED.



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Method

The MPE was calculated at 35 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.3 MPE Exemption

Option (A): 1.1307(b)(3)(i)(A): Available maximum time-averaged power is < 1 mW

Option (B): 1.1307(b)(3)(i)(B): Device operates between 300 MHz and 6 GHz and the maximum time-averaged power or effective radiated power (ERP), whichever is greater, <= Pth.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

Option (C): 1.1307(b)(3)(i)(C): ERP is below a threshold calculated based on the distance R between the person and the antenna / radiating structure, where $R > \lambda / 2 \pi$.

Single RF Sources Subject to Routine Environmental Evaluation	
RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	1,920 R ² .
1.34-30	3,450 R ² /f ² .
30-300	3.83 R ² .
300-1,500	0.0128 R ² f.
1,500-100,000	19.2R ² .

Note: R is in meters, f is in MHz.



2.4 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	2.50	25.79	26.14	0.50	461.318	35	B	3060.0	0.1508
5.2G;D1D	6.27	26.54	30.66	0.50	1306.171	35	B	3060.0	0.4270
5.3G;D1D	6.32	23.00	27.17	0.50	584.790	35	B	3060.0	0.1912
5.6G;D1D	6.22	23.73	27.80	0.04	608.135	35	B	3060.0	0.1988
5.8G;D1D	6.38	29.36	33.59	0.25	2421.029	35	B	3060.0	0.7915
5.81G;D1D	6.38	28.78	33.01	0.50	2243.882	35	B	3060.0	0.7336
2.4G;BT-EDR	3.53	10.69	12.07	0.50	18.072	35	B	3060.0	0.0059
2.4G;BT-LE	3.53	3.96	5.34	0.50	3.837	35	B	3060.0	0.0013

Simultaneous Transmission Analysis Mode: WLAN 2.4GHz+WLAN 5GHz+Bluetooth

Mode	DG (dBi)	Power (dBm)	ERP (dBm)	Tolerance (dB)	Tune-up ERP (mW)	Distance (cm)	Option	TL ERP (mW)	TL Ratio
2.4G;G1D	2.50	25.79	26.14	0.50	461.318	35	B	3060.0	0.1508
5.8G;D1D	6.38	29.36	33.59	0.25	2421.029	35	B	3060.0	0.7915
2.4G;BT-EDR	3.53	10.69	12.07	0.50	18.072	35	B	3060.0	0.0059
Sum TL Ratio_B	0.9482								
Ratio Limit	1								

Note: The above antenna gain was declared by manufacturer.

—THE END—