

## Request for Modular/Limited Modular Approval

Date: February 2, 2023				
Subject: Manufacturer's Declaration for		☐ - Split Modula ☐ - Limited Spli		pproval
Request for: 2AYSQ60LTR11A1				
	asic Requirements – FCC Part 15.2120 Limited Module Description Must be		llowing Page	s
	pproval Requirement			ment Met
The modular transmitter must have its own does not have to rely upon the shielding promodular transmitter emissions to comply we between the RF circuitry of the module and installed. Such coupling may result in non-capacitors may be located external to the shape.	ovided by the device into which it is instartith FCC limits. It is also intended to preval any wires or circuits in the device into a compliant operation. The physical crystartic intended in the physical crystartic intended in the physical crystartic.	alled in order for all went coupling which the module is	⊠ - YES	□ - NO(*)
	Details: The module contains a NON RF section on FR4 carrier PCB and a RF section built by the mmW RF system in Package (SiP), where the BGT60LTR11 System on Chip (SoC) is extended by the package with mmW TX and RX antenna			
In the NON RF section there are only assisting components e.g. for clock generation (crystal resonator), LDO section, Vcc filter elements and hard coded ports to select the autonomous working mode without external software.				
The RF section, based on the mmW "Field distribution sensor" (FDS) System in Package (SiP) BGT60LTR11AIP with TX and RX antenna in package. The naming Short Range Radar is common as well.  This RF radar chip includes the state machine for process control, the entire TX and RX mmW section with on chip antennas, crystal oscillator (w.o.crystal resonator) and the baseband signal processing.				
A complete metal shielding of the RF SoP section and the entire radar module is not possible at any time, because the mmW antenna radiation (of the antennas on chip topside) would be blocked. The mmW Si chip is working in a shielded area.				
Description: Between the entire active area (the silicon die) and the on chip antenna for TX and RX, a ground plane for shielding is placed. Blow this shield GND, the Si mmW chip is located. Furthermore the mentioned shield GND is connected with vertical package through vias to the GND plane on the FR4 PCB.  Both shield GND planes (the above the Si mmW Chip and the below one) are combined together via vertical package through vias and GND solderballs. These measures generates a 3D Faraday cage with the active RF silicon in the center. The radiation of the on chip antennas keeps unaffected.  We referre strongly to the drawing in filed document "Autonomous BGT60LTR11AIP Principle Block diagram.docx"				
2. The modular transmitter must have buffered ensure that the module will comply with FC over-modulation. 15.212(a)(1)(ii)			⊠ - YES	□ - NO(*)
Details: The module does not have modul	<u>*</u>			
3. The modular transmitter must have its own ensure that the module will comply with FC supplying circuitry in the device into which	CC requirements regardless of the design	of the power	🖾 - YES	□ - NO(*)
Details: The module contains its own pow	Details: The module contains its own power supply regulation. LDO is on the module board. LDO marked in Schematic>			
4. The modular transmitter must comply with §§ 15.203, 15.204(b), 15.204(c), 15.212(a), attached or employ a "unique" antenna cot antenna, including the cable). The "profess to modules but can apply to limited modula	and 2.929(b). The antenna must either bupler (at all connections between the motional installation" provision of § 15.203	e permanently dule and the is not applicable	⊠ - YES	□ - NO(*)
Details: On chip antennas are used. NO o	ther antenna can be connected to the cl	hip.		



5.	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)	⊠ - YES	□ - NO(*)	
	Details: The module was tested stand-alone as shown in test setup photographs filed with this application>			

	Modular Approval Requirement	Require	ment Met
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748).  If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.  If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for	⊠ - YES	□ - NO(*)
	equipment authorization. 15.212(a)(1)(vi)  Details: The module is to small for a label with 4pt text. The module does not have an electron display Host specific labeling instructions are given in the installation manual, filed with this application.	y.	
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: The module complies with FCC Part 15C requirements. Instructions to the host manufacture integration instruction document, filed with this application.	er are provide	d in the
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: The module meets human exposure requirements for fixed equipment. Please refer to the human exposure RF test report, filed with this application.		



## **Limited Module Description – When Applicable**

\* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: Not applicable

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)			
Requirement Requirement		Requirement M	et
1.	For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.	☐ - Provided in Separate  Cover Letter	⊠ - N/A
Details: Radio is not using SW. RF functionality is controlled intern by a hard coded statemachine.			
2.	For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	☐ - Provided in Separate Cover Letter	⊠ - N/A
	Details: N/A		

Split Modular Requirements			
Requirement	Provided in Manual		
<ol> <li>For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained.</li> </ol>	☐ - Provided in Separate Cover Letter	⊠ - N/A	
Details: <example a="" n="" –=""></example>			



## OEM Integration Manual Guidance - KDB 996369 D03 Section 2 Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures for third-parties to use and/or integrate the module into a host device. Requirement ☐ - No. If No, and LMA applies, the applicant can optionally choose to not make the following detailed info public. However there still needs to be basic integration instructions for a users manual and the Is this module intended for ✓ - YES information below must still be included in the operational sale to third parties? description. If the applicant wishes to keep this info confidential, this will require a separate statement cover letter explaining the module is not for sale to third parties and that integration instructions are internal confidential documents. Items required to be in the manual - See KDB 996369 D03, Section 2 As of May 1, 2019, the FCC requires ALL the following information to be in the installation manual. Modular transmitter applicants should include information in their instructions for all these items indicating clearly when they are not applicable. For example information on trace antenna design could indicate "Not Applicable". Also if a module is limited to only a grantees own products and not intended for sale to third parties, the user instructions may not need to be detailed and the following items can be placed in the operational description, but this should include a cover letter as cited above. 1. List of applicable FCC rules. KDB 996369 D03, Section 2.2 Only list rules related to the transmitter. 2. Summarize the specific operational use conditions. KDB 996369 D03, Section 2.3 Conditions such as limits on antennas, cable loss, reduction of power for point to point systems, professional installation info 3. Limited Module Procedures. KDB 996369 D03, Section 2.4 Describe alternative means that the grantee uses to verify the host meets the necessary limiting conditions □ - All Items shown to When RF exposure evaluation is necessary, state how control will be maintained such the left are provided in that compliance is ensured, such as Class II for new hosts, etc. the Modular Integration 4. Trace antenna designs. KDB 996369 D03, Section 2.5 Guide (or UM) for Full Layout of trace design, parts list, antenna, connectors, isolation requirements, tests for Modular Approval (MA) design verification, and production test procedures for ensuring compliance. If or LMA. confidential, the method used to keep confidential must be identified and information provided in the operational description. ☐ - An LMA applies 5. RF exposure considerations. KDB 996369 D03, Section 2.6 and is approved ONLY Clearly and explicitly state conditions that allow host manufacturers to use the module. for use by the grantee in Two types of instructions are necessary: first to the host manufacturer to define their own products, and conditions (mobile, portable - xx cm from body) and second additional text needed to be not intended for sale to provided to the end user in the host product manuals. 3<sup>rd</sup> parties as provided in 6. Antennas. KDB 996369 D03, Section 2.7 a separate cover letter. List of antennas included in the application and all applicable professional installer Therefore the instructions when applicable. The antenna list shall also identify the antenna types information shown to the (monopole, PIFA, dipole, etc - note that "omni-directional" is not considered a type) left is found in the 7. Label and compliance information. KDB 996369 D03, Section 2.8 theory of operation. Advice to host integrators that they need to provide a physical or e-label stating "Contains FCC ID: " with their finished product 8. Information on test modes and additional testing requirements. KDB 996369 D03, Section 2.9 Test modes that should be taken into consideration by host integrators including clarifications necessary for stand-alone and simultaneous configurations. Provide information on how to configure test modes for evaluation 9. Additional testing, Part 15 Subpart B disclaimer. KDB 996369 D03, Section 2.10

Sincerely,

By: Merender Mes Lead \_\_ Alexander Glas / Lead Principal \_\_

(Signature/Title) Principal

<sup>-</sup> Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.