



RF - TEST REPORT

- Human Exposure -

Type / Model Name : REF BGT60LTR11AIP

Product Description : 60 GHz short range radar module

HVIN: Ref BGT60LTR11AIP_1

Applicant : Infineon Technologies AG

Address : Am Campeon 1-15

85579 NEUBIBERG, GERMANY

Manufacturer : Infineon Technologies AG

Address : Am Campeon 1-15

85579 NEUBIBERG, GERMANY

<p>Test Result according to the standards listed in clause 1 test standards:</p>	<p>POSITIVE</p>
---	------------------------

<p>Test Report No. : 80103696-02 Rev_1</p>	<p>03. February 2023 Date of issue</p>
---	--



Deutsche
Akkreditierungsstelle
D-PL-12030-01-03
D-PL-12030-01-04

FCC ID: 2AYSQ60LTR11A1

IC: 28678-60LTR11A1

Contents

1	<u>TEST STANDARDS</u>	3
2	<u>EQUIPMENT UNDER TEST</u>	4
2.1	Information provided by the Client	4
2.2	Sampling	4
2.3	Photo documentation of the EUT – see Attachment A	4
2.4	Equipment type, category	4
2.5	Short description of the equipment under test (EUT)	4
2.6	Variants of the EUT	4
2.7	Operation frequency and channel plan	4
2.8	Transmit operating modes	5
2.9	Antennas	5
2.10	Power supply system utilised	5
3	<u>TEST RESULT SUMMARY</u>	6
3.1	Revision history of test report	6
3.2	Final assessment	6
4	<u>TEST ENVIRONMENT</u>	7
4.1	Address of the test laboratory	7
4.2	Environmental conditions	7
4.3	Statement of the measurement uncertainty	7
5	<u>HUMAN EXPOSURE</u>	8
5.1	RF output power	8
5.2	Maximum permissible exposure (MPE)	9
5.3	Co-location and Co-transmission	11
5.4	SAR test exclusion considerations	11
5.5	Exemption limits for routine evaluation - SAR evaluation	11
6	<u>USED TEST EQUIPMENT AND ACCESSORIES</u>	12
 ATTACHMENT A AS SEPARATE SUPPLEMENT		

FCC ID: 2AYSQ60LTR11A1

IC: 28678-60LTR11A1

1 TEST STANDARDS

The tests were performed according to following standards:

FCC Rules and Regulations Part 1, Subpart I - Procedures Implementing the National Environmental Policy Act of 1969

Part 1, Subpart I, Section 1.1310	Radiofrequency radiation exposure limits
Part 1, Subpart 2, Section 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.
KDB 447498 D01	RF Exposure procedures and equipment authorisation policies for mobile and portable devices, April 20, 2021.

ANSI C95.1: 2005	IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
------------------	--

RSS-102, Issue 5, February 2, 2021

Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

ANSI C95.1: 2005	IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz
------------------	--

FCC ID: 2AYSQ60LTR11A1
IC: 28678-60LTR11A1

2 EQUIPMENT UNDER TEST

2.1 Information provided by the Client

Please note, we do not take any responsibility for information provided by the client or his representative which may have an influence on the validity of the test results.

2.2 Sampling

The customer is responsible for the choice of sample. Sample configuration, start-up and operation is carried out by the customer or according his/her instructions.

2.3 Photo documentation of the EUT – see Attachment A

2.4 Equipment type, category

The EUT qualifies under FCC 15.255, (c)(2), field disturbance sensor, fixed equipment

2.5 Short description of the equipment under test (EUT)

The EUT is a field disturbance sensor in the operating band of 61.0 GHz to 61.5 GHz.

Number of tested samples: 2
 Serial number: #1 (CW)
 #4 (pulsed)
 Firmware version: NO firmware,
 RF relevant register settings hard coded.
 Only channel selection in 61.0-61.5 GHz band possible (CH1-4)

2.6 Variants of the EUT

There are no variants of the EUT.

2.7 Operation frequency and channel plan

The operating frequency is 61.0 GHz to 61.5 GHz.

Channel	Frequency (GHz)
1	61.1
2	61.2
3	61.3
4	61.4

Note: The blue marked channels are measured.

FCC ID: 2AYSQ60LTR11A1
IC: 28678-60LTR11A1

2.8 Transmit operating modes

 TX modulated
 TX CW

2.9 Antennas

The following integrated antennas are used with the EUT:

Number	Characteristic	Model number	Plug	Frequency range (GHz)	Max gain (dBi)
1	linear	On chip patch antenna for TX	-	61.0-61.5	5.0
2	linear	On chip patch antenna for RX	-	61.0-61.5	5.0

The antennas cannot be unattached by the user.

2.10 Power supply system utilised

 Power supply voltage, V_{nom} : 5 V/DC (test jig)
 Power supply voltage EUT : 3.3 V/DC

FCC ID: 2AYSQ60LTR11A1
IC: 28678-60LTR11A1

3 TEST RESULT SUMMARY

Operating in the 61 GHz – 61.5 GHz band:

FCC Rule Part	RSS Rule Part	Description	Result
KDB 447498, 7.1	RSS 102, 2.5.2	MPE	passed
KDB 447498, 4.3.1	RSS 102, 2.5.1	SAR exclusion consideration	not applicable
KDB 447498, 7.2	RSS102, 3.2	Co-location, Co-transmission	not applicable

3.1 Revision history of test report

Test report No	Rev.	Issue Date	Changes
80103696-02	0	20 December 2022	Initial test report
80103696-02	1	03 February 2023	5.2.2 reference to FCC Part 15, Section 15.255(g) aligned

The test report with the highest revision number replaces the previous test reports.

3.2 Final assessment

The equipment under test fulfils the requirements cited in clause 1 test standards.

 Date of receipt of test sample : acc. to storage records

 Testing commenced on : 25 November 2021

 Testing concluded on : 26 November 2021

Checked by:

Tested by:

 Jürgen Pessinger
Radio Team

 Sabine Kugler
Radio Team

FCC ID: 2AYSQ60LTR11A1

IC: 28678-60LTR11A1

4 TEST ENVIRONMENT

4.1 Address of the test laboratory

**CSA Group Bayern GmbH
Ohmstrasse 1-4
94342 STRASSKIRCHEN
GERMANY**

4.2 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15 - 35 °C

Humidity: 30 - 60 %

Atmospheric pressure: 86 - 106 kPa

4.3 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. It is noted that the expanded measurement uncertainty corresponds to the measurement results from the standard measurement uncertainty multiplied by the coverage factor $k = 2$. The true value is located in the corresponding interval with a probability of 95 %. The measurement uncertainty was calculated for all measurements listed in this test report on basis of the ETSI Technical Report TR 100 028 Electromagnetic compatibility and Radio spectrum Matters (ERM); Uncertainties in the measurement of mobile radio equipment characteristics; Part 1 and Part 2. The results are documented in the quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

4.4 Conformity Decision Rule

The applied conformity decision rule is based on ILAC G8:09/2019 clause 4.2.1 Binary Statement for Simple Acceptance Rule ($w = 0$).

Details can be found in the procedure CSA_B_V50_29.

FCC ID: 2AYSQ60LTR11A1
IC: 28678-60LTR11A1

5 HUMAN EXPOSURE

5.1 RF output power

For test instruments and accessories used see section 6 Part **CPR 3**.

5.1.1 Description of the test location

Test location: NONE

5.1.2 Test result

The output power of the device is taken from the power measurement in the test report 80103696-01 according to FCC Part 15 C, 15.255 issued by CSA Group Bayern GmbH.

Channel	Frequency (GHz)	Level PK (dBm)	Limit PK (dBm)	Margin PK (dB)	Level AV (dBm)	Limit AV (dBm)	Margin AV (dB)
CH1	61.1	9.1	43.0	-33.9	7.7	40.0	-32.3
CH2	61.2	9.4	43.0	-33.6	7.9	40.0	-32.1
CH4	61.4	10.5	43.0	-32.6	9.2	40.0	-30.9

Remarks: As worst case the power values are not averaged over time.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2AYSQ60LTR11A1
IC: 28678-60LTR11A1

5.2 Maximum permissible exposure (MPE)

For test instruments and accessories used see section 6 Part **CPC 3**.

5.2.1 Description of the test location

Test location: NONE

5.2.2 Applicable standard

According to FCC Part 15, Section 15.255(g):

Systems operating under the provisions of this section shall be operated in a manner that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

The test methods used comply with ANSI/IEEE C95.1, "IEEE Standard for Safety Levels with respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz".

This test report shows the compliance with the limits for Maximum Permissible Exposure (MPE) specified in FCC Part 1, Section 1.1310 and the criteria to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in FCC Part 1, Section 1.1307(b).

5.2.3 Description of Determination

The maximum rated output power conducted included the tune up tolerance is used to calculate the EIRP. Through the Friis transmission formula, the known maximum gain of the antenna and the maximum power, can be calculated the MPE in a defined distance away from the product.

Friis transmission formula:

$$P_d = \frac{P_{out} * G}{4 * \Pi * r^2}$$

Where:

P_d = power density (mW/cm²)

P_{out} = output power to antenna (mW)

G = gain of antenna (linear scale)

r = distance between antenna and observation point (cm)

According to FCC Rules 47CFR 2.1093(b) the EUT is not a portable device. The EUT is designed to be used that radiating structures are 20 cm outside of the body of the user. ($r = 20$ cm)

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2AYSQ60LTR11A1
IC: 28678-60LTR11A1
5.2.4 Determination of MPE according FCC

Frequency	EIRP	Tune-up	max EIRP	r	S	Limit S_{eq}	Margin	Exposure ratio
(GHz)	(dBm)	(dBi)	(mW)	(cm)	(mW/cm ²)	(mW/cm ²)	(mW/cm ²)	(%)
61.1	9.1	3.0	16.2	20.0	0.0032	1.0	-0.9968	0.32
61.2	9.4	3.0	17.4	20.0	0.0035	1.0	-0.9965	0.35
61.4	10.5	3.0	22.4	20.0	0.0045	1.0	-0.9955	0.45

Limits for maximum permissible exposure (MPE):

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	100	30
1.34 – 30	824/ <i>f</i>	2.19/ <i>f</i>	180/ <i>f</i> ²	30
30 - 300	27.5	0.073	0.2	30
300-1500	---	---	<i>f</i> /1500	30
1500-100000	---	---	1.0	30

f = Frequency in MHz

5.2.5 Determination of MPE according ISED:

Frequency	EIRP	Tune-up	max EIRP	Limit S_{eq}	Margin	Exposure ratio
MHz	(dBm)	(dBi)	(mW)	(W)	(W)	(%)
61250	9.1	3.0	16.22	5.0	-4.98	0.32
61250	9.4	3.0	17.38	5.0	-4.98	0.35
61250	10.5	3.0	22.39	5.0	-4.98	0.45

Exemption limits for routine Evaluation – RF exposure evaluation according RSS102, 2.5.2:

At or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance)

 The requirements are **FULFILLED**.

Remarks: None

FCC ID: 2AYSQ60LTR11A1

IC: 28678-60LTR11A1

5.3 Co-location and Co-transmission

Applicable standard:

OET Bulletin 65, Edition 97-01, Section 2: Multiple-transmitter sites and Complex Environments

The FCC's MPE limits vary with frequency. Therefore, in mixed or broadband RF fields where several sources and frequencies are involved, the fraction of the recommended limit (in terms of power density or square of the electric or magnetic field strength) incurred within each frequency interval should be determined, and the sum of all fractional contributions should not exceed 1.0, or 100 % in terms of percentage.

Remarks: Not applicable, EUT has only one transmitter with one transmitting antenna.

5.4 SAR test exclusion considerations

5.4.1 Applicable standard

According to RF exposure guidance:

Systems operating under the provisions of this section shall be operated in a manner that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines.

Remarks: Not applicable, EUT is not portable.

5.5 Exemption limits for routine evaluation - SAR evaluation

5.5.1 Applicable standard

According to RSS-102, item 2.5.1:

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1.

Remarks: Not applicable, EUT is not portable.

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.

FCC ID: 2AYSQ60LTR11A1

IC: 28678-60LTR11A1

6 USED TEST EQUIPMENT AND ACCESSORIES

All test instruments used are calibrated and verified regularly. The calibration history is available on request.

Test ID	Model Type	Equipment No.	Next Calib.	Last Calib.	Next Verif.	Last Verif.
---------	------------	---------------	-------------	-------------	-------------	-------------

- End of test report -

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test results without the written permission of the test laboratory.