

FCC TEST REPORT

FCC ID: 2BEPA-LIFEBOX

Product : Portable Power Station
Model(s) Name : 2AYT3-AC180T
Brand : BLUETTI
Report No. : NCT24008097-1

Prepared for

SHENZHEN POWEROAK NEWENER CO., LTD

F19, BLD No.1, Kaidaer, Tongsha Rd No.168, Xili Street, Nanshan, Shenzhen, China

Prepared by

Shenzhen NCT Testing Technology Co., Ltd.

**A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District,
Shenzhen, People's Republic of China**

TEL: 400-8868-419

FAX: 86-755-27790922


1 TEST RESULT CERTIFICATION

Applicant: : SHENZHEN POWEROAK NEWENER CO., LTD
Address: : F19, BLD No.1, Kaidaer, Tongsha Rd No.168, Xili Street, Nanshan, Shenzhen, China
Manufacturer: : SHENZHEN POWEROAK NEWENER CO., LTD
Address: : F19, BLD No.1, Kaidaer, Tongsha Rd No.168, Xili Street, Nanshan, Shenzhen, China
Product name : Portable Power Station
Model name: : AC180T
Series Model(s): N/A
Standards : FCC CFR47 Part 15 Section 15.247
Test procedure : KDB 558074 D01 15.247 Meas Guidance v05r02, ANSI C63.10-2020
Date of test : 2024-01-04 to 2024-01-20
Date of Issue : 2024-01-20


This device described above has been tested by NCT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NCT, this document may be altered or revised by NCT, personal only, and shall be noted in the revision of the document.

Test Engineer:


Keven Wu / Engineer

Technical Manager:


Henry Wang / Manager



Contents

	Page
1 TEST RESULT CERTIFICATION.....	2
2 TEST SUMMARY.....	5
2.1 TEST SITE.....	6
3 GENERAL INFORMATION.....	7
3.1 GENERAL DESCRIPTION OF E.U.T.....	7
3.2 CHANNEL LIST.....	8
3.3 TEST SETUP CONFIGURATION.....	9
3.4 TEST MODE.....	9
4 EQUIPMENT DURING TEST.....	10
4.1 EQUIPMENTS LIST.....	10
4.2 MEASUREMENT UNCERTAINTY.....	12
4.3 DESCRIPTION OF SUPPORT UNITS.....	12
5 CONDUCTED EMISSION.....	13
5.1 E.U.T. OPERATION.....	13
5.2 EUT SETUP.....	13
5.3 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
5.4 MEASUREMENT PROCEDURE.....	14
5.5 CONDUCTED EMISSION LIMIT.....	14
5.6 MEASUREMENT DESCRIPTION.....	14
5.7 CONDUCTED EMISSION TEST RESULT.....	14
6 RADIATED SPURIOUS EMISSIONS.....	17
6.1 EUT OPERATION.....	17
6.2 TEST SETUP.....	18
6.3 SPECTRUM ANALYZER SETUP.....	19
6.4 TEST PROCEDURE.....	20
6.5 SUMMARY OF TEST RESULTS.....	25
7 CONDUCT BAND EDGE AND SPURIOUS EMISSIONS MEASUREMENT.....	35
7.1 TEST PROCEDURE.....	35
7.2 TEST RESULT.....	35

BAND EDGE MEASUREMENTS	36
8 6DB BANDWIDTH MEASUREMENT	47
8.1 TEST PROCEDURE.....	47
8.2 TEST RESULT	47
9 MAXIMUM PEAK OUTPUT POWER	51
9.1 TEST PROCEDURE.....	51
9.2 TEST RESULT	51
10 POWER SPECTRAL DENSITY	55
10.1 TEST PROCEDURE.....	55
10.2 TEST RESULT	55
11 ANTENNA APPLICATION	59
11.1 ANTENNA REQUIREMENT	59
11.2 RESULT.....	59
12 TEST SETUP PHOTOS AND EUT PHOTOS	60

2 Test Summary

Test Items	Test Requirement	Result
Conduct Emission	FCC part 15.207	PASS
Radiated Spurious Emissions	FCC part 15.247(d), 15.209, 15.205	PASS
Conducted Spurious Emission	FCC part 15.247(d), 15.209, 15.205	PASS
Band edge	FCC part 15.247(d), 15.209, 15.205	PASS
6dB&99% Bandwidth	FCC part 15.247 (a)(2)	PASS
Maximum Peak Output Power	FCC part 15.247 (b)(3)	PASS
Power Spectral Density	FCC part 15.247 (e)	PASS
Antenna Requirement	FCC part 15.203/15.247 (c)	PASS

2.1 Test Site

Site Description

EMC Lab. : Accredited by CNAS, 2022-09-27

The certificate is valid until 2028.01.07

The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2017)

The Certificate Registration Number is L8251

Designation Number: CN1347

Test Firm Registration Number: 894804

Accredited by A2LA, June 14, 2023

The Certificate Registration Number is 6837.01

Accredited by Industry Canada, November 09, 2018

The Conformity Assessment Body Identifier is CN0150

Company Number: 30806

Name of Firm : Shenzhen NCT Testing Technology Co., Ltd.

Site Location : A101&2F B2, Fuqiao 6th Area, Xintian Community, Fuhai Street, Baoan District, Shenzhen, People's Republic of China

3 General Information

3.1 General Description of E.U.T.

Product Name	:	Portable Power Station
Model Name	:	AC180T
Sample ID	:	NCT24008097-1
Sample(s) Status:	:	Engineer sample
Series Models	:	N/A
Model Different.:	:	N/A
Hardware version:	:	V5.0
Software version:	:	25.0301.2081-07
Bluetooth version:	:	V5.0
Operating frequency	:	2402-2480MHz
Number of Channels	:	40 channels
Type of Modulation	:	GFSK
Antenna installation	:	PCB antenna
Antenna Gain	:	-2.31dBi
Power supply	:	Input: AC: 120V 50/60Hz, 15A Max. DC/PV: 12V-60V, 10A Max., 500W Max. Output: AC: 120V 50/60Hz, 1800VA, 1800W (with 2 packs) AC: 120V 50/60Hz, 1200VA, 1200W (with 1 pack) USB-A: DC 5V3A USB-C: DC 5/9/12/15/20V3A, 20V5A Cigarette Lighter port: DC 12V10A AC and DC output: 1900W Total
<p>Remark: the Antenna gain is provided by customer from Antenna spec. and the laboratory will not be responsible for the accumulated calculation results which covers the information provided by the applicant.</p>		

3.2 Channel List

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2020 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

Note:


1. Test of channel was included the lowest, middle and highest frequency in highest data rate and to perform the test, then record on this report.

3.3 Test Setup Configuration

Conducted Emission (Note: 2. The device is a DC power supply and does not apply to conducted emissions.)



Radiated Emission(30MHz-1GHz)



Radiated Emission(above 1GHz)



Conducted Spurious



3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

Test Software	SSCOM V5.13.1
Power level setup	01 for BLE 1M&2M

	Channel	Frequency(MHz)
Low Channel	0	2402
Mid Channel	19	2440
High Channel	39	2480

4 Equipment During Test

4.1 Equipments List

Conducted emission Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
944 Shielded Room	944 Room	/	EMToni	2022/5/31	2025/5/30
EMI Test Receiver	ESPI	101604	Rohde & Schwarz	2023/6/21	2024/6/20
LISN	ENV 216	102796	Rohde & Schwarz	2023/6/21	2024/6/20
LISN	VN1-13S	004023	CRANAGE	2023/6/21	2024/6/20
Cable	RG223-1500MM	NA	RG	2023/6/21	2024/6/20

Radiated emission & Radio Frequency Test Equipment

Name	Model No.	Serial No.	Manufacturer	Date of Cal.	Due Date
966 Shielded Room	966 Room	/	EMToni	2022/5/31	2025/5/30
EMI Test Receiver	ESCI	101178	Rohde & Schwarz	2023/6/21	2024/6/20
Amplifier (30MHz-1GHz)	BBV 9743 B	00374	SCHNWARZBECK	2023/6/21	2024/6/20
Bilog Antenna (30MHz-1GHz)	VULB9162	00473	SCHNWARZBECK	2023/3/19	2025/3/18
Horn antenna (1GHz-18GHz)	BBHA 9120 D	02622	SCHNWARZBECK	2023/3/19	2025/3/18
Preamplifier (1GHz-18GHz)	BBV 9718D	0024	SCHNWARZBECK	2023/6/21	2024/6/20
Spectrum Analyze (10Hz-40GHz)	FSV 40	100952	Rohde & Schwarz	2023/6/21	2024/6/20
Preamplifier (18GHz-40GHz)	BBV 9721	0056	SCHNWARZBECK	2023/6/21	2024/6/20
Double Ridge Guide Horn Antenna (18GHz-40GHz)	SAS-574	588	A.H.System	2023/3/19	2025/3/18
Loop Antenna (9KHz-30MHz)	FMZB1519B	014	SCHNWARZBECK	2023/6/21	2024/6/20

Amplifier (9KHz-30MHz)	CVP 9222 C	00109	CHNWARZBECK	2023/6/21	2024/6/20
MXG Signal Analyzer	N9020A	MY50510202	Agilent	2023/6/21	2024/6/20
MXG Vector Signal Generator	N5182A	MY50140020	Agilent	2023/6/21	2024/6/20
MXG Analog Signal Generator	N5181A	MY47420919	Agilent	2023/6/21	2024/6/20
Power Sensor	TR1029-2	512364	Techoy	2023/6/21	2024/6/20
RF Swith	TR1029-1	512364	Techoy	2023/6/21	2024/6/20
Cable	DA800-4000MM	NA	DA	2023/6/21	2024/6/20
Cable	DA800-11000MM	NA	DA	2023/6/21	2024/6/20

Other

Item	Name	Manufacturer	Model	Software version
1	EMC Conduction Test System	AUDIX	e3	6.120718
2	EMC radiation test system	AUDIX	e3	6.120718
3	RF test system	TACHOY	RFTest	V1.0.0
4	RF communication test system	TACHOY	RFTest	V1.0.0

4.2 Measurement Uncertainty

Parameter	Uncertainty
RF output power, conducted	±1.0dB
Power Spectral Density, conducted	±2.2dB
Radio Frequency	± 1 x 10 ⁻⁶
Bandwidth	± 1.5 x 10 ⁻⁶
Time	±2%
Duty Cycle	±2%
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±3%
Conducted Emissions (150kHz~30MHz)	±3.64dB
Radiated Emission(9kHz~30MHz)	±4.51dB
Radiated Emission(30MHz~1GHz)	±5.03dB
Radiated Emission(1GHz~25GHz)	±4.74dB
Remark: The coverage Factor (k=2), and measurement Uncertainty for a level of Confidence of 95%	

4.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
N/A	N/A	N/A	N/A	N/A	N/A

Note: (1)The support equipment was authorized by Declaration of Confirmation.

(2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.

5 Conducted Emission

Test Requirement : FCC CFR 47 Part 15 Section 15.207
ANSI C63.10-2020 section 6.10
Test Method :
KDB 558074 D01 15.247 Meas Guidance v05r02
Test Result : PASS
Frequency Range : 150kHz to 30MHz
Class/Severity : Class B


5.1 E.U.T. Operation

Operating Environment :


Temperature : 26 °C
Humidity : 44 % RH
Atmospheric Pressure : 101kPa

5.2 EUT Setup

The conducted emission tests were performed using the setup accordance with the ANSI C63.10:2020



5.3 Test SET-UP (Block Diagram of Configuration)



5.4 Measurement Procedure

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.5 Conducted Emission Limit

Conducted Emission

Frequency(MHz)	Quasi-peak	Average
0.15-0.5	66-56	56-46
0.5-5.0	56	46
5.0-30.0	60	50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.6 Measurement Description


The maximised peak emissions from the EUT was scanned and measured for both the Live and Neutral Lines. Quasi-peak & average measurements were performed if peak emissions were within 6dB of the average limit line.

5.7 Conducted Emission Test Result

Pass


All the modulation modes were tested the data of the worst mode (GFSK 2M PHY) are recorded in the following pages and the others modulation methods do not exceed the limits.

Channel:	LOW	Phase :	L
----------	-----	---------	---



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1500	42.43	10.28	52.71	66.00	-13.29	QP	
2	0.1620	22.78	10.28	33.06	55.36	-22.30	AVG	
3	0.2380	34.96	10.75	45.71	62.17	-16.46	QP	
4	0.2420	28.73	10.75	39.48	52.03	-12.55	AVG	
5	0.4020	21.08	11.10	32.18	47.81	-15.63	AVG	
6	0.6419	24.74	11.63	36.37	56.00	-19.63	QP	
7	0.9620	16.85	12.33	29.18	46.00	-16.82	AVG	
8	1.8420	22.83	10.07	32.90	56.00	-23.10	QP	
9	4.8819	25.54	10.26	35.80	56.00	-20.20	QP	
10	4.8819	21.28	10.26	31.54	46.00	-14.46	AVG	
11 *	29.2820	29.46	10.87	40.33	50.00	-9.67	AVG	
12	29.4420	32.36	10.88	43.24	60.00	-16.76	QP	

Channel:	LOW	Phase :	N
----------	-----	---------	---



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	0.1500	41.54	10.29	51.83	66.00	-14.17	QP	
2	0.1620	22.11	10.27	32.38	55.36	-22.98	AVG	
3	0.2420	35.20	10.69	45.89	62.03	-16.14	QP	
4 *	0.2420	29.65	10.69	40.34	52.03	-11.69	AVG	
5	0.4020	27.36	11.04	38.40	57.81	-19.41	QP	
6	0.5620	24.30	11.46	35.76	56.00	-20.24	QP	
7	0.5620	22.10	11.46	33.56	46.00	-12.44	AVG	
8	0.6380	23.38	11.64	35.02	56.00	-20.98	QP	
9	0.9620	16.30	12.26	28.56	46.00	-17.44	AVG	
10	2.1619	16.17	10.44	26.61	46.00	-19.39	AVG	
11	22.0020	27.42	10.74	38.16	60.00	-21.84	QP	
12	29.2820	23.27	10.85	34.12	50.00	-15.88	AVG	

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Measurement Level = Reading level + Correct Factor

6 Radiated Spurious Emissions

Test Requirement : FCC CFR47 Part 15 Section 15.247(d), 15.209, 15.205
 Test Method : KDB 558074 D01 15.247 Meas Guidance v05r02, ANSI C63.10-2020
 Test Result : PASS
 Measurement Distance : 3m
 Limit : See the follow table

Frequency (MHz)	Field Strength		Field Strength Limit at 3m Measurement Dist	
	uV/m	Distance (m)	uV/m	dBuV/m
0.009 ~ 0.490	2400/F(kHz)	300	10000 * 2400/F(kHz)	20log ^{(2400/F(kHz))} + 80
0.490 ~ 1.705	24000/F(kHz)	30	100 * 24000/F(kHz)	20log ^{(24000/F(kHz))} + 40
1.705 ~ 30	30	30	100 * 30	20log ⁽³⁰⁾ + 40
30 ~ 88	100	3	100	20log ⁽¹⁰⁰⁾
88 ~ 216	150	3	150	20log ⁽¹⁵⁰⁾
216 ~ 960	200	3	200	20log ⁽²⁰⁰⁾
Above 960	500	3	500	20log ⁽⁵⁰⁰⁾

6.1 EUT Operation


Operating Environment :

Temperature : 24 °C
 Humidity : 55 % RH
 Atmospheric Pressure : 101kPa


6.2 Test Setup

The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site


The test setup for emission measurement below 30MHz



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz



6.3 Spectrum Analyzer Setup

	Frequency	Detector	RBW	VBW	Remark
Receiver Setup	Below 30MHz	--	10kHz	10kHz	--
	30MHz ~ 1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
		RMS	1MHz	3MHz	Average Value

6.4 Test Procedure

1. The testing follows the guidelines in Spurious Radiated Emissions of ANSI C63.10-2020 section 6.10
2. KDB 558074 D01 15.247 Meas Guidance v05r02
3. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degree) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
6. Set to the maximum power setting and enable the EUT transmit continuously.
7. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
8. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

The radiation measurements are tested under 3-axes(X,Y,Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand), After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

9.

For Average Measurement:


VBW=10Hz, when duty cycle is no less than 98 percent.

VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Test Result:

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2402	19.00	19.00	100	0
		2440	19.00	19.00	100	0
		2480	19.00	19.00	100	0
BLE_2M	Ant1	2402	19.00	19.00	100	0
		2440	19.00	19.00	100	0
		2480	19.00	19.00	100	0


Test Graphs




BLE_1M_Ant1_2480




BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



6.5 Summary of Test Results

Test Frequency: 9KHz-30MHz

Freq. (MHz)	Ant.Pol. H/V	Emission Level (dBuV/m)	Limit 3m (dBuV/m)	Over (dB)
--	--	--	--	>20

Note:

The amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.


Distance extrapolation factor = $40\log(\text{Specific distance/ test distance})$ (dB);
Limit line = Specific limits (dBuV) + distance extrapolation factor.

Test Frequency: 30MHz ~ 1GHz

Pass.

Please refer to the following test plots for the worst test mode (GFSK (1M PHY) (CH39: 2480MHz)).


Temperature:	24°C	Relative Humidity:	55%
Pressure:	101 kPa	Polarization:	Vertical
Test Voltage:	DC 25.6V from Battery		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	63.0915	29.02	-9.83	19.19	40.00	-20.81	QP	
2		100.9338	28.13	-8.46	19.67	43.50	-23.83	QP	
3		143.8294	28.89	-10.56	18.33	43.50	-25.17	QP	
4		167.8241	33.35	-11.01	22.34	43.50	-21.16	QP	
5		233.3486	30.54	-7.18	23.36	46.00	-22.64	QP	
6		400.4318	28.70	-5.14	23.56	46.00	-22.44	QP	

Remark: Emission Level = Reading + Cable Loss + ANT Factor - AMP Factor

Temperature:	24°C	Relative Humidity:	55%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 25.6V from Battery		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		49.0144	24.96	-7.22	17.74	40.00	-22.26	QP	
2		72.0841	33.90	-11.27	22.63	40.00	-17.37	QP	
3	*	168.4137	44.17	-11.01	33.16	43.50	-10.34	QP	
4		168.4137	44.17	-11.01	33.16	43.50	-10.34	QP	
5		263.8190	37.01	-7.39	29.62	46.00	-16.38	QP	
6		336.0350	32.87	-4.13	28.74	46.00	-17.26	QP	
7		629.4772	26.29	0.39	26.68	46.00	-19.32	QP	

Remark: Emission Level=Reading+Cable Loss+ANT Factor-AMP Factor

Note:

The amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.

All modes of operation of the EUT were investigated, and only the worst-case results are reported. There were no emissions found below 30MHz within 20dB of the limit.

Test Frequency 1GHz-25GHz:

Polarization: Horizontal / CH: 2402

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4804.000	61.55	-7.40	54.15	74.00	-19.85	peak
2	*	4804.000	57.54	-7.40	50.14	54.00	-3.86	AVG
3		7206.000	52.52	0.96	53.48	74.00	-20.52	peak
4		7206.000	48.65	0.96	49.61	54.00	-4.39	AVG
5		9608.000	48.54	2.16	50.70	74.00	-23.30	peak
6		9608.000	44.21	2.16	46.37	54.00	-7.63	AVG

Polarization: Vertical / CH: 2402

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		4804.000	54.13	-7.40	46.73	74.00	-27.27	peak
2		4804.000	49.63	-7.40	42.23	54.00	-11.77	AVG
3		7206.000	49.57	0.96	50.53	74.00	-23.47	peak
4		7206.000	45.18	0.96	46.14	54.00	-7.86	AVG
5		9608.000	48.92	2.16	51.08	74.00	-22.92	peak
6	*	9608.000	45.20	2.16	47.36	54.00	-6.64	AVG

Polarization: Horizontal / CH: 2440

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4880.000	61.66	-7.45	54.21	74.00	-19.79	peak
2	*	4880.000	58.42	-7.45	50.97	54.00	-3.03	AVG
3		7320.000	51.62	0.77	52.39	74.00	-21.61	peak
4		7320.000	47.49	0.77	48.26	54.00	-5.74	AVG
5		9760.000	48.65	3.11	51.76	74.00	-22.24	peak
6		9760.000	44.10	3.11	47.21	54.00	-6.79	AVG

Polarization: Vertical / CH: 2440

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4880.000	54.56	-7.45	47.11	74.00	-26.89	peak
2		4880.000	50.80	-7.45	43.35	54.00	-10.65	AVG
3		7320.000	48.11	0.77	48.88	74.00	-25.12	peak
4		7320.000	43.44	0.77	44.21	54.00	-9.79	AVG
5		9760.000	49.18	3.11	52.29	74.00	-21.71	peak
6	*	9760.000	45.51	3.11	48.62	54.00	-5.38	AVG

Polarization: Horizontal / CH: 2480

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4960.000	58.94	-7.20	51.74	74.00	-22.26	peak
2		4960.000	54.41	-7.20	47.21	54.00	-6.79	AVG
3		7440.000	50.51	0.98	51.49	74.00	-22.51	peak
4		7440.000	46.37	0.98	47.35	54.00	-6.65	AVG
5		9920.000	48.14	3.02	51.16	74.00	-22.84	peak
6	*	9920.000	44.60	3.02	47.62	54.00	-6.38	AVG

Polarization: Vertical / CH: 2480

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		4960.000	52.13	-7.20	44.93	74.00	-29.07	peak
2		4960.000	47.55	-7.20	40.35	54.00	-13.65	AVG
3		7440.000	49.34	0.98	50.32	74.00	-23.68	peak
4		7440.000	45.40	0.98	46.38	54.00	-7.62	AVG
5		9920.000	47.55	3.02	50.57	74.00	-23.43	peak
6	*	9920.000	43.72	3.02	46.74	54.00	-7.26	AVG

Note:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. Test frequency are from 1GHz to 25GHz, the amplitude of spurious emissions which are attenuated more than 20 dB below the limits are not reported.

All modes of operation of the EUT were investigated, and only the worst-case (GFSK (1M PHY) results are reported.



Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

Polarization: Horizontal / CH: 2402

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2310.000	52.84	-12.83	40.01	74.00	-33.99	peak
2		2310.000	42.30	-12.83	29.47	54.00	-24.53	AVG
3		2390.000	52.65	-12.42	40.23	74.00	-33.77	peak
4	*	2390.000	42.36	-12.42	29.94	54.00	-24.06	AVG

Polarization: Vertical / CH: 2402

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2310.000	52.19	-12.83	39.36	74.00	-34.64	peak
2	*	2310.000	42.69	-12.83	29.86	54.00	-24.14	AVG
3		2390.000	51.55	-12.42	39.13	74.00	-34.87	peak
4		2390.000	41.77	-12.42	29.35	54.00	-24.65	AVG

Polarization: Horizontal / CH: 2480

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2483.500	59.77	-12.44	47.33	74.00	-26.67	peak
2	*	2483.500	49.24	-12.44	36.80	54.00	-17.20	AVG
3		2500.000	51.33	-12.35	38.98	74.00	-35.02	peak
4		2500.000	41.95	-12.35	29.60	54.00	-24.40	AVG

Polarization: Vertical / CH: 2480

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
1		2483.500	53.83	-12.44	41.39	74.00	-32.61	peak
2	*	2483.500	44.34	-12.44	31.90	54.00	-22.10	AVG
3		2500.000	52.00	-12.35	39.65	74.00	-34.35	peak
4		2500.000	41.79	-12.35	29.44	54.00	-24.56	AVG

Note:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin=
Emission Level - Limit
2. The amplitude of spurious emissions which are attenuated more than 20 dB below the
limits are not reported.

All modes of operation of the EUT were investigated, and only the worst-case (GFSK (1M PHY) results are reported.



7 Conduct Band Edge And Spurious Emissions Measurement

- Test Requirement : Section 15.247(d) In addition, radiated emissions which fall in the restricted bands. as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).
- Test Method : ANSI C63.10-2020 section 6.10
KDB 558074 D01 15.247 Meas Guidance v05r02
- Test Limit : Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


7.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz, Sweep = auto
Detector function = peak, Trace = max hold

7.2 Test Result


Band edge measurements

Test Graphs






BLE_2M_Ant1_High_2480




Appendix E: Conducted Spurious Emission


Test Graphs




BLE_1M_Ant1_2402_1000~26500




BLE_1M_Ant1_2440_0~Reference




BLE_1M_Ant1_2440_30~1000




BLE_1M_Ant1_2440_1000~26500




BLE_1M_Ant1_2480_0~Reference



BLE_1M_Ant1_2480_30~1000




BLE_1M_Ant1_2480_1000~26500




BLE_2M_Ant1_2402_0~Reference



BLE_2M_Ant1_2402_30~1000




BLE_2M_Ant1_2402_1000~26500




BLE_2M_Ant1_2440_0~Reference



BLE_2M_Ant1_2440_30~1000




BLE_2M_Ant1_2440_1000~26500




BLE_2M_Ant1_2480_0~Reference



BLE_2M_Ant1_2480_30~1000



BLE_2M_Ant1_2480_1000~26500



8 6dB Bandwidth Measurement

Test Requirement : FCC CFR47 Part 15 Section 15.247(a)(2)

Test Method : ANSI C63.10-2020 section 6.10
KDB 558074 D01 15.247 Meas Guidance v05r02

Test Limit : Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.1 Test Procedure


1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: RBW = 100kHz, VBW = 300kHz

8.2 Test Result


Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.680	0.5	PASS
		2440	0.680	0.5	PASS
		2480	0.680	0.5	PASS
BLE_2M	Ant1	2402	0.988	0.5	PASS
		2440	1.012	0.5	PASS
		2480	1.100	0.5	PASS

Test Graphs


BLE_1M_Ant1_2402



BLE_1M_Ant1_2440



BLE_1M_Ant1_2480




BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



9 Maximum Peak Output Power

Test Requirement : FCC CFR47 Part 15 Section 15.247(b)(3)

Test Method : ANSI C63.10-2020 section 6.10
KDB 558074 D01 15.247 Meas Guidance v05r02

Test Limit : Regulation 15.247 (b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power.


9.1 Test Procedure

1. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Measure the conducted output power and record the results in the test report.


9.2 Test Result

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	2402	0.5	≤30	PASS
		2440	0.52	≤30	PASS
		2480	0.52	≤30	PASS
BLE_2M	Ant1	2402	0.52	≤30	PASS
		2440	0.48	≤30	PASS
		2480	0.52	≤30	PASS


BLE_1M_Ant1_2402




BLE_1M_Ant1_2440




BLE_1M_Ant1_2480




BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



10 Power Spectral density

Test Requirement : FCC CFR47 Part 15 Section 15.247 (e)
 Test Method : ANSI C63.10-2020 section 6.10
 KDB 558074 D01 15.247 Meas Guidance v05r02
 Test Limit : Regulation 15.247(f) The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


10.1 Test Procedure

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 3kHz. VBW = 10kHz , Span = 1.5 times the DTS channel bandwidth(6 dB bandwidth). Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section Submit this plot.


10.2 Test Result

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-14.52	≤8.00	PASS
		2440	-14.48	≤8.00	PASS
		2480	-14.66	≤8.00	PASS
BLE_2M	Ant1	2402	-15.96	≤8.00	PASS
		2440	-16.36	≤8.00	PASS
		2480	-17.41	≤8.00	PASS


Test Graphs




BLE_1M_Ant1_2480




BLE_2M_Ant1_2402



BLE_2M_Ant1_2440



BLE_2M_Ant1_2480



11 Antenna Application

11.1 Antenna Requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

11.2 Result

The antenna is ceramic antenna, the best case gain of the antennas is -2.31 dBi, reference to the attachment for details.

12 Test Setup Photos and EUT Photos

Please see the attachment for details.

*****THE END REPORT*****

