+0/-0.3mm 120mm Output: AC: 120V~50/60Hz, 600W Max. USB-A: 5V==3A **Portable Power Station** USB-C: 5/9/12/15/20V=3A; 20V=5A Model No.: AC60P (With E-Marker chip built in) Battery Capacity: 504Wh, 22.4V==22.5Ah Wireless Charging: 5/7.5/10/15W Cigarette Lighter Port: 12V==10A Input: AC & DC output: 600W Total AC: 120V~50/60Hz, 10A Max. 60mm Battery Expansion: 22.4V==30A Total DC/PV: 12V-28V-8A, 200W Max. Discharging Temperature: -20°C-40°C Charging Temperature: 0°C-40°C Working Humidity: 10%-90% FCC ID: 2AYT3-AC60P IC: 29079-AC60P CAN ICES-003 (B) / NMB-003 (B)

SHENZHEN POWEROAK NEWENER CO., LTD.

P/N:17.0301.1256-01A1

Address: F19, BLD No.1, Kaidaer, Tongsha Rd

No.168, Xili Street, Nanshan, Shenzhen, China

3

3

4

Ъ

4

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. MADE IN CHINA

2

2

1

+0/-0.3mm

R3mm

A

В

С

D

120*60mm

C:0 M:0 Y:0 K:25



5

6

Label location map

J

6

D

В

С