



RF Exposure

For

Fluid Life Corporation

4371 Savaryn Drive SW
Edmonton, Alberta
T6X 2E8, Canada

Date: 23 December 2020
Model No.: Telematics
FCC ID: 2AYWR-FLTEL1

ONE STOP GLOBAL CERTIFICATION SOLUTIONS



Unit 205 – 8291 92 ST., Delta, BC
V4G 0A4, Canada
Phone: 604-247-0444
Fax: 604-247-0442
www.labtestcert.com

1. RF Exposure

1.1 Limits for Maximum Permissible Exposure (MPE)

TABLE 1 TO §1.1310(E)(1)—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

f = frequency in MHz. * = Plane-wave equivalent power density.

1.2 MPE Calculation Formula

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

1.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Therefore, the device is classified as applicable of Table 1, Maximum Permissible Exposure

1.4 Antenna Gain

Brand	Model	Antenna Gain (dBi)	Freq. Range (GHz)	Antenna Type	Connector Type
TAOGLAS	MA600.A.AB C.007	-4.7	0.824 ~ 0.896	MA600 Spartan Screw mount 3 in1 Combination Antenna	SMA(M)
		-2.7	1.71 ~ 1.88		RP-SMA(M)
		-2.3	2.4 ~ 2.5		

1.5 Calculation Result of Maximum Conducted Power

Operation Mode	Evaluation Frequency (MHz)	Max Power (mW)	Antenna Gain (numeric)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
Cellular 1	846.6	326.6	0.339	20	0.0213	0.551
Cellular 2	1712.4	323.6	0.537	20	0.0334	1
Cellular 3	1880	297.9	0.537	20	0.0308	1
WLAN	2437	92.7	0.589	20	0.0105	1

1.6 Colocation calculation

Per KDB Publication 447498 D01, Section 7.2, Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 , according to calculated/estimated, numerically modeled, or measured field strengths or power density. The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to the MPE limit at the test frequency.

$$[Pd(1) / LPd(1)] + [Pd(2) / LPd(2)] + \dots + [Pd(n) / LPd(n)] < 1,$$

Where,

Pd(n) = Power density of nth transmitter at 20 cm

LPd(n) = Power density limit for the nth transmitter

$$[Pd(\text{Cellular 1}) / 0.551] + [Pd(\text{Cellular 2}) / 1] + [Pd(\text{Cellular 3}) / 1] + [Pd(\text{WLAN}) / 1] = 0.1134 < 1$$

Conclusion. The device complies with KDB Publication 447498 D01 RF radiation exposure limit as a mobile device under the collocation conditions described above.