

TEST REPORT

Product Name : Jaffas Bluetooth Module
Brand Mark : Cricut
Model No. : CBM002 v2
FCC ID : 2AYX6-JAFA
Report Number : BLA-EMC-202303-A6504
Date of Sample Receipt : 2023/3/16
Date of Test : 2023/3/17 to 2023/8/3
Date of Issue : 2023/8/3
Test Standard : KDB447498D04 General RF Exposure
Guidance v01
Test Result : Pass

Prepared for:

Cricut Inc.

10855 South River Front Parkway, South Jordan, Utah, USA

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

**Building C, No. 107, Shihuan Road, Shiyuan Sub-District, Baoan District,
Shenzhen, Guangdong Province, China**

TEL: +86-755-23059481

Compiled by:

charlie

Approved by:

Blue Zheng

Review by:

Sueels

Date:

2023/8/3



REPORT REVISE RECORD

Version No.	Date	Description
00	2023/8/3	Original

TABLE OF CONTENTS

1 GENERAL INFORMATION	4
2 GENERAL DESCRIPTION OF E.U.T.....	5
3 LABORATORY LOCATION	6
4 RF EXPOSURE COMPLIANCE REQUIREMENT	7
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	7
<i>Standard Requirement</i>	7
<i>Limits</i>	7

1 GENERAL INFORMATION

Applicant	Cricut Inc.
Address	10855 South River Front Parkway, South Jordan, Utah, USA
Manufacturer	Cricut Inc.
Address	10855 South River Front Parkway, South Jordan, Utah, USA
Factory	Microtronics Technology SDN BHD
Address	No. 10 & 10A, Jalan Bayu, Kawasan Perindustrian Hsail, 81200, Tampoi, Johor, Malaysia
Product Name	Jaffas Bluetooth Module
Test Model No.	CBM002 v2

2 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	v2
Software Version	application-Cricut-v1.8-573382650-wd.bin
BLE	
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Ceramic Antenna
Antenna Gain:	1.69dBi(Provided by the customer)
BR/EDR	
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Ceramic Antenna
Antenna Gain:	1.69dBi(Provided by the customer)

3 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

4 RF EXPOSURE COMPLIANCE REQUIREMENT

4.1 RF EXPOSURE COMPLIANCE REQUIREMENT

Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

Limits

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)										
		5	10	15	20	25	30	35	40	45	50
	300	39	65	88	110	129	148	166	184	201	217
	450	22	44	67	89	112	135	158	180	203	226
	835	9	25	44	66	90	116	145	175	207	240
	1900	3	12	26	44	66	92	122	157	195	236
	2450	3	10	22	38	59	83	111	143	179	219
	3600	2	8	18	32	49	71	96	125	158	195
	5800	1	6	14	25	40	58	80	106	136	169

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

$$EIRP = p_t \times g_t = (EXd)^{2/30}$$

where:

p_t = transmitter output power in watts,

g_t = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10((dBuV/m)/20)/106$

d = measurement distance in meters (m)---3m

$$S_{opt} = (EXd)^{2/30} \times g_t$$

$$\text{Ant gain} = 1.69 \text{ dBi}$$

$$\text{Max Output power} = -0.492 \text{ dBm} @ 2442 \text{ MHz}$$

$$\text{ERP} = -0.492 \text{ dBm} + 1.62 \text{ dBi} - 2.15 = -0.952 \text{ dBm}$$

So

ERP is worse case

$$10^{-0.049} = 0.893 \text{ mW} < 3060 \text{ mW}$$

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.