Test Report No.: RZCE2021-0124-H

RF Test Report

EUT : module

MODEL : YGC-C302

BRAND NAME : N/A

CLIENT : HANGZHOU YAGUAN

TECHNOLOGY CO.,LTD

Classification Of Test: Commission Test

Vkan Certification & Testing Co., Ltd.



Test Report No.: R	-H			Page 2 of 8		
		Name :HANGZHOU YAGUAN TECHNOLOGY CO.,LTD				
Client		Address :33rd Floor, T4 US Center, European and American Financial City, Yuhang District,Hangzhou,Zhejiang,China				
Manufacturer		Name :She	Name :Shenzhen SiboZhilian Technology Co., Ltd			
		Address :903,building8,Chuangxin Valley, Dashi 2nd Road,Nanshan District, Shenzhen				
		Name :mo	dule			
		Model/Typ	e:YGC-C3	02		
Equipment Ur	nder Test	Trade marl	k :N/A			
		SerialNO.:N/A				
		Sampe NC				
Date of Receipt. 2021.02.24		- Jumpo Ito		f Testing	2021.02.24~2021.03.11	
Test Specificat		ion			Test Result	
FCC Part 2 (Section KDB 447498 D IEEE C95.1		DACC		PASS		
Evaluation of Test Result		The equipment under test was found to comply with the requirements of the standards applied.				
					Issue Date: 2021.03.11	
Tested by:		Reviewed by:			Approved by:	
Robert Cheng_ Name Signature		<u>/</u> Name	Andy Zhu Name Signature		<u>Sam Tung</u> Name Signature	
Other Aspects: N	Other Aspects: NONE.					
Abbreviations:OK, Pas	s= passed	Fail = failed	N/A= not ap	pplicable	EUT= equipment, sample(s) under tested	
This test report relates only to the EUT, and shall not be reproduced except in full, without written approval of CVC.						



Test Report No.: RZCE2021-0124-H	Page 3 of 8
TABLE OF CONTENTS	
RELEASE CONTROL RECORD	4
1. GERTIFICATION	5
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER	6



Test Report No.: RZCE2021-0124-H Page 4 of 8

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RZCE2021-0124-H	Original release	2021.03.11



Test Report No.: RZCE2021-0124-H	Page 5 of 8
----------------------------------	-------------

1. GERTIFICATION

FCC ID	2AYYQ-YGC-C302
PRODUCT	module
BRAND	N/A
MODEL	YGC-C302
ADDITIONAL MODEL	N/A
APPLICANT	HANGZHOU YAGUAN TECHNOLOGY CO.,LTD
	FCC Part 2 (Section 2.1091)
STANDARDS	KDB 447498 D01
	IEEE C95.1

2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE(MHz)	ELECTRIC FIELD MAGNETIC FIELD STRENGTH (V/m) STRENGTH (A/m)		POWER DENSITY(mW/cm²)	AVERAGE TIME(minutes)			
LIMI'	LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500 F/1500 30							
1500-100,000			1.0	30			

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



Test Report No.: RZCE2021-0124-H Page 6 of 8

5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Frequency Band	Antenna Gain (dBi)	Antenna Type	
Wi-Fi 2.4GHz	2	PCB Antenna	
BT-LE(GFSK)	2	PCB Antenna	

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
802.11b	2412-2462MHz	13	+-2	11	15
802.11g	2412-2462MHz	14	+-2	12	16
802.11n HT20	2412-2462MHz	14	+-2	12	16
BT-LE (GFSK)	2402-2480MHz	6	+-2	4	8

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
BT-LE (GFSK)	2480	6.44
802.11b	2437	12.82
802.11g	2437	14.60
802.11n HT20	2437	14.42



Test Report No.: RZCE2021-0124-H	Page 7 of 8
Test Report No.: RZCE2021-0124-H	Page / of 8

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
Wi-Fi 2.4GHz	39.811	2	20	0.012552	1.0
BT-LE (GFSK)	6.310	2	20	0.001989	1.0

CONCLUSION:

The BT and WLAN can transmit simultaneously, the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1 CPD = Calculation power density LPD = Limit of power density

(0.012552/1)+(0.001989/1) = 0.014541<1, which is less than the "1" limit.



Test Report No.: RZCE2021-0124-H Page 8 of 8

Important

- (1) The test report is valid with the official seal of the laboratory and the signatures of Test engineer, Author and Reviewer simultaneously.
- (2) The test report is invalid if altered.
- (3) Any photocopies or part photocopies in the test report are forbidden without the written permission from the laboratory.
- (4) Objections to the test report must be submitted to the laboratory within 15 days.
- (5) Generally, commission test is responsible for the tested samples only.

Address of the laboratory:

Vkan Certification & Testing Co., Ltd.

Address: No.3, Tiantaiyi Road, Kaitai Avenue, Science City, Guangzhou, China

Post Code: 510663 Tel: 020-32293888

FAX: 020-32293889 E-mail: office@cvc.org.cn