

RF Exposure Evaluation Report

APPLICANT : VinCSS Internet Security Services Limited
Liability Company

EQUIPMENT : VinCSS FIDO2 Fingerprint

BRAND NAME : VinCSS

MODEL NAME : VFIDO2B

FCC ID : 2AYYU-VFIDO2B

STANDARD : 47 CFR PART 2.1093
FCC KDB 447498 D01 v06

We, Sporton International (Kunshan) Inc., would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1093 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Nick Hu

Reviewed by: Nick Hu / Supervisor

Kat Yin

Approved by: Kat Yin / Manager



Sporton International (Kunshan) Inc.

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE EVALUATION	7



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA171908	Rev. 01	Initial issue of report	Aug. 30, 2021



1. Administration Data

1.1. Testing Laboratory

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory		
Test Firm	Sporton International (Kunshan) Inc.	
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958	
Test Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CN1257	314309

Applicant	
Company Name	VinCSS Internet Security Services Limited Liability Company
Address	No. 7, Bang Lang 1 Street, Viet Hung Ward, Long Bien District, Ha Noi City, Viet Nam

Manufacturer	
Company Name	VinSmart Research and Manufacture Joint Stock Company
Address	Lot CN1-06B-1&2, Hi-tech Industrial Park 1, Hoa Lac Hi-tech Park, Ha Bang Commune, Thach That District, Ha Noi City, Viet Nam



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	VinCSS FIDO2 Fingerprint
Brand Name	VinCSS
Model Name	VFIDO2B
FCC ID	2AYYU-VFIDO2B
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz NFC: 13.56 MHz
Mode	Bluetooth LE NFC:ASK
Antenna Type	Bluetooth : Ceramic Patch Antenna NFC : Loop Antenna
Antenna Gain	Bluetooth: gain 2.7 dBi
Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.	

Comments and Explanations:
1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.



3. Maximum RF Tune Up power among production units

<Bluetooth>

Mode	Maximum Average Power (dBm)
Bluetooth LE	6.0



4. RF Exposure Evaluation

Mode	Average power(dBm)
	Bluetooth LE
Bluetooth LE	6.0

Note:

- Per KDB 447498 D01v06 the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:
 - $[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [\sqrt{f(GHz)}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
6.0	< 5	2.48	1.3

Conclusion:

Per KDB 447498 D01v06, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 1.3 which is ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, 1-g SAR and extremity SAR testing is not required, and complied with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for 1g SAR and 4.0 W/kg for extremity SAR) specified in FCC 47 CFR part 2 (2.1093).

-----THE END-----