

# TEST REPORT

Product Name: Winees Spotlight Battery Cam with Solar Panel  
FCC ID: 2AYZ8WP25002134  
Trademark: N/A  
Model Number: WP25002134  
Prepared For: Linkzone Technology Co., Limited  
Address: Room 510, 5/F, Wayson Commercial Building, 28 Connaught Road West, Sheung Wan, Hong Kong, China  
Manufacturer: Linkzone Technology Co., Limited  
Address: Room 510, 5/F, Wayson Commercial Building, 28 Connaught Road West, Sheung Wan, Hong Kong, China  
Prepared By: Shenzhen CTB Testing Technology Co., Ltd.  
Address: 1&2/F., Building A, No.26, Xinhe Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China  
Sample Received Date: Aug. 15, 2023  
Sample tested Date: Aug. 15, 2023 to Sep. 07, 2023  
Issue Date: Sep. 07, 2023  
Report No.: CTB230907011RFX  
Test Standards: 47 CFR Part 15 Subpart E  
KDB 789033 V02r01  
Test Results: PASS  
Remark: This is WIFI-5GHz band radio test report.

Compiled by:

*Zhou kui*Zhou Kui

Reviewed by:

*Arron Liu*Arron Liu

Approved by:

Bin Mei / Director

Note: If there is any objection to the inspection results in this report, please submit a written report to the company within 15 days from the date of receiving the report. The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen CTB Testing Technology Co., Ltd. this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client. "\*" indicates the testing items were fulfilled by subcontracted lab. "#" indicates the items are not in CNAS accreditation scope.

**TABLE OF CONTENT**

Test Report Declaration	Page
<b>1. VERSION</b> .....	4
<b>2. TEST SUMMARY</b> .....	5
<b>3. MEASUREMENT UNCERTAINTY</b> .....	6
<b>4. PRODUCT INFORMATION AND TEST SETUP</b> .....	7
4.1 Product Information .....	7
4.2 Test Setup Configuration .....	7
4.3 Support Equipment .....	7
4.5 Test Mode .....	9
4.6 Test Environment .....	9
<b>5. TEST FACILITY AND TEST INSTRUMENT USED</b> .....	10
5.1 Test Facility .....	10
5.2 Test Instrument Used .....	10
<b>6. AC POWER LINE CONDUCTED EMISSION</b> .....	12
6.1 Block Diagram Of Test Setup .....	12
6.2 Limit .....	12
6.3 Test procedure .....	12
6.4 Test Result .....	14
<b>7. RADIATED SPURIOUS EMISSIONS</b> .....	16
7.1 Block Diagram Of Test Setup .....	16
7.2 Limit .....	16
7.3 Test procedure .....	17
7.4 Test Result .....	18
<b>8. BAND EDGE</b> .....	24
8.1 Block Diagram Of Test Setup .....	24
8.2 Limit .....	24
8.3 Test procedure .....	24
8.4 Test Result .....	25
<b>9. CONDUCTED PEAK OUTPUT POWER</b> .....	33
9.1 Block Diagram Of Test Setup .....	33
9.2 Limit .....	33
9.3 Test procedure .....	34
9.4 Test Result .....	35
<b>10. EMISSION BANDWIDTH&amp; OCCUPIED BANDWIDTH</b> .....	49
10.1 Block Diagram Of Test Setup .....	49
10.2 Limits .....	49
10.3 Test Procedure .....	49
10.4 Test Results .....	51
<b>11. POWER SPECTRAL DENSITY</b> .....	65
11.1 Block Diagram Of Test Setup .....	65
11.2 Limit .....	65
11.3 Test procedure .....	65
11.4 Test Result .....	67
<b>12. FREQUENCY STABILITY</b> .....	81
12.1 Block Diagram Of Test Setup .....	81
12.2 Limit .....	81
12.3 Test procedure .....	81
12.4 Test Result .....	81
<b>13. OPERATION IN THE ABSENCE OF INFORMATION TO THE TRANSMIT</b> .....	82
13.1 Requirement .....	82



13.2 Test Results ..... 82

14. ANTENNA REQUIREMENT ..... 83

15. EUT TEST SETUP PHOTOGRAPHS ..... 84

(NOTE: N/A MEANS NOT APPLICABLE)



1. VERSION

Report No.	Issue Date	Description	Approved
CTB230907011RFX	Sep. 07, 2023	Original	Valid

## 2. TEST SUMMARY

The Product has been tested according to the following specifications:

Test Item	Test Requirement	Test method	Result
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15 Subpart E Section 15.407 (b)(9)	ANSI C63.10-2013	PASS
<b>Radiated Spurious emissions</b>	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033v02r01	PASS
<b>Band edge</b>	47 CFR Part 15 Subpart E Section 15.205/15.407(b)	KDB789033v02r01	PASS
<b>Conducted Peak Output Power</b>	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033v02r01	PASS
<b>Emission Bandwidth &amp; Occupied Bandwidth</b>	47 CFR Part 15 Subpart E Section 15.407 (a)(e)	KDB789033v02r01	PASS
<b>Power Spectral Density</b>	47 CFR Part 15 Subpart E Section 15.407 (a)	KDB789033v02r01	PASS
<b>Frequency stability</b>	47 CFR Part 15 Subpart E Section 15.407 (g)	KDB789033v02r01	PASS
<b>Operation in the absence of information to the transmit</b>	47 CFR Part 15 Subpart E Section 15.407 (c)	47 CFR Part 15 Subpart E	PASS
<b>Antenna Requirement</b>	47 CFR Part 15 Subpart E Section 15.203	/	PASS

Remark:

Test according to ANSI C63.10-2013.

### 3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Uncertainty
1	Occupancy bandwidth	U=±54.3Hz
2	Adjacent channel power	U=±1.3dB
3	Conducted Adjacent channel power	U=±1.38dB
4	Conducted output power Above 1G	U=±1.0dB
5	Conducted output power below 1G	U=±0.9dB
6	Power Spectral Density , Conduction	U=±1.0dB
7	Conduction spurious emissions	U=±2.8dB
8	Out of band emission	U=±54Hz
9	3m chamber Radiated spurious emission(30MHz-1GHz)	U=±4.3dB
10	3m chamber Radiated spurious emission(1GHz-18GHz)	U=±4.5dB
11	humidity uncertainty	U=±5.3%
12	Temperature uncertainty	U=±0.59℃
13	Supply volyages	U=±3%
14	Time	U=±5%
15	Conducted Emission (150KHz-30MHz)	3.2 dB
16	3m chamber Radiated spurious emission(9KHz-30MHz)	4.8dB
17	3m chamber Radiated spurious emission(18GHz-40GHz)	3.4dB

#### 4. PRODUCT INFORMATION AND TEST SETUP

##### 4.1 Product Information

Model(s): WP25002134

Model Description: N/A

Wi-Fi Specification: IEEE 802.11a/b/g/n/ac

Hardware Version: WP25002134

Software Version: N/A

Operation Frequency: IEEE 802.11a/n/ac(20M): 5150MHz ~5250MHz/ 4 channel  
 IEEE 802.11n/ac(40M): 5150MHz ~5250MHz/ 2 channel  
 IEEE 802.11ac(80M): 5150MHz ~5250MHz/ 1 channel

IEEE 802.11a/n/ac(20M): 5250MHz ~5350 MHz/ 4 channel  
 IEEE802.11n/ac(40M): 5250MHz ~5350 MHz/ 2 channel  
 IEEE802.11ac(80M): 5250MHz ~5350 MHz/ 1 channel

IEEE 802.11a/n/ac(20M): 5470MHz ~5725 MHz/ 11 channel  
 IEEE802.11n/ac(40M): 5470MHz ~5725 MHz/ 5 channel  
 IEEE802.11ac(80M): 5470MHz ~5725 MHz/ 3 channel

IEEE 802.11a/n/ac(20M): 5725MHz ~5850MHz/ 5 channel  
 IEEE 802.11n/ac(40M): 5725MHz ~5850MHz/ 2 channel  
 IEEE 802.11ac(80M): 5725MHz ~5850MHz/ 1 channel

Max. RF output power: WiFi (5G): 13.352dBm

Type of Modulation: WiFi: OFDM

Antenna installation: FPC antenna

Antenna Gain: WiFi (5.2G) : 2.71dBi  
 WiFi (5.3G) : 2.99dBi  
 WiFi (5.6G) : 2.27dBi  
 WiFi (5.8G) : 2.18dBi

Ratings: DC 5V charging from adapter  
 DC 3.7V from battery

##### 4.2 Test Setup Configuration

See test photographs attached in EUT TEST SETUP PHOTOGRAPHS for the actual connections between Product and support equipment.

##### 4.3 Support Equipment

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
1	Adapter	JIYIN	JY-05100C	/	/

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

#### 4.4 Channel List

For 802.11a/n/ac( 20M) Operation in the 5150MHz ~5250 MHz band			
Channel	Frequency	Channel	Frequency
36	5180MHz	44	5220MHz
40	5200MHz	48	5240MHz
For 802.11a/n/ac( 20M) Operation in the 5250MHz ~5350 MHz band			
Channel	Frequency	Channel	Frequency
52	5260MHz	60	5300MHz
56	5280MHz	64	5320MHz
For 802.11a/n/ac( 20M) Operation in the 5470MHz ~5725 MHz band			
Channel	Frequency	Channel	Frequency
100	5500MHz	124	5620 MHz
104	5520MHz	128	5640 MHz
108	5540MHz	132	5660 MHz
112	5560MHz	136	5680MHz
116	5580MHz	140	5700MHz
120	5600 MHz		
For 802.11a/n/ac( 20M) Operation in the 5725MHz ~5850 MHz band			
Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz	NA	NA
For 802.11n/ac(40M) Operation in the 5150MHz ~5250 MHz band			
Channel	Frequency	Channel	Frequency
38	5190MHz	46	5230MHz
For 802.11n/ac(40M) Operation in the 5250MHz ~5350 MHz band			
Channel	Frequency	Channel	Frequency
54	5270MHz	62	5310MHz
For 802.11n/ac(40M) Operation in the 5470MHz ~5725 MHz band			
Channel	Frequency	Channel	Frequency
102	5510MHz	126	5630MHz
110	5550MHz	134	5670MHz
118	5590MHz		
For 802.11n/ac(40M) Operation in the 5725MHz ~5850 MHz band			
Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz
For 802.11ac(80M) Operation in the 5150MHz ~5250 MHz band			
Channel	Frequency	Channel	Frequency
42	5210MHz	NA	NA
For 802.11ac(80M) Operation in the 5250MHz ~5350 MHz band			
Channel	Frequency	Channel	Frequency
58	5290MHz	NA	NA
For 802.11ac(80M) Operation in the 5470MHz ~5725 MHz band			
Channel	Frequency	Channel	Frequency
106	5530MHz	138	5690MHz
122	5610 MHz		
For 802.11ac(80M) Operation in the 5725MHz ~5850 MHz band			
Channel	Frequency	Channel	Frequency
155	5775MHz	NA	NA



NOTE: DutyCycle&gt;98%.

Test mode	rate
802.11a	54M
802.11n	500M
802.11/ac	500M

#### 4.5 Test Mode

All test mode(s) and condition(s) mentioned were considered and evaluated respectively by performing full tests, the worst data were recorded and reported.

Test Mode	Tx/Rx	RF Channel		
		Low(L)	Middle(M)	High(H)
802.11a/n/ac(20M)	5150MHz ~5250 MHz	Channel 36	Channel 40	Channel 48
		5180MHz	5200MHz	5240MHz
802.11n/ac(40M)		Channel 38	N/A	Channel 46
		5190MHz	N/A	5230MHz
802.11ac(80M)		N/A	Channel 42	N/A
		N/A	5210MHz	N/A
802.11a/n/ac(20M)	5250MHz ~5350 MHz	Channel 52	Channel 56	Channel 64
		5260MHz	5280MHz	5320MHz
802.11n/ac(40M)		Channel 54	N/A	Channel 62
		5270MHz	N/A	5310MHz
802.11ac(80M)		N/A	Channel 58	N/A
		N/A	5290MHz	N/A
802.11a/n/ac(20M)	5470MHz ~5725 MHz	Channel 100	Channel 116	Channel 140
		5500MHz	5580MHz	5700MHz
802.11n/ac(40M)		Channel 102	N/A	Channel 134
		5510MHz	N/A	5670MHz
802.11ac(80M)		N/A	Channel 106	N/A
		N/A	5530MHz	N/A
802.11a/n/ac(20M)	5725MHz ~5850 MHz	Channel 149	Channel 157	Channel 165
		5745MHz	5785MHz	5825MHz
802.11n/ac(40M)		Channel 151	N/A	Channel 159
		5755MHz	N/A	5795MHz
802.11ac(80M)		N/A	Channel 155	N/A
		N/A	5775MHz	N/A

#### 4.6 Test Environment

Humidity(%):	54
Atmospheric Pressure(kPa):	101
Normal Voltage(DC):NV	3.7V
Normal Temperature(°C):NT	23
Low Temperature(°C):LT	0
High Temperature(°C):HT	40

## 5. TEST FACILITY AND TEST INSTRUMENT USED

### 5.1 Test Facility

All measurement facilities used to collect the measurement data are located at 1&2F., Building A, No. 26, Xinh Road, Xinqiao, Xinqiao Street, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

### 5.2 Test Instrument Used

Item	Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	Agilent	N9020A	MY52090073	2024.07.05
2	Power Sensor	Agilent	U2021XA	MY56120032	2024.07.05
3	Power Sensor	Agilent	U2021XA	MY56120034	2024.07.05
4	Communication test set	R&S	CMW500	108058	2024.07.05
5	Spectrum Analyzer	KEYSIGHT	N9020A	MY51289897	2024.07.05
6	Signal Generator	Agilent	N5181A	MY50140365	2024.07.05
7	Vector signal generator	Agilent	N5182A	MY47420195	2024.07.05
8	Communication test set	Agilent	E5515C	MY50102567	2024.07.06
9	2.4 GHz Filter	Shenxiang	MSF2400-2483.5MS-1154	20181015001	2024.07.05
10	5 GHz Filter	Shenxiang	MSF5150-5850 MS-1155	20181015001	2024.07.06
11	Filter	Xingbo	XBLBQ-DZA120	190821-1-1	2024.07.06
12	BT&WI-FI Automatic test software	Microwave	MTS8000	Ver. 2.0.0.0	/
13	Rohde & Schwarz SFU Broadcast Test System	R&S	SFU	101017	2023.10.30
14	Temperature humidity chamber	Hongjing	TH-80CH	DG-15174	2024.07.05
15	234G Automatic test software	Microwave	MTS8200	Ver. 2.0.0.0	/
16	966 chamber	C.R.T.	966	/	2024.08.11
17	Receiver	R&S	ESPI	100362	2024.07.05
18	Amplifier	HP	8447E	2945A02747	2024.07.05
19	Amplifier	Agilent	8449B	3008A01838	2024.07.05
20	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	2024.07.08

21	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA9120D	01911	2024.07.08
22	EMI test software	Fala	EZ-EMC	FA-03A2 RE	/
23	Loop Antenna	Schwarzbeck	FMZB 1519B	1519B-224	2024.07.08
24	loop antenna	ZHINAN	ZN30900A	GTS534	/
25	40G Horn antenna	A/H/System	SAS-574	588	2023.10.30
26	Amplifier	AEROFLEX	Aeroflex	097	2023.10.30

**Continuous disturbance**


No.	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	LISN	ROHDE&SCHWARZ	ESH3-Z5	100318	2024.07.05
2	Pulse limiter	ROHDE&SCHWARZ	ESH3Z2	357881052	2024.07.05
3	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428/003	2024.07.05
4	Coaxial cable	ZDECL	Z302S-NJ-SMA J-12M	18091905	2024.07.05
5	ISN	Schwarzbeck	NTFM8158	183	2024.07.05
6	Communication test set	Agilent	E5515C	MY50102567	2024.07.05
7	Communication test set	R&S	CMW500	108058	2024.07.05
8	EZ-EMC	Frad	EMC-con3A1.1	/	/

**Radiated emission**

No.	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Double Ridged Broadband Horn Antenna	Schwarzbeck	BBHA 9120 D	01911	2024.07.08
2	TRILOG Broadband Antenna	Schwarzbeck	VULB 9168	00869	2024.07.08
3	Amplifier	Agilent	8449B	3008A01838	2024.07.05
4	Amplifier	HP	8447E	2945A02747	2024.07.05
5	EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100428/003	2024.07.05
6	Coaxial cable	ETS	RFC-SNS-100-NMS-80 NI	/	2024.07.05
7	Coaxial cable	ETS	RFC-SNS-100-NMS-20 NI	/	2024.07.05
8	Coaxial cable	ETS	RFC-SNS-100-SMS-20 NI	/	2024.07.05
9	Coaxial cable	ETS	RFC-NNS-100-NMS-300 NI	/	2024.07.05
10	Communication test set	Agilent	E5515C	MY50102567	2024.07.05
11	Communication test set	R&S	CMW500	108058	2024.07.05
12	EZ-EMC	Frad	EMC-con3A1.1	/	/

## 6. AC POWER LINE CONDUCTED EMISSION

### 6.1 Block Diagram Of Test Setup



### 6.2 Limit

Table 4 – AC power-line conducted emissions limits		
Frequency (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 <sup>Note 1</sup>	56 to 46 <sup>Note 1</sup>
0.5 - 5	56	46
5 - 30	60	50

**Note 1:** The level decreases linearly with the logarithm of the frequency.

\* Decreasing linearly with the logarithm of the frequency

### 6.3 Test procedure


- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50 $\Omega$ /50 $\mu$ H + 5 $\Omega$  linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0,4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0,8 m from the boundary of the unit under

test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0,8 m from the LISN 2.

- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.


6.4 Test Result

Test Specification: Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector
1		0.2802	28.97	9.69	38.66	60.81	-22.15	QP
2		0.2802	15.29	9.69	24.98	50.81	-25.83	AVG
3	*	0.5299	38.95	9.69	48.64	56.00	-7.36	QP
4		0.5299	11.60	9.69	21.29	46.00	-24.71	AVG
5		1.4500	29.12	9.79	38.91	56.00	-17.09	QP
6		1.4500	16.06	9.79	25.85	46.00	-20.15	AVG
7		2.8740	28.38	9.85	38.23	56.00	-17.77	QP
8		2.8740	13.48	9.85	23.33	46.00	-22.67	AVG
9		8.5539	29.04	10.10	39.14	60.00	-20.86	QP
10		8.5539	14.19	10.10	24.29	50.00	-25.71	AVG
11		21.9020	26.43	10.66	37.09	60.00	-22.91	QP
12		21.9020	12.47	10.66	23.13	50.00	-26.87	AVG

Test Specification: Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2260	30.35	9.70	40.05	62.60	-22.55	QP
2		0.2260	15.07	9.70	24.77	52.60	-27.83	AVG
3	*	0.5380	39.79	9.69	49.48	56.00	-6.52	QP
4		0.5380	15.65	9.69	25.34	46.00	-20.66	AVG
5		1.8939	27.15	9.81	36.96	56.00	-19.04	QP
6		1.8939	13.68	9.81	23.49	46.00	-22.51	AVG
7		4.0060	24.87	9.90	34.77	56.00	-21.23	QP
8		4.0060	14.23	9.90	24.13	46.00	-21.87	AVG
9		8.5700	27.94	10.10	38.04	60.00	-21.96	QP
10		8.5700	13.90	10.10	24.00	50.00	-26.00	AVG
11		19.3700	27.06	10.55	37.61	60.00	-22.39	QP
12		19.3700	10.42	10.55	20.97	50.00	-29.03	AVG

Remark:

- Factor = Cable loss + LISN factor, Margin = Limit – Level
- All modes were tested at AC 120V and 240V, only the worst result of AC 120V 60Hz was reported.
- All the test modes completed for test. Only the worst result of was reported.

## 7. RADIATED SPURIOUS EMISSIONS

### 7.1 Block Diagram Of Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1GHz

### 7.2 Limit

Spurious Emissions:

Frequency	Field strength (dB $\mu$ V/m)	Remark	Measurement distance (m)
0.009MHz-0.490MHz	$20\log 2400/F$ (kHz) + 80	Quasi-peak	3
0.490MHz-1.705MHz	$20\log 24000/F$ (kHz) + 40	Quasi-peak	3
1.705MHz-30MHz	$20\log 30$ + 40	Quasi-peak	3
30MHz-88MHz	40.0	Quasi-peak	3
88MHz-216MHz	43.5	Quasi-peak	3
216MHz-960MHz	46.0	Quasi-peak	3
960MHz-1GHz	54.0	Quasi-peak	3
Above 1GHz	54.0	Average	3

Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.



If radiated measurements are performed, field strength is then converted to EIRP as follows:

(i)  $EIRP = (E \cdot d)^2 / 30$

where:

- E is the field strength in V/m;
- d is the measurement distance in meters;
- EIRP is the equivalent isotropically radiated power in watts.

(ii) Working in dB units, the above equation is equivalent to:

$$EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$$

(iii) Or, if d is 3 meters:

$$EIRP[dBm] = E[dB\mu V/m] - 95.2$$

### 7.3 Test procedure

#### Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

#### Above 1GHz test procedure as below:

- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter( Above 18GHz the distance is 1 meter and table is 1.5 meter).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel
- j. Repeat above procedures until all frequencies measured was complete.

Receiver set:

Frequency	Detector	RBW	VBW	Remark
0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
30MHz-1GHz	Quasi-peak	120 kHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The X-plane results were found as the worst case and were shown in this report.

7.4 Test Result

30MHz-1GHz Test Results:  
 Modulation : 802.11a (the worst data)  
 Test Channel : 5180MHz  
 Antenna polarity: H



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		54.9310	27.21	-7.08	20.13	40.00	-19.87	QP
2		164.3301	30.58	-5.99	24.59	43.50	-18.91	QP
3		270.8492	33.75	-6.84	26.91	46.00	-19.09	QP
4		416.1791	33.81	-2.21	31.60	46.00	-14.40	QP
5		762.0384	31.77	5.05	36.82	46.00	-9.18	QP
6	*	948.7609	31.44	7.63	39.07	46.00	-6.93	QP

Antenna polarity: V



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		39.7146	35.28	-6.48	28.80	40.00	-11.20	QP
2		145.3506	32.08	-5.48	26.60	43.50	-16.90	QP
3		263.8190	37.25	-7.17	30.08	46.00	-15.92	QP
4		416.1791	36.31	-2.21	34.10	46.00	-11.90	QP
5		601.4265	34.85	2.47	37.32	46.00	-8.68	QP
6	*	948.7610	33.59	7.63	41.22	46.00	-4.78	QP

Remark: Factor = Cable lose + Antenna factor - Pre-amplifier; Margin = Measurement – Limit

1. The margin of 9K-30MH measurement exceeds 20dB, so the test chart is not included. Test Mode: 802.11a20 (the worst)

Radiated Spurious Emission ( Above 1GHz):  
 Modulation : 802.11(a) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5180MHz									
10360	41.22	16.39	57.61	74	-16.39	PK	1.53	58	H
10360	25.43	16.39	41.82	54	-12.18	AV	1.05	278	H
10360	39.82	16.39	56.21	74	-17.79	PK	1.19	8	V
10360	27.36	16.39	43.75	54	-10.25	AV	1.44	32	V
Channel:5240MHz									
10480	41.22	16.11	57.33	74	-16.67	PK	1.72	47	H
10480	26.28	16.11	42.39	54	-11.61	AV	1.59	349	H
10480	41.90	16.11	58.01	74	-15.99	PK	1.11	108	V
10480	25.08	16.11	41.19	54	-12.81	AV	1.88	178	V
Channel:5260MHz									
10520	40.40	16.39	56.79	74	-17.21	PK	1.46	64	H
10520	26.58	16.39	42.97	54	-11.03	AV	1.05	240	H
10520	39.00	16.39	55.39	74	-18.61	PK	1.46	138	V
10520	27.66	16.39	44.05	54	-9.95	AV	1.25	295	V
Channel:5320MHz									
10640	40.40	16.39	56.79	74	-17.21	PK	1.51	135	H
10640	26.14	16.39	42.53	54	-11.47	AV	1.57	205	H
10640	39.96	16.39	56.35	74	-17.65	PK	1.58	97	V
10640	25.31	16.39	41.70	54	-12.30	AV	1.05	270	V
Channel:5500MHz									
11000	39.88	16.39	56.27	74	-17.73	PK	1.36	319	H
11000	26.44	16.39	42.83	54	-11.17	AV	1.27	0	H
11000	40.74	16.39	57.13	74	-16.87	PK	1.57	252	V
11000	25.94	16.39	42.33	54	-11.67	AV	1.02	207	V

Channel:5700MHz									
11400	39.39	16.39	55.78	74	-18.22	PK	1.35	43	H
11400	25.98	16.39	42.37	54	-11.63	AV	1.06	341	H
11400	39.26	16.39	55.65	74	-18.35	PK	1.54	47	V
11400	25.22	16.39	41.61	54	-12.39	AV	1.19	172	V
Channel:5745MHz									
11490	40.41	17.46	57.87	74	-16.13	PK	1.70	292	H
11490	25.36	17.46	42.82	54	-11.18	AV	1.32	98	H
11490	39.22	17.46	56.68	74	-17.32	PK	1.36	153	V
11490	26.07	17.46	43.53	54	-10.47	AV	1.57	169	V
Channel:5825MHz									
11650	40.78	17.57	58.35	74	-15.65	PK	1.02	1	H
11650	26.13	17.57	43.70	54	-10.30	AV	1.11	222	H
11650	39.88	17.57	57.45	74	-16.55	PK	1.28	270	V
11650	26.92	17.57	44.49	54	-9.51	AV	1.23	274	V

Modulation : 802.11(n40) (the worst data)

Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5190MHz									
10380	41.16	16.34	57.50	74	-16.50	PK	1.86	293	H
10380	25.41	16.34	41.75	54	-12.25	AV	1.34	162	H
10380	41.33	16.34	57.67	74	-16.33	PK	1.85	333	V
10380	25.87	16.34	42.21	54	-11.79	AV	1.54	274	V
Channel:5230MHz									
10460	41.33	16.15	57.48	74	-16.52	PK	1.36	106	H
10460	27.16	16.15	43.31	54	-10.69	AV	1.69	241	H
10460	41.26	16.15	57.41	74	-16.59	PK	1.12	274	V
10460	27.21	16.15	43.36	54	-10.64	AV	1.29	298	V

Channel:5270MHz									
10540	41.70	16.34	58.04	74	-15.96	PK	1.31	322	H
10540	27.03	16.34	43.37	54	-10.63	AV	1.62	4	H
10540	41.63	16.34	57.97	74	-16.03	PK	1.12	31	V
10540	25.92	16.34	42.26	54	-11.74	AV	1.06	23	V
Channel:5310MHz									
10620	41.17	16.34	57.51	74	-16.49	PK	1.48	115	H
10620	27.63	16.34	43.97	54	-10.03	AV	1.31	272	H
10620	41.45	16.34	57.79	74	-16.21	PK	1.62	240	V
10620	27.14	16.34	43.48	54	-10.52	AV	1.19	14	V
Channel:5510MHz									
11020	39.01	16.34	55.35	74	-18.65	PK	1.70	160	H
11020	27.87	16.34	44.21	54	-9.79	AV	1.51	109	H
11020	39.53	16.34	55.87	74	-18.13	PK	1.64	32	V
11020	25.49	16.34	41.83	54	-12.17	AV	1.25	155	V
Channel:5670MHz									
11340	40.18	16.34	56.52	74	-17.48	PK	1.17	237	H
11340	26.60	16.34	42.94	54	-11.06	AV	1.74	244	H
11340	41.31	16.34	57.65	74	-16.35	PK	1.13	82	V
11340	25.27	16.34	41.61	54	-12.39	AV	1.76	42	V
Channel:5755MHz									
11510	40.73	17.49	58.22	74	-15.78	PK	1.38	304	H
11510	26.18	17.49	43.67	54	-10.33	AV	1.57	239	H
11510	40.10	17.49	57.59	74	-16.41	PK	1.77	57	V
11510	25.24	17.49	42.73	54	-11.27	AV	1.33	147	V
Channel:5795MHz									
11590	40.35	17.52	57.87	74	-17.45	PK	1.38	329	H
11590	25.14	17.52	42.66	54	-16.13	AV	1.76	166	H
11590	41.01	17.52	58.53	74	-15.47	PK	1.14	64	V
11590	27.03	17.52	44.55	54	-9.45	AV	1.70	350	V

Modulation : 802.11(VH80) (the worst data)


Freq (MHz)	Rd_level (dBuV/m)	Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over (dB)	detector	Height	Degree	Antenna polarization
Channel:5210MHz									
10420	40.23	16.25	56.48	74	-17.52	PK	1.85	36	H
10420	27.62	16.25	43.87	54	-10.13	AV	1.83	279	H
10420	41.24	16.25	57.49	74	-16.51	PK	1.32	340	V
10420	26.07	16.25	42.32	54	-11.68	AV	1.45	85	V
Channel:5290MHz									
10580	40.59	16.25	56.84	74	-17.16	PK	1.36	234	H
10580	26.31	16.25	42.56	54	-11.44	AV	1.61	264	H
10580	40.24	16.25	56.49	74	-17.51	PK	1.25	175	V
10580	27.37	16.25	43.62	54	-10.38	AV	1.56	98	V
Channel:5530MHz									
11060	39.20	17.50	56.70	74	-17.30	PK	1.18	218	H
11060	26.92	17.50	44.42	54	-9.58	AV	1.08	15	H
11060	39.91	17.50	57.41	74	-16.59	PK	1.51	267	V
11060	26.51	17.50	44.01	54	-9.99	AV	1.32	267	V
Channel:5775MHz									
11550	39.28	17.50	56.78	74	-17.22	PK	1.48	39	H
11550	26.75	17.50	44.25	54	-9.75	AV	1.49	346	H
11550	39.68	17.50	57.18	74	-16.82	PK	1.02	316	V
11550	25.46	17.50	42.96	54	-11.04	AV	1.63	18	V

**Remark:**

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier. Emission level = Reading Result + Factor, Margin = Emission level - Limits
2. The EUT was tested in the low, high channel and the worst case position data was reported.
3. Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

## 8. BAND EDGE

### 8.1 Block Diagram Of Test Setup



### 8.2 Limit

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an e.i.r.p. of  $-17$  dBm/MHz; for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an e.i.r.p. of  $-27$  dBm/MHz.
- (5) The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
- (6) Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in §15.209. Further, any U-NII devices using an AC power line are required to comply also with the conducted limits set forth in §15.207.


### 8.3 Test procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 1 MHz with a convenient frequency span.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.




8.4 Test Result

Test Graph  
5150-5250MHz







802.11n(HT40)-5190




802.11n(HT40)-5230




802.11ac(VH80)-5210





5250-5350MHz:







5470-5725MHz:






5725-5850MHz






802.11(n40)-5755



802.11(n40)-5795




802.11ac(VH80)-5775





## 9. CONDUCTED PEAK OUTPUT POWER

### 9.1 Block Diagram Of Test Setup



### 9.2 Limit

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p.

at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For mobile and portable client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the 5.25-5.35 GHz and 5.47-5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or  $11 \text{ dBm} + 10 \log B$ , where B is the 26 dB emission bandwidth in megahertz. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(4) The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.

(5) The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used. Measurements in the 5.725-5.85 GHz band are made over a reference bandwidth of 500 kHz or the 26 dB emission bandwidth of the device, whichever is less. Measurements in the 5.15-5.25 GHz, 5.25-5.35 GHz, and the 5.47-5.725 GHz bands are made over a

bandwidth of 1 MHz or the 26 dB emission bandwidth of the device, whichever is less. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full reference bandwidth.

(h) Transmit Power Control (TPC) and Dynamic Frequency Selection (DFS).

(1) Transmit power control (TPC). U-NII devices operating in the 5.25-5.35 GHz band and the 5.47-5.725 GHz band shall employ a TPC mechanism. The U-NII device is required to have the capability to operate at least 6 dB below the mean EIRP value of 30 dBm. A TPC mechanism is not required for systems with an e.i.r.p. of less than 500 mW.

### 9.3 Test procedure

According to KDB789033 D02v02r01 sectionE, the following is the measurement procedure.

(i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.

(ii) Set RBW = 1 MHz.

(iii) Set VBW  $\geq$  3 MHz.

(iv) Number of points in sweep  $\geq 2 \times \text{span} / \text{RBW}$ . (This ensures that bin-to-bin spacing is  $\leq \text{RBW}/2$ , so that narrowband signals are not lost between frequency bins.)

(v) Sweep time = auto.

(vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.

(vii) If transmit duty cycle  $< 98\%$ , use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle  $\geq 98\%$ , and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."

(viii) Trace average at least 100 traces in power averaging (rms) mode.

(ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

## 9.4 Test Result

## 5150-5250MHz:

Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5180	11.612	23.98
	5200	11.878	23.98
	5240	12.151	23.98
802.11ac20	5180	11.055	23.98
	5200	11.301	23.98
	5240	11.869	23.98
802.11ac40	5190	11.445	23.98
	5230	11.631	23.98
802.11ac80	5210	11.639	23.98
802.11n(HT20)	5180	11.178	23.98
	5200	11.249	23.98
	5240	11.946	23.98
802.11n(HT40)	5190	11.644	23.98
	5230	11.934	23.98

## 5250-5350 MHz

Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5260	11.942	23.98
	5280	12.613	23.98
	5320	12.184	23.98
802.11ac20	5260	11.94	23.98
	5280	12.518	23.98
	5320	11.906	23.98
802.11ac40	5270	12.353	23.98
	5310	12.417	23.98
802.11ac80	5290	12.685	23.98
802.11n(HT20)	5260	12.079	23.98
	5280	12.527	23.98
	5320	11.972	23.98
802.11n(HT40)	5270	12.348	23.98
	5310	12.533	23.98


5470-5725MHz:


Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5500	12.629	23.98
	5580	13.352	23.98
	5700	12.946	23.98
802.11ac20	5500	12.424	23.98
	5580	13.296	23.98
	5700	13.193	23.98
802.11ac40	5510	11.711	23.98
	5670	12.707	23.98
802.11ac80	5530	12.275	23.98
802.11n(HT20)	5500	11.899	23.98
	5580	12.847	23.98
	5700	12.563	23.98
802.11n(HT40)	5510	11.765	23.98
	5670	12.863	23.98

5725-5850MHz:


Test mode1	Test Channel (MHz)	Output Power dBm	Limit dBm
802.11a20	5745	11.888	30
	5785	12.128	30
	5825	10.538	30
802.11ac20	5745	11.507	30
	5785	11.838	30
	5825	10.43	30
802.11ac40	5755	12.32	30
	5795	11.16	30
802.11ac80	5775	12.599	30
802.11n(HT20)	5745	11.741	30
	5785	11.9	30
	5825	10.33	30
802.11n(HT40)	5755	12.785	30
	5795	11.371	30

5150-5250MHz-Power







802.11ac(VH80)-5210




802.11n(HT20)-5180




802.11n(HT20)-5200





802.11n(HT20)-5240




802.11n(HT40)-5190




802.11n(HT40)-5230




5250-5350MHz-Power









802.11ac(VH80)-5290




802.11n(HT20)-5260




802.11n(HT20)-5280





802.11n(HT20)-5320



802.11n(HT40)-5270



802.11n(HT40)-5310



5470-5725MHz-Power

