

## FCC RF EXPOSURE REPORT

#### **CERTIFICATION TEST REPORT**

For

Winees Spotlight Cam

MODEL NUMBER: WP280013267

FCC ID: 2AYZ8WP280013267

REPORT NUMBER: 4790099828.1-3

ISSUE DATE: October 13, 2021

### Prepared for

Linkzone Technology Co., Limited
ROOM 20 5/F WAYSON COMMERCIAL BLDG 28 CONNAUGHT ROAD WEST
SHEUNG WAN Hong Kong China

### Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products.



REPORT NO.: 4790099828.1-3 Page 2 of 7

# **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	10/13/2021	Initial Issue	



# **TABLE OF CONTENTS**

1.	ATTESTATION OF TEST RESULTS	. 4
2.	TEST METHODOLOGY	. 5
3.	FACILITIES AND ACCREDITATION	. 5
4	REQUIREMENT	6



REPORT NO.: 4790099828.1-3

Page 4 of 7

### 1. ATTESTATION OF TEST RESULTS

**Applicant Information** 

Company Name: Linkzone Technology Co., Limited

ROOM 20 5/F WAYSON COMMERCIAL BLDG 28 CONNAUGHT Address:

ROAD WEST SHEUNG WAN Hong Kong China

**Manufacturer Information** 

Company Name: Linkzone Technology Co., Limited

ROOM 20 5/F WAYSON COMMERCIAL BLDG 28 CONNAUGHT Address:

ROAD WEST SHEUNG WAN Hong Kong China

**EUT Information** 

**EUT Name:** Winees Spotlight Cam

Model: WP280013267

Sample Received Date: September 13, 2021

Sample Status: Normal Sample ID: 4208564

Date of Tested: September 13, 2021~ September 30, 2021

APPLICABLE STANDARDS			
STANDARD		TEST RESULTS	
	FCC 47CFR§2.1091	PASS	
Prepared By:	Ch	ecked By:	

Shemy les

Shawn Wen Kebo Zhang **Project Engineer** Laboratory Leader

Approved By:

kelo. Thung.

Stephen Guo

Laboratory Manager

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

## 3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4102.01)  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.  FCC (FCC Designation No.: CN1187)  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules ISED (Company No.: 21320)  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.  VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)  UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.  Facility Name:
	Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



## 4. REQUIREMENT

#### LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

### **RF EXPOSURE LIMIT**

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E ²,  H ² or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

### **CALCULATION METHOD**

S=PG/4πR<sup>2</sup>

Where:

S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna



REPORT NO.: 4790099828.1-3

Page 7 of 7

## **CALCULATED RESULTS**

Worst Case					
Mode	Output Power	Antenna Directional gain	Power Density	Power Density Limit	Test Result
	dBm	dBi	mW/cm2	mW/cm2	-
2.4G Wifi	20	6.15	0.08198	1.0	Complies

#### Note:

- 1. The Power comes from report operation description.
- 2. The EUT cannot support simultaneous emission.
- 3. The minimum separation distance of the device is greater than 20 cm.
- 4. Calculate by WORST-CASE mode.

**END OF REPORT**