



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V03

Report Template Revision Date: Mar.1st, 2017

# Test Report

**Report No. :** CQASZ20210801422E-04  
**Applicant:** Shenzhen Inkbird Technology Co., Ltd.  
**Address of Applicant:** Floor 4th East, Building 713, Pengji Industrial Zone, LianTang, Luohu District, Shenzhen, PRC.  
**Equipment Under Test (EUT):**  
**Product:** WI-FI Gateway  
**All Model No.:** IBS-M1, IBS-M1S, IBS-M2, IBS-M2S  
**Test Model No.:** IBS-M1  
**Brand Name:** INKBIRD  
**FCC ID:** 2AYZD-IBSM1S  
**Standards:** 47 CFR Part 15, Subpart C  
**Date of Test:** 2021-08-19 to 2021-09-07  
**Date of Issue:** 2021-09-15  
**Test Result :** PASS\*

**Tested By:** Lewis Zhou  
( Lewis Zhou )

**Reviewed By:** Rock Huang  
( Rock Huang )

**Approved By:** Jack ai  
( Jack ai )



\* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

## 2 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210801422E-04	Rev.01	Initial report	2021-09-15

### 3 Test Summary

Test Item	Test Requirement	Test method	Result
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
<b>Radiated Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

## 4 Contents

	Page
<b>1 COVER PAGE.....</b>	<b>1</b>
<b>2 VERSION.....</b>	<b>2</b>
<b>3 TEST SUMMARY.....</b>	<b>3</b>
<b>4 CONTENTS.....</b>	<b>4</b>
<b>5 GENERAL INFORMATION.....</b>	<b>5</b>
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT.....	5
5.3 DESCRIPTION OF SUPPORT UNITS.....	6
5.4 TEST LOCATION.....	6
5.5 TEST FACILITY.....	6
5.6 STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	7
5.7 DEVIATION FROM STANDARDS.....	7
5.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	7
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	7
5.10 EQUIPMENT LIST.....	8
5.11 CONDUCTED EMISSIONS.....	9
5.12 RADIATED SPURIOUS EMISSIONS.....	13
5.12.1 Radiated emission below 1GHz.....	16
5.12.2 Transmitter emission above 1GHz.....	18
<b>6 PHOTOGRAPHS - EUT TEST SETUP.....</b>	<b>19</b>
6.1 RADIATED SPURIOUS EMISSION.....	19
6.2 CONDUCTED EMISSION.....	20
<b>7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS.....</b>	<b>21</b>

## 5 General Information

### 5.1 Client Information

Applicant:	Shenzhen Inkbird Technology Co., Ltd.
Address of Applicant:	Floor 4th East, Building 713, Pengji Industrial Zone, LianTang, Luohu District, Shenzhen, PRC.
Manufacturer:	Shenzhen Inkbird Technology Co., Ltd.
Address of Manufacturer:	Floor 4th East, Building 713, Pengji Industrial Zone, LianTang, Luohu District, Shenzhen, PRC.
Factory:	Shenzhen Inkbird Technology Co., Ltd.
Address of Factory:	Floor 4th East, Building 713, Pengji Industrial Zone, LianTang, Luohu District, Shenzhen, PRC.

### 5.2 General Description of EUT

Product Name:	WI-FI Gateway
Model No.:	IBS-M1, IBS-M1S, IBS-M2, IBS-M2S
Test Model No.:	IBS-M1
Trade Mark:	INKBIRD
Hardware version:	REV3.0
Software version:	REV2.1
Operation Frequency:	433.92MHz BLE:2402MHz~2480MHz Wifi;IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	433.92MHz:1 CH BLE:40CH wifi: 11 CH
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	3dBi
Power Supply:	DC12V/1A
Test Mode:	433.92MHz+BLE+2.4G wifi Simultaneous launch

Note:

All model:IBS-M1, IBS-M1S, IBS-M2, IBS-M2S

Only the model IBS-M1 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

### 5.3 Description of Support Units

The EUT has been tested with associated equipment below.

Description	Manufacturer	Model No.	Remark	FCC certification
/	/	/	/	/

### 5.4 Test Location

All tests were performed at:

**Shenzhen Huaxia Testing Technology Co., Ltd.,**

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua New District, Shenzhen, Guangdong, China

### 5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **CNAS (No. CNAS L5785)**

CNAS has accredited Shenzhen Huaxia Testing Technology Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

• **ISED Registration No.: 22984-1**

The 3m Semi-anechoic chamber of Shenzhen Huaxia Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

• **A2LA (Certificate No. 4742.01)**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

Shenzhen Huaxia Testing Technology Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

## 5.6 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **Shenzhen Huaxia Testing Technology Co., Ltd.** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	±5.12dB	(1)
2	Radiated Emission (Above 1GHz)	±4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	±3.34dB	(1)
4	Radio Frequency	$3 \times 10^{-8}$	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	time	0.6 %.	(1)
14	Frequency Error	5.5 Hz	(1)

(1)This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 5.7 Deviation from Standards

None.

## 5.8 Abnormalities from Standard Conditions

None.

## 5.9 Other Information Requested by the Customer


None.

## 5.10 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2021/10/10	2022/10/9
Spectrum analyzer	R&S	FSU26	CQA-038	2021/10/10	2022/10/9
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2021/10/10	2022/10/9
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2021/10/10	2022/10/9
Bilog Antenna	R&S	HL562	CQA-011	2021/10/10	2022/10/9
Horn Antenna	R&S	HF906	CQA-012	2021/10/16	2024/10/15
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2021/10/16	2024/10/15
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2021/10/16	2024/10/15
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2021/10/16	2024/10/15
Antenna Connector	CQA	RFC-01	CQA-080	2021/10/10	2022/10/9
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2021/10/10	2022/10/9
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2021/10/10	2022/10/9




## 5.11 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207														
Test Method:	ANSI C63.10: 2013														
Test Frequency Range:	150kHz to 30MHz														
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
	Frequency range (MHz)		Limit (dBuV)												
		Quasi-peak	Average												
	0.15-0.5	66 to 56*	56 to 46*												
0.5-5	56	46													
5-30	60	50													
* Decreases with the logarithm of the frequency.															
Test Procedure:	<ol style="list-style-type: none"> <li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li> <li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li> <li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li> <li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li> <li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.</li> </ol>														
Test Setup:															

Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	433.92MHz+BLE+2.4G wifi Simultaneous launch
Test Voltage:	DC 12V by adapter input AC120V/60Hz
Test Results:	Pass

Measurement Data

Live Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.170	26.24	9.49	35.73	54.96	-19.23	Average	Line
2	0.170	31.85	9.49	41.34	64.96	-23.62	QP	Line
3	0.238	24.43	9.49	33.92	52.17	-18.25	Average	Line
4	0.238	30.52	9.49	40.01	62.17	-22.16	QP	Line
5 PP	0.514	22.28	9.54	31.82	46.00	-14.18	Average	Line
6 QP	0.514	26.80	9.54	36.34	56.00	-19.66	QP	Line
7	1.178	20.63	9.53	30.16	46.00	-15.84	Average	Line
8	1.178	25.24	9.53	34.77	56.00	-21.23	QP	Line
9	2.058	16.18	9.53	25.71	46.00	-20.29	Average	Line
10	2.058	21.02	9.53	30.55	56.00	-25.45	QP	Line
11	16.945	8.17	9.97	18.14	50.00	-31.86	Average	Line
12	16.945	13.26	9.97	23.23	60.00	-36.77	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.166	26.48	9.48	35.96	55.16	-19.20	Average	Neutral
2	0.166	30.91	9.48	40.39	65.16	-24.77	QP	Neutral
3	0.242	24.63	9.48	34.11	52.03	-17.92	Average	Neutral
4	0.242	29.32	9.48	38.80	62.03	-23.23	QP	Neutral
5	0.610	21.90	9.72	31.62	46.00	-14.38	Average	Neutral
6	0.610	27.02	9.72	36.74	56.00	-19.26	QP	Neutral
7	1.370	22.70	9.72	32.42	46.00	-13.58	Average	Neutral
8	1.370	26.53	9.72	36.25	56.00	-19.75	QP	Neutral
9	5.214	9.39	9.82	19.21	50.00	-30.79	Average	Neutral
10	5.214	15.68	9.82	25.50	60.00	-34.50	QP	Neutral
11	13.937	9.08	9.92	19.00	50.00	-31.00	Average	Neutral
12	13.937	14.13	9.92	24.05	60.00	-35.95	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

## 5.12 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
Peak		1MHz	10Hz	Average	
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	<p>Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.</p> <p>In any 4 kHz band, the center frequency of which is removed from the assigned frequency by more than 250 percent of the authorized bandwidth: An amount equal to 43 dB plus 10 times the logarithm (to the base 10) of the transmitter power in watts.</p>				
Limit (dBm)		Equivalent Field strength Limit at 3M (dBuV/m)			
-13		82.2			

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:


- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.  
 Note: For the radiated emission test above 1GHz: Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.



	<ul style="list-style-type: none"> <li>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>g. Test the EUT in the lowest channel ,the middle channel ,the Highest channel</li> <li>h. Repeat above procedures until all frequencies measured was complete.</li> </ul>
Exploratory Test Mode:	<p>Transmitting with all kind of modulations, data rates. Transmitting mode, Charge + Transmitting mode.</p>
Final Test Mode:	<p>433.92MHz+BLE+2.4G wifi Simultaneous launch</p>
Test Results:	<p>Pass</p>

5.12.1 Radiated emission below 1GHz

30MHz~1GHz		
Test mode:	Transmitting	Vertical



	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	36.64	10.93	14.01	24.94	40.00	-15.06	Peak	HORIZONTAL
2	45.69	10.46	10.11	20.57	40.00	-19.43	Peak	HORIZONTAL
3	98.49	10.10	10.56	20.66	43.50	-22.84	Peak	HORIZONTAL
4	289.00	11.60	13.37	24.97	46.00	-21.03	Peak	HORIZONTAL
5	558.73	12.23	18.89	31.12	46.00	-14.88	Peak	HORIZONTAL
6 pp	845.09	11.98	24.08	36.06	46.00	-9.94	Peak	HORIZONTAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:


Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.



Test mode:	Charge +Transmitting	Horizontal
------------	----------------------	------------



	Read Freq	Read Level	Factor	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	50.76	20.01	7.93	27.94	40.00	-12.06	Peak	VERTICAL
2	88.03	12.53	9.97	22.50	43.50	-21.00	Peak	VERTICAL
3	153.20	13.30	8.26	21.56	43.50	-21.94	Peak	VERTICAL
4	290.02	12.47	13.40	25.87	46.00	-20.13	Peak	VERTICAL
5	501.18	14.70	18.29	32.99	46.00	-13.01	Peak	VERTICAL
6 pp	860.04	10.78	24.01	34.79	46.00	-11.21	Peak	VERTICAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

### 5.12.2 Transmitter emission above 1GHz

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Over (dB)	Detector Type	Ant. Pol. H/V
4804	54.02	-4.33	49.69	74	-24.31	Peak	H
7206	51.21	1.01	52.22	74	-21.78	Peak	H
7232	42.32	1.01	43.33	74	-30.67	Peak	H
4804	54.44	-4.33	50.11	74	-23.89	Peak	V
7206	49.96	1.01	50.97	74	-23.03	Peak	V
7232	38.45	1.01	39.46	74	-34.54	Peak	V


Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.


## 6 Photographs - EUT Test Setup

### 6.1 Radiated Spurious Emission


9KHz~30MHz:




30MHz~1GHz:



Above 1GHz:



## 6.2 Conducted Emission



## 7 Photographs - EUT Constructional Details

Refer to Photographs - EUT Constructional Details  
for CQASZ20210801422E -01.

---

The End