



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No.:** CQASZ20210701183E-02  
**Applicant:** Shenzhen Inkbird Technology Co., Ltd.  
**Address of Applicant:** Floor 4th East, Building 713, Pengji Industrial Zone, LianTang, Luohu District, Shenzhen, PRC.  
**Equipment Under Test (EUT):**  
**EUT Name:** Temperature & Humidity Smart Sensor  
**Model No.:** IBS-TH1, IBS-TH1 PLUS, IBS-TH1 MINI, IBS-TH2, IBS-TH2 Plus  
**Teat Model No.:** IBS-TH2  
**Brand Name:** INKBIRD  
**FCC ID:** 2AYZD-IBSTH2  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2021-07-27  
**Date of Test:** 2021-07-27 to 2021-08-05  
**Date of Issue:** 2021-09-06  
**Test Result:** **PASS\***

\*In the configuration tested, the EUT complied with the standards specified above

**Tested By:** Lewis Zhou

( Lewis Zhou )

**Reviewed By:** Rock Huang

( Rock Huang )

**Approved By:** Jack ai

( Jack ai )



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210701183-02	Rev.01	Initial report	2021-09-06

## 2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	错误! 未定义书签。
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	错误! 未定义书签。
4.1.1 <i>Standard Requirement</i> .....	错误! 未定义书签。
4.1.2 <i>Limits</i> .....	错误! 未定义书签。
4.1.3 <i>EUT RF Exposure</i> .....	错误! 未定义书签。

### 3 General Information

#### 3.1 Client Information

Applicant:	Shenzhen Inkbird Technology Co., Ltd.
Address of Applicant:	Floor 4th East, Building 713, Pengji Industrial Zone, LianTang, Luohu District, Shenzhen, PRC.
Manufacturer:	Shenzhen Inkbird Technology Co., Ltd.
Address of Manufacturer:	Floor 4th East, Building 713, Pengji Industrial Zone, LianTang, Luohu District, Shenzhen, PRC.
Factory:	Shenzhen Inkbird Technology Co., Ltd.
Address of Factory:	Floor 4th East, Building 713, Pengji Industrial Zone, LianTang, Luohu District, Shenzhen, PRC.

#### 3.2 General Description of EUT

Product Name:	Temperature & Humidity Smart Sensor
Model No.:	IBS-TH1, IBS-TH1 PLUS, IBS-TH1 MINI, IBS-TH2, IBS-TH2 Plus
Test Model No.:	IBS-TH2
Trade Mark:	INKBIRD
Hardware Version:	REV2.0
Software Version:	REV3.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	BT5.0
Modulation Type:	GFSK
Transfer Rate:	1Mbps, 2Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input type="checkbox"/> Portable <input checked="" type="checkbox"/> Fix Location
Test Software of EUT:	PhyPlusKit
Antenna Type:	Integral antenna
Antenna Gain:	1dBi
EUT Power Supply:	This test EUT is powered by 2*AAA size batteries.

Note:

All model: IBS-TH1, IBS-TH1 PLUS, IBS-TH1 MINI, IBS-TH2, IBS-TH2 Plus

Only the model IBS-TH2 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, Only the sales customers, sales region, product appearance is different.

## 4 RF Exposure Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3–3.0 .....	614	1.63	*(100)	6
3.0–30 .....	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30–300 .....	61.4	0.163	1.0	6
300–1500 .....	.....	.....	f/300	6
1500–100,000 .....	.....	.....	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3–1.34 .....	614	1.63	*(100)	30
1.34–30 .....	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30–300 .....	27.5	0.073	0.2	30
300–1500 .....	.....	.....	f/1500	30
1500–100,000 .....	.....	.....	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

G = gain of antenna in linear scale

$\pi$  = 3.1416

R = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

### 4.1.3 EUT RF Exposure Evaluation standalone operations

#### 1) For BT Classic (for CSR chip)

Antenna Gain: 1dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.259 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

#### 1) For BLE

##### Measurement Data

GFSK(1Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.54	3.0±1	4.0	2.512
Middle(2440MHz)	3.35	3.5±1	4.5	2.818
Highest(2480MHz)	3.68	4.0±1	5.0	3.162
GFSK(2Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	2.65	3.0±1	4.0	2.512
Middle(2440MHz)	3.48	3.5±1	4.5	2.818
Highest(2480MHz)	3.79	4.0±1	5.0	3.162

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm <sup>2</sup> )	Limit	Result
3.162	1	0.00079	1.0	PASS

Note: 1) Refer to report No. CQASZ20210701126-01E for EUT test Max Conducted Peak Output Power value.

2)  $P_d = (P_{out} * G) / (4 * \pi * R^2) = (3.162 * 1.259) / (4 * 3.1416 * 20^2) = 0.00079$

--THE END--