## FCC ID: 2AZ2L-FT02

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

## GFSK:

Antenna Type : Cable Antenna Antenna Gain: 0 dBi

Modulatio	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)		1g SAR Exclusion threshold	SAR test exclusion	
GFSK	2.402	-4.955	0.320	-4±1	-3	0.501	<5	0.15535	3.00	YES	
	2.44	-6.855	0.206	-6±1	-5	0.316	<5	0.09879	3.00	YES	
	2.480	-5.565	0.278	-6±1	-5	0.316	<5	0.09960	3.00	YES	

Conclusion:

For the max result : 0.15535≤ 3.0 for 1-g SAR, No SAR is required.

**Signature: Date:** 2021-05-24

NAME AND TITLE (Please print or type): Alex Li /Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China