



# FCC TEST REPORT

## FCC ID: 2AZ2V-ZEN32V2

Product	:	SCENE CONTROLLER
Model Name	:	ZEN32 800LR, ZW35
Brand	:	ZOOZ
Report No.	:	PTC24090702201E-FC03
<b>Prepared for</b>		
Lorenz High Definition LLC		
230 Rt 206, STE 401, Flanders, NJ 07836, United States		
<b>Prepared by</b>		
Precise Testing & Certification Co., Ltd.		
Building 1, No. 6, Tongxin Road, Dongcheng Street, Dongguan, Guangdong, China.		



## TEST RESULT CERTIFICATION

Applicant's name : Lorenz High Definition LLC  
Address : 230 Rt 206, STE 401, Flanders, NJ 07836, United States  
Manufacture's name : Ultra Tech industries Co., Ltd.  
Address : Industrial cluster Non Sao, Tan Dinh commune, Lang Giang district, Bac Giang, VIETNAM  
Product name : SCENE CONTROLLER  
Model name : ZEN32 800LR, ZW35  
Test procedure : FCC CFR47 Part 1.1307(b)(1)  
Test Date : Sep. 21, 2024 to Oct. 15, 2024  
Date of Issue : Oct. 15, 2024  
Test Result : PASS

This device described above has been tested by PTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of PTC, this document may be altered or revised by PTC, personal only, and shall be noted in the revision of the document.

Test Engineer:

A handwritten signature in black ink that reads "Jack Zhou".

Jack Zhou / Engineer

Technical Manager:

A handwritten signature in black ink that reads "Simon Pu".

Simon Pu / Manager



## Contents

	<b>Page</b>
<b>2 TEST SUMMARY .....</b>	<b>4</b>
<b>3 GENERAL INFORMATION .....</b>	<b>5</b>
3.1 GENERAL DESCRIPTION OF E.U.T. ....	5
<b>4 RF EXPOSURE .....</b>	<b>6</b>
4.1 REQUIREMENTS .....	6
4.2 THE PROCEDURES / LIMIT .....	6
4.3 MPE CALCULATION METHOD .....	7
4.4 RF OUTPUT POWER .....	7
4.5 TEST RESULT .....	9



## 2 Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	15.247 (i)	PASS
Remark:		
N/A: Not Applicable		



### 3 General Information

#### 3.1 General Description of E.U.T.

Product Name	:	SCENE CONTROLLER
Model Name	:	ZEN32 800LR
Additional model	:	ZW35
Specification	:	908.40MHz 908.42MHz 916.00MHz 912 MHz 920 MHz
Operation Frequency	:	2FSK for 908.40MHz 2FSK for 908.42MHz 2GFSK for 916.00MHz DSSS OQPSK LR for 912 MHz and 920 MHz
Number of Channel	:	5
Type of Modulation	:	2FSK for 908.40MHz 2FSK for 908.42MHz 2GFSK for 916.00MHz DSSS OQPSK LR for 912 MHz and 920 MHz
Antenna installation	:	PCB antenna
Antenna Gain	:	3.55 dBi
Power supply	:	Input: AC 120V/60Hz Output: 120V AC 60Hz 15A
Hardware Version	:	V4.0
Software Version	:	N/A



## 4 RF Exposure

Test Requirement : FCC Part 1.1307(b)(1)

Evaluation Method : KDB 447498 D01 General RF Exposure Guidance v06

### 4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

### 4.2 The procedures / limit

(A) Limits for Occupational / Controlled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range	Electric Field	Magnetic Field	Power Density (S)	Averaging Time
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density



### 4.3 MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2} \theta\phi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2} \theta\phi$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

### 4.4 RF Output power



Freq. (MHz)	Field strength(max)(dBuV/m)	EIRP (max) (dBm)
908.40	89.82	-5.38
908.42	89.53	-5.67
916.00	90.03	-5.17

**Note:**  $EIRP = E - 104.8 + 20 \log D$ ,

Where

E is the electric field strength in dB $\mu$ V/m.

EIRP is the equivalent isotropically radiated power in dBm.

d is the specified measurement distance in m.

where  $D=3$ ,  $EIRP = E - 95.2$ .





#### 4.5 Test Result

Mode	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Tune up tolerance (dBm)	Max Tune Up Power (mW)	Power Density (mW/cm <sup>2</sup> )	Limit of Power Density (mW/cm <sup>2</sup> )	Result
912MHz	2.26	-0.383	0±1	1.258925	0.000567	1	Pass
920MH	2.26	0.122	0.5±1	1.412538	0.000636	1	Pass
908.40MH	2.26	-5.38	-5.00±1	0.398107	0.000179	1	Pass
908.42MH	2.26	-5.67	-5.50±1	0.354813	0.000160	1	Pass
916.00MH	2.26	-5.17	-5.00±1	0.398107	0.000179	1	Pass

Simultaneous SAR Evaluation:

The device can't support simultaneous transmitter.

**\*\*\*\*\*THE END REPORT\*\*\*\*\***