

# RF Exposure Evaluation Report

## 1 RF EXPOSURE

Product Name: Motion Sensor  
 Model No.: ZSE11 800LR  
 FCC ID: 2AZ2V-ZSE11800

## 2. RF Exposure Evaluation

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1091: Radiofrequency radiation exposure evaluation: mobile devices.

### 2.1 LIMITS

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

Table 1 to § 1.1310(e)(1)–Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	<6
30–300	61.4	0.163	1.0	<6
300–1,500			f/300	<6
1,500–100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	<30
30–300	27.5	0.073	0.2	<30
300–1,500			f/1500	<30
1,500–100,000			1.0	<30

F= Frequency in MHz Friis Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$  Where

$P_d$  = power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = gain of antenna in linear scale

$P_i = 3.1416$

$R$  = distance between observation point and center of the radiator in cm

$P_d$  is the limit of MPE. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance  $r$  where the MPE limit is reached.

Remark:

$P_d = (P_{out} * G) / (4 * P_i * R^2) \text{ dbm} = \text{dbuV/m} - 95.2$ ,  
so the power is **73.78-95.2=-21.42dBm**

## 2.2 EUT RF EXPOSURE EVALUATION

For operation Frequency: 908.40--916.00MHz, ant gain is -4.12dBi Max

operation Frequency: 912.0--920.0MHz, ant gain is -3.70dBi Max

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.0 in linear scale.

The Max Conducted Peak Output Power data refer to report No.: POCE240116005RL001, POCE240116005RL002

worst mode and channel:

Test channel	Emission Level (dBuV/m)	Emission Level(dBm)	Tune-up Power (dbm)	Maximum tune-up Power (dbm)	Maximum tune-up Power (mW)	Calculated value (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )
916.0MHz	73.78	<b>-21.42</b>	<b>-21.42±1</b>	<b>-20.42</b>	<b>0.091</b>	<b>0.0000071</b>	0.6056
912.0MHz	/	2.03	2.03±1	3.03	2.009	0.00017	0.608
Conclusion : the calculated value less than the limit, so there is no sar requirement.							

NOTE:1. EUT module is more than 20cm away from the human body.