



AGC Automotive Europe

Avenue Jean Monnet 4, 1348 Ottignies-Louvain-la-Neuve, Belgium

LEGAL NOTICE

Jack device (Model: JACK-V2):

- Must be glued to the car windshield only using the provided tape.
- Don't touch device solar cells.
- Operating Temperature: -40°C to +85°C.
- Operating Humidity range (not condensing): 10% to 90%.
- Apply the device only on a dry windshield. Don't operate this product near water.
- This product is certified to be used at a maximum height of 2.000m.
- Dimension: 134.01 x 22.30 x 27.60mm; Weight: 70g.
- Connectivity: BLE

Contains FCC ID: 2AZ5PJACK-V2

AGC declares that this device is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC.

In order to protect human health, this device meets the thresholds for exposure of the general public to electromagnetic fields according to Council Recommendation 1999/519/EC.

Warning: Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna
- Increase the separation between the equipment and receiver
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected
- Consult the dealer or an experienced radio/TV technician for help.

Description:	Windshield Transducer
Models:	Jack 2
Input Rated Voltage:	3.3Vdc battery powered
Maximum EIRP (RF Output Power):	3.35dBm Maximum

Mode	Work Frequency	
	Transmit Frequency (MHz)	Receive Frequency (MHz)
Bluetooth	2402MHz-2480MHz	2402MHz-2480MHz

