

FCC SAR Exclusion Report

Product name : Classified Handlebar unit
Applicant : Classified Cycling BV
FCC ID : 2AZ7ACLASSIAV1

Test report No. : 201001129 003 FCC RF exposure v2.00



Report number: 201001129 003 FCC RF exposure v2.00

Laboratory information

Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2017. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements.

The Industry Canada company number for Telefication is: 4173A.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

Testing Location

Test Site	Kiwa Telefication BV
Test Site location	Wilmersdorf 50 7327 AC Apeldoorn The Netherlands Tel. +31 88998 3393
Test Site FCC	NL0001
CABID	NL0001



Report number: 201001129 003 FCC RF exposure v2.00

Revision History

Version	Date	Remarks	By
v1.00	17-08-2021	Release version	RvB
v2.00	07-02-2022	Changed to different template	RvB



Report number: 201001129 003 FCC RF exposure v2.00

Table of Contents

Revision History	2
1 General Description	4
1.1 Applicant	4
1.2 Manufacturer	4
1.3 Tested Equipment Under Test (EUT).....	4
1.4 SAR Measurement Evaluation.....	5
1.4.1 Maximum Output Power	5
1.4.2 SAR Testing Exclusions, Portable use.....	5
1.5 Summary	5

1 General Description

1.1 Applicant

Client name: Classified Cycling BV
Address: Slachthuisstraat 120 B10,
2300, Turnhout, Belgium
Telephone: +32494843464
E-mail: Kristof.verpoorten@classified-cycling.cc
Contact name: Kristof Verpoorten

1.2 Manufacturer

Manufacturer name: Classified Cycling BV
Address: Slachthuisstraat 120 B10,
2300, Turnhout, Belgium
Telephone: +32494843464
E-mail: Kristof.verpoorten@classified-cycling.cc
Contact name: Kristof Verpoorten

1.3 Tested Equipment Under Test (EUT)

Product name: Classified Handlebar unit
Description: Handlebar unit
Brand name: Classified Cycling
FCC ID: 2AZ7ACLASSIAV1
Model(s): --
Software version: Module A V3.72
Hardware version: 029_003_01
Date of receipt 03-03-2021
Tests started: 04-03-2021
Testing ended: 04-05-2021

1.4 SAR Measurement Evaluation

1.4.1 Maximum Output Power

The maximum radiated power including tune-up tolerance is shown as below.

Mode	E.I.R.P Output power (dBm)
BLE	2.98

* from Telefication report 201001129 001

1.4.2 SAR Testing Exclusions, Portable use

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at } 50 \text{ mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at } 50 \text{ mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
BLE	2.98	1.99	5	0.62	No

Note:

1. When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 , the SAR testing exclusion is applied.
2. When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.

1.5 Summary

Since the SAR testing for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.