



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V05
Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20211202127E-02
Applicant: Smart Gadgets (Shenzhen), Ltd.
Address of Applicant: F6 Culture Chaoshan Expo, No. 280, Xixiang Blvd, Baoan District, Shenzhen, China
Equipment Under Test (EUT):
EUT Name: Smart Health Watch
Test Model No.: Vmed-W
Model No.: Vmed-W
Brand Name: SGG, Smart Gadgets Global, Vmed, Vmedical
FCC ID: 2AZ98-VMEDW-7651
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2021-12-07
Date of Test: 2021-12-07 to 2021-12-30
Date of Issue: 2022-01-10
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Lewis Zhou
(Lewis Zhou)

Reviewed By: Rock Huang
(Rock Huang)

Approved By: Jack ai
(Jack ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20211202127E-02	Rev.01	Initial report	2022-01-10

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
.....	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
3.3 GENERAL DESCRIPTION OF BT&BLE.....	4
4 SAR EVALUATION	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Smart Gadgets (Shenzhen), Ltd.
Address of Applicant:	F6 Culture Chaoshan Expo, No. 280, Xixiang Blvd, Baoan District, Shenzhen, China
Manufacturer:	Smart Gadgets (Shenzhen), Ltd.
Address of Manufacturer:	F6 Culture Chaoshan Expo, No. 280, Xixiang Blvd, Baoan District, Shenzhen, China
Factory:	Smart Gadgets (Shenzhen), Ltd.
Address of Factory:	F6 Culture Chaoshan Expo, No. 280, Xixiang Blvd, Baoan District, Shenzhen, China

3.2 General Description of EUT

Product Name:	Smart Health Watch
Model No.:	Vmed-W
Test Model No	Vmed-W
Trade Mark:	SGG, Smart Gadgets Global, Vmed, Vmedical
EUT Supports Radios application:	Bluetooth mode 2402-2480MHz
Software Version:	V1.1
Hardware Version:	A6
Sample Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
EUT Power Supply:	Li-ion battery: DC 3.7V 280mAh, Charge by DC 5V for adapter

3.3 General Description of BT&BLE

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Non Frequency Hopping Spread Spectrum(NFHSS)
Modulation Type:	GFSK
Number of Channel:	40
Transfer Rate:	1Mbps/2Mbps
Test Software of EUT:	RTL8762x_RFTTestTool_v1.0.1.9(manufacturer declare)
Antenna Type:	FPC antenna
Antenna Gain:	-1.8dBi

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

Measurement Data

Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	5.67	5.5±1	6.5	4.467	1.385	3.0
Middle (2440MHz)	6.46	6.5±1	7.5	5.623	1.757	
Highest (2480MHz)	7.26	7.0±1	8.0	6.310	1.987	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20211202127E-01.

*** END OF REPORT ***