




FCC PART 15.247 TEST REPORT

For

Shenzhen Clever bright Imp.&Exp.Co.,ltd

Rm1701, ZhouYue Building, FuHua Yi Rd, FuTian Central Zone, Shenzhen, P.R.China

FCC ID: 2AZ9D-CB335067

Report Type: Original Report	Product Type: AMBIENT LED OUTDOOR SPEAKER
Report Number:	<u>ATC210526-19457E-RF</u>
Report Date:	<u>2021-06-08</u>
Reviewed By:	<u>Candy Li</u> 
Prepared By:	<u>RF Engineer</u>
Prepared By: Shenzhen Accurate Technology Co., Ltd. 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China Tel: (0755) 26503290 Fax: (0755) 26503396 Http://www.atc-lab.com	

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
SPECIAL ACCESSORIES.....	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
TEST EQUIPMENT LIST	9
FCC §15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE.....	10
APPLICABLE STANDARD	10
TEST RESULT:	10
FCC §15.203 – ANTENNA REQUIREMENT	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	12
APPLICABLE STANDARD	12
EUT SETUP.....	12
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
TRANSD FACTOR & MARGIN CALCULATION	13
TEST DATA	13
FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS.....	16
APPLICABLE STANDARD	16
EUT SETUP.....	16
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	17
TEST PROCEDURE	17
FACTOR & MARGIN CALCULATION	17
TEST DATA	17
FCC §15.247(a) (1)-CHANNEL SEPARATION TEST	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA	22
FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA	25

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME).....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34
FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT	41
APPLICABLE STANDARD	41
TEST PROCEDURE	41
TEST DATA	41
FCC §15.247(d) - BAND EDGES TESTING	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST DATA	45

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	AMBIENT LED OUTDOOR SPEAKER
Tested Model No.	CB-335067
Multiple Model No.	18831, 99316, 98999
Model Differences	Only appearance colour is different.
Frequency Range	2402~2480MHz
Maximum conducted Peak output power	-4.41dBm
Modulation Technique	GFSK, $\pi/4$ -DQPSK
Antenna Specification*	PCB Antenna: -0.68dBi(provided by the applicant)
Voltage Range	DC 3.7V by battery or DC 5V from USB port.
Date of Test	2021-06-02 to 2021-06-07
Sample number	ATC210526-19457E-RF-S1(Assigned by ATC)
Received date	2021-05-26
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

For Radiated Emissions testing, please refer to DA 00-705 Released March 30, 2000, Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A-2.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in an engineering mode.

EUT Exercise Software

Software "FCC_Assist" was used during testing and the power level was 10*.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
HUAWEI	Adapter	HW-050200C01	Unknown

External I/O Cable

Cable Description	Length (m)	From Port	To
Unshielded Detachable USB cable	0.45	EUT	Adapter

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i), §1.1307 (b) (1) & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209 & §15.247(d)	Radiated Emissions	Compliance
§15.247(a)(1)	20 dB Emission Bandwidth & 99% Occupied Bandwidth	Compliance
§15.247(a)(1)	Channel Separation Test	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(a)(1)(iii)	Quantity of hopping channel Test	Compliance
§15.247(b)(1)	Peak Output Power Measurement	Compliance
§15.247(d)	Band edges	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	Test Receiver	ESPI3	100396	2020/12/24	2021/12/23
R & S	L.I.S.N.	ENV216	101314	2020/12/25	2021/12/24
Anritsu Corp	50Ω Coaxial Switch	MP59B	6200506474	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-2m	No.2	2020/12/25	2021/12/24
Radiated Emissions Test					
Rohde&Schwarz	Test Receiver	ESR	101817	2020/12/24	2021/12/23
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101495	2020/12/24	2021/12/23
A.H. Systems, inc.	Preamplifier	PAM-0118P	531	2020/07/08	2021/07/07
SONOMA INSTRUMENT	Amplifier	310 N	186131	2020/12/25	2021/12/24
Quinstar	Amplifier	QLW-184055 36-J0	15964001002	2020/11/28	2021/11/27
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2020/01/04	2023/01/03
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Unknown	RF Coaxial Cable	N-5m	No.3	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-5m	No.4	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.5	2020/12/25	2021/12/24
Unknown	RF Coaxial Cable	N-1m	No.6	2020/12/25	2021/12/24
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV40	101495	2020/12/24	2021/12/23
Rohde & Schwarz	Open Switch and Control Unit	OSP120 +OSP -B157	101244 + 100866	2020/12/24	2021/12/23

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i), §1.1307 (b) (1) & §2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. f(GHz) is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Test Result:

For worst case:

Mode	Frequency (MHz)	Maximum Tune-up power		Calculated Distance (mm)	Calculated Value	Threshold (1-g SAR)	SAR Test Exclusion
		(dBm)	(mW)				
Bluetooth	2480	-4	0.4	5	0.13	3.0	Yes

Result: No Standalone SAR test is required

FCC §15.203 – ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one internal Antenna arrangement, which was permanently attached and the antenna gain is -0.68dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Transd Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Transd Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin} &= \text{Limit} - \text{level} \\ \text{Level} &= \text{reading level} + \text{Transd Factor} \end{aligned}$$

Test Data


Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Icey Huang on 2021-06-02.

EUT operation mode: Transmitting (the worst case is GFSK Mode, High channel)

AC 120V/60 Hz, Line



MEASUREMENT RESULT: "9457E-L1_fin"

2021-6-2 10:26 AM


Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.205000	43.20	10.8	63	19.8	QP	L1	GND
0.570000	33.10	11.0	56	22.9	QP	L1	GND
1.705000	32.10	11.2	56	23.9	QP	L1	GND
2.160000	31.00	11.3	56	25.0	QP	L1	GND
7.400000	28.00	11.5	60	32.0	QP	L1	GND
19.350000	20.00	11.7	60	40.0	QP	L1	GND

MEASUREMENT RESULT: "9457E-L1_fin2"

2021-6-2 10:26 AM

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.200000	28.40	10.8	54	25.6	AV	L1	GND
0.570000	24.90	11.0	46	21.1	AV	L1	GND
1.705000	21.00	11.2	46	25.0	AV	L1	GND
3.980000	16.80	11.4	46	29.2	AV	L1	GND
6.250000	14.70	11.5	50	35.3	AV	L1	GND
13.075000	10.10	11.6	50	39.9	AV	L1	GND

AC 120V/60 Hz, Neutral



MEASUREMENT RESULT: "9457E-N1_fin"

2021-6-2 10:31 AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.195000	41.30	10.8	64	22.7	QP	N	GND
0.575000	32.50	11.0	56	23.5	QP	N	GND
1.540000	34.00	11.2	56	22.0	QP	N	GND
2.310000	29.30	11.3	56	26.7	QP	N	GND
5.150000	28.30	11.4	60	31.7	QP	N	GND
25.725000	17.10	11.7	60	42.9	QP	N	GND

MEASUREMENT RESULT: "9457E-N1_fin2"

2021-6-2 10:31 AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.230000	26.10	10.9	52	25.9	AV	N	GND
0.575000	27.30	11.0	46	18.7	AV	N	GND
1.720000	28.60	11.2	46	17.4	AV	N	GND
2.860000	22.10	11.3	46	23.9	AV	N	GND
5.150000	20.50	11.4	50	29.5	AV	N	GND
13.175000	17.80	11.6	50	32.2	AV	N	GND


FCC §15.205, §15.209 & §15.247(d) – RADIATED EMISSIONS

Applicable Standard


FCC §15.205; §15.209; §15.247(d)

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, according to the DA 00-705 Released March 30, 2000, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Average

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode for frequency range of 30 MHz -1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Result} - \text{Limit}$$

Test Data

Environmental Conditions


Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Icey Huang on 2021-06-02.

EUT operation mode: Transmitting (Scan with GFSK, $\pi/4$ -DQPSK mode, the worst case is GFSK Mode)


Below 1GHz: GFSK Mode, High channel

Horizontal



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	118.6014	36.00	-18.09	17.91	43.50	-25.59	QP			
2	191.7450	47.65	-17.73	29.92	43.50	-13.58	QP			
3	287.9904	41.51	-14.95	26.56	46.00	-19.44	QP			
4	383.9318	43.11	-12.88	30.23	46.00	-15.77	QP			
5	480.5276	34.92	-10.73	24.19	46.00	-21.81	QP			
6	576.6443	31.43	-8.28	23.15	46.00	-22.85	QP			

Vertical



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	125.8864	39.74	-18.69	21.05	43.50	-22.45	QP			
2	191.7450	45.01	-17.73	27.28	43.50	-16.22	QP			
3	287.9904	45.79	-14.95	30.84	46.00	-15.16	QP			
4	383.9318	45.55	-12.88	32.67	46.00	-13.33	QP			
5	480.5276	45.50	-10.73	34.77	46.00	-11.23	QP			
6	576.6443	34.43	-8.28	26.15	46.00	-19.85	QP			

Above 1GHz:

Frequency (MHz)	Receiver		Turntable Angle Degree	Tx Antenna		Factor (dB/m)	Absolute Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)
	Reading (dBuV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel									
2310	49.92	PK	320	1.2	H	-6.84	43.08	74	30.92
2310	50.04	PK	56	1.4	V	-6.84	43.2	74	30.8
2390	49.76	PK	320	1.3	H	-6.44	43.32	74	30.68
2390	50.2	PK	21	2.6	V	-6.44	43.76	74	30.24
4804.11	50.86	PK	52	2.2	H	2.81	53.67	74	20.33
4804.11	37.71	AV	52	2.2	H	2.81	40.52	54	13.48
4804.11	51.8	PK	85	1.7	V	2.81	54.61	74	19.39
4804.11	39.36	AV	85	1.7	V	2.81	42.17	54	11.83
7200.309	52.69	PK	130	1.3	H	7.46	60.15	74	13.85
7200.309	39.86	AV	130	1.3	H	7.46	47.32	54	6.68
Middle Channel									
7323	55.15	PK	140	1.2	H	8.31	63.46	74	10.54
7323	39.21	AV	140	1.2	H	8.31	47.52	54	6.48
7323	50.16	PK	101	2.5	V	8.31	58.47	74	15.53
7323	38.41	AV	101	2.5	V	8.31	46.72	54	7.28
High Channel									
2483.5	50.44	PK	230	1.7	H	-5.96	44.48	74	29.52
2483.5	50.73	PK	46	2.1	V	-5.96	44.77	74	29.23
2500	50.32	PK	67	1.3	H	-5.88	44.44	74	29.56
2500	50.51	PK	101	1	V	-5.88	44.63	74	29.37
4960.662	53.2	PK	346	2.2	V	3.32	56.52	74	17.48
4960.662	38.42	AV	346	2.2	V	3.32	41.74	54	12.26
7440.646	55.59	PK	120	1.4	H	9.53	65.12	74	8.88
7440.646	41.16	AV	120	1.4	H	9.53	50.69	54	3.31
7440.429	53.35	PK	315	1.5	V	9.22	62.57	74	11.43
7440.429	41.02	AV	315	1.5	V	9.22	50.24	54	3.76

Note:

Absolute Level = Factor + Reading


Margin = Limit - Absolute Level

The test result of peak was less than the limit of average, so just peak values were recorded.


1 GHz - 18 GHz: (Pre-Scan plots)

High Channel

Horizontal




Vertical




18-25GHz: (Pre-Scan plots)

High Channel

Horizontal



Vertical



FCC §15.247(a) (1)-CHANNEL SEPARATION TEST

Applicable Standard

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Test Procedure

1. Set the EUT in transmitting mode, maxhold the channel.
2. Set the adjacent channel of the EUT and maxhold another trace.
3. Measure the channel separation.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Icey Huang on 2021-06-02


EUT operation mode: Transmitting

Test Result: Compliant.


Test Mode	Antenna	Channel	Result[MHz]	Limit[MHz]	Verdict
DH1	Ant1	Hop	1.000	≥ 0.590	PASS
2DH1	Ant1	Hop	1.000	≥ 0.844	PASS

Please refer to the below plots:

DH1_Ant1_Hop



2DH1_Ant1_Hop



FCC §15.247(a) (1) – 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH

Applicable Standard

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


Test Procedure

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / 20 dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / 20 dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).



Test Data**Environmental Conditions**

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa

The testing was performed by Icey Huang on 2021-06-02.

EUT operation mode: Transmitting

Test Result: Compliant.


Test Mode	Antenna	Channel	20db EBW[MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.882	---	PASS
		2441	0.885	---	PASS
		2480	0.885	---	PASS
2DH1	Ant1	2402	1.266	---	PASS
		2441	1.233	---	PASS
		2480	1.251	---	PASS

Test Mode	Antenna	Channel	99% Occupied Bandwidth [MHz]	Limit[MHz]	Verdict
DH1	Ant1	2402	0.842	---	PASS
		2441	0.845	---	PASS
		2480	0.845	---	PASS
2DH1	Ant1	2402	1.202	---	PASS
		2441	1.187	---	PASS
		2480	1.196	---	PASS


Please refer to the below plots:

20 dB EMISSION BANDWIDTH


DH1_Ant1_2402MHz



DH1_Ant1_2441MHz




DH1_Ant1_2480MHz




Date: 2.JUN.2021 16:52:52

2DH1_Ant1_2402MHz




Date: 2.JUN.2021 16:54:02

2DH1_Ant1_2441MHz




2DH1_Ant1_2480MHz




99% OCCUPIED BANDWIDTH


DH1_Ant1_2402MHz




DH1_Ant1_2441MHz




DH1_Ant1_2480MHz



2DH1_Ant1_2402MHz



2DH1_Ant1_2441MHz



Date: 2.JUN.2021 16:55:27

2DH1_Ant1_2480MHz



Date: 2.JUN.2021 16:56:23

FCC §15.247(a) (1) (iii)-QUANTITY OF HOPPING CHANNEL TEST

Applicable Standard

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Icey Huang on 2021-06-02.

EUT operation mode: Transmitting

Test Result: Compliant.


TestMode	Antenna	Channel	Result[Num]	Limit[Num]	Verdict
DH1	Ant1	Hop	79	>=15	PASS
2DH1	Ant1	Hop	79	>=15	PASS

DH1_Ant1_Hop



Date: 2.JUN.2021 17:01:43

2DH1_Ant1_Hop



Date: 2.JUN.2021 17:05:27

FCC §15.247(a) (1) (iii) - TIME OF OCCUPANCY (DWELL TIME)

Applicable Standard

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

Test Procedure

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses

Test Data

Environmental Conditions

Temperature:	24 °C
Relative Humidity:	41 %
ATM Pressure:	101.0 kPa

The testing was performed by Icey Huang on 2021-06-02 and 2021-06-07.

EUT operation mode: Transmitting

Test Result: Compliant.


Test Mode	Antenna	Channel	BurstWidth [ms]	TotalHops [Num]	Result[s]	Limit[s]	Verdict
DH1	Ant1	Hop	0.37	330	0.123	≤ 0.4	PASS
DH3	Ant1	Hop	1.62	100	0.162	≤ 0.4	PASS
DH5	Ant1	Hop	2.86	50	0.143	≤ 0.4	PASS
2DH1	Ant1	Hop	0.38	320	0.122	≤ 0.4	PASS
2DH3	Ant1	Hop	1.63	90	0.147	≤ 0.4	PASS
2DH5	Ant1	Hop	2.87	80	0.229	≤ 0.4	PASS

Note 1: A period time= $0.4 \times 79 = 31.6(S)$, Result=Burst Width*Total Hops


Note 2: Total Hops =Hopping Number in $3.16s \times 10$

Note 3: Hopping Number in $3.16s =$ Total of highest signals in $3.16s$ (Second high signals were other channel)

DH1_Ant1_Hop




Date: 2.JUN.2021 17:02:01




Date: 2.JUN.2021 17:02:06

DH3_Ant1_Hop




Date: 2.JUN.2021 17:02:57




Date: 7.JUN.2021 16:58:53

DH5_Ant1_Hop




Date: 2.JUN.2021 17:03:29




Date: 7.JUN.2021 16:59:19

2DH1_Ant1_Hop




Date: 2.JUN.2021 17:26:27




Date: 2.JUN.2021 17:26:42

2DH3_Ant1_Hop




Date: 2.JUN.2021 17:27:09




Date: 7.JUN.2021 17:00:09

2DH5_Ant1_Hop



Date: 2.JUN.2021 17:24:14



Date: 2.JUN.2021 17:24:19

FCC §15.247(b) (1) - PEAK OUTPUT POWER MEASUREMENT

Applicable Standard

According to §15.247(b) (1), for frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

Test Procedure

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

Test Data

Environmental Conditions

Temperature:	24°C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Icey Huang on 2021-06-02.

EUT operation mode: Transmitting

Test Result: Compliant.


Test Mode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
DH1	Ant1	2402	-7.39	<=20.97	PASS
		2441	-6.42	<=20.97	PASS
		2480	-4.41	<=20.97	PASS
2DH1	Ant1	2402	-7.03	<=20.97	PASS
		2441	-8.51	<=20.97	PASS
		2480	-5.76	<=20.97	PASS

DH1_Ant1_2402MHz




Date: 2.JUN.2021 17:07:51

DH1_Ant1_2441MHz




Date: 2.JUN.2021 17:08:14


DH1_Ant1_2480MHz




2DH1_Ant1_2402MHz



2DH1_Ant1_2441MHz



2DH1_Ant1_2480MHz



FCC §15.247(d) - BAND EDGES TESTING

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions

Temperature:	24°C
Relative Humidity:	48 %
ATM Pressure:	101.0 kPa


The testing was performed by Icey Huang on 2021-06-02.

EUT operation mode: Transmitting


Test Result: Compliant.

Conducted Band Edge Result:


DH1_Ant1_Low_2402MHz



DH1_Ant1_High_2480MHz




DH1_Ant1_Low_Hop_2402MHz




Date: 2.JUN.2021 16:57:17

DH1_Ant1_High_Hop_2480MHz




Date: 2.JUN.2021 17:03:54

2DH1_Ant1_Low_2402MHz




Date: 2.JUN.2021 16:54:34

2DH1_Ant1_High_2480MHz




Date: 2.JUN.2021 16:56:38

2DH1_Ant1_Low_Hop_2402MHz



Date: 2.JUN.2021 17:04:17

2DH1_Ant1_High_Hop_2480MHz



Date: 2.JUN.2021 17:07:17

***** END OF REPORT *****