#### Request for Modular/Limited Modular Approval

Date: January 22, 2022					
Subject: Manufacturer's Declaration for ⊠ - Modular Approval □ - Split Modular Approval □ - Limited Modular Approval □ - Limited Split Modular Approval					
Confidentiality Request for: 2AZCK-B100					
8 Basic Requirements – FCC Part 15.212(a)(1)					
For Items Marked "NO(*)", the Limited Module Description Must be Filled Out on the Fo Modular Approval Requirement		ment Met			
1. The modular transmitter must have its own RF shielding. This is intended to ensure that the module does not have to rely upon the shielding provided by the device into which it is installed in order for all modular transmitter emissions to comply with FCC limits. It is also intended to prevent coupling between the RF circuitry of the module and any wires or circuits in the device into which the module is installed. Such coupling may result in non-compliant operation. The physical crystal and tuning capacitors may be located external to the shielded radio elements. 15.212(a)(1)(i)	⊠ - YES	□ - NO(*)			
Details: <example a="" all="" and="" antenna="" board="" circuitry.="" components="" connector="" contains="" covers="" is="" located="" metal="" module="" next="" of="" on="" rf="" shield="" the="" to="" top="" which="" –=""></example>					
2. The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with FCC requirements under conditions of excessive data rates or over-modulation. 15.212(a)(1)(ii)	⊠ - YES	□ - NO(*)			
Details: <example application="" as="" buffered="" circuit="" data="" described="" descrip="" in="" is="" modulation="" operational="" the="" to="" –=""></example>	tion provided	with the			
3. The modular transmitter must have its own power supply regulation on the module. This is intended to ensure that the module will comply with FCC requirements regardless of the design of the power supplying circuitry in the device into which the module is installed. 15.212(a)(1)(iii)	⊠ - YES	□ - NO(*)			
Details: <example application="" contains="" filed="" its="" module="" own="" please="" power="" refer="" regulation.="" schematic="" supply="" the="" this="" to="" with="" –=""></example>					
4. The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b), 15.204(c), 15.212(a), and 2.929(b). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph 15.212(b). 15.212(a)(1)(iv)	⊠ - YES	□ - NO(*)			
Details: <example a="" an="" and="" antenna="" antennas="" application="" approved="" be="" connector="" connector.="" connects="" considered="" device="" found="" in="" is="" its="" list="" manual="" may="" module="" non-standard="" of="" provided="" tested="" the="" this="" to="" ufl="" users="" using="" which="" with="" –=""></example>					
5. The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing. This is intended to demonstrate that the module is capable of complying with Part 15 emission limits regardless of the device into which it is eventually installed. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in Section 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see Section 15.27(a)). The length of these lines shall be length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified or commercially available (see Section 15.31(i)). 15.212(a)(1)(v)	⊠ - YES	□ - NO(*)			
Details: <example as="" filed="" in="" module="" photographs="" setup="" shown="" stand-alone="" test="" tested="" th="" the="" was="" with<="" –=""><th>this application</th><th>on&gt;</th></example>	this application	on>			

		ъ .	435.4
	Modular Approval Requirement	Requirement Met	
6.	The modular transmitter must be labeled with its own FCC ID number, or use an electron display (see KDB Publication 784748).  If using a permanently affixed label with its own FCC ID number, if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module. This exterior label can use wording such as the following: "Contains Transmitter Module FCC ID: XYZMODEL1" or "Contains FCC ID: XYZMODEL1." Any similar wording that expresses the same meaning may be used. The Grantee may either provide such a label, an example of which must be included in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.  If the modular transmitter uses an electronic display of the FCC identification number, the information must be readily accessible and visible on the modular transmitter or on the device in which it is installed. If the module is installed inside another device, then the outside of the device into which the module is installed must display a label referring to the enclosed module. This exterior label can use	⊠ - YES	□ - NO(*)
	wording such as the following: "Contains FCC certified transmitter module(s)." Any similar wording that expresses the same meaning may be used. The user manual must include instructions on how to access the electronic display. A copy of these instructions must be included in the application for equipment authorization. 15.212(a)(1)(vi)		
	Details: <example a="" application="" application.="" are="" as="" exhibit="" filed="" in="" installation="" is="" label="" labeling="" manual="" module="" on="" shown="" the="" there="" this="" with="" –=""></example>	olication. Hos	t specific
7.	The modular transmitter must comply with all specific rule or operating requirements applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured. 15.212(a)(1)(vii)	⊠ - YES	□ - NO(*)
	Details: <example 15c="" application.="" complies="" fcc="" filed="" installation="" instructions="" manual="" module="" oem="" part="" requirements.="" the="" this="" to="" with="" –=""></example>	1 installer are	provided in
8.	The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance. 15.212(a)(1)(viii)	⊠ - YES	□ - NO(*)
	Details: <example application.="" as="" exclusion="" exposure="" in="" inform="" levels="" meets="" module="" portable="" rf="" shown="" the="" –=""></example>	ation filed wi	th this

#### **Limited Module Description – When Applicable**

\* If a module does NOT meet one or more of the above 8 requirements, the applicant may request Limited Modular Approval (LMA). This Limited Modular Approval (LMA) is applied with the understanding that the applicant will demonstrate and will retain control over the final installation of the device, such that compliance of the end product is always assured. The operating condition(s) for the LMA; the module is only approved for use when installed in devices produced by grantee. A description regarding how control of the end product, into which the module will be installed, will be maintained by the applicant/manufacturer, such that full compliance of the end product is always ensured should be provided here.

Details: <example - N/A>

Software Considerations – KDB 594280 / KDB 442812 (One of the following 2 items must be applied)				
Requirement		Requirement Met		
1.	For <u>non-Software Defined Radio</u> transmitter modules where software is used to ensure compliance of the device, technical description must be provided about how such control is implemented to ensure prevention of third-party modification; see KDB Publication 594280.	□ - Provided in Separate     Cover Letter	□ - N/A	
	Details: <example a="" adjusted="" application.="" as="" be="" by="" can="" cover="" described="" device="" end="" filed="" firmware="" in="" letter="" modified="" not="" of="" or="" separate="" the="" this="" user="" with="" –=""></example>			
2.	For <u>Software Defined Radio (SDR)</u> devices, transmitter module applications must provide a software security description; see KDB Publication 442812.	☐ - Provided in Separate  Cover Letter	□ - N/A	
	Details: <example -n="" a=""></example>			

Split Modular Requirements			
Requirement	Provided in Manual		
<ol> <li>For split modular transmitters, specific descriptions for secure communications between front-end and control sections, including authentication and restrictions on third-party modifications; also, instructions to third-party integrators on how control is maintained.</li> </ol>	☐ - Provided in Separate  Cover Letter	⊠ - N/A	
Details: <example a="" n="" –=""></example>			

	OEM	Integration Ma	anual Guid	ance – KDB 996369 D03 Section 2		
Clear and Specific Instructions Describing the Conditions, Limitations, and Procedures for third-parties to use and/or integrate the module into a host device.						
	ior tilli	1-parties to use a	anu/or mu	egrate the module into a nost device.		
Require	ment					
2234				□ - No,		
				If No, and LMA applies, the applicant ca	un antionally chaose to not	
				make the following detailed info public.		
Is this module	intended for			to be basic integration instructions for		
sale to third pa		🛛 - YES	S	information below must still be inclu		
sale to till pa	itties:			description. If the applicant wishes to k		
				this will require a separate statement co		
				module is not for sale to third partie		
	T.			instructions are internal confide	ential documents.	
As of May 1 2				al – See KDB 996369 D03, Section 2	Madulay tyangmittay	
				ormation to be in the installation manual. All these items indicating clearly when the		
				Not Applicable". Also if a module is limit		
				structions may not need to be detailed an		
				this should include a cover letter as cited		
	ble FCC rules. KDB					
a.	Only list rules relate	d to the transmitt	ter.			
2. Summarize the	e specific operational	use conditions. I	KDB 9963	69 D03, Section 2.3		
a.	Conditions such as 1	imits on antennas	s, cable los	s, reduction of power for point to point		
	systems, professiona				-	
	le Procedures. KDB					
		means that the g	grantee uses	s to verify the host meets the necessary		
	limiting conditions	ovalvation is mass	account atot	a have control will be maintained such	□ - All Items shown to	
	that compliance is en			e how control will be maintained such	the left are provided in	
	designs. KDB 9963			new nosts, etc.	the Modular Integration	
				ectors, isolation requirements, tests for	Guide (or UM) for Full	
				res for ensuring compliance. If	Modular Approval (MA)	
				ial must be identified and information	or LMA.	
	provided in the oper					
	onsiderations. KDB				- An LMA applies	
				v host manufacturers to use the module.	and is approved ONLY for use by the grantee in	
				the host manufacturer to define	their own products, and	
	provided to the end			y) and second additional text needed to be	not intended for sale to	
	B 996369 D03, Secti		moduct mai	iuais.	3 <sup>rd</sup> parties as provided in	
			ication and	all applicable professional installer	a separate cover letter.	
				hall also identify the antenna types	Therefore the	
				-directional" is not considered a type)	information shown to the	
7. Label and com	pliance information.				left is found in the	
				vide a physical or e-label stating	theory of operation.	
	"Contains FCC ID:					
8. Information on test modes and additional testing requirements. KDB 996369 D03, Section 2.9						
a. Test modes that should be taken into consideration by host integrators including						
clarifications necessary for stand-alone and simultaneous configurations.						
b. Provide information on how to configure test modes for evaluation  On Additional testing, Part 15 Subpart P. disalaimer, VDP 006260 D03, Section 2.10						
7. Muumonai test	9. Additional testing, Part 15 Subpart B disclaimer. KDB 996369 D03, Section 2.10					
Sincaraly	,	0 —				
Sincerely,	Ch o~	yl Tane e/Title1)	ø			
D	Ultul	7		CI 1T /D : A		
By:		/m:d 1x	1	Cheryl Tang/Project Manager	<u> </u>	
	(Signatur	e/Title <sup>1</sup> )	/	(Print name)		

<sup>&</sup>lt;sup>1</sup> - Must be signed by applicant contact given for applicant on the FCC site, or by the authorized agent if an appropriate authorized agent letter has been provided. Letters should be placed on appropriate letterhead.