



中认信通
CHINA CERTIFICATION ICT CO., LTD (DONGGUAN)



RF EXPOSURE EVALUATION REPORT

Applicant: FJ Dynamics Technology Co., Ltd

Address: No.1, Dongfeng-Iseki Road, Xiangzhou International Logistic Park,
Xiangyang, Hubei China

FCC ID: 2AZD3FJNBD25SD

Product Name: FJDynamics Autosteering Kit

**Standard(s): 47 CFR Part 15, Subpart C(15.247)
ANSI C63.10-2013
KDB 558074 D01 15.247 Meas Guidance v05r02**

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230205842-00E

Date Of Issue: 2023/06/01

Reviewed By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan,
Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
DOCUMENT REVISION HISTORY	4
1. RF EXPOSURE EVALUATION	5
1.1 SIMULTANEOUS TRANSMISSION WITH BOTH SAR-BASED	5
1.1.1 Applicable Standard.....	5
1.1.2 EUT WWAN Information▲:	7

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230205842-00E	Original Report	2023/6/1

1. RF EXPOSURE EVALUATION

1.1 Simultaneous Transmission with both SAR-based

1.1.1 Applicable Standard

According to §1.1307(b)(3)(ii)(B)

Simultaneous Transmission with both SAR-based and MPE-Based Test Exemptions

This case is described in detail in § 1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an RF exempt device if the condition of Formula (1) is satisfied.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

Where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right) \text{ and } f \text{ is in GHz;}$$

and

$$ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

d = the separation distance (cm);

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1 \quad (1)$$

Where:

a = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for P_{th} , including existing exempt transmitters and those being added.

b = number of fixed, mobile, or portable RF sources claiming exemption using [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section for Threshold ERP, including existing exempt transmitters and those being added.

c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.

P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).

$P_{th,j}$ = the exemption threshold power (P_{th}) according to [paragraph \(b\)\(3\)\(i\)\(B\)](#) of this section for fixed, mobile, or portable RF source i .

ERP_j = the ERP of fixed, mobile, or portable RF source j .

$ERP_{th,j}$ = exemption threshold ERP for fixed, mobile, or portable RF source j , at a distance of at least $\lambda/2\pi$ according to the applicable formula of [paragraph \(b\)\(3\)\(i\)\(C\)](#) of this section.

$Evaluated_k$ = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.

$Exposure\ Limit_k$ = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k , as applicable from [§ 1.1310 of this chapter](#).

1.1.2 EUT WWAN Information ▲ :

Operation Modes	Operation Frequency (MHz)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	ERP or EIRP (dBm)	Limit (dBm)
GSM850	824-849	25.81	1.71	25.81	38.45
GSM1900	1850-1910	22.81	3.31	23.97	33
WCDMA B2	1850-1910	25	3.31	26.16	33
WCDMA B4	1710-1755	25	1.67	25	30
WCDMA B5	824-849	25	1.71	25	38.45
LTE B2	1850-1910	25	3.31	26.16	33
LTE B4	1710-1755	25	1.67	25	30
LTE B5	824-849	25	1.71	25	38.45
LTE B7	2500-2570	25	2.42	25.27	33
LTE B12	699-716	25	3.51	26.36	34.77
LTE B13	777-787	25	2.66	25.51	34.77
LTE B25	1850-1915	25	3.31	26.16	33
LTE B26	814-849	25	1.92	25	38.45
LTE B38	2570-2620	25	3.71	26.56	33
LTE B41	2496-2690	25	3.96	26.81	33

Note:
The devices may contain certified WWAN Module, FCC ID: XMR201903EG25G.

1.1.3 Measurement Result

Radio	Frequency (MHz)	Distance (mm)	P _{th} (mW)	Maximum Conducted Power including Tune-up Tolerance (dBm)	Antenna Gain (dBi)	The Greater of Conducted Power or ERP		SAR-Based Exemption
						dBm	mW	
2.4G WLAN	2412-2462	200	3060	20.5	-0.40	20.5	112.2	Compliant
BLE	2402-2480	200	3060	6.5	-0.40	6.5	4.47	Compliant
BDR/EDR	2402-2480	200	3060	9	-0.40	9	7.94	Compliant
GSM850	824-849	200	1681	25.81	1.71	25.81	381.07	Compliant
GSM1900	1850-1910	200	3060	22.81	3.31	23.97	249.46	Compliant
WCDMA B2	1850-1910	200	3060	25	3.31	26.16	413.05	Compliant
WCDMA B4	1710-1755	200	3060	25	1.67	25	316.23	Compliant
WCDMA B5	824-849	200	1681	25	1.71	25	316.23	Compliant
LTE B2	1850-1910	200	3060	25	3.31	26.16	413.05	Compliant
LTE B4	1710-1755	200	3060	25	1.67	25	316.23	Compliant
LTE B5	824-849	200	1681	25	1.71	25	316.23	Compliant
LTE B7	2500-2570	200	1681	25	2.42	25.27	336.51	Compliant
LTE B12	699-716	200	1426	25	3.51	26.36	432.51	Compliant
LTE B13	777-787	200	1585	25	2.66	25.51	355.63	Compliant
LTE B25	1850-1915	200	3060	25	3.31	26.16	413.05	Compliant
LTE B26	814-849	200	1661	25	1.92	25	316.23	Compliant
LTE B38	2570-2620	200	1661	25	3.71	26.56	452.9	Compliant
LTE B41	2496-2690	200	3060	25	3.96	26.81	479.73	Compliant

Note:

The WWAN and WiFi or BLE or BDR/EDR can transmit simultaneously.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k}$$

$$\begin{aligned} &= P_{WWAN} / P_{th} + P_{WiFi} / P_{th} \\ &= 432.51/1426 + 112.2/3060 \\ &= 0.34 \end{aligned}$$

< 1.0

Note:

The Maximum Conducted Power including Tune-up Tolerance was declared by manufacturer.

Result: The device meet FCC MPE at 20 cm distance.

===== END OF REPORT =====