



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20210200157E-02
Applicant: ShenZhen YingBoJingKong Technology Co., Ltd.
Address of Applicant: No. 602, West of 6th Floor, Building 713, PengJi Industrial Zone, Liantang Street, Luohu District, Shenzhen, Guangdong, China
Equipment Under Test (EUT):
EUT Name: Wireless Bluetooth BBQ Thermometer
Model No.: IBT-4XS, IBT-4XC, IBT-4XP, IBT-4X
Test Model No.: IBT-4XS
Brand Name: N/A
FCC ID: 2AZDE-IB-IBT01
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2021-2-24
Date of Test: 2021-2-24 to 2021-3-4
Date of Issue: 2021-3-22
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Jun Li
(Jun Li)
Reviewed By: Ares Liu
(Ares Liu)
Approved By: Sheek Luo
(Sheek Luo)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20210200157E-02	Rev.01	Initial report	2021-3-22

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5

3 General Information

3.1 Client Information

Applicant:	ShenZhen YingBoJingKong Technology Co., Ltd.
Address of Applicant:	No. 602,West of 6th Floor,Building 713,PengJi Industrial Zone, Liantang Street,Luohu District, Shenzhen,GuangDong,China
Manufacturer:	ShenZhen YingBoJingKong Technology Co., Ltd.
Address of Manufacturer:	No. 602,West of 6th Floor,Building 713,PengJi Industrial Zone, Liantang Street,Luohu District, Shenzhen,GuangDong,China
Factory:	ShenZhen YingBoJingKong Technology Co., Ltd.
Address of Factory:	No. 602,West of 6th Floor,Building 713,PengJi Industrial Zone, Liantang Street,Luohu District, Shenzhen,GuangDong,China

3.2 General Description of EUT

Product Name:	Wireless Bluetooth BBQ Thermometer
All Model No.:	IBT-4XS, IBT-4XC, IBT-4XP, IBT-4X
Test Model No.:	IBT-4XS
Trade Mark:	N/A
Hardware Version:	Version :2.2 _2.5
Software Version:	Version:3.11
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	BLE
Modulation Type:	GFSK
Transfer Rate:	1Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	Setup_SmartRF_Studio_7-2.4.1
Antenna Type:	Pcb antenna
Antenna Gain:	0dBi
EUT Power Supply:	lithium battery:DC3.7V, Charge by DC4.2V

Note: IBT-4XS, IBT-4XC, IBT-4XP, IBT-4X

Only the model IBT-4XS was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being color of appearance and model name.

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

2) For BLE

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	1.77	1±1	2	1.585
Middle(2440MHz)	2.09	1.5±1	2.5	1.778
Highest(2480MHz)	2.30	1.5±1	2.5	1.778

Worst case: GFSK mode						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	1.77	1±1	2	1.585	0.491	3.0
Middle (2440MHz)	2.09	1.5±1	2.5	1.778	0.556	
Highest (2480MHz)	2.30	1.5±1	2.5	1.778	0.560	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20210200157E-01
BDR and BLE can not simultaneous transmitting at same time.