

# EXHIBIT A- LABELING AND LABEL LOCATION

## Label


**WARNING CAUTION**

- READ OWNERS MANUAL BEFORE USE.
- FOR USE WITH ELECTRIC VEHICLES.
- VENTILATION NOT REQUIRED.
- TO AVOID A RISK OF FIRE OR ELECTRIC SHOCK, DO NOT USE THIS DEVICE WITH AN EXTENSION CORD.
- THE SUITABILITY OF THE USE OF FLEXIBLE CORD IN ACCORDANCE WITH CE CODE, PART I, RULE4-012, IS TO BE DETERMINED BY THE LOCAL INSPECTION AUTHORITY HAVING JURISDICTION.
- TO REDUCE THE RISK OF ELECTRIC SHOCK, CONNECT ONLY TO PROPERLY GROUNDED OUTLETS.
- DO NOT USE THIS PRODUCT IF THERE IS ANY DAMAGE TO THE UNIT.
- RISK OF ELECTRIC SHOCK. DO NOT REMOVE COVER OR ATTEMPT TO OPEN THE ENCLOSURE. NO USER SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.
- RISK OF EXPLOSION. THIS EQUIPMENT HAS ARCING OR SPARKING PARTS THAT SHOULD NOT BE EXPOSED TO FLAMMABLE VAPORS. THIS EQUIPMENT SHOULD BE LOCATED AT LEAST 460 MM (18 INCHES) ABOVE THE FLOOR.
- RISK OF EXPLOSION. THIS EQUIPMENT HAS INTERNAL ARCING OR SPARKING PARTS WHICH SHOULD NOT BE EXPOSED TO FLAMMABLE VAPORS. IT SHOULD NOT BE LOCATED IN A RECESSED AREA OR BELOW FLOOR LEVEL.
- THIS DEVICE IS INTENDED ONLY FOR CHARGING VEHICLES NOT REQUIRING VENTILATION DURING CHARGING.
- GFI CIRCUIT BREAKING FEATURES INSIDE.
- FCC ID:2AZGWM3P-2104.
- TYPE 4 ENCLOSURE.
- TEMPERATURE RATING: -22°F TO 131°F (-30°C TO 55°C).
- INPUT VOLTAGE: 177 TO 264 VAC.
- RATED VOLTAGE: LEVEL2 240 VAC.
- INPUT FREQUENCY: 47HZ TO 63HZ.
- RATED FREQUENCY: 60HZ.

**FC**

**MFG. DATE.**  
10/21/2020

**UL** US



**SICHUAN WEIYU ELECTRIC CO., LTD.**  
MADE IN CHINA

**Label Location**

